

Single core Copper & Aluminum Conductors

XLPE Insulated and PVC Sheathed

Voltage Grade

6 / 10 (12) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and banded with a Copper tape to achieve electrical contact • Overlapped Copper Tape then Copper Wires are also available (in single core only) Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Outer Sheath	Extruded PVC Compound
Outer Sheath Color	Black (default color), or any other color according to customer request
Maximum Operating Temp.	90° C
Minimum bending Radius	12 x outer diameter
Packing Condition	Our standard length on Wooden Drum / or according to customer request

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request
the below data are applicable for cables with rated voltage 6.35/11 (12) KV

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance			Operating Capacitance	Inductance		Current Rating					Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Flat	Trefoil	Laid in Ground			Laid in Free Air			
			Flat	Trefoil				Flat	Trefoil	Duct	Flat Touched	Trefoil		
mm²	Ω/km	Ω/km	Ω/km	μF/km	mH/km	mH/km	A	A	A	A	A	mm	kg/km	
A - Copper Conductors														
PM-CT14-X6-01-UP	50	0.3870	0.4937	0.4938	0.2630	0.4426	0.3963	225	218	183	241	236	22.0	885
PM-CT15-X6-01-UP	70	0.2680	0.3421	0.3421	0.3029	0.4187	0.3725	277	267	225	302	295	23.8	1105
PM-CT16-X6-01-UP	95	0.1930	0.2466	0.2467	0.3359	0.4030	0.3568	330	316	269	366	358	25.5	1370
PM-CT17-X6-01-UP	120	0.1530	0.1958	0.1959	0.3667	0.3878	0.3415	373	361	307	420	412	26.9	1610
PM-CT18-X6-01-UP	150	0.1240	0.1590	0.1592	0.3996	0.3777	0.3315	412	404	343	474	469	28.6	1985
PM-CT19-X6-01-UP	185	0.0991	0.1275	0.1278	0.4391	0.3660	0.3198	463	456	390	545	540	30.4	2345
PM-CT20-X6-01-UP	240	0.0754	0.0977	0.0981	0.4893	0.3523	0.3061	532	528	454	642	636	32.7	2890
PM-CT21-X6-01-UP	300	0.0601	0.0786	0.0792	0.5374	0.3438	0.2976	594	591	511	733	728	35.1	3505
PM-CT22-X6-01-UP	400	0.0470	0.0625	0.0633	0.5963	0.3349	0.2887	663	665	582	835	842	38.0	4425
PM-CT23-X6-01-UP	500	0.0366	0.0501	0.0512	0.6682	0.3260	0.2797	742	749	662	964	969	41.5	5505
PM-CT24-X6-01-UP	630	0.0283	0.0404	0.0417	0.7574	0.3202	0.2740	829	833	747	1104	1097	45.8	6835
PM-CT25-X6-01-UP	800	0.0221	0.0335	0.0351	0.8532	0.3113	0.2650	908	924	855	1246	1237	50.2	8630
B - Aluminum Conductors														
PM-AT14-X6-01-UP	50	0.6410	0.8219	0.8220	0.2719	0.4364	0.3902	174	169	141	185	184	22.4	610
PM-AT15-X6-01-UP	70	0.4430	0.5682	0.5683	0.3051	0.4165	0.3703	213	207	174	232	232	23.9	695
PM-AT16-X6-01-UP	95	0.3200	0.4106	0.4107	0.3403	0.4011	0.3549	255	247	209	281	278	25.7	810
PM-AT17-X6-01-UP	120	0.2530	0.3248	0.3249	0.3689	0.3869	0.3407	290	281	238	324	324	27.0	905
PM-AT18-X6-01-UP	150	0.2060	0.2646	0.2648	0.4062	0.3756	0.3294	321	315	268	366	366	28.9	1110
PM-AT19-X6-01-UP	185	0.1640	0.2110	0.2112	0.4456	0.3643	0.3180	363	358	306	422	426	30.7	1245
PM-AT20-X6-01-UP	240	0.1250	0.1612	0.1615	0.4893	0.3523	0.3061	419	414	355	506	498	32.7	1435
PM-AT21-X6-01-UP	300	0.1000	0.1294	0.1298	0.5374	0.3438	0.2976	463	465	401	581	574	35.1	1655
PM-AT22-X6-01-UP	400	0.0778	0.1013	0.1018	0.5963	0.3349	0.2887	533	530	463	672	670	38.0	2060
PM-AT23-X6-01-UP	500	0.0605	0.0798	0.0805	0.6682	0.3260	0.2797	602	605	534	782	781	41.5	2450
PM-AT24-X6-01-UP	630	0.0469	0.0630	0.0639	0.7596	0.3200	0.2738	686	686	618	911	907	45.9	2970
PM-AT25-X6-01-UP	800	0.0367	0.0508	0.0520	0.8532	0.3113	0.2650	775	775	714	1051	1038	50.2	3565

The above data is approximate and subject to manufacturing tolerances