

Multicores Copper & Aluminum Conductors

XLPE Insulated, Steel Tape armored and PVC Sheathed

Voltage Grade

8.7 / 15 (17.5) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated, semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, three cores assembled together with non hygroscopic Polypropylene fillers, banded with suitable tape armored with steel tape and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and binded with a Copper tape to achieve electrical contact Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Assembly	The insulated Cores are assembled together using nonhygroscopic polypropylene filler (if needed), then banded with suitable tape
Inner Sheath	Extruded PVC Compound
Armoring	Double Steel Tapes applied helically over the inner sheath.
Outer Sheath	Extruded PVC Compound
Cores Indentification	by inserting Red, Yellow, Blue narrow plastic tapes between the non metallic & the metallic insulation screen, or any other color according to customer request
Outer Sheath Color	Black (default color), or any other color according to customer request



Maximum Operating Temp. 90° C

Minimum bending Radius 12 x outer diameter

Packing Condition Our standard length on Wooden Drum / or according to customer request

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance		Operating Capacitance	Inductance	Current Rating		Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Laid in Ground	Laid in Free Air		
					mm²	Ω/km	Ω/km	µF/km	mH/km
	A - Copper Conductors								
PM-CT14-X7-03-TP	50	0.3870	0.4957	0.2141	0.3705	207	213	48.8	3780
PM-CT15-X7-03-TP	70	0.2680	0.3437	0.2448	0.3488	255	266	53.3	4695
PM-CT16-X7-03-TP	95	0.1930	0.2481	0.2702	0.3330	302	319	56.5	5530
PM-CT17-X7-03-TP	120	0.1530	0.1973	0.2938	0.3191	343	365	59.9	6430
PM-CT18-X7-03-TP	150	0.1240	0.1605	0.3191	0.3105	383	413	64.0	7695
PM-CT19-X7-03-TP	185	0.0991	0.1293	0.3492	0.3002	432	469	68.1	8980
PM-CT20-X7-03-TP	240	0.0754	0.0999	0.3877	0.2866	498	548	73.0	10880
PM-CT21-X7-03-TP	300	0.0601	0.0813	0.4245	0.2783	558	623	79.3	13640
PM-CT22-X7-03-TP	400	0.0470	0.0660	0.4695	0.2710	628	714	86.1	16685
PM-CT23-X7-03-TP	500	0.0366	0.0545	0.5244	0.2626	701	810	94.1	20510
B - Aluminum Conductors									
PM-AT14-X7-03-TP	50	0.6410	0.8252	0.2209	0.3648	161	165	49.6	2970
PM-AT15-X7-03-TP	70	0.4430	0.5705	0.2465	0.3467	197	205	53.5	3470
PM-AT16-X7-03-TP	95	0.3200	0.4125	0.2736	0.3313	235	248	56.9	3860
PM-AT17-X7-03-TP	120	0.2530	0.3265	0.2955	0.3184	268	284	60.1	4315
PM-AT18-X7-03-TP	150	0.2060	0.2662	0.3241	0.3086	299	321	64.6	5080
PM-AT19-X7-03-TP	185	0.1640	0.2126	0.3543	0.2986	339	368	68.7	5705
PM-AT20-X7-03-TP	240	0.1250	0.1630	0.3877	0.2866	392	431	73.0	6510
PM-AT21-X7-03-TP	300	0.1000	0.1314	0.4245	0.2783	443	494	79.3	8090
PM-AT22-X7-03-TP	400	0.0778	0.1038	0.4695	0.2710	503	570	86.1	9575
PM-AT23-X7-03-TP	500	0.0605	0.0828	0.5244	0.2626	572	660	94.1	11330

The above data is approximate and subject to manufacturing tolerances

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request
Galvanized Steel Tapes is available according to customer request