

Multicores Copper & Aluminum Conductors

XLPE Insulated, Steel Wires armored and PVC Sheathed

Voltage Grade

8.7 / 15 (17.5) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated, semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, three cores assembled together with non hygroscopic Polypropylene fillers, banded with suitable tape banded with suitable tape, armored with Galvanized steel wires, banded with suitable tape and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502 or BS 6622
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and binded with a Copper tape to achieve electrical contact Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Assembly	The insulated Cores are assembled together using nonhygroscopic polypropylene filler (if needed), then banded with suitable tape
Inner Sheath	Extruded PVC Compound
Armoring	Double Steel Tapes applied helically over the inner sheath.
Outer Sheath	Extruded PVC Compound
Cores Indentification	by inserting Red, Yellow, Blue narrow plastic tapes between the non metallic & the metallic insulation screen, or any other color according to customer request
Outer Sheath Color	Black (default color), or any other color according to customer request



Maximum Operating Temp. 90° C

Minimum bending Radius 12 x outer diameter

Packing Condition Our standard length on Wooden Drum / or according to customer request

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance		Operating Capacitance	Inductance	Current Rating		Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Laid in Ground	Laid in Free Air		
					mm²	Ω/km	Ω/km		
	A - Copper Conductors								
PM-CT14-X7-03-WP	50	0.3870	0.4957	0.2141	0.3705	208	218	52.8	5160
PM-CT15-X7-03-WP	70	0.2680	0.3437	0.2448	0.3488	256	272	57.1	6185
PM-CT16-X7-03-WP	95	0.1930	0.2481	0.2702	0.3330	304	326	60.5	7155
PM-CT17-X7-03-WP	120	0.1530	0.1973	0.2938	0.3191	344	372	63.9	8165
PM-CT18-X7-03-WP	150	0.1240	0.1605	0.3191	0.3105	386	424	69.5	10255
PM-CT19-X7-03-WP	185	0.0991	0.1293	0.3492	0.3002	432	479	73.4	11695
PM-CT20-X7-03-WP	240	0.0754	0.0999	0.3877	0.2866	496	558	78.3	13780
PM-CT21-X7-03-WP	300	0.0601	0.0813	0.4245	0.2783	552	632	83.5	16115
PM-CT22-X7-03-WP	400	0.0470	0.0660	0.4695	0.2710	617	714	90.3	19385
PM-CT23-X7-03-WP	500	0.0366	0.0545	0.5244	0.2626	683	804	98.3	23475
B - Aluminum Conductors									
PM-AT14-X7-03-WP	50	0.6410	0.8252	0.2209	0.3648	162	169	53.6	4375
PM-AT15-X7-03-WP	70	0.4430	0.5705	0.2465	0.3467	198	210	57.3	4960
PM-AT16-X7-03-WP	95	0.3200	0.4125	0.2736	0.3313	236	253	60.9	5475
PM-AT17-X7-03-WP	120	0.2530	0.3265	0.2955	0.3184	269	290	64.1	6065
PM-AT18-X7-03-WP	150	0.2060	0.2662	0.3241	0.3086	301	331	70.1	7695
PM-AT19-X7-03-WP	185	0.1640	0.2126	0.3543	0.2986	339	376	74.0	8470
PM-AT20-X7-03-WP	240	0.1250	0.1630	0.3877	0.2866	392	441	78.3	9405
PM-AT21-X7-03-WP	300	0.1000	0.1314	0.4245	0.2783	440	501	83.5	10565
PM-AT22-X7-03-WP	400	0.0778	0.1038	0.4695	0.2710	498	574	90.3	12275
PM-AT23-X7-03-WP	500	0.0605	0.0828	0.5244	0.2626	562	659	98.3	14295

The above data is approximate and subject to manufacturing tolerances

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request