

Single core Copper & Aluminum Conductors

XLPE Insulated, Aluminum Wire armored and PVC Sheathed

Voltage Grade

8.7 / 15 (17.5) KV

Description

Soft annealed Stranded circular compacted Copper or Stranded circular compacted Aluminum conductor, semiconducting layer as conductor screen, XLPE insulated semiconducting layer as non metallic insulation screen, Copper tape or wire as metallic insulation screen, armored with aluminum wire and PVC sheathed.

Application

These cables are generally suitable for direct burial or for installation on trays or in ducts.

Technical Data

Relevant Standard	IEC 60502 or BS 6622
Conductor	Plain copper conductor class 2 or Aluminum conductor class 2
Conductor Screen	Extruded Semiconductive Compound
Insulation	Extruded XLPE Compound Rated 90° C
Insulation Screen	Non Metallic part: Extruded Semiconductive Compound (Bonded or Strippable) to the insulation Metallic part: (by one of the following) • Copper tape is applied helically with a suitable overlap. • Copper Wires helically applied and banded with a Copper tape to achieve electrical contact • Overlapped Copper Tape then Copper Wires are also available (in single core only) Conductor screen, XLPE insulation and non metallic insulation screen are applied at the same time using triple head extruder.
Inner Sheath	Extruded PVC Compound
Armoring	Aluminum Wires applied over the inner sheath.
Outer Sheath	Extruded PVC Compound
Outer Sheath Color	Black (default color), or any other color according to customer request
Maximum Operating Temp.	90° C
Minimum bending Radius	12 x outer diameter
Packing Condition	Our standard length on Wooden Drum / or according to customer request



MEDIUM VOLTAGE CABLES

Product Code	Nominal Cross Sectional Area	Max. Conductor Resistance			Operating Capacitance	Inductance		Current Rating				Approx. Overall Diameter	Approx. Weight
		DC at 20 °C	AC at 90° C			Flat	Trefoil	Laid in Ground		Laid in Free Air			
			Flat	Trefoil				Flat	Trefoil	Flat Touched	Trefoil		
	mm²	Ω/km	Ω/km	Ω/km	μF/km	mH/km	mH/km	A	A	A	A	mm	kg/km
A - Copper Conductors													
PM-CT14-X7-01-RP	50	0.3870	0.4937	0.4937	0.2141	0.5053	0.4590	228	220	241	236	30.1	1380
PM-CT15-X7-01-RP	70	0.2680	0.3420	0.3421	0.2448	0.4773	0.4311	275	268	301	295	31.9	1635
PM-CT16-X7-01-RP	95	0.1930	0.2465	0.2466	0.2702	0.4617	0.4155	323	318	364	358	34.2	1995
PM-CT17-X7-01-RP	120	0.1530	0.1957	0.1958	0.2938	0.4438	0.3976	360	358	417	412	35.6	2260
PM-CT18-X7-01-RP	150	0.1240	0.1588	0.1589	0.3191	0.4308	0.3846	394	398	471	468	37.3	2675
PM-CT19-X7-01-RP	185	0.0991	0.1273	0.1275	0.3492	0.4164	0.3701	443	445	536	530	39.1	3065
PM-CT20-X7-01-RP	240	0.0754	0.0974	0.0977	0.3877	0.4005	0.3543	501	503	627	623	41.6	3685
PM-CT21-X7-01-RP	300	0.0601	0.0782	0.0786	0.4245	0.3944	0.3482	545	556	708	689	45.2	4500
PM-CT22-X7-01-RP	400	0.0470	0.0621	0.0625	0.4695	0.3812	0.3350	592	614	804	768	47.9	5470
PM-CT23-X7-01-RP	500	0.0366	0.0495	0.0502	0.5244	0.3695	0.3233	646	675	909	851	51.6	6655
PM-CT24-X7-01-RP	630	0.0283	0.0397	0.0406	0.5925	0.3601	0.3138	691	735	964	990	55.9	8095
PM-CT25-X7-01-RP	800	0.0221	0.0327	0.0338	0.6656	0.3492	0.3030	743	785	1057	1093	60.7	10055
B - Aluminum Conductors													
PM-AT14-X7-01-RP	50	0.6410	0.8219	0.8219	0.2209	0.4982	0.4519	180	171	185	184	30.5	1115
PM-AT15-X7-01-RP	70	0.4430	0.5682	0.5682	0.2465	0.4749	0.4287	218	209	232	232	32.0	1230
PM-AT16-X7-01-RP	95	0.3200	0.4106	0.4106	0.2736	0.4594	0.4132	258	249	281	278	34.4	1445
PM-AT17-X7-01-RP	120	0.2530	0.3247	0.3248	0.2955	0.4428	0.3966	289	282	324	324	35.7	1555
PM-AT18-X7-01-RP	150	0.2060	0.2645	0.2646	0.3241	0.4282	0.3820	320	313	366	366	37.6	1800
PM-AT19-X7-01-RP	185	0.1640	0.2109	0.2110	0.3543	0.4142	0.3679	357	353	422	424	39.4	1980
PM-AT20-X7-01-RP	240	0.1250	0.1611	0.1612	0.3877	0.4005	0.3543	402	404	506	498	41.6	2230
PM-AT21-X7-01-RP	300	0.1000	0.1292	0.1294	0.4245	0.3944	0.3482	442	450	574	561	45.2	2655
PM-AT22-X7-01-RP	400	0.0778	0.1010	0.1013	0.4695	0.3812	0.3350	489	505	661	639	47.9	3105
PM-AT23-X7-01-RP	500	0.0605	0.0794	0.0798	0.5244	0.3695	0.3233	539	565	760	722	51.6	3600
PM-AT24-X7-01-RP	630	0.0469	0.0624	0.0631	0.5942	0.3598	0.3135	600	623	833	840	56.0	4230
PM-AT25-X7-01-RP	800	0.0367	0.0501	0.0510	0.6656	0.3492	0.3030	663	689	936	953	60.7	4990

The above data is approximate and subject to manufacturing tolerances

Note:-

Flame retardant PVC sheathed or Polyethylene Sheathed are available according to customer request
Longitudinal or radial Water tightness layers are also available according to customer request