User Guide and Package Reference

April 9, 2026

ENLP Beamer Theme Documentation

Ehime University Natural Language Processing Laboratory

Eito Yoneyama

NLP LAB
Ehime University

Overview

Purpose

- This document is the primary user documentation for the ENLP Beamer theme.
- The package reproduces the ENLP PowerPoint template as a Beamer theme with natively drawn Ti*k*Z backgrounds.
- The official theme name is `\usetheme{enlp}`.
- The document is also built by `l3build`, so the rendered PDF doubles as a packaging check.

Requirements

- LuaLaTeX, XeLaTeX, pLaTeX, and upLaTeX are supported. pdfLaTeX is not supported.
- pLaTeX and upLaTeX must use `dvipdfmx`, i.e. `\documentclass[dvipdfmx]{beamer}`.
- The default page size is 33.87cm $\times$ 19.05cm.
- The default Latin sans font is `TeX Gyre Heros`; the default Japanese sans font is `HaranoAji Gothic`.
- The default monospaced font is `Latin Modern Mono`.
- Under LuaLaTeX, mixed Japanese-Latin text is handled by `luatexja-fontspec` on top of `luaotfload`.
- Title, heading, and content backgrounds are drawn natively using Ti*k*Z.

Engine-Specific Notes

- LuaLaTeX uses `fontspec` with `luatexja-fontspec`; `luaotfload` resolves the Latin and Japanese OpenType fonts.
- XeLaTeX uses `fontspec` with `xeCJK` and the same HaranoAji font family.
- pLaTeX and upLaTeX use a `dvipdfmx`-based workflow with `pxchfon` and `pxjahyper`.
- The theme defaults both Latin and Japanese body text to sans serif so mixed Japanese-Latin slides stay visually consistent.
- Hyperlinks and bookmarks are configured for Unicode output across every supported engine.

Package Contents

- `beamerthemeenlp.sty`: main theme integration
- `beamer*themeenlp.sty`: split sub-themes (color, font, inner, outer)
- `enlplogo.sty`: lab logo definitions
- `enlpbeamer.bbx`, `enlpbeamer.cbx`, `enlpbeamer.bst`: bibliography styles

Getting Started

Minimal Preamble for LuaLaTeX / XeLaTeX

Basic Usage

```
\documentclass{beamer}
\usetheme{enlp}
\title{Title}
\author{Author}
\institute{Institute}
\date{\today}
```

- The theme applies the ENLP page size automatically.
- No manual background configuration is required.
- Japanese and Latin text are both initialized to sans-serif defaults for stable mixed-script slides.
- The recommended title slide command is `\enlptitleframe`.

Minimal Preamble for pLaTeX / upLaTeX

Basic Usage

```
\documentclass[dvipdfmx]{beamer}
\usetheme{enlp}
\title{Title}
\author{Author}
\institute{Institute}
\date{\today}
```

- The document class must use the `dvipdfmx` option.
- The same mixed Japanese-Latin sans-serif defaults are applied after the theme loads.
- The recommended title slide command is `\enlptitleframe`.

Recommended Document Skeleton

Typical Structure

```
\begin{document}
\enlptitleframe
\enlpsectionframe{Introduction}
\begin{frame}{Motivation}
  ...
\end{frame}
\insertbibliographyframe
\end{document}
```

Custom Fonts Overview

- Custom fonts can already be configured in the preamble after `\usetheme{enlp}`.
- LuaLaTeX uses the `fontspec` and `luatexja-fontspec` interfaces.
- XeLaTeX uses the `fontspec` and `xeCJK` interfaces.
- pLaTeX and upLaTeX use `pxchfon` for Japanese fonts and regular NFSS family selection for Latin fonts.
- Because the theme defaults to sans-serif and gothic text, update the sans and Japanese gothic side when changing body fonts.

Custom Fonts with LuaLaTeX

Example

```
\usetheme{enlp}
\setmainfont{TeX Gyre Termes}
\setsansfont{IBM Plex Sans}
\setmonofont{JetBrains Mono}
\setmainjfont[BoldFont=HaranoAjiMincho-Bold.otf]{HaranoAjiMincho-Regular.otf}
\setsansjfont[BoldFont=HaranoAjiGothic-Bold.otf]{HaranoAjiGothic-Regular.otf}
```

- Place these commands after `\usetheme{enlp}` and before `\begin{document}`.
- Use `\setmainjfont` and `\setsansjfont` for the Japanese side of mixed Japanese-Latin text.
- LuaLaTeX relies on `luatexja-fontspec` for Japanese layout and `luaotfload` for font resolution, so this is the preferred path when mixed Japanese-Latin spacing matters.
- If you need luatexja-specific options such as JFM tuning, pass them in the optional argument.

Custom Fonts with XeLaTeX

Example

```
\usetheme{enlp}
\setmainfont{TeX Gyre Termes}
\setsansfont{IBM Plex Sans}
\setmonofont{JetBrains Mono}
\setCJKmainfont[BoldFont=HaranoAjiMincho-Bold.otf]{HaranoAjiMincho-Regular.otf}
\setCJKsansfont[BoldFont=HaranoAjiGothic-Bold.otf]{HaranoAjiGothic-Regular.otf}
```

- XeLaTeX uses `xeCJK`, so Japanese fonts are changed with `\setCJKmainfont` and `\setCJKsansfont`.
- The theme keeps body text in sans-serif by default, so `\setsansfont` and `\setCJKsansfont` are the most important pair.
- Font names and font file names are both acceptable if XeTeX can resolve them.

Custom Fonts with pLaTeX / upLaTeX

Example

```
\documentclass[dvipdfmx]{beamer}
\usepackage{tgtermes}
\usetheme{enlp}
\renewcommand{\rmdefault}{qtm}
\renewcommand{\sfdefault}{qhv}
\renewcommand{\ttdefault}{lmtt}
\setminchofont{HaranoAjiMincho-Regular.otf}
\setboldminchofont{HaranoAjiMincho-Bold.otf}
\setgothicfont{HaranoAjiGothic-Regular.otf}
\setboldgothicfont{HaranoAjiGothic-Bold.otf}
```

- Latin fonts are changed through normal LaTeX family declarations such as `\rmdefault`, `\sfdefault`, and `\ttdefault`.
- Japanese fonts are changed through `pxchfon` commands such as `\setminchofont` and `\setgothicfont`.
- Keep `dvipdfmx` enabled or the theme backgrounds and Japanese font mapping will not work correctly.
- The same procedure applies to both pLaTeX and upLaTeX; upLaTeX is usually preferable for fully Unicode sources.

Default Typography

Title and Heading Slides

- title: 44pt
- subtitle: 20pt
- author / institute / date: 24pt
- section title: 48pt

Regular Slides

- frame title: 36pt
- body text: 24pt
- block title / block body: 24pt
- footnote / footline: 12pt

LayoutControl

Title Slide Defaults

- The title slide background is drawn internally via the outer theme.
- The subtitle and date are placed in the upper-left metadata region.
- The title is centered in the large middle box.
- Institute and author are centered in the lower metadata region.

Title Slide Position Macros

Position Controls

```
\enlpsetsubtitleposition{<x>}{<y>}
\enlpsetdateposition{<x>}{<y>}
\enlpsettitleposition{<x>}{<y>}
\enlpsetinstituteposition{<x>}{<y>}
\enlpsetauthorposition{<x>}{<y>}
```

Width Controls

```
\enlpsetsubtitlewidth{<width>}
\enlpsetdatewidth{<width>}
\enlpsettitlewidth{<width>}
\enlpsetinstitutewidth{<width>}
\enlpsetauthorwidth{<width>}
```

Title Slide Default Coordinates

- subtitle: `x=.063w`, `y=-.090h`, `width=.28w`
- date: `x=.063w`, `y=-.145h`, `width=.30w`
- title: `x=.50w`, `y=-.47h`, `width=.78w`
- institute: `x=.50w`, `y=-.64h`, `width=.78w`
- author: `x=.50w`, `y=-.72h`, `width=.78w`

Regular Slide Geometry

- Regular slides use the natively drawn content background.
- The default left and right text margins are both 24mm.
- The content width is matched to the title underline length in the background.
- Frame contents are top-aligned instead of vertically centered.
- The frame number is placed in the lower right; custom footer text appears in the lower left.

Block and List Styling

- Blocks use an ENLP-specific template sized for 24pt body text.
- Block titles are white on a dark turquoise background.
- Block bodies use a pale wash background.
- Item markers are enlarged slightly relative to Beamer defaults for better visibility at 24pt.

Section Slides

Section Heading Pages

- Section heading pages use the natively drawn heading background.
- The recommended command is `\enlpsectionframe{...}`.
- This command registers the section and immediately inserts the heading page.
- The default heading size is 48pt.

Optional Section Subtitle

Usage

```
\sectionpagesubtitle{Spring Semester}
\enlpsectionframe{Background}
```

- The subtitle is shown only on the section heading page.
- Pass an empty string to clear it for later sections.

Bibliography

Supported Backends

- The theme supports both `biblatex + biber` and `BibTeX`.
- The theme option `bib=biblatex` is the default.
- `bib=bibtex` switches to the bundled `enlpbeamer.bst`.
- In either mode, bibliography files are registered with `\enlpusebibresource{...}`.
- If a document does not use bibliography features yet, `\enlpusebibresource` may be omitted entirely.

Backend Selection

biblatex + biber

```
\usetheme[bib=biblatex]{enlp}
\enlpusebibresource{references.bib}
```

BibTeX

```
\usetheme[bib=bibtex]{enlp}
\enlpusebibresource{references.bib}
```

Backend Initialization Without a .bib File

```
\usetheme[bib=biblatex]{enlp}
\enlpusebibresource{}
```

- This is useful when you want to decide the backend up front but do not have a bibliography database yet.
- The same empty registration also works with `bib=bibtex`.

Citation Semantics

- `\cite{...}` and `\enlptextcite{...}` produce superscripted numeric references such as[1].
- `\enlpauthorcite{...}` produces an author-style citation, for example Smith, Tanaka, and Chen [2].
- `\enlpparencite{...}` produces a parenthetical citation.
- Citation keys used inside a frame are collected automatically and rendered as full entries in the footer.
- Footer bibliography labels remain ordinary bracketed numbers such as `[1]`.

Automatic Footer Citations

This frame cites[1] and [2], so both entries appear in the footer automatically.

- Repeated citations are deduplicated in first-use order.
- `\usetheme[autocitefooter=false]{enlp}` disables the automatic footer behavior.

Manual Footer Citations and Bibliography Pages

- `\framefullcite{...}` overrides the automatic footer content with a fixed citation set.
- Footer entries are rendered in bibliography-number order, even if keys are passed in a different order.
- Footer entries use the 12pt footer font, not the 24pt body font.
- `\insertbibliographyframe` inserts a bibliography section heading followed by bibliography pages.
- Bibliography pages themselves use the same 24pt body layout as regular content slides.

[1] J. Doe and T. Lee. “Dialogue Summarization with Large Language Models”. In: *Transactions of Natural Language Processing* 12.2 (2025), pp. 101–118

[2] A. Smith, Y. Tanaka, and M. Chen. “A Benchmark for Long Dialogue Summarization”. In: *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*. 2024, pp. 2201–2215

Bibliography Color

- The default bibliography color is black.
- This applies to in-text citations, footer citations, and bibliography pages.
- Use `\enlpsetbibliographycolor{...}` to override it globally.
- `\enlpsetcitecolor{...}` is provided as an alias.

Build and Install

l3build Workflow

- `l3build doc` builds this documentation.
- `l3build install -full -dry-run` verifies the TDS installation layout without copying files into the live tree.
- When running LuaLaTeX in a sandboxed or CI environment, make sure `luaotfload` has writable `TEXMFVAR` and `TEXMFCACHE` paths.
- The documentation PDF and source are installed under `doc/latex/enlp-beamer/`.
- The theme files, logo package, and bibliography styles are installed under `tex/latex/enlp-beamer/`.

TDS Layout

- `tex/latex/enlp-beamer/beamerthemeenlp.sty`
- `tex/latex/enlp-beamer/beamer*themeenlp.sty`
- `tex/latex/enlp-beamer/enlplogo.sty`
- `bibtex/bst/enlp-beamer/enlpbeamer.bst`
- `doc/latex/enlp-beamer/documentation.pdf`

Design Policy

- Background assets are defined directly using Ti*k*Z within the outer theme.
- User-facing customization is focused on text placement, page size, bibliography backend, and bibliography color.
- This keeps visual reproduction stable across local builds and installed TDS trees.
- If the underlying artwork changes, the Ti*k*Z drawing commands in the outer theme should be updated.

References

References

[1] J. Doe and T. Lee. “Dialogue Summarization with Large Language Models”. In: *Transactions of Natural Language Processing* 12.2 (2025), pp. 101–118.

[2] A. Smith, Y. Tanaka, and M. Chen. “A Benchmark for Long Dialogue Summarization”. In: *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*. 2024, pp. 2201–2215.