



DEEPHEALTH

EDDL

Deep Learning with EDDL

Winter School 24/01/2022



The project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 825111.



Contents


Monday 24 and Tuesday 25

What is Deep Learning?	3
------------------------	---

Neural Networks	18
-----------------	----

EDDL basics	60
-------------	----

Layers and Tensors	68
--------------------	----



What is Deep Learning?



The project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 825111.





What is Deep Learning?

- Machine learning models based on neural networks:
 - Non-linear models
 - Learning by iteratively showing pairs (input,target) examples
 - Topology defined from know-how, hand-crafted
 - Learn the weights (parameters) by **gradient descent** of a particular **loss function**, iterative procedure
- Deep means that we stack lot of layers (20, 50, 100, 1000)
- Historically neural nets failed to learn with more than (let's say) 10 layers
- Why we need to go deep ? —→ Representation Learning



What is Deep Learning?


- Going deep



What is Deep Learning?


- Non-linear models

Linear vs. nonlinear problems




What is Deep Learning?

- Non-linear models



Linear function



Non-linear function

Best fit linear and non-linear models

What is Deep Learning?

- Learning by iteratively showing pairs (input,target) examples

Training set




Input



Target

“Cat”



What is Deep Learning?

- Learning by iteratively showing pairs (input,target) examples

Training set




Input




Target

“Dog”




What is Deep Learning?

- Learning by iteratively showing pairs (input,target) examples




What is Deep Learning?

- Learning by iteratively showing pairs (input,target) examples




What is Deep Learning?

- Learn the weights (parameters) by **gradient descent** of a particular **loss function**, iterative procedure




What is Deep Learning?

- Learn the weights (parameters) by **gradient descent** of a particular **loss function**, iterative procedure



What is Deep Learning?

- Learn the weights (parameters) by **gradient descent** of a particular **loss function**, iterative procedure



What is Deep Learning?

- Learn the weights (parameters) by **gradient descent** of a particular **loss function**, iterative procedure

$$\Delta = \delta \text{Loss} / \delta \phi$$


$$\phi = \phi - \mu \Delta$$

- μ is what we call learning rate



What is Deep Learning?


- Topology defined from know-how
 - Raw Data : Dense Layers
 - Temporal: Recurrent Layers
 - Images: Covolutional Layers






What is Deep Learning?

- Topology defined from know-how
 - Raw Data : Dense Layers
 - Temporal: Recurrent Layers
 - Images: Covolutional Layers
 - Classification: resnet, densenet,
 - Segmentation: U-net
 - Detection: FasterRCNN, Yolo, SSD
 - Pixel annotation: MaskRCNN
 - Image Generation: DCGAN, CylceGan
 - Fine grain classification: Bilinear CNN






What is a Neural Network?






What is a Neural Network?





A connectionist model





What is a Neural Network?






What is a Neural Network?

Layer: Operation over tensors (1D, 2D, 3D ...)



Connection: the output tensor of a layer (result) is used as input tensor of the following layer

We would refer “x” as input and “y” as output





What is a Neural Network?





What is a Neural Network?


Input Layer: Receive the input examples (images of cats)

Dense Layer: Is a **parametric** layer with the following operation:

$$y = Wx + b \quad W \text{ and } b \text{ are the parameters to learn}$$



Activation Layer: Normally is a non-parametric layer. In the case of ReLu:

$$y = \begin{cases} x & \text{if } x \geq 0 \\ 0 & \text{if } x < 0 \end{cases}$$






What is a Neural Network?



What is a Neural Network?





What is a Neural Network?

Classification problems. n classes output with n neurons


Output: Softmax


$$y_i = \frac{e^{x_i}}{\sum_{j=1}^n e^{x_j}} \quad y_i = p(c = i | \mathbf{x})$$

Loss: Categorical cross-entropy

$$\text{Loss} = - \sum_{i=1}^n y_i \cdot \log \hat{y}_i$$

target







What is a Neural Network?


Regression problems. d dimensions output with d neurons

Output: Linear

$$y_i = x_i$$



Loss: Sum of
Quadratic Errors

$$Loss = \sum_{i=1}^d (y_i - \hat{y}_i)^2$$






What is a Neural Network?





What is a Neural Network?





What is a Neural Network?



The Chain Rule

For $F(x) = f(g(x))$

$$F'(x) = f'(g(x)) \cdot g'(x)$$

Derivative of outer function

Derivative of inner function




What is a Neural Network?

In order to compute the gradient $\Delta = \delta \text{Loss} / \delta \phi$ w.r.t any parameter we can use **the chain rule** to back-propagate the loss

This leads us to the well-know Backpropagation algorithm

Essentially the training phase of a NN is composed by three steps:



- Forward : the output of all the layers are computed
- Backward: the gradient w.r.t all the parameters of all the layers is computed (backpropagation)
- Update: the parameters are updated in the opposite direction of the gradient (optimizer)






What is a Neural Network?

Forward



What is a Neural Network?



Forward






What is a Neural Network?

Forward




What is a Neural Network?

Forward



What is a Neural Network?



Forward





What is a Neural Network?



Forward






What is a Neural Network?

Forward



What is a Neural Network?

Forward




What is a Neural Network?

Forward



Input




Output


Target

What is a Neural Network?


Forward



What is a Neural Network?





What is a Neural Network?







What is a Neural Network?




What is a Neural Network?



What is a Neural Network?





What is a Neural Network?







What is a Neural Network?





What is a Neural Network?

Update






What is a Neural Network?

Training:

- Forward
- Backward
- Update

Inference:

- Forward





What is a Neural Network?

Training:


- Forward
- Backward
- Update

EDDL: `model.fit(input, target)`

Inference:

- Forward

EDDL: `output = model.predict(input)`






What is a Neural Network?

Training:

- Forward
- Backward
- Update



The samples (input,target) are presented in batch, then the gradient is computed for all the samples in a **batch**





What is a Neural Network?



Forward





What is a Neural Network?


Forward





What is a Neural Network?


Forward





What is a Neural Network?

Forward





What is a Neural Network?

Training:


- Forward
- Backward
- Update

EDDL: `model.fit(input, target, batch_size)`

Inference:

- Forward

EDDL: `output = model.predict(input)`





What is a Neural Network?


Training

Definition of **epoch**: train all the samples, then is to train the number of batches that fit in your training set.

Training set of 50.000 samples

Batch_size= 100

Epoch means to train 500 batches (randomly selected) covering all the samples of the training set



What is a Neural Network?

Training:

- Forward
- Backward
- Update

EDDL: `model.fit(input, target, batch_size, epochs)`


Inference:

- Forward

EDDL: `output = model.predict(input)`



EDDL Basic






EDDL Basic

EDDL is an open source library for Distributed Deep Learning and Tensor Operations in C++ for **CPU**, **GPU** and **FPGA**. EDDL is developed inside the DeepHealth project.

EDDL provides a high level API to develop Deep learning projects in C++

PyEDDL is a Python wrapper for the EDDL






EDDL Basic

EDDL is like Keras in the way the models are defined and the training is carried out. The main difference between EDDL and other toolkits is the introduction of the Computing Service (CS) object.

The DL model created with EDDL has a CS attached where this model will be deployed. This CS could be CPU, GPU or FPGA and even we could define a distributed CS.

This CS definition only affects to a single line in your programs.





EDDL Basic

```
download_mnist();

// Define network
layer in = Input({784});
layer l = in;

l = LeakyReLu(Dense(l, 1024));
l = LeakyReLu(Dense(l, 1024));
l = LeakyReLu(Dense(l, 1024));

layer out = Softmax(Dense(l, 10), -1);
model net = Model({in}, {out});

// Computing service
compserv cs = CS_CPU();
// cs = CS_GPU({1}, "low_mem"); // one GPU
// cs = CS_GPU({1,1}, 100); // two GPU
// cs = CS_FPGA({1});
```

```
// Build model
build(net,
    adam(0.001), // Optimizer
    {"softmax_cross_entropy"}, // Losses
    {"categorical_accuracy"}, // Metrics
    cs ); // Computing service


// Train model
fit(net, {x_train}, {y_train}, 32, 10);

// Evaluate
evaluate(net, {x_test}, {y_test});
```



EDDL Basic


MNIST Digits Classification



28x28 images (2D)

stored as 784 pixels (1D)

10 classes






EDDL Basic Data

```
# Download dataset
eddl.download_mnist()
# Load the dataset
x_train = Tensor.load('mnist_trX.bin')
y_train = Tensor.load('mnist_trY.bin')
x_test = Tensor.load('mnist_tsX.bin')
y_test = Tensor.load('mnist_tsY.bin')

# Preprocess the images. From [0-255] to [0-1]
x_train.div_(255.0)
x_test.div_(255.0)

# Show data shape
print('Dataset shape:')
print(f'Train split images: {x_train.shape}')
print(f'Train split labels: {y_train.shape}')
print(f'Test split images: {x_test.shape}')
print(f'Test split labels: {y_test.shape}')
```






EDDL Basic Model

```
# Define the model topology
num_classes = 10
in_ = Input([784])
layer = Reshape(in_, [1, 28, 28]) # EDDL needs channel first images
layer = ReLu(BatchNormalization(Conv(layer, 32, [3, 3]), affine=True))
layer = MaxPool(layer, [2, 2])
layer = ReLu(BatchNormalization(Conv(layer, 64, [3, 3]), affine=True))
layer = MaxPool(layer, [2, 2])
layer = ReLu(BatchNormalization(Conv(layer, 128, [3, 3]), affine=True))
layer = MaxPool(layer, [2, 2])
layer = ReLu(BatchNormalization(Conv(layer, 256, [3, 3]), affine=True))
layer = GlobalAveragePool(layer)
layer = Flatten(layer)
out_ = Softmax(Dense(layer, num_classes))

# Create the model
model = eddl.Model([in_], [out_])
```





EDDL Basic Learning


```
# Build the model to prepare it for training or inference
eddl.build(model,
            opt,                    # Optimizer
            ['categorical_crossentropy'], # Losses
            ['accuracy'],           # Metrics
            cs)                     # Computing Service


# Show the model layers
eddl.summary(model)

eddl.fit(model, [x_train], [y_train], batch_size, epochs) # Train
eddl.evaluate(model, [x_test], [y_test], args.batch_size) # Validation
```



Layers and Tensors







Layers

Dense

- **Input a 1D Tensor (d)**
- **Output a 1D Tensor (d')**
- **Operation: $y = Wx + b$**
- **Parameters: W, b**
 - **W is a (d', d) 2D Tensor**
 - **B is a (d') 1D Tensor**







Layers

Activation

- **Input any D Tensor**
- **Output the same dim as input Tensor**
- **Operation: depends on activation function**
- **Parameters: NO**






Layers


Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




tanh

$$\tanh(x)$$




ReLU

$$\max(0, x)$$



Leaky ReLU

$$\max(0.1x, x)$$





Maxout

$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

ELU

$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$







Layers

Activation


- **The backpropagated gradient is multiply by the derivative of the activation function**




What is a Neural Network?



What is a Neural Network?







Layers

Activation



- **The backpropagated gradient is multiply by the derivative of the activation function**
- **Vanishing gradient problem with some activation functions**
- **Most used: ReLu, ELU and similar**






Layers


Activation






Layers

Activation






Layers


Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




tanh

$$\tanh(x)$$




ReLU

$$\max(0, x)$$



Leaky ReLU

$$\max(0.1x, x)$$





Maxout

$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

ELU

$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$







Layers

Activation - Softmax

Output

$$y_i = \frac{e^{x_i}}{\sum_{j=1}^n e^{x_j}} \quad y_i = p(c = i | \mathbf{x})$$






Layers


More Layers?

Deep Learning features






EDDL with Dense topology (MLP)



28x28 images (2D)

stored as 784 pixels (1D)

10 classes





EDDL with Dense topology (MLP)

```
num_classes = 10
```


```
in = eddl.Input([784])
```

```
layer = eddl.ReLu(eddl.Dense(in, 1024))
```

```
layer = eddl.ReLu(eddl.Dense(layer, 512))
```



```
out = eddl.Softmax(eddl.Dense(layer, num_classes))
```


```
net = eddl.Model([in], [out])
```





EDDL with Dense topology (MLP)










Layers

Conv2D

- Input a 3D Tensor (channels_in, height_in, width_in)
- Output a 3D Tensor (channels_out, height_in, width_out)
- Operation: $y = K * x + b$
- Parameters: K,b
 - K is a (num_filters, channels_in, kernel_height, kernel_width) 4D Tensor
 - B is a (num_filters) 1D Tensor









Layers

Conv2D



Layers

0	0	0	0	0	0	...
0	156	155	156	158	158	...
0	153	154	157	159	159	...
0	149	151	155	158	159	...
0	146	146	149	153	158	...
0	145	143	143	148	158	...
...

Input Channel #1 (Red)

0	0	0	0	0	0	...
0	167	166	167	169	169	...
0	164	165	168	170	170	...
0	160	162	166	169	170	...
0	156	156	159	163	168	...
0	155	153	153	158	168	...
...

Input Channel #2 (Green)

0	0	0	0	0	0	...
0	163	162	163	165	165	...
0	160	161	164	166	166	...
0	156	158	162	165	166	...
0	155	155	158	162	167	...
0	154	152	152	157	167	...
...

Input Channel #3 (Blue)

-1	-1	1
0	1	-1
0	1	1

Kernel Channel #1



308

1	0	0
1	-1	-1
1	0	-1

Kernel Channel #2



-498

0	1	1
0	1	0
1	-1	1

Kernel Channel #3




164

+ 1 = -25

Bias = 1

Output


-25			...
			...
			...
			...
...




Layers

Conv2D

- Input a 3D Tensor (channels_in, height_in, width_in)
- Output a 3D Tensor (channels_out, height_in, width_out)
- channels_out = num_filters
- with padding="same"
 - height_out= height_in
 - width_out= width_in






Layers


Maxpool2D

- Input a 3D Tensor (channels_in, height_in, width_in)
- Output a 3D Tensor (channels_in, height_in/s, width_in/s)

Normally $s=2$



- Parameters: None






Layers

Maxpool2D






Layers


AveragePool2D

4	3	1	5
1	3	4	8
4	5	4	3
6	5	9	4

2 x 2 Avg-Pool




2.8	4.5
5.3	5.0






EDDL with Dense topology (MLP)




28x28 images (2D)

stored as 784 pixels (1D)

10 classes






Layers

num_classes = 10

```
in = eddl.Input([784])           # 784 components vector
layer = eddl.Reshape(in, [1, 28, 28]) # 28 x 28 gray-level image
layer = eddl.MaxPool(eddl.ReLu(eddl.Conv(layer, 32, [3, 3]))) # (32,14,14)
layer = eddl.MaxPool(eddl.ReLu(eddl.Conv(layer, 64, [3, 3]))) # (64,7,7)
layer = eddl.MaxPool(eddl.ReLu(eddl.Conv(layer, 128, [3, 3]))) # (128,3,3)
layer = eddl.MaxPool(eddl.ReLu(eddl.Conv(layer, 256, [3, 3]))) # (256,1,1)
layer = eddl.Reshape(layer, [-1])    # 256 components vector
out = eddl.Softmax(eddl.Dense(layer, num_classes))
```








eddl.summary(net)


```

-----
model
-----
input1      | (784)          => (784)          0
reshape1    | (784)          => (1, 28, 28)    0
conv2d1     | (1, 28, 28)    => (32, 28, 28)   320
relu1       | (32, 28, 28)   => (32, 28, 28)   0
maxpool2d2  | (32, 28, 28)   => (32, 14, 14)   0
conv2d2     | (32, 14, 14)   => (64, 14, 14)  18496
relu2       | (64, 14, 14)   => (64, 14, 14)   0
maxpool2d4  | (64, 14, 14)   => (64, 7, 7)     0
conv2d3     | (64, 7, 7)     => (128, 7, 7)    73856
relu3       | (128, 7, 7)    => (128, 7, 7)    0
maxpool2d6  | (128, 7, 7)    => (128, 3, 3)    0
conv2d4     | (128, 3, 3)    => (256, 3, 3)   295168
relu4       | (256, 3, 3)    => (256, 3, 3)    0
maxpool2d8  | (256, 3, 3)    => (256, 1, 1)    0
reshape2    | (256, 1, 1)    => (256)          0
dense1      | (256)          => (10)           2570
softmax5    | (10)           => (10)           0
-----

```








Layers

Recurrent Layers:


- Vanilla RNN
- LSTM
- GRU

All accept a 1D tensor (vector) as Input and returns 1D vector as Output






EDDL with Dense topology (MLP)



28x28 images (2D)




stored as 784 pixels (1D)

10 classes



EDDL with Dense topology (MLP)

s
e
q
u
e
n
c
e



We are going to consider the digits as a sequence of 28 rows of 28 pixels

Then the recurrent layers expect to receive a 1D tensor of 28 components



Layers

```
num_classes = 10
```

```
in = eddl.Input([28])
```




```
layer = eddl.ReLu(eddl.Dense(in, 32))
```

```
layer = eddl.LSTM(layer, 128)
```

```
out = eddl.Softmax(eddl.Dense(layer, num_classes))
```

```
...
```

```
x_train.reshape_([x_train.shape[0], 28, 28]).      # (N, sequence length, dim)
```





DEEPHEALTH

Thank you!

Roberto Paredes

rparedes@prhlt.upv.es



The project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 825111.