lista07

```
library(DBI)
library(RSQLite)
knitr::opts_chunk$set(max.print = Inf)
con <- dbConnect(RSQLite::SQLite(), "purchase.sqlite")
```

1.

```
SELECT PNO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
GROUP BY PNO
```

Table 1: 8 records

PNO	CUSTO_TOTAL
P1	1450
P2	3200
P3	6150
P4	6700
P5	8400
P6	1800
P7	5400
P8	600

2.

```
SELECT ENO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
GROUP BY ENO
```

Table 2: 4 records

ENO	CUSTO_TOTAL
E1	11700
E2	6600
E3	7800
E4	7600

3.

```
SELECT PJNO, ENO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
GROUP BY PJNO, ENO
ORDER BY PJNO, ENO
```

Table 3: 9 records

PJNO	ENO	CUSTO_TOTAL
PJ1	E1	9500
PJ1	E3	3900
PJ1	E4	3500
PJ2	E1	1200
PJ2	E2	6000
PJ2	E3	3900
PJ2	E4	4100
PJ3	E1	1000
PJ3	E2	600

4.

```
SELECT PNO, SNO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
GROUP BY PNO, SNO
ORDER BY PNO, SNO
```

Table 4: 19 records

PNO	SNO	CUSTO_TOTAL
P1	S1	1150
P1	S2	300
P2	S1	3200
P3	S1	1550
P3	S3	2400
P3	S4	2200
P4	S1	900
P4	S2	1000
P4	S3	2400
P4	S4	2400
P5	S1	3900
P5	S3	3000
P5	S4	1500
P6	S2	300
P6	S4	1500
P7	S3	2000
P7	S4	3400
P8	S1	500
P8	S2	100

5.

```
SELECT PJNO, ENO, SNO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
GROUP BY PJNO, ENO, SNO
ORDER BY PJNO, ENO, SNO
```

Table 5: 14 records

PJNO	ENO	SNO	CUSTO_TOTAL
PJ1	E1	S1	6500
PJ1	E1	S3	2000
PJ1	E1	S4	1000
PJ1	E3	S3	3900
PJ1	E4	S4	3500
PJ2	E1	S1	1100
PJ2	E1	S2	100

PJNO	ENO	SNO	CUSTO_TOTAL
PJ2	E2	S1	2600
PJ2	E2	S2	1000
PJ2	E2	S4	2400
PJ2	E3	S3	3900
PJ2	E4	S4	4100
PJ3	E1	S1	1000
PJ3	E2	S2	600

6.

```
SELECT PNO, ENO, SNO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
GROUP BY PNO, ENO, SNO
ORDER BY PNO, ENO, SNO
```

Table 6: 23 records

PNO	ENO	SNO	CUSTO_TOTAL
P1	E1	S1	1150
P1	E2	S2	300
P2	E1	S1	1000
P2	E2	S1	2200
P3	E1	S1	1550
P3	E3	S3	2400
P3	E4	S4	2200
P4	E1	S1	600
P4	E2	S1	300
P4	E2	S2	1000
P4	E3	S3	2400
P4	E4	S4	2400
P5	E1	S1	3900
P5	E3	S3	3000
P5	E4	S4	1500
P6	E2	S2	300
P6	E4	S4	1500
P7	E1	S3	2000
P7	E1	S4	1000
P7	E2	S4	2400
P8	E1	S1	400

PNO	ENO	SNO	CUSTO_TOTAL
P8	E1	S2	100
P8	E2	S1	100

7.

```
SELECT PJNO, SNO, ENO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
WHERE PJNO <> "PJ2"
GROUP BY PJNO, SNO, ENO
```

Table 7: 7 records

PJNO	SNO	ENO	CUSTO_TOTAL
PJ1	S1	E1	6500
PJ1	S3	E1	2000
PJ1	S3	E3	3900
PJ1	S4	E1	1000
PJ1	S4	E4	3500
PJ3	S1	E1	1000
PJ3	S2	E2	600

8.

```
SELECT PNO, SNO, ENO, SUM(COST) AS CUSTO_TOTAL FROM PURCHASE
GROUP BY PNO, SNO, ENO
HAVING CUSTO_TOTAL > 2000
```

Table 8: 8 records

PNO	SNO	ENO	CUSTO_TOTAL
P2	S1	E2	2200
P3	S3	E3	2400
P3	S4	E4	2200
P4	S3	E3	2400
P4	S4	E4	2400
P5	S1	E1	3900

PNO	SNO	ENO	CUSTO_TOTAL
P5	S3	E3	3000
P7	S4	E2	2400

```
Sys.setenv(TZ = "America/Sao_Paulo")
Sys.time()
```

```
[1] "2026-09-30 20:01:01 -03"
```