

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

SECTION 1. IDENTIFICATION

Product name : Ceftiofur Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Respiratory sensitization : Category 1
Skin sensitization : Category 1
Specific target organ toxicity - repeated exposure (Oral) : Category 2

Other hazards

None known.

GHS label elements

Hazard pictograms :	
Signal Word :	Danger
Hazard Statements :	H317 May cause an allergic skin reaction. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
Precautionary Statements :	Prevention: P260 Do not breathe mist or vapors. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves. P285 In case of inadequate ventilation wear respiratory protection.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P342 + P311 If experiencing respiratory symptoms: Call a doctor.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Ceftiofur	103980-44-5*	>= 3 - <= 7	TSC
Benzyl alcohol	100-51-6*	>= 0.5 - <= 1.5	TSC
Silicon, amorphous	112945-52-5*	>= 0.5 - <= 1.5	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version 10.0	Revision Date: 06/20/2025	SDS Number: 7674006-00016	Date of last issue: 04/14/2025 Date of first issue: 12/15/2020
-----------------	------------------------------	------------------------------	---

Most important symptoms and effects, both acute and delayed	Rinse mouth thoroughly with water. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome). May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause damage to organs through prolonged or repeated exposure if swallowed.
Protection of first-aiders	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapors.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Ceftiofur	103980-44-5	TWA	100 mcg/m3	Internal

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version 10.0	Revision Date: 06/20/2025	SDS Number: 7674006-00016	Date of last issue: 04/14/2025 Date of first issue: 12/15/2020
-----------------	------------------------------	------------------------------	---

			(OEB 2)	
Further information: RSEN, DSEN				
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL
Silicon, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Engineering measures

- : Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections). All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment. Laboratory operations do not require special containment.

Personal protective equipment

Respiratory protection

- : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material

- : Chemical-resistant gloves

Eye protection

- : Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection

Hygiene measures

- : Work uniform or laboratory coat.
- : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment,

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version 10.0	Revision Date: 06/20/2025	SDS Number: 7674006-00016	Date of last issue: 04/14/2025 Date of first issue: 12/15/2020
-----------------	------------------------------	------------------------------	---

appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	suspension
Color	:	white to off-white, cream
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	0.850 - 1.050 g/cm ³ No data available
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version 10.0 Revision Date: 06/20/2025 SDS Number: 7674006-00016 Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available
Particle characteristics	
Particle size	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Ceftiofur:

Acute oral toxicity : LD50 (Rat): > 7,760 mg/kg

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation hazard.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

tion toxicity

Silicon, amorphous:

- | | | |
|---------------------------|---|---|
| Acute oral toxicity | : | LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials |
| Acute inhalation toxicity | : | LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials |
| Acute dermal toxicity | : | LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials |

Skin corrosion/irritation

Not classified based on available information.

Components:

Benzyl alcohol:

- | | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Method | : | OECD Test Guideline 404 |
| Result | : | No skin irritation |

Silicon, amorphous:

- | | | |
|---------|---|--------------------------------------|
| Species | : | Rabbit |
| Method | : | OECD Test Guideline 404 |
| Result | : | No skin irritation |
| Remarks | : | Based on data from similar materials |

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Benzyl alcohol:

- | | | |
|---------|---|--|
| Species | : | Rabbit |
| Result | : | Irritation to eyes, reversing within 21 days |
| Method | : | OECD Test Guideline 405 |

Silicon, amorphous:

- | | | |
|---------|---|--------------------------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Method | : | OECD Test Guideline 405 |
| Remarks | : | Based on data from similar materials |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

Ceftiofur:

Routes of exposure	:	Inhalation
Result	:	Sensitizer
Remarks	:	May cause sensitization by inhalation.

Benzyl alcohol:

Test Type	:	Human repeat insult patch test (HRIPT)
Routes of exposure	:	Skin contact
Species	:	Humans
Result	:	positive
Assessment	:	Probability or evidence of low to moderate skin sensitization rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Ceftiofur:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
	:	Test Type: unscheduled DNA synthesis assay Result: negative

Genotoxicity in vivo	:	Test Type: Micronucleus test Species: Rat Application Route: Intraperitoneal Result: negative
----------------------	---	--

Benzyl alcohol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

II

Silicon, amorphous:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Benzyl alcohol:

Species	:	Mouse
Application Route	:	Ingestion
Exposure time	:	103 weeks
Method	:	OECD Test Guideline 451
Result	:	negative

Silicon, amorphous:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative

Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Ceftiofur:

Effects on fertility	:	Test Type: Fertility Application Route: Oral Fertility: NOAEL: 1,000 mg/kg body weight Result: No adverse effects.
----------------------	---	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

Effects on fetal development : Test Type: Development
Application Route: Oral
Developmental Toxicity: NOAEL: 1,000 mg/kg body weight
Result: No adverse effects.

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

Silicon, amorphous:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed.

Components:

Ceftiofur:

Routes of exposure : Oral
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Ceftiofur:

Species : Rat
NOAEL : 30 mg/kg
Application Route : Oral
Exposure time : 90 d
Target Organs : Gastrointestinal tract
Symptoms : Gastrointestinal disturbance
Remarks : May cause damage to organs.

Species : Dog

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version 10.0 Revision Date: 06/20/2025 SDS Number: 7674006-00016 Date of last issue: 04/14/2025 Date of first issue: 12/15/2020

NOAEL	:	30 mg/kg
Application Route	:	Oral
Exposure time	:	90 d
Target Organs	:	Blood, Central nervous system
Remarks	:	May cause damage to organs.

Benzyl alcohol:

Species	:	Rat
NOAEL	:	1.072 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	28 Days
Method	:	OECD Test Guideline 412

Silicon, amorphous:

Species	:	Rat
NOAEL	:	1.3 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Ceftiofur:

General Information	:	Repeated contact may cause allergic reactions in very susceptible persons.
Inhalation	:	Symptoms: Nausea, Vomiting, Abdominal pain, vaginitis, Headache, Dizziness, dry mouth, Fatigue, constipation, colitis

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Benzyl alcohol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 460 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 230 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

	NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 51 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Silicon, amorphous:	
Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 24 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials

Persistence and degradability

Components:

Benzyl alcohol:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 92 - 96 % Exposure time: 14 d
------------------	--

Bioaccumulative potential

Components:

Benzyl alcohol:

Partition coefficient: n-octanol/water	: log Pow: 1.05
--	-----------------

Mobility in soil

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version 10.0	Revision Date: 06/20/2025	SDS Number: 7674006-00016	Date of last issue: 04/14/2025 Date of first issue: 12/15/2020
-----------------	------------------------------	------------------------------	---

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

- : Respiratory or skin sensitization
Specific target organ toxicity (single or repeated exposure)

SARA 313

- : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version
10.0

Revision Date:
06/20/2025

SDS Number:
7674006-00016

Date of last issue: 04/14/2025
Date of first issue: 12/15/2020

US State Regulations

Pennsylvania Right To Know

Glycerides, mixed decanoyl and octanoyl	73398-61-5
Ceftiofur	103980-44-5
Benzyl alcohol	100-51-6

California Permissible Exposure Limits for Chemical Contaminants

Silicon, amorphous	112945-52-5
--------------------	-------------

The ingredients of this product are reported in the following inventories:

DSL : not determined


AICS : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-3 / TWA	: 8-hour time weighted average
US WEEL / TWA	: 8-hr TWA

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ceftiofur Formulation

Version 10.0	Revision Date: 06/20/2025	SDS Number: 7674006-00016	Date of last issue: 04/14/2025 Date of first issue: 12/15/2020
-----------------	------------------------------	------------------------------	---

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/20/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.