

Single-Cyclist Crashes: A review of the current classifications and analyses

Lorem ipsum



Figure 1: Yes, that's me in a ditch with the sidecar bicycle

Benjamin Eimol Gonzalez Toledo

Promotor:
Alfred Schouten

Supervisors:
Jason Moore
Ajay Seth

BioMechanical Engineering Department
Delft University of Technology
The Netherlands
May 12, 2025

Contents

1	Introduction	2
1.1	Key concepts	2
1.2	Research target	3
2	Methods	3
2.1	Inclusion and exclusion criteria	3
2.1.1	Some remarks on crashes with other road users	3
3	Results	4
3.1	Single-cyclist crash classifications	6
3.2	Bicycle dynamics	6
3.3	Single Bicycle Crashes: Types and Characteristics	6
3.4	Active Safety Systems	7
3.4.1	Antilock Braking System (ABS)	7
3.4.2	Stability Control (SC)	7
3.4.3	Steering Assistance	7
4	The Human	7
5	Characterization of the point of no return	8
6	Discussion	9
7	Conclusion	9

1 Introduction

Cycling population is on arise due to the advantages of the bicycle as a commuter vehicle. This refers from almost free transportation and less pollution to healthier lifestyles and less traffic congestion. However, as the cycling population increases, their exposure to crashes also increase.

Regarding bicycle crashes, one configuration that stands out due to their major share on statistics are the Single-Cyclist Crashes (SCC) (Wegman and Schepers, 2024). These are events where no other road user is involved as an active perturbation, i.e. its effect does not depend on the source. Its share ranges from 50% to 85% of cyclist-related hospital admissions. Moreover, it is known that these events are commonly underreported Boele-Vos et al. (2017); Beck et al. (2019); Schnee et al. (2021); Utriainen (2020); Utriainen et al. (2023a).

In the last decade, Europe has seen a reduction in the fatality rate of total road accidents, except for bicycle crashes (CBS, 2024; Commission, 2024; Gildea et al., 2024; Salmon et al., 2022; Utriainen et al., 2023a). Indeed, in the Netherlands the risk of death in SCCs has not only remained constant, but increased up to 7% (Schepers et al., 2017). Therefore, it is a matter of interest when bicycle usage is intended to be promoted and risks need to be minimised. Furthermore, if these issues are not attended, bicycle usage can be expected to decrease (Gu et al., 2019). However, the dynamics of these crashes are not well understood Haworth and Debnath (2013). Therefore, research on the dynamics of SCCs is needed to continue developing cyclists road safety.

Up to this point, most work has been done in descriptive analysis of common factors that lead to SCCs (Beck et al., 2019; Gildea et al., 2024; Hertach et al., 2018; Salmon et al., 2022; ?; Schepers and Wolt, 2012; Schepers et al., 2015; Utriainen et al., 2023a). Within these descriptive analyses we find common factors and mechanism with a major role in the crash. However, none of these classifications take into account the particular dynamics of the bicycle. Therefore, the aim of this article is to review current classifications and develop a bicycle dynamics based classification of SCCs.

The importance of provide a classification based on bicycle dynamics is to highlight the challenges that are needed to overcome to continue developing the safety of the bicycles. Also to better understand what are the key factors that casuse bicycle crashes and propose more effective countermeasures.

1.1 Key concepts

Since some concepts in this matter are not standarised, we include important definitions used in this work.

First, the events of interest receive different names: single-bicycle crash, single-actor bicycle crash, single-cyclist crash, among others (see Table 3). On one hand, the expresion single-bicycle crash neglects the rider, making reference to a problem only oriented on the bicycle. On the other hand, single-actor bicycle crashes assumes that there are no other actors involved in the event, which neglects indirect effects of other road users, e.g. pedestrian entering into the bike lane and triggering an avoidance manoeuvre that ends in a crash. In addition, any other denomination that includes the word ‘accident’ is not appropriate due to the preventable nature of these events (Davis and Pless, 2001). Therefore, for this work we adopt single-cyclist crash, due to its reference to the rider and the bicycle as the main actors in the event, allowing other indirect actors.

Second, during this article, we will refer to the bicycle and the human coupled together in motion as a dynamical system, which is modelled by non-linear differential equations. Assuming the rider as a controller of the system, we identify the existence of *controllability*, which means that all system variables can be influenced by the input (Seffen et al., 2001; Verlinden and Kabeya, 2012).

Third, a perturbation will be understood by its dictionary definition as any variation in the system that causes it to change its regular movement (?). An active perturbation is a controlled force from an external source, such as other vehicle colliding with the system. A passive perturbation is a non-controlled force, e.g. the force exerted by road irregularities on bicycle tyres.

Fourth, we will call a crash to any sudden and unintended event that results in a disruption of the normal and controlled motion of the human-bicycle system. In the analysis of vehicular collisions, there are three phases: pre-impact motion, impact motion and post-impact motion (Park and Han, 2001). Translating this approach to bicycle crashes, pre-crash motion encompasses the time window from the perturbation to the moment where the bicycle is no longer controllable. Then, the crash stage begins, until the moment when the system stops its motion. Post-crash stage is limited in SCCs and can be assessed as the moment when the vehicle and the rider are disconnected and presenting independent motions (Lloyd, 2016).

At last, bicycles and motorcycles share characteristics as a dynamical systems, which makes them similar for studies. In its analytical study, both are usually assumed as a four-bodies single-track vehicle Sharp (1971); Meijaard et al. (2007); Lot and Sadauckas (2021), with two basic degrees of freedom: roll φ and steering δ . Both vehicles experience similar crash configurations (Haworth and Debnath, 2013; ?; ?), including tyre sliding, inability of control the system through the steering, excessive pitch rotation, among others later discussed in this paper. The main differences are the mass, the working speed range, and power input from the user, being this last what defines if the vehicle is a bicycle or a motorcycle. Despite some modern electric bicycles include

advanced suspension systems, heavy batteries and electric motors that increase overall mass, and are capable of reaching speeds up to 45 [km/h], they are still dependant on rider force for longitudinal motion.

1.2 Research target

The questions that shape the present article are:

1. What are the common approaches to study and analyse human-bicycle dynamics and control in crash scenarios?
2. Is there a classification of crashes that captures the particular behaviour of the human-bicycle system?
3. Is there single-cyclist crash data that is useful to study the dynamics of these events?

The article is structured as follows, Section ?? contains the basic anatomy of a crash, explaining the required factors to occur. Additionally, we review current work on classifications and SCC characteristics, along with the main concepts on the field of bicycle dynamics. The proposed classification is developed on Section ?. Finally, Sections 6 and 7 present the discussion and conclusion, respectively.

2 Methods

The literature search was made in Google Scholar and Dimensions database in October 2024. * The interest relied on studies that analysed the dynamics of single-track vehicle crashes, which include bicycles, motorcycles and scooters. Therefore, the initial query for the broad range search on October 2024 was:

(bicycle OR bike OR two-wheel* OR single-track OR “two wheel*” OR “single track”) AND (crash OR collision OR accident OR fall).

The results of the search provided the main articles in the field, however, we used ‘snowballing’ methodology to complement the search. This approach was particularly useful to cover base concepts that are not always clarified.

2.1 Inclusion and exclusion criteria

The inclusion criteria for the snowballing technique was:

- The study presented statistics related to single-cyclist crashes.
- The study takes into account the dynamics of the bicycle for the crash analysis.
- Studies concerning human control of vehicles.
- Studies that explain the techniques to control a bicycle.
- Analyses on bicycle dynamics that explain its rideability and controllability.

On the other hand, the exclusion of articles was based on the following criteria:

- Studies focused only on injury outcomes.
- Analyses of crashes of bicycles with other road users.
- Articles in a language different than English.

2.1.1 Some remarks on crashes with other road users

Bicycle crashes can be clustered in four categories like Gildea et al. (2024), classifying them according to the nature of the other road user. In these categories, we find bicycle-bicycle, bicycle-motorised vehicle, bicycle-pedestrian and single-cyclist crashes. Categories including other road users are out of the scope of this review since those perturbations act as an active, uncontrollable and unpredictable perturbation on the human-bicycle system.

3 Results

- Schepers classification -¿ what does it miss? - Crash motions -¿ Gildea, Rose and Petit. - Mechanisms?

In the most basic understanding of a single-cyclist crash, this event is the result of the rider losing control of the vehicle. Fuller (2005) describes the loss of control as a relation between task demand and rider capability, when the task demand surpasses the rider capability, the rider loses control and the crash occurs.

Fuller (2005) presents the task-capability model for car drivers, which can be extrapolated to bicycle riders. This model considers physical characteristics and knowledge of the driver on what to do under determined circumstances to define the boundaries its capability. However, this capacity is also affected by other factors related to the circumstance, such as awareness, emotion, fatigue, among others. On the other hand, task demanding elements encompass travelling speed, environmental factors, such as road characteristics and other road users. Of these factors, the driver has direct control of the travelling speed, achieving balance between driver capacity and its awareness to the task. While car drivers can reduce task demand by decreasing speed, this is not always the case for bicycle riders, due to the increase of user stabilisation requirements at low speeds Kooijman et al. (2011); Schwab and Meijaard (2013); Vlakveld et al. (2015). In general, the theory shows an almost constant driver capability balancing with changing task demands, which should not surpass the capability threshold.

When the task demand increases exponentially, possibly leading to a loss of control, it is understood as a critical scenario. Critical scenarios and factors that contribute to them are known in the literature. As seen in Table 3, the most repeated events are sliding, low speed riding, braking, loss of control, collision with an object and interactions with tram tracks.

3.1 Single-cyclist crash classifications

- Schepers classify them according to the causes. - Put notes here

3.2 Bicycle dynamics

A bicycle is a **human-powered single-track vehicle**, which behaviour has been a matter of scientific interest for more than 100 years. The now classical approach for its study considers the bicycle as a dynamical system composed of four rigid bodies: rear frame, front frame, and two wheels.

Assuming a rider rigidly attached to the bicycle, Meijaard et al. (2007) presents the linearised equations of motion for the three degree of freedom model. From these linear equations, the stability of the system is studied, showing two main modes of vibration: Weave and Capsize, which are the particular interest due to its danger to the rider when unstable. Where weave is an oscillatory motion, from roll and steering, while capsizes is a non-oscillatory inverted pendulum-like motion. Thus, the linearised bicycle model was shown to be stable in the range of 4.3 to 6.0 $[\text{m s}^{-1}]$. Furthermore, if tyre parameters are included, wobble mode arises (Sharp, 1971; Schwab and Meijaard, 2013), which is an oscillatory motion of the steering, also danger when unstable.

(Kooijman et al., 2011) demonstrated that the basis of bicycles' self-stability relies on mass distribution and steering coupled to lean angle. These results showed that self-stability is more than angular momentum of the wheels and geometric trail distance as was commonly assumed.

Once understood the basic behaviour of the bicycle itself as a dynamical system, the intuitive next step is the control of the bicycle: How do we ride a bicycle? The task of riding a bicycle can be simplified to maintaining system stability and following a desired trajectory. On the other hand, maintaining system stability has been assessed to understand how bicycles are controlled. In this field, it is known that most control actions come from the steering, and at low speeds knees start to play a role in the control task (Kooijman et al., 2009).

Then, research has focused in developing a human controller to model rider behaviour (Schwab and Meijaard, 2013; Kooijman and Schwab, 2013). An aircraft pilot control simplified model was presented by Hess et al. (2012). Additionally, Wang et al. (2020) develops a controller which takes into account time delays of human body and compared the results with experimental data. Equally, Dialynas et al. (2023) takes into account steering torque feedback and sensory delays to develop his rider model.

The next step, after understanding the basics of human control, is to assess the handling of the bicycle. In particular, Ronné et al. (2024) defines it as '*...the ease and precision with which a human can perform a given control task*'. With this approach, the analysis enters into the concept of Task Demand (TD) and Rider Capability (RC) (Fuller, 2005). As a result, when TD increases over RC, the rider loses control of the system and enters in the crash scenario.

3.3 Single Bicycle Crashes: Types and Characteristics

Concerning the classification of SBCs, in the literature we found several approaches to differentiate the phenomena. Schepers and Wolt (2012); Schepers et al. (2015); Utriainen (2020) propose four main categories:

Author	Country	Data origin	Share of SABC ¹	Classification	Main type (%)	Name
Alguén and Rizzi (2022)	Sweden	-	48 - 95% ²	Crash characteristics	Skidding (26%)	SBC ⁶
Beck et al. (2019)	Australia	Hospital data	48%	Mechanisms	Avoidance braking	SCO ⁷
Boele-Vos et al. (2017)	Netherlands	Ambulance and police reports	80%	Crash type	Object collision	SBC
Boufous et al. (2013)	-	Hospital and police data	>50% ²	Collision/No-collision	Loss of control (80%)	SVBC ⁸
Gildea and Simms (2021)	Ireland	Self-made survey	29%	Causes and factors	Slippery roads	SCC ⁹
Hertach et al. (2018)	Switzerland	Survey	-	Mechanisms and factors	Skidding (31%)	SVC ¹⁰
Meuleners et al. (2020)	-	Hospital data	39%	-	-	SCC
Schepers and Wolt (2012)	Netherlands	-	-	Mechanisms	Riding off the road (21%)	SBC
Schepers et al. (2015)	International	-	60 - 95% ²	-	-	SBC
Schepers et al. (2017)	Netherlands	Police report	-	-	-	SBC
Schwab et al. (2018)	Netherlands	-	68% ³ / 77% ⁴	-	-	SBC
Utraiainen (2020)	Finland	Insurance data	-	Mechanisms	Skidding (47%)	SBC
Utraiainen et al. (2023b)	-	-	52 - 85%	-	Loss of control or skidding	SBC
?	Finland	Crash institute data	35.2% ⁵	Factors and mechanisms	Riding off the road (71.9%)	SBC
Vanparijs et al. (2016)	-	Insurance data	31%	Human factors	Riding off the road (21%)	SBC

Table 1: Literature with statistics about single-cyclist crashes.

¹ Of total bicycle crashes.

² Of total cyclist hospital admission.

³ Normal bicycles.

⁴ Electric bicycles.

⁵ Of fatal bicycle crashes.

⁶ Single-Bicycle Crash.

⁷ Single-Cyclist Only.

⁸ Single-Vehicle Bicycle Crash.

⁹ Single-Cyclist Crash.

¹⁰ Single-Vehicle Crash.

infrastructure-related, cyclist-related, bicycle malfunction and other where there is no recall by the victim. Utriainen et al. (2023a) divides them by the mechanisms such as fall, drift and collision with objects, along with a classification regarding the factors, where we find Human, Bicycle, Traffic and Legislation. Similarly, Gildea et al. (2021) proposes a classification from the factors that cause the accident: slippery roads, tram tracks, kerb collision, avoidance manoeuvres and collision with potholes. Alternatively, Beck et al. (2019) divides them by loss of control, interaction with tram tracks, striking an object, mechanical issues and other. Within loss of control classification, (Gildea et al., 2023) proposes a sub-division where it can be Minor, Substantial or Complete.

In this point, we encounter the lack of information about the dynamics of the accidents. Across the studies, the conclusion is that the most frequent causes of SBCs are skidding, loss of control by braking or steering manoeuvres, and external perturbations such as hitting a kerb (Schepers and Wolt, 2012; Hertach et al., 2018; Utriainen, 2020; Algurén and Rizzi, 2022). Moreover, the way of interaction with the environment can increase the risk, e.g. the angle of crossing a tram line (Gildea et al., 2023). However, there is no information about which one of the wheels slips, longitudinal or lateral velocity, steering angle, braking force, etc. Therefore, it is necessary to gather data to assess bicycle crash dynamics and propose countermeasures from the human-bicycle system itself.

From the factors mentioned, it is possible to identify the main mechanisms that trigger the critical situation. When the front wheel slips, the main control input from the rider disappears, reducing the system to an inverted pendulum without user input. Events such as getting into tram tracks, lock the steering, first eliminating one of the intrinsic characteristics of bicycle's self-stability (Kooijman et al., 2011) and then, the rider is unable to input any control action. Collisions in the front assembly (front wheel, fork and handlebar) generate a sudden steering input. Bicycle malfunction such as chain slip can lead to rider disengagement. At last, avoidance manoeuvres initially occurs in a open-loop control action (Nugent et al., 2019), which leads to excessive roll and steering rates, or in a few cases, it leads to pitch over.

3.4 Active Safety Systems

The interest of including current active safety systems in the present review is to analyse the way they detect a critical scenario and what is the response provided to minimise risks.

3.4.1 Antilock Braking System (ABS)

This system consists in a constant reading of vehicle's wheels speed and it is capable of detecting when a wheel locks, decreasing the braking pressure and maintain the wheel spinning while diminishing the velocity. The main result in four-wheeled vehicles have been the possibility of maintain the control of the vehicle during the whole braking manoeuvre. Concerning motorcycles, it prevents low-side and pitch-over crashes by avoiding front wheel lock and high-side crashes by avoiding rear wheel lock. It was discovered that motorcycles with ABS system reduce in more than 20% on average the involvement in crashes (Rizzi et al., 2013). Similarly, (Teoh, 2022) found a 22% reduction of fatal crashes per year with ABS motorcycles.

3.4.2 Stability Control (SC)

Stability control, in simple terms, is the evolution of ABS, additionally processing steering input to evaluate if the current trajectory matches with driver's objective (Ferguson, 2007). When the system detects a mismatch between desired and actual behaviour, possible control actions to counteract it are independent wheel braking, differential locking or throttle reduction. This system have been implemented in high-end automobiles for more than 20 years, however, nowadays is a more common feature among mid-range cars. The reduction of fatal rollover crashes is estimated about 70 - 90% (Ferguson, 2007) Moreover, its impact has shown to reduce risk of single-vehicle accidents by 31% (Lyckegaard et al., 2015).

The possibility of developing a system like this for single-track vehicles have been scarcely explored . An attempt to stabilise roll rate in critical situations evaluated the possibilities of active suspension, concluding that this method was unable to stabilise capsize (Seiniger and Winner, 2009). Then, Seiniger et al. (2012) talks about stabilising first the roll angle and then the yaw movement, but concluding that active stabilisation for motorcycles may not be possible with today's technology. However, BoschTM developed a towards-rotation centre thrust system that prevents falls from front wheel slip (Anderson, 2018; Tsantilas, 2018), which provides new perspectives on active safety systems.

3.4.3 Steering Assistance

The closest implementation of stability control on bicycles that we found, is the steering assistance. Matsuzawa et al. (2012) develops a steering assistance system focused on improving manoeuvrability of bicycles with child restraint seats. Similarly, (Alizadehsaravi and Moore, 2022, 2023) present a steering assisted bicycle, which has enhanced low-speed stability and reduced lateral motion under external disturbances.

4 The Human

In the aim of characterise the PNR, we look for Rider Physiological Limits (RPLs), which are defined by Schwab and Meijaard (2013) as: ‘...human limitations such as the time required to sense a change in a state (time delay), the maximum force a rider can apply, the maximum speed a limb can move and its maximum acceleration.’

To know what are the RPLs, it is necessary to delve into human biomechanics of already analysed situations such as fall or slip in gait.

Thelen et al. (1996) performed experiments to measure the time required to develop 15 [Nm] of torque in ankles, comparing between males and females, young and old adults. His experiments used a visual cue to trigger the response, which had a delay of 157 [ms] for young males (YM) and 141 [ms] for young females (YF). The time to develop 15 [Nm] was of 74 and 95 [ms] for YM and YF, respectively.

Likewise, in forward fall accidents, recovery step has been proved to occur at an average constant time of 293 [ms] (Do et al., 1999). However, the first reaction detected takes place around 85.4 and 100.2 [ms], which corresponds to reflex response to the fall (Do et al., 1982).

A different approach to forward fall accidents can be found in (Van Den Bogert et al., 2002), where the threshold for a fall is given by tilt angle. The working model was based in a rigid inverted pendulum, which suppose a limitation to results due to its simplicity compared to real biomechanics. After all, his work concludes that the maximum angles where a recovery is possible are between 23° and 26°. Additionally, it was found an increase of 77% in safe walking by reducing response time from 267 to 175 [ms].

The boundaries of slipping accidents have been studied by Strandberg and Lanshammar (1981), where it was found that slip motion starts on average 0.05 [s] after heel contact in low-grip surfaces. The maximum slip distance where the result was not a fall was 0.1 [m], along with a slip velocity of 0.5 [ms⁻¹]. With these conclusions, Strandberg indicates that the friction properties of shoe-floor interface are most important for speeds below 0.5 [ms⁻¹].

These results are consistent with findings provided by Cham and Redfern (2002b) in his experiments of foot slip on leaned ramps. On the one hand, it is concluded that slip distances over 14 [cm] and slip velocities above 0.8 [ms⁻¹] will end in a fall. On the other hand, it was found a time delay between 100 and 150 [ms] before the first reaction to maintain balance. Besides, Cham and Redfern (2002a) found a reduced slip potential by modifying lower extremity joint moments when test subjects were aware of an incoming slippery surface.

Haufe et al. (2011) explored the possibilities of detecting driver intention before action using electroencephalography (EEG) and electromyography (EMG). His research focused on emergency braking, were results demonstrated that a system based on EEG and EMG detected emergency braking 130 [ms] earlier than pedal action-based systems. Similarly, Green (2000) found an average time to action the brake pedal of 0.70 - 0.75 [s], with a 0.3 [s] movement time.

Knowing that the main control input from the rider is the steering, Nugent et al. (2019) explored the reaction time in motorcycles in pre-collision scenarios. He examined the relation between time to collision (TTC) and success rate in avoiding the crash, in this case, against a car obstructing the way. With TTC = 1 [s] avoidance success was a low 6%, however, setting TTC = 1.5 [s] probability of avoiding a collision increased to 45%. Concerning response times, the median steer response time was 570 [ms], while the range for successful manoeuvres was between 370 and 770 [ms]. Alternatively, Savino et al. (2012) talks about a maximum possible delay of 280 [ms] to success in an avoidance manoeuvre. Besides, it is talked () that under emergency steering, it occurs in open-loop control during initial 250 [ms] on average. Finally, Nugent recalls over simulators’ limitations, where system delays can increase time of open-loop control up to 820 [ms].

At last, one of the closest works to human analysis in bicycle crashes is presented by Gildea et al. (2024). This work relies on deep-learning based pose estimation and inverse kinematics to analyse kinematic forms and impact patterns on bicycle falls, specially from getting into tram tracks.

5 Characterization of the point of no return

As stated in the previous section, the average response time for different accidents is around 200 - 300 [ms], which gives us the first characteristic for the PNR: the time window. In other words, the time boundary of human response is at 200 [ms], which will be called the Response Threshold (RT). If the combination of states that are outside of rideability of the bicycle occurs before of 200 [ms] since the start of the motion, the system is outside of its control boundaries.

Then, taking into account the findings from Strandberg and Lanshammar (1981) and Cham and Redfern (2002b), both results are consistent with the time window. Considering the 200 [ms] time, at 0.5 [ms⁻¹], the slipped distance is 0.1 [m], which is in accordance with conclusions of Strandberg and Lanshammar (1981). Similarly, in same time, at 0.8 [ms⁻¹], the slipped distance results in 0.16 [m], which would result in a fall according to Cham and Redfern (2002b). Therefore, the most basic characterisation of PNR for human falls from slipping is 0.14 [m] and 0.8 [ms⁻¹] within 200 [ms] since slipping starts. When any of these states is reached before

the RT, the system surpasses the PNR, since any response will continue outside of the boundaries for human standing.

Regarding forward falls, the maximum angle is 26° (Van Den Bogert et al., 2002), while applying the RT, the maximum angular velocity results in $2.27 \text{ [rad s}^{-1}\text{]}$.

Concerning bicycle crashes, we could not find literature where crash behaviour is mathematically described, the closest approach is Bretting et al. (2010), where pitch-over crashes are analysed. Britten analyses the changes in the dynamics of pitch-over accidents for different causes, comparing excessive front braking, front wheel lock by an object, and frontal crash. Surprisingly, one of the findings was that in these kind of accidents, the front wheel lifts off before the Centre of Mass (CoM) reaches the vertical position with respect to its contact point. The two possible reasons hypothesised are: potential energy stored in the elements of the system during the deceleration phase and inertia of the bodies in the rotation phase. For the objective of the present article, we can highlight that, in this case, the PNR is more related to kinetic energy than to a state of the system such as pitch angle. In other words, the PNR shows to be the moment where the front wheel loses contact with the ground.

Additionally, from Lot and Sadauckas (2021), we know that the maximum possible deceleration to avoid pitch-over motion is given by the equation

$$|a_x| < \frac{(w - b)g}{h}, \quad (1)$$

where h and b are the vertical and longitudinal CoM position, while w is the wheelbase and g is the gravitational acceleration. Using the parameters from Meijaard et al. (2007), the maximum deceleration is $7.722 \text{ [ms}^{-2}\text{]} = 0.787g$, similar to the $0.7g$ found by Bretting et al. (2010). Therefore, we can define a boundary of bicycle longitudinal deceleration in $6.87 \text{ [ms}^{-2}\text{]}$.

A braking manoeuvre over $0.7g$ will trigger a critical situation where rear wheel lifts from the ground, thus, the time to counteract the effect will be limited to the moment when the CoM is vertically aligned with the front wheel contact point.

With analogous analysis, we could explore the maximum roll rate that the rider is capable to handle and the maximum slipping related to the roll rate. For slipping and starting accidents. In the case of external perturbations, it will be necessary to analyse the maximum steering angle that the rider can handle.

6 Discussion

7 Conclusion

Acknowledgement

References

- Algurén, B. and Rizzi, M. (2022). In-depth understanding of single bicycle crashes in Sweden - Crash characteristics, injury types and health outcomes differentiated by gender and age-groups. *Journal of Transport & Health*, 24:101320.
- Alizadehsaravi, L. and Moore, J. K. (2022). The effects of a steer assist system on bicycle postural control in real-life safety challenges. In *Contributions to the 10th International Cycling Safety Conference 2022 (ICSC2022)*, pages 243–245. Technische Universität Dresden.
- Alizadehsaravi, L. and Moore, J. K. (2023). Bicycle balance assist system reduces roll and steering motion for young and older bicyclists during real-life safety challenges. *PeerJ*, 11:e16206.
- Anderson, S. (2018). Bosch Wants To Put Rockets On Your Motorcycle. <https://www.cycleworld.com/bosch-wants-to-put-rockets-on-your-motorcycle/>.
- Beck, B., Stevenson, M. R., Cameron, P., Oxley, J., Newstead, S., Olivier, J., Boufous, S., and Gabbe, B. J. (2019). Crash characteristics of on-road single-bicycle crashes: An under-recognised problem. *Injury Prevention*, 25(5):448–452.
- Boele-Vos, M., Van Duijvenvoorde, K., Doumen, M., Duivenvoorden, C., Louwerse, W., and Davidse, R. (2017). Crashes involving cyclists aged 50 and over in the Netherlands: An in-depth study. *Accident Analysis & Prevention*, 105:4–10.
- Boufous, S., De Rome, L., Senserrick, T., and Ivers, R. Q. (2013). Single- versus multi-vehicle bicycle road crashes in Victoria, Australia. *Injury Prevention*, 19(5):358–362.

- Bretting, G. P., Jansen, H. P., Callahan, M., Bogler, J., and Prunckle, J. (2010). Analysis of Bicycle Pitch-Over in a Controlled Environment. *SAE International Journal of Passenger Cars - Mechanical Systems*, 3(1):57–71.
- CBS, S. N. (2024). 684 road traffic deaths in 2023. <https://www.cbs.nl/en-gb/news/2024/15/684-road-traffic-deaths-in-2023>.
- Cham, R. and Redfern, M. S. (2002a). Changes in gait when anticipating slippery floors. *Gait & Posture*, 15(2):159–171.
- Cham, R. and Redfern, M. S. (2002b). Heel contact dynamics during slip events on level and inclined surfaces. *Safety Science*, 40(7-8):559–576.
- Commission, E. (2024). Facts and Figures Cyclists. Technical report, European Road Safety Observatory, Brussels.
- Davis, R. M. and Pless, B. (2001). BMJ bans "accidents". 322:1320–1321.
- Dialynas, G., Christoforidis, C., Happee, R., and Schwab, A. (2023). Rider control identification in cycling taking into account steering torque feedback and sensory delays. *Vehicle System Dynamics*, 61(1):200–224.
- Do, M., Breniere, Y., and Brenguier, P. (1982). A biomechanical study of balance recovery during the fall forward. *Journal of Biomechanics*, 15(12):933–939.
- Do, M. C., Schneider, C., and Chong, R. K. Y. (1999). Factors influencing the quick onset of stepping following postural perturbation.
- Ferguson, S. A. (2007). The Effectiveness of Electronic Stability Control in Reducing Real-World Crashes: A Literature Review. *Traffic Injury Prevention*, 8(4):329–338.
- Fuller, R. (2005). Towards a general theory of driver behaviour. *Accident Analysis & Prevention*, 37(3):461–472.
- Gildea, K., Hall, D., Cherry, C. R., and Simms, C. (2024). Forward dynamics computational modelling of a cyclist fall with the inclusion of protective response using deep learning-based human pose estimation. *Journal of Biomechanics*, 163:111959.
- Gildea, K., Hall, D., Mercadal-Baudart, C., Caulfield, B., and Simms, C. (2023). Computer vision-based assessment of cyclist-tram track interactions for predictive modeling of crossing success. *Journal of Safety Research*, 87:202–216.
- Gildea, K., Hall, D., and Simms, C. (2021). Configurations of underreported cyclist-motorised vehicle and single cyclist collisions: Analysis of a self-reported survey. *Accident Analysis & Prevention*, 159:106264.
- Gildea, K. and Simms, C. (2021). Characteristics of cyclist collisions in Ireland: Analysis of a self-reported survey. *Accident Analysis & Prevention*, 151:105948.
- Green, M. (2000). "How Long Does It Take to Stop?" Methodological Analysis of Driver Perception-Brake Times. *Transportation Human Factors*, 2(3):195–216.
- Gu, Y., Shao, Z., Qin, L., Lu, W., and Li, M. (2019). A Deep Learning Framework for Cycling Maneuvers Classification. *IEEE Access*, 7:28799–28809.
- Haufe, S., Treder, M. S., Gugler, M. F., Sagebaum, M., Curio, G., and Blankertz, B. (2011). EEG potentials predict upcoming emergency brakings during simulated driving. *Journal of Neural Engineering*, 8(5):056001.
- Haworth, N. and Debnath, A. K. (2013). How similar are two-unit bicycle and motorcycle crashes? *Accident Analysis & Prevention*, 58:15–25.
- Hertach, P., Uhr, A., Niemann, S., and Cavegn, M. (2018). Characteristics of single-vehicle crashes with e-bikes in Switzerland. *Accident Analysis & Prevention*, 117:232–238.
- Hess, R., Moore, J. K., and Hubbard, M. (2012). Modeling the Manually Controlled Bicycle. *IEEE Transactions on Systems, Man, and Cybernetics - Part A: Systems and Humans*, 42(3):545–557.
- Kooijman, J. and Schwab, A. (2013). A review on bicycle and motorcycle rider control with a perspective on handling qualities. *Vehicle System Dynamics*, 51(11):1722–1764.
- Kooijman, J. D. G., Meijaard, J. P., Papadopoulos, J. M., Ruina, A., and Schwab, A. L. (2011). A Bicycle Can Be Self-Stable Without Gyroscopic or Caster Effects. *Science*, 332(6027):339–342.

- Kooijman, J. D. G., Schwab, A. L., and Moore, J. K. (2009). Some Observations on Human Control of a Bicycle. In *Volume 4: 7th International Conference on Multibody Systems, Nonlinear Dynamics, and Control, Parts A, B and C*, pages 2021–2028, San Diego, California, USA. ASMEDC.
- Lloyd, J. (2016). Biomechanics of Solo Motorcycle Accidents. *Journal of Forensic Biomechanics*, 07(01).
- Lot, R. and Sadauckas, J. (2021). *Motorcycle Design: Vehicle Dynamics Concepts and Applications*, volume 1. Roberto Lot, 1 edition.
- Lyckegaard, A., Hels, T., and Bernhoft, I. M. (2015). Effectiveness of Electronic Stability Control on Single-Vehicle Accidents. *Traffic Injury Prevention*, 16(4):380–386.
- Matsuzawa, S., Sato, N., and Iwase, M. (2012). Control design of electrically-assisted steering systems for bicycles with child restraint seats. In *2012 American Control Conference (ACC)*, pages 2749–2754, Montreal, QC. IEEE.
- Meijaard, J., Papadopoulos, J. M., Ruina, A., and Schwab, A. (2007). Linearized dynamics equations for the balance and steer of a bicycle: A benchmark and review. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 463(2084):1955–1982.
- Meuleners, L. B., Fraser, M., Johnson, M., Stevenson, M., Rose, G., and Oxley, J. (2020). Characteristics of the road infrastructure and injurious cyclist crashes resulting in a hospitalisation. *Accident Analysis & Prevention*, 136:105407.
- Nugent, M., Savino, G., Mulvihill, C., Lenné, M., and Fitzharris, M. (2019). Evaluating rider steering responses to an unexpected collision hazard using a motorcycle riding simulator. *Transportation Research Part F: Traffic Psychology and Behaviour*, 66:292–309.
- Park, S.-U. and Han, I. (2001). Inverse Analysis of Pre- and Post-Impact Dynamics for Vehicle Accident Reconstruction. *Vehicle System Dynamics*, 36(6):413–433.
- Rizzi, M., Strandroth, J., Kullgren, A., Tingvall, C., and Fildes, B. (2013). EFFECTIVENESS OF ANTILOCK-BRAKES (ABS) ON MOTORCYCLES IN REDUCING CRASHES, A MULTI-NATIONAL STUDY.
- Ronné, J., Dubuis, L., and Robert, T. (2024). Assessing the handling quality of bicycles: A review of current theoretical approaches. *Vehicle System Dynamics*, pages 1–20.
- Salmon, P. M., Naughton, M., Hulme, A., and McLean, S. (2022). Bicycle crash contributory factors: A systematic review. *Safety Science*, 145:105511.
- Savino, G., Pierini, M., and Baldanzini, N. (2012). Decision logic of an active braking system for powered two wheelers. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*, 226(8):1026–1036.
- Schepers, P., Agerholm, N., Amoros, E., Benington, R., Bjørnskau, T., Dhondt, S., De Geus, B., Hagemester, C., Loo, B. P. Y., and Niska, A. (2015). An international review of the frequency of single-bicycle crashes (SBCs) and their relation to bicycle modal share. *Injury Prevention*, 21(e1):e138–e143.
- Schepers, P., Stipdonk, H., Methorst, R., and Olivier, J. (2017). Bicycle fatalities: Trends in crashes with and without motor vehicles in The Netherlands. *Transportation Research Part F: Traffic Psychology and Behaviour*, 46:491–499.
- Schepers, P. and Wolt, K. K. (2012). Single-bicycle crash types and characteristics. 2.
- Schnee, J., Stegmaier, J., and Li, P. (2021). A probabilistic approach to online classification of bicycle crashes. *Accident Analysis & Prevention*, 160:106311.
- Schwab, A. L., Dialynas, G., and Happee, R. (2018). Some Effects of Crosswind on the Lateral Dynamics of a Bicycle. In *The 12th Conference of the International Sports Engineering Association*, page 218. MDPI.
- Schwab, A. L. and Meijaard, J. P. (2013). A review on bicycle dynamics and rider control. *Vehicle System Dynamics*, 51(7):1059–1090.
- Seffen, K. A., Parks, G. T., and Clarkson, P. J. (2001). Observations on the controllability of motion of two-wheelers. *Proceedings of the Institution of Mechanical Engineers, Part I: Journal of Systems and Control Engineering*, 215(2):143–156.

- Seiniger, P., Schröter, K., and Gail, J. (2012). Perspectives for motorcycle stability control systems. *Accident Analysis & Prevention*, 44(1):74–81.
- Seiniger, P. and Winner, H. (2009). Potential of Active Suspension Systems for Vehicle Stabilization.
- Sharp, R. (1971). The Stability and Control of Motorcycles. *Journal of Mechanical Engineering Science*, 13(5):316–329.
- Strandberg, L. and Lanshammar, H. (1981). The dynamics of slipping accidents. *Journal of Occupational Accidents*, 3(3):153–162.
- Teoh, E. R. (2022). Motorcycle antilock braking systems and fatal crash rates: Updated results. *Traffic Injury Prevention*, 23(4):203–207.
- Thelen, D. G., Schultz, A. B., Alexander, N. B., and Ashton-Miller, J. A. (1996). Effects of Age on Rapid Ankle Torque Development. *The Journals of Gerontology Series A: Biological Sciences and Medical Sciences*, 51A(5):M226–M232.
- Tsantilas, S. (2018). Bosch plans to use side thrusters to stop motorcycle lowsiding. <https://newatlas.com/bosch-motorcycle-side-thrusters/54676/>.
- Utriainen, R. (2020). Characteristics of Commuters’ Single-Bicycle Crashes in Insurance Data. *Safety*, 6(1):13.
- Utriainen, R., O’Hern, S., and Pöllänen, M. (2023a). Review on single-bicycle crashes in the recent scientific literature. *Transport Reviews*, 43(2):159–177.
- Utriainen, R., Pöllänen, M., O’Hern, S., and Sihvola, N. (2023b). Single-bicycle crashes in Finland – Characteristics and safety recommendations. *Journal of Safety Research*, 87:96–106.
- Van Den Bogert, A., Pavol, M., and Grabiner, M. (2002). Response time is more important than walking speed for the ability of older adults to avoid a fall after a trip. *Journal of Biomechanics*, 35(2):199–205.
- Vanparijs, J., Int Panis, L., Meeusen, R., and De Geus, B. (2016). Characteristics of bicycle crashes in an adolescent population in Flanders (Belgium). *Accident Analysis & Prevention*, 97:103–110.
- Verlinden, O. and Kabeya, P. (2012). Presentation and assessment of rideability of a novel single-track vehicle: The Anaconda. *Vehicle System Dynamics*, 50(8):1297–1317.
- Vlakveld, W. P., Twisk, D., Christoph, M., Boele, M., Sikkema, R., Remy, R., and Schwab, A. L. (2015). Speed choice and mental workload of elderly cyclists on e-bikes in simple and complex traffic situations: A field experiment. *Accident Analysis & Prevention*, 74:97–106.
- Wang, P., Yi, J., and Liu, T. (2020). Stability and Control of a Rider–Bicycle System: Analysis and Experiments. *IEEE Transactions on Automation Science and Engineering*, 17(1):348–360.
- Wegman, F. and Schepers, P. (2024). Safe System approach for cyclists in the Netherlands: Towards zero fatalities and serious injuries? *Accident Analysis & Prevention*, 195:107396.