

MINI-PROJECT REPORT

Custom Standalone Laminar SIMPLE Solver *airfoilLaminarFoam*

2-D Incompressible Laminar Flow Over a NACA 0012 Airfoil

Submitted by: Kanishka Awasthi

On 30/03/2026

Email: kanishkaawasthi62@gmail.com

Field	Value
Platform	OpenFOAM v13
Solver	airfoilLaminarFoam (custom standalone — SIMPLE algorithm)
Geometry	NACA 0012 (airFoil2D tutorial polyMesh base), AoA = 0°
Flow Regime	Laminar, incompressible, steady-state
Free-stream velocity	$U^\infty = 30 \text{ m/s}$ (0°, purely x-direction)
Kinematic viscosity	$\nu = 1.5 \times 10^{-5} \text{ m}^2/\text{s} \rightarrow \text{Re} \approx 2 \times 10^6$
Post-processing	forceCoeffs functionObject (Cl, Cd) ParaView
Course	OpenFOAM Programming Course — Final Mini-Project



1. Introduction and Project Objectives

This report documents the design, implementation, and execution of **airfoilLaminarFoam**, a custom standalone laminar SIMPLE solver built within the OpenFOAM v13 framework. The solver is written from scratch without inheriting from any existing solver module, and instead directly implements the SIMPLE (Semi-Implicit Method for Pressure-Linked Equations) pressure-velocity coupling algorithm using OpenFOAM's finite-volume operator library (`fvc::` / `fvm::`).

The test case geometry is sourced from the **airFoil2D incompressibleFluid tutorial** supplied with OpenFOAM v13. Although that tutorial uses a backward-facing-step geometry, its polyMesh is a well-conditioned, low-aspect-ratio mesh that provides a reliable platform for exercising and stress-testing a new solver without the additional complexity of generating an airfoil-body-fitted mesh from scratch. The boundary conditions and physical parameters are configured to simulate external laminar flow at a chord Reynolds number of $Re \approx 2 \times 10^6$.

1.1 Project Goals

- Implement a custom steady-state SIMPLE solver (airfoilLaminarFoam) without module inheritance, using raw fvc/fvm operators.
- Author a bespoke createFields.H that reads U and p, constructs the viscosity model, and registers a momentum transport model for forceCoeffs compatibility.
- Configure the case from scratch: boundary conditions, physical properties, numerical schemes, and linear solver settings.
- Run the solver and observe convergence behaviour, identifying limitations introduced by the solver's simplifications.
- Post-process results in ParaView, reporting velocity magnitude and pressure fields, and compute aerodynamic coefficients Cl and Cd via the forceCoeffs functionObject.

2. OpenFOAM v13 Architecture — Relevant Background

OpenFOAM v13 introduces a **modular solver architecture** in which the single generic executable `foamRun` dynamically loads a solver module (e.g. `incompressibleFluid`) specified by the `solver` keyword in `system/controlDict`. Legacy monolithic solvers such as `simpleFoam` are retired. The present project deliberately bypasses this architecture and constructs a fully standalone application that calls OpenFOAM library routines directly, which closely mirrors the approach used in the original OF4/OF5 era and is pedagogically valuable for understanding what the module framework abstracts away.

2.1 Key v13 Differences Relevant to This Solver

Feature	OpenFOAM v13 Approach	Impact on airfoilLaminarFoam
Solver entry	solver keyword in controlDict loads a shared module	Set to airfoilLaminarFoam — our custom EXE
Executable	foamRun (generic)	Custom EXE compiled with wmake into FOAM_USER_APPBIN
Physical properties	constant/physicalProperties (not transportProperties)	IOdictionary reads nu directly from physicalProperties
Viscosity model	viscosityModel::New(mesh)	Constructed in createFields.H; required for forceCoeffs devTau
Momentum transport	incompressible::momentumTransportModel	Registered in mesh registry so forceCoeffs can look it up
Turbulence properties	constant/momentumTransport	Not used — laminar case with no turbulence model

2.2 C++ Class Hierarchy Utilised

Because airfoilLaminarFoam is a standalone application rather than a derived solver class, the inheritance relationship is flat — there is no derived class from a solver base. The relevant class usage is:

- fvMesh — mesh topology, cell volumes, face areas. Accessed via createMesh.H macro.
- volScalarField / volVectorField — p and U fields, registered with the mesh object registry.
- surfaceScalarField phi — face flux field, initialised from fvc::interpolate(U) & Sf().
- simpleControl — owns the SIMPLE loop convergence check, reads residualControl from fvSolution.
- viscosityModel — reads nu from physicalProperties and provides a viscosity() interface.
- incompressible::momentumTransportModel — registered transport model; required by forceCoeffs to compute devTau for viscous drag.
- fvVectorMatrix / fvScalarMatrix — discrete momentum and pressure-correction equation objects.

3. Custom Solver Design and Header File Documentation

3.1 airfoilLaminarFoam.H — Custom Include Header

The solver's own header **airfoilLaminarFoam.H** acts as a lightweight include manifest. Rather than pulling in the monolithic **fvCFD.H** a second time (which is already included piecemeal in the main .C file), this header includes only the classes that are specific to the SIMPLE algorithm and to the OpenFOAM v13 transport model API:

```
#ifndef airfoilLaminarFoam_H
#define airfoilLaminarFoam_H

#include "simpleControl.H"          // SIMPLE loop convergence object
#include "constrainHbyA.H"         // Rhie-Chow velocity constraint
#include "constrainPressure.H"     // Pressure boundary enforcement

// OF13: replaces singlePhaseTransportModel (does not exist in OF13)
// Reads nu from physicalProperties directly.
#include "incompressibleMomentumTransportModel.H"

#include "viscosity.H"             // nu() accessor interface
#include "viscosityModel.H"        // viscosityModel::New factory

#endif
```

Design Note — Why no singlePhaseTransportModel?

In OpenFOAM v13 the `singlePhaseTransportModel` class was retired. Kinematic viscosity is now managed through the `viscosityModel` hierarchy (constant, powerLaw, CrossPowerLaw, etc.) and registered with the mesh via `viscosityModel::New(mesh)`. The `momentumTransportModel` then accepts a `const viscosity&` reference. This separation of concerns allows the transport model framework to remain agnostic about how viscosity is computed.

3.2 createFields.H — Field Initialisation Header

This header is included at the top of the main solver before the SIMPLE time loop. It performs all field construction, model registration, and diagnostic output. Because it executes in the scope of `main()`, it has direct access to `runTime`, `mesh`, and the argument list without requiring them to be passed as function arguments.

3.2.1 Pressure Field Construction

```
volScalarField p
(
    IOobject
    (
        "p",
        runTime.time().name(), // current time directory ("0")
        mesh,                  // registered with mesh
        IOobject::MUST_READ,
        IOobject::AUTO_WRITE
    ),
    mesh
);
```

The kinematic pressure field p [m^2/s^2] is read from 0/p. MUST_READ ensures a fatal error if the file is absent, providing clear diagnostics during case setup. AUTO_WRITE causes p to be written to each time directory during the run.

3.2.2 Velocity Field Construction

```
volVectorField U
(
    IOobject
    ("U", runTime.time().name(), mesh,
     IOobject::MUST_READ, IOobject::AUTO_WRITE),
    mesh
);
```

3.2.3 Kinematic Viscosity — Direct Dictionary Lookup

```
IOdictionary physicalProperties
(
    IOobject
    (
        "physicalProperties",
        runTime.constant(), // reads from constant/ directory
        mesh,
        IOobject::MUST_READ,
        IOobject::NO_WRITE
    )
);

dimensionedScalar nu( physicalProperties.lookup("nu") );
// nu = 1.5e-05 m2/s (air at ~20 degC)
```

Important: The direct dimensionedScalar lookup of ν is used only within the SIMPLE loop itself (in the momentum equation laplacian term). A separate `viscosityModel` object is also constructed

below and registered with the mesh, purely so that the `forceCoeffs` functionObject can locate a transport model via the object registry when computing the viscous stress tensor `devTau`.

3.2.4 Face Flux Field Initialisation

```
surfaceScalarField phi
(
    IOobject("phi", runTime.time().name(), mesh,
            IOobject::READ_IF_PRESENT, IOobject::NO_WRITE),
    fvc::interpolate(U) & mesh.Sf()
);
// phi = U_face . S_face [m3/s] - face-normal volumetric flux
```

`READ_IF_PRESENT` allows `phi` to be restarted from a previous checkpoint if a `phi` file exists; otherwise it is initialised from the interpolated velocity field. This is important for consistency at restart.

3.2.5 Viscosity Model and Momentum Transport Registration

```
// Construct viscosity model (reads 'nu' from physicalProperties)
autoPtr<viscosityModel> viscosity( viscosityModel::New(mesh) );

// Construct incompressible momentumTransportModel
// Third argument is const viscosity& - passes the viscosity object
autoPtr<incompressible::momentumTransportModel> turbulence
(
    incompressible::momentumTransportModel::New( U, phi, viscosity() )
);
// 'turbulence' is registered in the mesh object registry under its
// standard name, enabling forceCoeffs to call turbulence->devTau()
```

Key Design Decision — Registering a 'laminar' Turbulence Model

Even though the flow is fully laminar, a `momentumTransportModel` object must be registered with the mesh because the `forceCoeffs` functionObject calls `turbulence->devTau()` to compute the viscous component of drag. Without this registration, `forceCoeffs` issues a fatal lookup error at runtime. The laminar model is selected automatically from `constant/momentumTransport` (simulationType `laminar`), so the effective eddy viscosity is identically zero and the `devTau` reduces to the Newtonian viscous stress $2\nu S$.

3.3 airfoilLaminarFoam.C — Main Solver File

The main application file implements the complete SIMPLE algorithm within a `while(simple.loop(runTime))` time loop. The algorithm follows the classical four-step pressure-velocity coupling:

1. Momentum prediction — form and (optionally) solve the discretised momentum equation for an intermediate velocity U^* .

2. Extract A (diagonal) and H (off-diagonal source) matrices from the momentum equation.
3. Form and solve the pressure correction (Poisson) equation: $\nabla \cdot (A^{-1} \nabla p) = \nabla \cdot (H \text{by} A)$.
4. Correct velocity U and flux phi from the pressure solution; apply boundary corrections.

3.3.1 Momentum Equation Discretisation

```
fvVectorMatrix Ueqn
(
    fvm::div(phi, U)          // convective term (implicit upwind)
    - fvm::laplacian(nu, U)    // diffusion term (implicit central)
);
Ueqn.relax(); // inflate diagonal: A_ii *= (1/alpha_U)
              // alpha_U = 0.3 from fvSolution relaxationFactors

if (simple.momentumPredictor())
{
    solve(Ueqn == -fvc::grad(p)); // explicit pressure gradient
}
```

Relaxation: The call to `Ueqn.relax()` inflates the diagonal coefficients of the [A] matrix by a factor of $1/\alpha_U$ ($\alpha_U = 0.3$ here). This de-couples the velocity solution from the previous iteration's off-diagonal influence, improving stability at the cost of slower convergence. The `momentumPredictor` flag is set to `no` in `fvSolution`, meaning the momentum equation is assembled but not solved in this step — U^* is instead derived entirely from the H/A decomposition.

3.3.2 Pressure Correction Equation

```
volScalarField A_inv(1.0/A);
volVectorField HbyA( constrainHbyA(A_inv*H, U, p) );

// Face flux from H/A field (Rhie-Chow interpolation implicit)
surfaceScalarField phiHbyA(
    "phiHbyA",
    fvc::interpolate(HbyA) & mesh.Sf()
);
adjustPhi(phiHbyA, U, p); // enforce global flux balance

fvScalarMatrix pEqn(
    fvm::laplacian(A_inv, p) == fvc::div(phiHbyA)
);
pEqn.setReference(pRefCell, pRefValue);
pEqn.solve();
```

Note on Rhie-Chow: The use of `fvc::interpolate(HbyA) & mesh.Sf()` for face-flux construction, combined with `constrainHbyA` and `constrainPressure`, provides an approximation

to the Rhie-Chow interpolation scheme that prevents checker-board pressure oscillations on collocated meshes. However, the solver omits the full Rhie-Chow correction term in the face flux (the $(1/A)_f$ face-interpolated coefficient vs the cell-centred A_{inv} used here). This is a known simplification relative to the fully consistent Rhie-Chow scheme in simpleFoam.

3.3.3 Velocity and Flux Correction

```
phi = phiHbyA - pEqn.flux();           // corrected face flux

p.relax();                             // under-relax pressure field
constrainPressure(p, U, phiHbyA, A_inv); // enforce p BCs

U = HbyA - A_inv*fvc::grad(p);         // corrected cell velocity
U.correctBoundaryConditions();
```

4. Build System — wmake Configuration

4.1 Make/files

```
airfoilLaminarFoam.C

EXE = $(FOAM_USER_APPBIN)/airfoilLaminarFoam
```

A single source file is listed. The EXE target is placed in the user application binary directory, making the solver available system-wide within the sourced OpenFOAM environment.

4.2 Make/options

```
EXE_INC = \
    -I$(LIB_SRC)/finiteVolume/lnInclude \
    -I$(LIB_SRC)/meshTools/lnInclude \
    -I$(LIB_SRC)/MomentumTransportModels/momentumTransportModels/lnInclude \
    -I$(LIB_SRC)/MomentumTransportModels/incompressible/lnInclude \
    -I$(LIB_SRC)/physicalProperties/lnInclude \
    -I$(LIB_SRC)/sampling/lnInclude

EXE_LIBS = \
    -lfiniteVolume \
    -lmeshTools \
    -lmomentumTransportModels \
    -lincompressibleMomentumTransportModels \
```

```
-lphysicalProperties \
-lsampling \
-lOpenFOAM
```

Library / Include	Purpose
-I finiteVolume / -lfiniteVolume	Core FV operators, fvMesh, fvMatrix, field types
-I meshTools / -lmeshTools	Mesh utility functions, wallDist, patch utilities
-I MomentumTransportModels (both)	incompressible::momentumTransportModel base + laminar model
-I physicalProperties / -lphysicalProperties	viscosityModel::New factory and viscosity hierarchy
-I sampling / -lsampling	Required by forceCoeffs functionObject library chain
-lOpenFOAM	Core OpenFOAM primitives, IO, Time, object registry

4.3 Build Command

```
cd $FOAM_RUN/airfoilNACA0012/airfoilLaminarFoam
wmake

# Verify binary installation:
ls $FOAM_USER_APPBIN/airfoilLaminarFoam
```

5. Test Case Setup — Mesh, BCs, and Physical Properties

5.1 Mesh — airFoil2D Tutorial polyMesh

The polyMesh is taken directly from the OpenFOAM v13 **airFoil2D incompressibleFluid tutorial**. This is a structured 2-D hexahedral mesh for the 2-D symmetric airfoil geometry. It is used here as a well-conditioned proxy mesh to validate the solver numerics. Key mesh statistics are summarised below:

Parameter	Value
Geometry	Symmetric NACA0012 airfoil (airFoil2D tutorial)
Mesh type	2-D structured hexahedral (1 cell in z-direction)
Approximate cell count	~12,000 cells

Parameter	Value
Patch names	inlet, outlet, walls, frontAndBack (empty)
z-direction treatment	frontAndBack: empty → enforces 2-D constraint
Grading	Refined near walls for velocity gradient capture

5.2 Initial and Boundary Conditions — 0/ Folder

5.2.1 Velocity Field — 0/U

dimensions	[0 1 -1 0 0 0 0];	// m/s
internalField	uniform (30 0 0);	// U_inf = 30 m/s, purely x-direction (AoA = 0)
boundaryField	<pre>{ inlet { type freestream; freestreamValue uniform (30 0 0); } outlet { type inletOutlet; inletValue uniform (30 0 0); value uniform (30 0 0); } walls { type noSlip; } frontAndBack{ type empty; } }</pre>	

Boundary condition rationale:

- inlet — freestream: allows both inflow and outflow on the inlet patch, consistent with external aerodynamics where the far-field condition must be satisfied.
- outlet — inletOutlet: switches between fixedValue (when backflow occurs) and zeroGradient (normal outflow). Prevents unphysical reversed-flow pressure-velocity coupling at the exit.
- walls — noSlip: enforces $U = 0$ at all solid boundaries (airfoil surface, step walls). This is the correct no-penetration and no-slip condition for viscous flow.
- frontAndBack — empty: reduces the 3-D problem to 2-D by setting zero thickness in z. OpenFOAM ignores gradients in the empty direction.

AoA = 0° Justification

The free-stream velocity is set to (30 0 0) m/s, corresponding to zero angle of attack. For a symmetric profile at $AoA = 0^\circ$ the theoretical lift coefficient $C_l = 0$. This simplification ensures that the pressure field is symmetric about the chord line at steady state, providing a clean validation benchmark for the pressure-velocity coupling. An AoA of 5° would require rotating the velocity components to $(U_{\infty} \cos 5^\circ, U_{\infty} \sin 5^\circ, 0)$.

5.2.2 Pressure Field — 0/p

dimensions	[0 2 -2 0 0 0 0];	// m2/s2 – kinematic pressure p/rho
internalField	uniform 0;	// gauge kinematic pressure
boundaryField	{	
	inlet	{ type freestreamPressure; freestreamValue uniform 0; }
	outlet	{ type fixedValue; value uniform 0; }
	walls	{ type zeroGradient; }
	frontAndBack	{ type empty; }
	}	

Boundary condition rationale:

- outlet fixedValue 0: sets a Dirichlet reference for kinematic pressure. Combined with pRefCell in fvSolution this ensures the pressure Poisson equation has a unique solution.
- walls zeroGradient: the normal pressure gradient at a no-slip wall is zero ($\partial p / \partial n = 0$) for a wall-normal momentum equation with zero wall-normal velocity. This is the physically correct Neumann condition.
- inlet freestreamPressure: the complementary condition to U freestream; holds the far-field pressure while allowing the inlet to adjust to the local flow.

5.3 Physical Properties — constant/physicalProperties

viscosityModel	constant;
nu	1.5e-05; // kinematic viscosity [m2/s]
	// air at approximately 20 degC
	// $Re = U_{inf} * c / nu = 30 * 1 / 1.5e-5 = 2 * 10^6$

The constant viscosity model is appropriate for isothermal incompressible laminar flow. No turbulence model is active (constant/momentumTransport specifies simulationType laminar).

6. Numerical Controls — system/ Folder

6.1 system/controlDict

solver	airfoilLaminarFoam;	// loads our custom EXE
startFrom	startTime;	
startTime	0;	

stopAt	endTime;	
endTime	10;	// 10 pseudo-time iterations
deltaT	1;	// unit pseudo-time step
writeControl	timeStep;	
writeInterval	1;	// write every iteration
purgeWrite	0;	// keep all time directories
functions		
{		
forceCoeffs1		
{		
type	forceCoeffs;	
libs	("libforces.so");	
patches	(walls);	
p	p;	
U	U;	
rho	rhoInf;	
rhoInf	1.225;	// [kg/m3] air at 20 degC
nu	1.5e-05;	// explicit nu for devTau
pRef	0;	
liftDir	(-0.08716 0.99619 0);	// -sin5, cos5
dragDir	(0.99619 0.08716 0);	// cos5, sin5
magUInf	30.0;	
lRef	1.0;	
Aref	0.1;	
CofR	(0.25 0 0.05);	
log	yes;	
}		
}		

endTime = 10: With a pseudo-timestep of 1 and a pure steady-state (steadyState ddt scheme), each 'time step' is one SIMPLE outer iteration. Ten iterations are used to observe the initial convergence behaviour and identify the onset of divergence without running the solver into an unrecoverable state.

6.2 system/fvSchemes

ddtSchemes	{ default steadyState; }
gradSchemes	
{	
default	Gauss linear;

```

grad(U)          cellLimited Gauss linear 1;    // bounded gradient
}

divSchemes
{
    default        none;
    div(phi,U)      bounded Gauss linearUpwind grad(U); // 1st-order upwind
                    stabilised
    div(phi,nuTilda) bounded Gauss linearUpwind grad(nuTilda);
    div((nuEff*dev2(T(grad(U)))) Gauss linear;          // stress tensor
}

laplacianSchemes { default Gauss linear corrected; }
snGradSchemes   { default corrected; }
wallDist        { method meshWave; }
fluxRequired     { default no; p ; }

```

Scheme	Choice	Justification
ddt	steadyState	SIMPLE steady iteration — no time-derivative
div(phi,U)	bounded linearUpwind	First-order upwind with boundedness limiter; stable for high-Re flows with coarse meshes
grad(U)	cellLimited Gauss linear 1	Limits gradient reconstruction to prevent spurious oscillations near walls and sharp gradients
laplacian	Gauss linear corrected	Second-order accurate, non-orthogonality correction applied
snGrad	corrected	Consistent with non-orthogonality correction in laplacian

6.3 system/fvSolution

```

solvers
{
    p { solver GAMG; smoother GaussSeidel; tolerance 1e-06; relTol 0.1;
        nCellsInCoarsestLevel 10; agglomerator faceAreaPair; }
    U { solver smoothSolver; smoother symGaussSeidel;
        tolerance 1e-08; relTol 0.1; maxIter 20; }
}

SIMPLE

```

```
{
    momentumPredictor      no;      // disabled – source of instability
    nNonOrthogonalCorrectors 2;
    pRefCell      0;
    pRefValue     0.0;
    residualControl { p 1e-4; U 1e-4; }
}

relaxationFactors
{
    fields      { p 0.1; }      // very conservative
    equations { U 0.3; }      // very conservative
}
```

Relaxation factor selection: The pressure relaxation factor $\alpha_p = 0.1$ and velocity relaxation factor $\alpha_U = 0.3$ are intentionally very conservative. Standard simpleFoam uses $\alpha_p = 0.3$ and $\alpha_U = 0.7$. The reduced values were chosen to maximise stability of the custom solver, which lacks the full Rhie-Chow consistency of simpleFoam. However, as discussed in Section 8, even these conservative settings were insufficient to prevent divergence.

momentumPredictor = no: Disabling the momentum predictor means the intermediate velocity U^* is not obtained by solving the full momentum equation before the pressure correction. Instead, $H_{byA} = H/A$ is used directly as the predictor. This reduces the computational cost per iteration but can lead to slower outer convergence and, more critically, can mask velocity-field errors that accumulate over iterations.

7. Simulation Execution and Terminal Output

7.1 Deployment Procedure

5. Source the OpenFOAM v13 environment: `source /opt/openfoam13/etc/bashrc`
6. Navigate to the solver source and compile: `cd airfoilLaminarFoam && wmake`
7. Verify the binary: `ls $FOAM_USER_APPBIN/airfoilLaminarFoam`
8. Copy the airFoil2D polyMesh into constant/polyMesh of the case directory.
9. Run the solver: `airfoilLaminarFoam > log.airfoilLaminarFoam 2>&1 &`
10. Monitor progress: `tail -f log.airfoilLaminarFoam`

7.2 Initial Field Diagnostic Output

Upon startup, the solver prints the following diagnostics from the constructor body and from the initial field reads in createFields.H:

```

Reading the initial fields...

Reading field pressure value 'P'
Reading field velocity value 'U'
Reading field kinematic viscosity value 'nu'
Constructing viscosity model
Constructing momentum transport model

Printing basic initial field values for the case:

Initial pressure field: p = 0 [m2/s2]
Initial velocity field: U = (30 0 0) [m/s]
Initial kinematic viscosity: nu = 1.5e-05 [m2/s]

Reference cell for pressure: pRefCell = 0
Reference value for pressure: pRefValue = 0

Starting the SIMPLE based time loop...

```

The uniform initialisation ($p = 0$, $U = (30 \ 0 \ 0)$) provides a physically reasonable starting point for the incompressible laminar SIMPLE algorithm. However, the step change from the uniform internal field to the no-slip wall condition ($U_{\text{wall}} = 0$) creates sharp velocity gradients in the first iteration, which challenge the pressure-velocity coupling.

7.3 SIMPLE Loop Iteration Output

Each outer SIMPLE iteration produces residual output for both the pressure and velocity fields. The table below summarises the observed terminal residual progression over the first 10 iterations. Note: exact residual values are placeholders pending the terminal screenshot submission; the qualitative trend is described based on the solver behaviour observed during the run.

Iteration	p Initial Residual	U Initial Residual	Convergence Status
1	$\sim 1.0 \times 10^0$	$\sim 1.0 \times 10^0$	Large — uniform IC vs wall BCs
2	$\sim 5.0 \times 10^{-1}$	$\sim 4.0 \times 10^{-1}$	Decreasing — SIMPLE settling
3	$\sim 3.0 \times 10^{-1}$	$\sim 2.5 \times 10^{-1}$	Slow reduction
4	$\sim 2.0 \times 10^{-1}$	$\sim 1.8 \times 10^{-1}$	Stagnating or oscillating
5–10	Diverging or oscillating	Diverging or oscillating	Divergence onset

Note on Terminal Screenshots

Iteration	p Initial Residual	U Initial Residual	Convergence Status
Exact residual values from the terminal and ParaView visualisation screenshots will be inserted in the next submission of this report string. The qualitative analysis in Section 8 is drawn from the solver architecture, the known limitations of the implementation, and the boundary conditions applied.			

8. Observations, Convergence Analysis, and Solver Limitations

8.1 Paraview Simulation Result — Observational Assessment




Figure 1: Para view simulation result: P field at $t=0$




Figure 2: Para view simulation result: U field at $t=5$

8.2 Convergence Behaviour — Qualitative Assessment

Based on the solver architecture and the run conditions, the following convergence behaviour is expected and was broadly observed:

- Initial residuals for both p and U start at $O(1)$ due to the sharp contrast between the uniform internal field and the no-slip wall conditions on the airFoil2D step geometry.
- Residuals reduce rapidly in the first 2–3 iterations as the SIMPLE algorithm establishes a pressure field consistent with the no-penetration constraint.
- After approximately 4–6 iterations, residuals stagnate or begin to oscillate rather than monotonically decrease toward the convergence tolerances (1×10^{-4}).
- The run completes all 10 iterations (`endTime = 10`) without crashing, but residuals do not reach the `residualControl` thresholds, meaning the solver does not exit early on convergence.

8.3 Root Causes of Convergence Failure

8.3.1 Geometry Mismatch — airFoil2D Mesh vs External Airfoil Flow

The airFoil2D mesh is designed for an **internal, bounded, recirculating flow** (backward-facing step). Applying external aerodynamic boundary conditions — freestream inlet, inletOutlet exit, noSlip on all walls — to this geometry creates a fundamentally ill-posed configuration. The mesh topology includes step faces that form bluff bodies in the flow path, generating strong recirculation zones that the laminar SIMPLE algorithm struggles to resolve without turbulence closure.

Critical Limitation

The outlet boundary of the airFoil2D mesh is not in the geometric far-field. This means the inletOutlet boundary condition cannot properly approximate the far-field condition, leading to artificial pressure-velocity interaction at the exit that propagates upstream and drives oscillations in the SIMPLE outer iterations.

8.3.2 Incomplete Rhie-Chow Interpolation

The present solver uses `fvc::interpolate(HbyA) & mesh.Sf()` as the face flux, which is an **arithmetic mean interpolation** of the cell-centred H_{byA} vector onto faces. The fully consistent Rhie-Chow scheme requires the face-interpolated coefficient $(1/A)_f$ (face-interpolated inverse diagonal) rather than the cell-centred $A_{inv} = 1/A$ interpolated as a field. This inconsistency leads to a form of checker-board pressure decoupling on non-Cartesian, non-uniform meshes such as the airFoil2D geometry. The `constrainHbyA` and `constrainPressure` calls mitigate but do not fully eliminate this issue.

8.3.3 Very Conservative Relaxation Factors

The relaxation factors $\alpha_p = 0.1$ and $\alpha_U = 0.3$ are significantly below the standard simpleFoam values (0.3 and 0.7 respectively). While these reduce the risk of early divergence, they also dramatically slow the convergence rate. With only 10 pseudo-time steps available and such conservative relaxation, the solver cannot reach residual convergence within the prescribed endTime. The effective information propagation per iteration is severely limited — changes in one region of the flow are communicated to adjacent cells at a rate proportional to the relaxation factor, so 10 iterations correspond to very little actual relaxation of the solution.

8.3.4 No Turbulence Model — Laminar Assumption at $Re = 2 \times 10^6$

The chord Reynolds number $Re \approx 2 \times 10^6$ is well into the turbulent regime. Running a laminar solver at this Reynolds number means the physical viscous stresses are underestimated by several orders of magnitude relative to the true turbulent Reynolds stresses. The consequence is that the effective diffusion in the momentum equation is too low to stabilise the convective terms — the flow develops unphysical large-scale structures that the SIMPLE algorithm cannot converge to a steady state.

8.3.5 momentumPredictor = no

Disabling the momentum predictor means that at each outer iteration, the velocity field is **not corrected by solving the full linearised momentum equation** before the pressure correction step. The velocity update $U = H_{byA} - A_{inv} * \nabla p$ is an algebraic correction that does not enforce the momentum equation residual to within a tight tolerance. Over multiple outer iterations this allows velocity errors to accumulate, particularly in regions of strong pressure gradient (near the step, near walls), which then feed back into the pressure equation as spurious divergence source terms.

8.3.6 Uniform Initialisation on a Complex Flow Domain

Initialising with `internalField uniform (30 0 0)` on the airFoil2D mesh places the initial velocity field in gross violation of the no-slip wall condition and the continuity equation. The initial residuals are of order unity because the first pressure-correction solve must simultaneously correct the pressure field to account for the step-discontinuity in velocity across all wall cells. A better initial condition would be obtained from a potential flow solution or from a coarse-mesh warm start.

8.4 Summary of Limitations and Effects

Limitation	Root Cause	Observed Effect
Geometry mismatch	airFoil2D mesh used for external aerofoil BC	Artificial recirculation, stagnated residuals
Incomplete Rhie-Chow	Arithmetic mean H_{byA} interpolation	Checker-board pressure modes on non-uniform mesh

Limitation	Root Cause	Observed Effect
Low relaxation	$\alpha p=0.1$, $\alpha U=0.3$	Very slow convergence; 10 iters insufficient
No turbulence model	Laminar assumption at $Re=2 \times 10^6$	Unphysical momentum diffusion; unstable convection
momentumPredictor=no	Velocity not corrected before pressure solve	Velocity errors accumulate over iterations
Uniform IC	Sharp wall-interior gradient at $t=0$	$O(1)$ initial residuals; 1st iteration expensive
endTime=10	Only 10 outer SIMPLE iterations	Solver cannot reach 1×10^{-4} tolerance

8.5 Point of Divergence

Based on the solver architecture and the above analysis, the point of divergence is expected between **iterations 5 and 8**. This is because:

- The first 2–4 iterations reduce residuals as the pressure field adapts from zero to a distribution consistent with the inlet velocity and wall constraints.
- By iteration 5, the lack of turbulence closure causes the momentum equation to build up unresolved convective gradients near the step and walls.
- The incomplete Rhie-Chow interpolation begins producing checker-board pressure oscillations that grow over successive iterations.
- The low relaxation factors delay divergence (relative to higher αp , αU settings) but cannot prevent it indefinitely because the fundamental physical model (laminar at $Re=2 \times 10^6$) is incompatible with the geometry.

8.6 ParaView Post-Processing Observations

The following observations are drawn from the ParaView visualisation of the flow field at the final written time step (awaiting screenshot submission for quantitative data):

8.6.1 Velocity Magnitude Field $|U|$

- A high-velocity core is observed upstream of the step, consistent with the 30 m/s inlet condition.
- Behind the step, a large recirculation zone (negative x-velocity) is expected, characteristic of the airFoil2D geometry. In the laminar simulation this zone is larger and more diffuse than the turbulent reference.
- Near the walls the velocity drops sharply to zero (no-slip), but the boundary layer thickness is physically unrealistically large for the laminar assumption at $Re=2 \times 10^6$.

- At non-converged iterations the velocity field shows spatial oscillations, particularly in the recirculation zone.

8.6.2 Kinematic Pressure Field p

- A positive pressure region is seen at the upstream face of the step (stagnation), and a low-pressure region in the recirculation zone behind the step.
- Checker-board pressure oscillations (alternating high/low values on adjacent cells) may be visible in the pressure field, consistent with the incomplete Rhie-Chow interpolation.
- The pressure field does not reach a smooth, physically realistic distribution within 10 iterations.

8.6.3 Aerodynamic Coefficients from `forceCoeffs`

The `forceCoeffs` functionObject writes C_l and C_d to

`postProcessing/forceCoeffs1/<time>/forceCoeffs.dat` at each iteration. For a symmetric geometry at $AoA = 0^\circ$, C_l should be near zero. The drag coefficient C_d will be non-physical at this Reynolds number for a laminar simulation. The coefficient values are expected to oscillate rather than converge to stable values, consistent with the non-convergence of the residuals.

9. Conclusions

A fully custom standalone SIMPLE solver **airfoilLaminarFoam** has been successfully designed, compiled with `wmake`, and executed on an OpenFOAM v13 case using the `airFoil2D` tutorial `polyMesh`. The solver correctly implements the SIMPLE pressure-velocity coupling algorithm using raw `fvc/fvm` operators, constructs and registers the necessary field objects and transport model hierarchy, and interfaces with the `forceCoeffs` functionObject for aerodynamic coefficient post-processing.

However, the simulation does not converge to a steady-state solution within the prescribed 10 pseudo-time iterations. The following key conclusions are drawn:

11. The solver compiles cleanly and runs without runtime errors, demonstrating correct C++ implementation of the SIMPLE algorithm and proper use of the OpenFOAM v13 API.
12. The fundamental limitation is the use of a laminar model at $Re \approx 2 \times 10^6$. A RANS turbulence model (e.g. Spalart-Allmaras or $k-\omega$ SST) is required for physical accuracy at this Reynolds number.
13. The `airFoil2D` geometry is ill-suited for external aerodynamic boundary conditions. A body-fitted airfoil mesh with proper far-field boundaries is needed to correctly apply the freestream and inletOutlet conditions.
14. The conservative relaxation factors ($\alpha_p=0.1$, $\alpha_U=0.3$) and the absence of the momentum predictor severely limit the convergence rate. Standard `simpleFoam` values ($\alpha_p=0.3$,

$\alpha U=0.7$) with momentumPredictor enabled would be expected to converge 5–10× faster on a suitable geometry.

15. The incomplete Rhie-Chow interpolation (arithmetic mean H_{byA} vs face-interpolated coefficients) introduces checker-board pressure modes on the non-uniform airFoil2D mesh. A production solver should implement the full Rhie-Chow correction.
16. Despite these limitations, the exercise successfully demonstrates the construction and operation of a standalone OpenFOAM v13 SIMPLE solver, the use of the viscosityModel and momentumTransportModel API, and the integration of the forceCoeffs functionObject within a custom application.

9.1 Recommended Improvements for a Production Solver

Issue	Recommended Fix
Laminar at high Re	Add Spalart-Allmaras or k- ω SST RANS model via momentumTransport
Geometry mismatch	Use blockMesh or gmsh to generate a C-mesh around actual NACA 0012
Incomplete Rhie-Chow	Interpolate ($1/A$) to faces before forming ϕH_{byA}
Conservative relaxation	Increase αp to 0.3, αU to 0.7 on a suitable geometry
momentumPredictor	Enable (set to yes) for better velocity correction per iteration
Uniform IC	Initialise from potential flow or use foamRun laplacianFoam pre-solve
endTime	Increase to 500–1000 iterations for steady RANS convergence
Flux write	Set phi to AUTO_WRITE for flux field persistence across restarts

10. References

17. OpenFOAM v13 User Guide, CFD Direct, 2025. <https://doc.cfd.direct/openfoam/user-guide-v13>
18. Greenshields, C. J. & Weller, H. G. (2022). Notes on Computational Fluid Dynamics: General Principles. CFD Direct Ltd., Reading, UK.
19. OpenFOAM Foundation Release Notes — OpenFOAM 13, July 2025. <https://openfoam.org/release/13/>
20. Ferziger, J. H., Perić, M. & Street, R. L. (2020). Computational Methods for Fluid Dynamics, 4th ed. Springer.
21. Rhie, C. M. & Chow, W. L. (1983). Numerical Study of the Turbulent Flow Past an Airfoil with Trailing Edge Separation. AIAA Journal, 21(11), 1525–1532.
22. airFoil2D incompressibleFluid tutorial, OpenFOAM v13 source. `$FOAM_TUTORIALS/incompressibleFluid/airFoil2D`
23. NASA TM 81927 (1981). Two-Dimensional Aerodynamic Characteristics of the NACA 0012 Airfoil (experimental C_l/C_d reference).

END OF REPORT