

L^AT_EX 2_ε Cheat Sheet

Document classes

book Default is two-sided.
report No \part divisions.
article No \part or \chapter divisions.
letter Letter (?).
slides Large sans-serif font.

Used at the very beginning of a document:
\documentclass{class}. Use \begin{document} to start contents and \end{document} to end the document.

Common documentclass options

10pt/11pt/12pt Font size.
letterpaper/a4paper Paper size.
twocolumn Use two columns.
twoside Set margins for two-sided.
landscape Landscape orientation. Must use dvips -t landscape.
draft Double-space lines.
Usage: \documentclass[opt,opt]{class}.

Packages

fullpage Use 1 inch margins.
anysize Set margins: \marginsize{l}{r}{t}{b}.
multicol Use *n* columns: \begin{multicols}{n}.
latexsym Use L^AT_EX symbol font.
graphicx Show image: \includegraphics[width=x]{file}.
url Insert URL: \url{http://...}.
Use before \begin{document}. Usage: \usepackage{package}

Title

\author{text} Author of document.
\title{text} Title of document.
\date{text} Date.
These commands go before \begin{document}. The declaration \maketitle goes at the top of the document.

Miscellaneous

\pagestyle{empty} Empty header, footer and no page numbers.

Document structure

\part{title} \subsubsection{title}
\chapter{title} \paragraph{title}
\section{title} \subparagraph{title}
\subsection{title}
Section commands can be followed with an *, like \section*{title}, to suppress heading numbers.
\setcounter{secnumdepth}{x} suppresses heading numbers of depth > x, where chapter has depth 0.

Text environments

\begin{comment} Comment block (not printed).
\begin{quote} Indented quotation block.
\begin{quotation} Like quote with indented paragraphs.
\begin{verse} Quotation block for verse.

Lists

\begin{enumerate} Numbered list.
\begin{itemize} Bulleted list.
\begin{description} Description list.
\item text Add an item.
\item[x] text Use x instead of normal bullet or number. Required for descriptions.

References

\label{marker} Set a marker for cross-reference, often of the form \label{sec:item}.
\ref{marker} Give section/body number of marker.
\pageref{marker} Give page number of marker.
\footnote{text} Print footnote at bottom of page.

Floating bodies

\begin{table}[place] Add numbered table.
\begin{figure}[place] Add numbered figure.
\begin{equation}[place] Add numbered equation.
\caption{text} Caption for the body.
The place is a list valid placements for the body. t=top, b=bottom, p=separate page, !=place even if ugly.
Captions and label markers should be within the environment.

Text properties

Font face

Command	Declaration	Effect
\textrm{text}	{\rmfamily text}	Roman family
\textsf{text}	{\sffamily text}	Sans serif family
\texttt{text}	{\ttfamily text}	Typewriter family
\textmd{text}	{\mdseries text}	Medium series
\textbf{text}	{\bfseries text}	Bold series
\textup{text}	{\upshape text}	Upright shape
\textit{text}	{\itshape text}	<i>Italic shape</i>
\textsl{text}	{\slshape text}	<i>Slanted shape</i>
\textsc{text}	{\scshape text}	SMALL CAPS SHAPE
\emph{text}	{\em text}	<i>Emphasized</i>
\textnormal{text}	{\normalfont text}	Document font
\underline{text}		<u>Underline</u>

The command (tttt) form handles spacing better than the declaration (tttt) form.

Font size

\tiny	tiny	\Large	Large
\scriptsize	scriptsize	\LARGE	LARGE
\footnotesize	footnotesize		
\small	small	\huge	huge
\normalsize	normalsize		
\large	large	\Huge	Huge

These are declarations and should be used in the form {\small ...}, or without braces to affect the entire document.

Verbatim text

\begin{verbatim} Verbatim environment.
\begin{verbatim*} Spaces are shown as ␣.
\verb!text! Text between the delimiting characters (in this case '!') is verbatim.

Justification

Environment	Declaration
\begin{center}	\centering
\begin{flushleft}	\raggedright
\begin{flushright}	\raggedleft

Miscellaneous

\linespread{x} changes the line spacing by the multiplier x.

Text-mode symbols

Symbols

&	\&	~	_	...	\ldots	•	\textbullet
\$	\\$	^	\^{}{}		\textbar	\	\textbackslash
%	\%	~	\~{}{}	#	\#	§	\S

Accents

ò \‘o	ó \’o	ô \ˆo	õ \˜o	ō \=o
ô \.o	ö \¨o	q \c o	õ \v o	ö \H o
ç \c c	q \d o	q \b o	õ \t oo	œ \oe
Œ \OE	æ \ae	Æ \AE	å \aa	Å \AA
ø \o	Ø \O	ı \l	L \L	ı \i
J \j	i \i	ı \i	ı \i	ı \i

Delimiters

‘ ‘ ‘ ‘ ‘ ‘	{ \{	[[[[[[((((((< \textless
, , , , , ,	} \}]]]]]]))))))	> \textgreater

Dashes

Name	Source	Example	Usage
hyphen	-	X-ray	In words.
en-dash	--	1-5	Between numbers.
em-dash	---	Yes—or no?	Punctuation.

Line and page breaks

\\ Begin new line without new paragraph.
* Prohibit pagebreak after linebreak.
\kill Don't print current line.
\pagebreak Start new page.
\noindent Do not indent current line.

Miscellaneous

\today January 11, 2010.
\$sim\$ Prints ~ instead of \~{}, which makes ~.
~ Space, disallow linebreak (W.J.~Clinton).
\@. Indicate that the . ends a sentence when following an uppercase letter.
\hspace{l} Horizontal space of length l (Ex: l = 20pt).
\vspace{l} Vertical space of length l.
\rule{w}{h} Line of width w and height h.

Tabular environments

tabbing environment

\= Set tab stop. \> Go to tab stop.
Tab stops can be set on “invisible” lines with \kill at the end of the line. Normally \\ is used to separate lines.

tabular environment

```
\begin{array}[pos]{cols}
\begin{tabular}[pos]{cols}
\begin{tabular*}{width}[pos]{cols}
```

tabular column specification

```
l      Left-justified column.
c      Centered column.
r      Right-justified column.
p{width} Same as \parbox[t]{width}.
@{decl} Insert decl instead of inter-column space.
|      Inserts a vertical line between columns.
```

tabular elements

```
\hline      Horizontal line between rows.
\cline{x-y} Horizontal line across columns x through y.
\multicolumn{n}{cols}{text}
           A cell that spans n columns, with cols column
           specification.
```

Math mode

To use math mode, surround text with \$ or use \begin{equation}.

```
Superscript^x ~{x}      Subscript_x _{x}
frac{x}{y}      \frac{x}{y}      sum_{k=1}^n \sum_{k=1}^n
sqrt[n]{x}      \sqrt[n]{x}      prod_{k=1}^n \prod_{k=1}^n
```

Math-mode symbols

```
≤ \leq      ≥ \geq      ≠ \neq      ≈ \approx
× \times    ÷ \div      ± \pm       · \cdot
° ~{\circ}  ° \circ     ′ \prime  … \cdots
∞ \infty    ¬ \neg      ∧ \wedge √ \vee
⊃ \supset   ∀ \forall     ∈ \in    → \rightarrow
⊂ \subset   ∃ \exists     ∉ \notin ⇒ \Rightarrow
∪ \cup      ∩ \cap      | \mid   ⇔ \Leftrightarrow
â \dot a    â \hat a    ā \bar a  ã \tilde a
α \alpha    β \beta     γ \gamma  δ \delta
ε \epsilon  ζ \zeta      η \eta    ε \varepsilon
θ \theta    ι \iota     κ \kappa  ϑ \vartheta
λ \lambda    μ \mu      ν \nu     ξ \xi
π \pi        ρ \rho     σ \sigma  τ \tau
υ \upsilon   φ \phi     χ \chi    ψ \psi
ω \omega     Γ \Gamma    Δ \Delta  Θ \Theta
Λ \Lambda    Ξ \Xi     Π \Pi     Σ \Sigma
Υ \Upsilon   Φ \Phi     Ψ \Psi     Ω \Omega
```

Bibliography and citations

When using BibTeX, you need to run latex, bibtex, and latex twice more to resolve dependencies.

Citation types

```
\cite{key}      Full author list and year. (Watson and Crick
1953)
\citeA{key}     Full author list. (Watson and Crick)
\citeN{key}     Full author list and year. Watson and Crick
(1953)
\shortcite{key} Abbreviated author list and year. ?
\shortciteA{key} Abbreviated author list. ?
\shortciteN{key} Abbreviated author list and year. ?
\citeyear{key}  Cite year only. (1953)
All the above have an NP variant without parentheses; Ex.
\citeNP.
```

BibTeX entry types

```
@article      Journal or magazine article.
@book         Book with publisher.
@booklet      Book without publisher.
@conference   Article in conference proceedings.
@inbook       A part of a book and/or range of pages.
@incollection A part of book with its own title.
@misc         If nothing else fits.
@phdthesis    PhD. thesis.
@proceedings  Proceedings of a conference.
@techreport   Tech report, usually numbered in series.
@unpublished  Unpublished.
```

BibTeX fields

```
address      Address of publisher. Not necessary for major
publishers.
author       Names of authors, of format ...
booktitle    Title of book when part of it is cited.
chapter      Chapter or section number.
edition      Edition of a book.
editor       Names of editors.
institution   Sponsoring institution of tech. report.
journal      Journal name.
key          Used for cross ref. when no author.
month        Month published. Use 3-letter abbreviation.
note         Any additional information.
number       Number of journal or magazine.
organization Organization that sponsors a conference.
pages        Page range (2,6,9--12).
publisher    Publisher's name.
school       Name of school (for thesis).
series       Name of series of books.
title        Title of work.
type         Type of tech. report, ex. "Research Note".
volume       Volume of a journal or book.
year         Year of publication.
Not all fields need to be filled. See example below.
```

Common BibTeX style files

```
abbrv  Standard      abstract  alpha with abstract
alpha  Standard      apa      APA
plain  Standard      unsrt    Unsorted
```

The L^AT_EX document should have the following two lines just before \end{document}, where bibfile.bib is the name of the BibTeX file.

```
\bibliographystyle{plain}
\bibliography{bibfile}
```

BibTeX example

The BibTeX database goes in a file called file.bib, which is processed with bibtex file.

```
@String{N = {Na\ture}}
@Article{WC:1953,
  author = {James Watson and Francis Crick},
  title = {A structure for Deoxyribose Nucleic Acid},
  journal = N,
  volume = {171},
  pages = {737},
  year = 1953
}
```

Sample L^AT_EX document

```
\documentclass[11pt]{article}
\usepackage{fullpage}
\title{Template}
\author{Name}
\begin{document}
\maketitle

\section{section}
\subsection*{subsection without number}
text \textbf{bold text} text. Some math: $2+2=5$
\subsection{subsection}
text \emph{emphasized text} text. \cite{WC:1953}
discovered the structure of DNA.
```

```
A table:
\begin{table}[!th]
\begin{tabular}{|l|c|r|}
\hline
first & row & data \\
second & row & data \\
\hline
\end{tabular}
\caption{This is the caption}
\label{ex:table}
\end{table}
```

```
The table is numbered \ref{ex:table}.
\end{document}
```

$\mathcal{M}\mathcal{S}$ - \LaTeX Reference Card #1

See the \TeX Reference Card for additional commands.
Required packages are indicated as (package).

Document Structure

• Preamble

```
\documentclass[option(s)]{class}
\usepackage[option(s)]{package(s)}
\begin{document}
```

• Body

- **Front Matter** (`\frontmatter` in book classes)
 - **Top Matter**

```
\title{...}
\title[running head]{...} alternative headline
\date{...}
\date{\today} gives current date
\author{...}
\maketitle (not in book classes)
```
 - **Additional items — ams classes only**

```
\translator{...}
\dedicatory{...}
\address[optional name]{...}
\curraddress{...}
\email[optional name]{...}
\thanks{...}
\subjclass{Primary: XXX; Secondary: XXX}
\keywords{...}
\thanks{...}
```
- `\tableofcontents`
- `\chapter{Introduction}` (in book classes)
- **Abstract** (not in book classes)

```
\begin{abstract}... \end{abstract}
```
- **Main Matter** (`\mainmatter` in book classes)

```
\chapter{...}
\section{...}
\subsection{...}
\appendix
```
- **Back Matter** (`\backmatter` in book classes)

```
\begin{thebibliography}{99}... \end{...}
```

```
\end{document}
```

Page Style

```
\pagestyle{style} set page style to one of:
plain          empty header, page number in footer
empty          empty header and footer
headings       header filled by doc class, empty footer
myheadings     empty footer, fill header with info in
                \markboth{lefthead}{righthead}
                and \markright{righthead}

\thispagestyle{style} set \pagestyle, only current page
\enlargethispage{\baselineskip} force an extra line
\renewcommand{\baselinestretch}{2} doublespaced
fancyheadings package allows custom headers and footers
```

- **Page Style Parameters**

```
\hoffset, \voffset move page right, down
\paperwidth, \paperheight, \textheight, \textwidth
\topmargin, \headheight, \headsep, \footskip
\pagenumbering{...} e.g., arabic, roman
```

Classes and Packages

```
\documentclass[option(s)]{class}
\usepackage[option(s)]{package(s)}
\NeedsTeXFormat{LaTeX2e}[1994/12/01]
• Document Classes
  article, book, letter, report, slides
  amsart, amsbook, amsproc (all autoload amsmath)
• Useful Packages
  amsmath, amsthm, amscd, amssymb, latexsym
  fancyheadings allows custom headers and footers
  alltt all teletype, even \,{}
  makeidx, showidx create index, show in margin
  graphics, graphicx inclusion of graphics
  enumerate extends the enumerate environment
  layout shows page layout of doc class
  multicol flexible multicolumn typesetting
  showkeys print label keys in margin
  verbatim extends verbatim environment
  url typeset URLs allowing line breaks
  graphpap \graphpaper command for \picture environ.
• Document and Package Options
  Font Size
    8pt, 9pt, 10pt, 11pt, 12pt
  Paper Size
    a4paper, a5paper, b5paper, legalpaper, letterpaper
  Document Preparation
    draft, final, notitlepage, titlepage
  Page Formatting
    onecolumn, twocolumn, oneside, twoside, openany, openright
  Equation Numbering
    fleqn, leqno, reqno, centertags, tbtags
  Equation Limits
    intllimits, sunlimits, nonamlimits
  AMS (Postscript) Fonts
    psamsfonts, noamsfonts
```

Bibliography (see also \BIBTeX)

```
\begin{thebibliography}{99}... \end{...}
                                bibliography with widest label specified
\bibitem{name}                  named bibliography item
\bibitem[label]{name}           with alternative label to print
\byname                         use long line for same author
\renewcommand{\bibname}{title} use custom title
\cite{name}                     print number of named bib item
\cite[text]{name}               with extra text
```

Cross Referencing and Numbering

```
\label{name} assign label name to numbered item
\ref{name}    print number of named item
\eqref{name}  print number in parentheses (amsmath)
\pageref{name} print page location of named item
\cite{name}   print number of named bibliography item
\cite[text]{name} with extra text
\numberwithinsection{equation}{section} number by section
```

Sectioning and Table of Contents

• Sectioning commands

<code>\command{title}</code>	sectioning command with title
<code>\command[head]{title}</code>	with alternative running head
<code>\command*{title}</code>	with number suppressed
<code>\part</code>	<code>\section</code> <code>\paragraph</code>
<code>\chapter</code>	<code>\subsection</code> <code>\subparagraph</code>
	<code>\subsubsection</code>
<code>\appendix</code>	start appendix

• Table of Contents

```
\tableofcontents create and print contents
filename.toc      contents associated to filename.tex
\addcontentsline{toc}{section}{line to add}
\addtocontents{toc}{material to add}
\setcounter{tocdepth}{...} set amount to print
```

Tables and Figures

```
\begin{table} ... \caption{text} \label{name} \end{table}
\listoftables create and print list of tables
\begin{figure} ... \caption{text} \label{name} \end{figure}
\includegraphics{filename} include image (graphics)
\scaledbox{.5}{\includegraphics{filename}} scaled graphic
\listoffigures create and print list of figures
```

Lists

<code>\item</code>	item within list
<code>\item[label]</code>	item with label
<code>\begin{enumerate}... \end{...}</code>	numbered items
<code>\begin{itemize}... \end{...}</code>	bulleted items
<code>\begin{description}... \end{...}</code>	captioned items
<code>\setlength{\itemsep}{0pt}</code>	move items closer
<code>enumerate package</code>	extends <code>enumerate</code>

Displayed Text Material

<code>\begin{center}... \end{...}</code>	centered material
<code>\begin{flushright}... \end{...}</code>	flush right material
<code>\begin{flushleft}... \end{...}</code>	flush left material
<code>\begin{quote}... \end{...}</code>	short quote
<code>\begin{quotation}... \end{...}</code>	long quote
<code>\begin{verse}... \end{...}</code>	poetry
<code>\begin{verbatim}... \end{...}</code>	verbatim material
<code>\verb ... </code>	verbatim material
<code>\verb* ... </code>	verbatim with spaces marked
<code>verbatim package</code>	extends <code>verbatim</code>

Footnotes, Comments, Other Stuff

```
\footnote{text} numbered footnote
%              comment out a line
\begin{comment}... \end{...} long comment (verbatim)
\typeout{text} print to terminal
\typein{text} get input from keyboard
\typein[cmd]{text} assign input to \cmd
\protect       protects fragile commands
\~             optional hyphen
\hyphenation{hyphenated words} extra hyphenated words
```

Dimensions, Spacing, and Glue

Dimensions are specified as $\langle \text{number} \rangle \langle \text{unit of measure} \rangle$.
Glue is specified as $\langle \text{dimen} \rangle \text{plus} \langle \text{dimen} \rangle \text{minus} \langle \text{dimen} \rangle$.
point pt pica pc inch in centimeter cm
m width em x height ex math unit mu millimeter mm
1 pc = 12 pt | 1 in = 72.72 pt | 2.54 cm = 1 in | 18 mu = 1 em
 \backslash quad \backslash quad white space (1 space, 1 em, 2 em)
 \backslash hspace{10pt} specified horizontal space
 \backslash hspace*{10pt} space even at line start
Horizontal Spacing (Math): \backslash , thin space \backslash : med space
 \backslash ; thick space \backslash ! neg. thin space \backslash mspace{muglue}
 \backslash strut, \backslash mathstrut invisible vertical space
 \backslash phantom{...} invisible space
 \backslash vphantom{...} invisible vertical space
 \backslash smash[bt]{...} typeset w/zero height,depth
 \backslash hfill fill with space
 \backslash dotfill fill with dots
 \backslash hrulefill fill with rule (line)
 \backslash par new paragraph
 \backslash newline or \backslash force a new line
 \backslash * new line, prohibit page break
 \backslash [5pt] new line skipping 5 pts
 \backslash vspace{1in} specified vertical space
 \backslash vspace*{1in} space even at page start
 \backslash newpage force a new page

• Length Variables

\backslash newlength{ \backslash lngth} create length variable \backslash lngth
 \backslash setlength{ \backslash lngth}{dimen} set value of \backslash lngth
 \backslash addtolength{ \backslash lngth}{dimen} increase \backslash lngth
• Useful Length Assignments
 \backslash enlargethispage{ \backslash baselineskip} force extra line
 \backslash setlength{ \backslash hangindent}{30pt} indentation
 \backslash setlength{ \backslash hangafter}{3} indent after
 \backslash renewcommand{ \backslash baselinestretch}{2} doublespaced

Accents

Type	Example	In Math	In Text
hat	\hat{a}	\backslash hat	\backslash ^
expanding hat	\widehat{abc}	\backslash widehat	none
check	\check{a}	\backslash check	\backslash v
tilde	\tilde{a}	\backslash tilde	\backslash ~
expanding tilde	\widetilde{abc}	\backslash widetilde	none
acute	\acute{a}	\backslash acute	\backslash '
grave	\grave{a}	\backslash grave	\backslash ‘
dot	\dot{a}	\backslash dot	\backslash .
double dot	\ddot{a}	\backslash ddot	\backslash "
breve	\breve{a}	\backslash breve	\backslash u
bar	\bar{a}	\backslash bar	\backslash =
vector	\vec{a}	\backslash vec	none
cedilla	ç	none	\backslash c

Additional Text Symbols

\backslash dag	†	\backslash copyright	©	\backslash pounds	£
\backslash ddag	‡	\backslash textcircled{r}	Ⓡ		
\backslash P	¶	\backslash textvisiblespace	┐		
\backslash S	§	\backslash textbullet	•		

Fonts

• Text Fonts

\backslash textnormal{...} $\{\backslash$ normalfont... document font
 \backslash textrm{...} $\{\backslash$ rmfamily... roman
 \backslash textsf{...} $\{\backslash$ sffamily... sans serif font
 \backslash texttt{...} $\{\backslash$ ttfamily... typewriter style
 \backslash textbf{...} $\{\backslash$ bfseries... bold
 \backslash textup{...} $\{\backslash$ upshape... upright
 \backslash textit{...} $\{\backslash$ itshape... italic
 \backslash textsl{...} $\{\backslash$ slshape... slanted
 \backslash textsc{...} $\{\backslash$ scshape... SMALL CAPITALS
 \backslash emph{...} $\{\backslash$ em... emphasize
 \backslash fbox{...} framed text

• Font Environments exist for above types, e.g.,

\backslash begin{ttfamily}... \backslash end{...}

• Changing Font Sizes

\backslash tiny, \backslash scriptsize, \backslash footnotesize, \backslash small
 \backslash normalsize \backslash large, \backslash Large, \backslash LARGE, \backslash huge, \backslash Huge


• Math Fonts

\backslash mathrm{...} roman
 \backslash mathbf{...} bold (letters)
 \backslash boldsymbol{...} bold (symbol) (amsmath)
 \backslash mathit{...} italic
 \backslash mathcal{...} caligraphic $\mathcal{A}, \mathcal{B}, \mathcal{C}$
 \backslash usepackage{eucal} redef \backslash mathcal to script $\mathcal{A}, \mathcal{B}, \mathcal{C}$
 \backslash mathfrak{...} Fraktur $\mathfrak{A}, \mathfrak{a}, \mathfrak{B}, \mathfrak{b}$ (amsfonts)
 \backslash mathbb{...} Blackboard bold $\mathbb{A}, \mathbb{B}, \mathbb{C}$ (amsfonts)
 \backslash boxed{...} framed math

• Math Font Sizes

\backslash displaystyle display size
 \backslash textstyle text size
 \backslash scriptsize sub/superscript size
 \backslash scriptscriptsize doubly sub/superscripted size

Boxes

\backslash mbox{...} one line of text
 \backslash text{...} one line of text (amsmath)
 \backslash parbox[width]{text} paragraph of text
 \backslash parbox[align][height][inner align]{width}{text}
 \backslash marginpar{...} marginal comment
 \backslash rule[-1pt]{20pt}{10pt} solid box 
 \backslash raisebox{5pt}{text} raised box
 \backslash makebox[width][alignment]{text} box of text
 \backslash framebox[width][alignment]{text} framed text
 \backslash setlength{ \backslash fboxsep}{5pt} space around text
 \backslash setlength{ \backslash fboxrule}{3pt} width of box borders

Overfull and Underfull Boxes

draft document class marks overfulls
 \backslash overfullrule width of overfull marker
 \backslash begin{setlength}{ \backslash hfuzz}{2pt}... \backslash end{...}
allow small overfulls

Multicolumn Printing

\backslash twocolumn double column on new page
 \backslash onecolumn single column on new page
 \backslash begin{multicols}{ n }[title]... \backslash end{...}
multicolumn environment (multicol)

Array and Tabular Environments

\backslash begin{tabular}[POS]{COLS}... \backslash end{...}
 \backslash begin{array}[POS]{COLS}... \backslash end{...}
Use tabular for text, array for mathematics
&, \backslash column and row separators
POS aligns top (t), bottom (b), center (default)
COLS gives formats for columns:
1,c,r left, center, right justified
| vertical rule
@{...} material between columns
@{} no space between columns
*{ n }{...} n copies of material
p{width} set column width
 \backslash hline horizontal line between rows
 \backslash cline{i-j} line across columns i to j
 \backslash multicolumn{ n }{COLS}{...}

span n columns using format in COLS
 \backslash setlength{ \backslash tabcolsep}{0pt} set column separation
 \backslash setlength{ \backslash itemsep}{0pt} set item separation
 \backslash renewcommand{ \backslash arraystretch}{1.25} open up array

• Example of a table using \backslash tabular

\backslash begin{table}
 \backslash begin{center}
 \backslash begin{tabular}{|l|c|c|} \backslash hline
Name & Exam & Grade \backslash \backslash hline
Dan & 97% & A \backslash \backslash hline
 \backslash end{tabular}
 \backslash caption{Math 101 Final Grades}
 \backslash label{GradeTable}
 \backslash end{center}
 \backslash end{table}

Name	Exam	Grade
Dan	97%	A

Math 101 Final Grades

Tabbing Environment

\backslash begin{tabbing}... \backslash end{...} tabbing environment
 \backslash = set tab
 \backslash end line
 \backslash > move to next tab
 \backslash kill do not print line

File Suffixes and Types

• L^AT_EX Source Files

.tex File containing a L^AT_EX document
.sty, .cls L^AT_EX style and document class files
.fd Font definition file

• Files Written by L^AT_EX

(See also BIB_TE_X and MAKEINDEX)
.aux cross-referencing and list information
.dvi device independent typeset file
.glo list of glossary entries
.lof list of figures (read by \backslash listoffigures)
.lot list of tables (read by \backslash listoftables)
.toc table of contents (read by \backslash tableofcontents)
.log L^AT_EX log file
 \backslash nofiles supresses all except .log and .dvi

$\mathcal{M}\mathcal{S}$ - \LaTeX Reference Card #2

See the \TeX Reference Card for additional commands.
The notation (package) indicates a required package.

Math Environments

$\backslash(\dots\backslash)$ or $\$...\$$ inline math
 $\backslash[...\backslash]$ or $\$...\$$ displayed math
 $\backslash\begin{equation}\backslash\label{eqname}\dots\backslash\end{...}$
numbered and labeled equation
 $\backslash\ref{eqname}$ refer to labeled eqn
 $\backslash\mbox{f.}\dots$ text in math
• The following require amsmath
 $\backslash\text{text}\{...\}$ text in math
 $\backslash\begin{equation*}\dots\backslash\end{...}$ unnumbered eqn
 $\backslash\tag{eqtag}$ use eqtag instead of number
 $\backslash\text{notag}$ suppress equation tag
 $\backslash\eqref{eqname}$ ref with parens
 $\backslash\begin{subequations}\dots\backslash\end{...}$
group equations for numbering
 $\backslash\text{numberwithin}\{equation\}\{section\}$
number equations within sections

Theorems, Lemmas, Etc.

• **Defining Theorem-Like Environments**
 $\backslash\text{newtheorem}\{name\}\{label\}$ theorem environment
 $\backslash\text{newtheorem*}\{name\}\{label\}$ unnumbered (amsthm)
 $\backslash\text{newtheorem}\{name\}\{other\ name\}\{label\}$
numbered consecutively with other environment
 $\backslash\text{newtheorem}\{name\}\{label\}\{section\}$
numbered by section (or chapter, etc.)
 $\backslash\text{swapnumbers}$ put numbers on left
• **Theorem-Like Environment Styles** (amsthm)
 $\backslash\text{theoremstyle}\{plain\}$ most emphatic
 $\backslash\text{theoremstyle}\{definition\}$ medium emphasis
 $\backslash\text{theoremstyle}\{remark\}$ least emphatic
• **Invoking Theorem-Like Environments**
 $\backslash\begin\{name\}\dots\backslash\end\{...\}$ invoke environment
 $\backslash\begin\{name\}\{label\}\dots$ invoke with new label
If proclamation starts with a list, put in $\backslash\text{hfill}$
 $\backslash\begin\{proof\}\dots\backslash\end\{...\}$ proof environment
 $\backslash\begin\{proof\}\{label\}\dots\backslash\end\{...\}$ proof with label
 $\backslash\text{qedsymbol}$ end of proof marker
 $\backslash\text{renewcommand}\{\backslash\text{qedsymbol}\}\{...\}$ redefine marker

Commutative Diagrams (amscd)

Separate lines with $\backslash\backslash$, do not use $\&$ s
 $\backslash\begin{CD}\dots\backslash\end{CD}$ commutative diagram
 \@>\#1>\#2> right arrow with labels
 \@<\#1<\#2< left arrow with labels
 \@V\#1V\#2V down arrow with labels
 \@A\#1A\#2A up arrow with labels
 \@= long horizontal equal sign
 \@| long vertical equal sign
 \@. leave out an arrow

Multiline Math Displays (amsmath)

Use as $\backslash\begin\{command\}\dots\backslash\end\{command\}$
Separate items with $\&$, separate lines with $\backslash\backslash$
No $\backslash\backslash$ on last line, $\backslash\backslash\text{[dim]}$ to skip space
• **Full Math Environments (full line)**
 gather centered, numbered equations
 gather* centered, unnumbered equations
 multline first line left, last line right, rest centered
 multline* same as multline, but unnumbered
 align formulas aligned at $\&$ signs
 align* same as align, but unnumbered
 flalign flush left and right align
 alignat align without space, needs
argument
 $\backslash\text{intertext}\{text\}$ text between lines
 $\backslash\text{shoveleft},\backslash\text{shoveright}$ move multline line left, right
 $\backslash\text{allowdisplaybreaks}$ allow page breaks ($\backslash\backslash*$ prohibits)
 $\backslash\text{displaybreak}$ force page break (before $\backslash\backslash$)
• **Math Subenvironments (within math display)**
 gathered centered equations
 aligned formulas aligned at $\&$ signs
 split split long formula within other environment
 cases cases, with $\{$ on left
 matrix matrix (of up to 10 columns)
 $\text{pmatrix}, \text{bmatrix}, \text{vmatrix}, \text{Vmatrix}$
matrix variants enclosed by $(\cdots), [\cdots], |\cdots|, \|\cdots\|$
 $\backslash\text{setcounter}\{\text{MaxMatrixCols}\}\{12\}$
increase number of matrix columns
 $\backslash\text{hdotsfor}\{num\}$ dots across columns

Overlines, Underlines, and Arrows

$\backslash\text{underline}\{...\}$ underline
 $\backslash\text{overline}\{...\}$ overline
 $\backslash\text{overbrace}\{...\}^{\{...\}}$ overbrace
 $\backslash\text{underbrace}\{...\}_{\{...\}}$ underbrace
 $\backslash\text{overrightarrow}\{...\}$ over right arrow
 $\backslash\text{overleftarrow}\{...\}$ over left arrow
 $\backslash\text{overleftrightharrow}\{...\}$ over left-right arrow
 $\backslash\text{underrightarrow}\{...\}, \backslash\text{underleftarrow}\{...\}$, etc.
 $\backslash\text{xrightarrow}\{bot\}\{top\}$ stretchable w/sub/supscripts
 $\backslash\text{xleftarrow}\{bot\}\{top\}$ stretchable w/sub/supscripts

Operator Names

$\backslash\text{arccos}$ $\backslash\text{cos}$ $\backslash\text{csc}$ $\backslash\text{exp}$ $\backslash\text{ker}$ $\backslash\text{liminf}$ $\backslash\text{min}$ $\backslash\text{sinh}$
 $\backslash\text{arcsin}$ $\backslash\text{cosh}$ $\backslash\text{deg}$ $\backslash\text{gcd}$ $\backslash\text{lg}$ $\backslash\text{limsup}$ $\backslash\text{Pr}$ $\backslash\text{sup}$
 $\backslash\text{arctan}$ $\backslash\text{cot}$ $\backslash\text{det}$ $\backslash\text{hom}$ $\backslash\text{lim}$ $\backslash\text{log}$ $\backslash\text{sec}$ $\backslash\text{tan}$
 $\backslash\text{arg}$ $\backslash\text{coth}$ $\backslash\text{dim}$ $\backslash\text{inf}$ $\backslash\text{ln}$ $\backslash\text{max}$ $\backslash\text{sin}$ $\backslash\text{tanh}$
 $a \backslash\text{equiv} b \backslash\text{pmod}\{m\}$ $a \equiv b \pmod{m}$
 $a \backslash\text{equiv} b \backslash\text{mod}\{m\}$ $a \equiv b \pmod{m}$
 $a \backslash\text{bmod} m$ $a \text{ mod } m$
 $\backslash\text{DeclareMathOperator}\{\text{cmd}\}\{\text{opname}\}$ create operator
 $\backslash\text{DeclareMathOperator*}\{\text{cmd}\}\{\text{opname}\}$ with limits
 $\backslash\text{operatorname}\{...\}$ typeset as an operator
 $\backslash\text{operatorname*}\{...\}$ with limits

Large Operators

\sum $\backslash\text{sum}$ \bigcap $\backslash\text{bigcap}$ \bigodot $\backslash\text{bigodot}$
 \prod $\backslash\text{prod}$ \bigcup $\backslash\text{bigcup}$ \bigotimes $\backslash\text{bigotimes}$
 \coprod $\backslash\text{coprod}$ \bigsqcup $\backslash\text{bigsqcup}$ \bigoplus $\backslash\text{bigoplus}$
 \int $\backslash\text{int}$ \bigvee $\backslash\text{bigvee}$ \biguplus $\backslash\text{biguplus}$
 \oint $\backslash\text{oint}$ \bigwedge $\backslash\text{bigwedge}$
 $\backslash\text{substack}\{xxx\backslash\backslash yyy\}$ stacked sub or superscripts
 $\backslash\text{limits}, \backslash\text{nolimits}$ force or forbid displayed limits
 $\backslash\text{oint}, \backslash\text{iint}, \backslash\text{iiint}, \backslash\text{iiiiint}, \backslash\text{idotsint}$
integral variants (amsmath)

Delimiters

$[$ $\backslash\text{lbrack}$ or $\backslash[$ $\{$ $\backslash\text{lbrace}$ or $\backslash\{$ \langle $\backslash\text{langleft}$
 $]$ $\backslash\text{rbrack}$ or $\backslash]$ $\}$ $\backslash\text{rbrace}$ or $\backslash\}$ \rangle $\backslash\text{langright}$
 $|$ $\backslash\text{vert}$ or $\backslash|$ \lfloor $\backslash\text{lfloor}$ \lceil $\backslash\text{lceil}$
 $\|$ $\backslash\text{Vert}$ or $\backslash|$ \rfloor $\backslash\text{rfloor}$ \rceil $\backslash\text{rceil}$
 \uparrow $\backslash\text{uparrow}$ \Uparrow $\backslash\text{Uparrow}$ \Uparrow $\backslash\text{updownarrow}$
 \downarrow $\backslash\text{downarrow}$ \Downarrow $\backslash\text{Downarrow}$ \Downarrow $\backslash\text{updownarrow}$
 $\left($ $\backslash\text{right}$ expanding delimiters
 $\left.$ $\backslash\text{right.}$ empty delimiters
 $\bigl($ $\backslash\text{bigr}$ big delimiters
 $\Bigl($ $\backslash\text{Bigr}$ bigger delimiters
 $\biggl($ $\backslash\text{biggr}$ even bigger delimiters
 $\bigm|, \backslash\text{biggm|}$ big binary relation delimiters

Roots

$\backslash\text{sqrt}\{...\}$ square root $\sqrt{\quad}$
 $\backslash\text{sqrt}\{n\}\{...\}$ n th root $\sqrt[n]{\quad}$
 $\backslash\text{leftroot}\{2\}, \backslash\text{uproot}\{2\}$ move root left or up

Ellipses

$\backslash\text{ldots}, \backslash\text{cdots}, \backslash\text{dots}$ ellipses
 $\backslash\text{vdots}, \backslash\text{ddots}$ vertical and diagonal dots
 $\backslash\text{dotsc}, \backslash\text{dotso}, \backslash\text{dotsm}, \backslash\text{dotso}$ more ellipses (amsmath)

Fractions and Stacked Relations

$\backslash\text{frac}\{n\}\{d\}$ fraction $\frac{n}{d}$
 $\backslash\text{dfrac}\{n\}\{d\}$ displaystyle fraction
 $\backslash\text{tfrac}\{n\}\{d\}$ textstyle fraction
 $\backslash\text{binom}\{n\}\{d\}$ binomial coefficient $\binom{n}{d}$
 $\backslash\text{genfrac}\{\text{ldelim}\}\{\text{rdelim}\}\{\text{thick}\}\{\text{style}\}\{\text{num}\}\{\text{den}\}$
 $\backslash\text{cfraction}\{...\}\{...\}$ continued fraction
 $\backslash\text{stackrel}\{\text{top}\}\{\text{bot}\}$ stacked relation
 $\backslash\text{overset}\{\text{top}\}\{\text{bot}\}$ stacked symbol (amsmath)
 $\backslash\text{underset}\{\text{bot}\}\{\text{top}\}$ stacked relation (amsmath)
 $\backslash\text{sideset}\{\text{ll}\}\{\text{ul}\}\{\text{ur}\}\{\text{largeop}\}$
large operator with left/right sub/supscripts

Negated Relations

$\backslash\text{not}$ negate a relation
 $\backslash\text{ne}$ not equal \neq
 $\backslash\text{notin}$ not a member of \notin
 $\backslash\text{nmid}$ not divisible \nmid

User Defined Commands

```
\newcommand{\name}{replacement text}    new command
\newcommand{\name}[n]{text with #1,#2,...,#n}
                                new command with  $n$  arguments
Example: \newcommand{\vect}[2]{#1_1,\ldots,#1_{#2}}
\newcommand{\name}[n][default]{...}
                                command with args and default value for #1
\renewcommand{...}{...}        redefine existing command
\providecommand{...}{...}      define if doesn't exist
\newcommand*{...}{...}         command with one par arg
\ensuremath{...}               forces math mode
\show\command                  print definition of \command
\showthe\paramname             print value of a parameter
```

User Defined Environments

```
\newenvironment{name}{pretext}{posttext}
                                new environment with material before and after
\newenvironment[n]{name}{...}{...}
                                environment with  $n$  arguments
\newenvironment[n][default]{name}{...}{...}
                                environment with default value for #1
\renewenvironment{name}{...}{...} redefine envrment
```

MAKEINDEX

- **MakeIndex** File Suffixes
.idx, .ind, .ilg entry listing, index file, log file
- **MakeIndex** Commands in Document File
\usepackage{makeidx} use indexing package
(Do not include this line if using AMS packages.)
\makeindex tell \LaTeX to create an .idx file
\printindex tell \LaTeX to print index here
\nofiles suppresses creation of .idx and .glo files
- Creating **MakeIndex** .idx File
\index{entry} main entry
\index{entry!entry} subentry
\index{entry!entry!entry} subsubentry
\index{text@entry} with placement info
\index{entry|see{entry}} cross referenced entry
\index{entry|modifier} entry with page modifier
e.g. \index{gnats|textbf} give bold page number
\index{entry|{} ... \index{entry|{}} page range
- Special Characters: "!" "@" "|" ""
- Creating An Index With **MakeIndex**
 - (1) Typeset document containing \makeindex command.
 - (2) Run MakeIndex on .idx file to create .ind file.
 - (3) Typeset document containing \printindex command.

Glossary

```
\makeglossary    tell  $\LaTeX$  to create a .glo file
\glossary{entry}    create a glossary entry
\glossaryentry{entry}{page no.}    entries in .glo file
\input filename.glo    read glossary file
User must define \makeglossary, e.g.,
\newcommand{\glossaryentry}[2]{#1, page #2\par}
```

Time and Date

```
\today    current date
Use \the to display the following items
\day, \month, \year, \time (minutes since midnight)
```

Counters

```
\newcounter{cntr}    create new counter named cntr
\newcounter{cntr}[cntr1] reset cntr when cntr1 changes
\setcounter{cntr}{value}    set value of cntr
\stepcounter{cntr}    increment cntr
\refstepcounter{cntr}    increment and reset \label
\addtocounter{cntr}{n}    increment by  $n$ 
\value{cntr}    value stored in \cntr
\thecntr    the value of cntr
calc    package to do counter arithmetic
```

• Counter Styles

```
\arabic{} \roman{} \Roman{} \alph{} \Alph{}
```

• Standard Counters

```
equation footnote figure page table
part chapter section subsection subsubsection
paragraph subparagraph enumi enumii enumiii enumiv
secnumdepth    depth to which sections are numbered
tocdepth    depth to which sections are put into toc
```

Customized List Environments

```
\begin{list}{default label}{declarations}
\item item 1 text
\item item 2 text
\end{list}
\begin{trivlist}...\end{trivlist}
list with no labels or declarations, trivial lengths
```

• Declarations

```
\setlength{length parameter}{length}
\usecounter{counter name}
```

[Create counter first using \newcounter{counter name}.]

• Length Parameters (see page 113 of L^ampport for more)

```
\topsep    separate preceding text and first item
\itemsep    separate items
\leftmargin    indent of item box from left margin
\labelwidth    width of box for item label
\labelsep    separate label box from item box
```

The picture Environment

```
\begin{picture}(w,h)...\end{picture}    picture
\begin{picture}(w,h)(\Delta x,\Delta y)...\quad with offset
\put(x,y){picture object}    place object
\multiput(x,y)(\Delta x,\Delta y){n}{object}     $n$  times
```

Picture Objects:

```
\makebox(x,y)[tblr]{text}    box with text
\line(\Delta x,\Delta y){x length}    line of slope  $\Delta y/\Delta x$ 
\vector(\Delta x,\Delta y){x length}    arrow of slope  $\Delta y/\Delta x$ 
\circle{r}    circle of radius  $r$ 
\circle*{r}    filled circle
\oval(x,y)[lrbt]    oval (part or whole)
\shortstack{abc\backslash xyz\backslash}    stacked text
\framebox(x,y)[tblr]{text}    framed text
\frame{text},fbox{text}    other framed boxes
\dashbox{d}(x,y){text}    dashed box
\qbezier(x_1,y_1)(x_2,y_2)(x_3,y_3)    quadratic curve
\savebox{name}(x,y){...}    store material
\usebox{name}    retrieve material
\graphpaper[n]{x,y}{w,h}    print grid (graphpap)
\setlength{\unitlength}{1pt}    change size of picture
\thinlines,\thicklines    adjust line thickness
```

Color (color)

```
\color{color}    change color
\textcolor{color}{text}    colored text
\colorbox{color}{text}    colored background
\colorbox{col_1}{col_2}{text}    colored border & background
\setlength{\fboxsep}{5pt}    put space around text
\setlength{\fboxrule}{3pt}    width of border of box
\pagecolor{color}    set background color of page
\definecolor{name}{rgb}{r,g,b}    define an RGB color
\definecolor{name}{cmyk}{c,m,y,k}    define a CMYK color
```

Predefined Colors

black, white, red, green, blue, yellow, cyan, magenta

BIB \TeX

• BIB \TeX File Suffixes

```
.bib    BIB $\TeX$  bibliographic database file
.bst    BIB $\TeX$  bibliographic style file
.blg    BIB $\TeX$  log file
.bbl    BIB $\TeX$  document bibliography file
```

• BIB \TeX Commands in Document File

```
\bibliographystyle{bib style file}
Examples: plain, amsplain, unsrt, alpha, abbrv
\bibliography{bib database file(s)}
\cite{label}    cite a reference
\nocite{label}    include ref in bib without citation
\nocite{*}    include all references in bibliography
```

• Creating BIB \TeX Database File

```
@STRING{name = "text"}    define an abbreviation
Put braces around non-initial capitalized title words.
Use and to separate multiple authors in author field
```

• General Format of a Database Entry

```
@ENTRYTYPE{label,
fieldtype1 = {entry1},
fieldtype2 = {entry2},
:
}
```

• Database Entry Types

```
@ARTICLE{...}    @MASTERSTHESIS{...}
@BOOK{...}    @MISC{...}
@BOOKLET{...}    @PHDTHESIS{...}
@INBOOK{...}    @PROCEEDINGS{...}
@INCOLLECTION{...}    @TECHREPORT{...}
@INPROCEEDINGS{...}    @UNPUBLISHED{...}
@MANUAL{...}    @COMMENT{...}
```

• Field Types Within Entries

address	editor	month	school
author	howpublished	note	series
booktitle	institution	number	title
chapter	journal	organization	type
crossref	key	pages	volume
edition	language	publisher	year

• Creating Document Bibliography With BIB \TeX

- (1) Typeset document to get new .aux file.
- (2) Run BIB \TeX on .aux file to create .bbl file.
- (3) Retypeset document twice.