INSTRUMENT APPROACH CHART (IAC)

RNP Z RWY 26 AD ELEV: 18' ATIS APP FLORIANÓPOLIS GNDC TWR NAVEGANTES 127.625 119.50 119.65 128.95 118.20 NIL 129.45 120.325 I NAV/VNAV TEMP LNAV/VNAV FINAL CRS FAF INAV MIN -10°C / MAX 44°C 256° 2020 DA / (OCH): 325' / (309') MDA / (OCH): 410' / (400') APCH Perdida: Subir para 4000°. Manter proa 258 até 2000°. Após, curvar à ESQUERDA direto EGBID para espera. Missed APCH: Climb to 4000'. Maintain heading 253 until 2000'. After, turn LEFT direct EGBID for holding. DEPARTAMENTO DE 50 600 (IAF) DOVRO Ν 4000 NOTES VAR. RNP APCH. 7 20° W - 2024 ALT, ELEV, HGT: FT DIST: NM BRG: MAG 00 DOVAC VA/CHG: 07'W (IF) 4500' NF019 4000 DOVRO 2 2500 Z 4000'💸 990 (FAF) NF021 9 (MAPT) EGBID 016 RWY26 (IAF/MAHF) 165 4000 7M 370' **EGBID** 58 4000' IAS MAX 240KT 70 EGBID 2000' 751 SCALE 5 NM 1417 A Ω 10 Km IF **TA** 9000' FAF LNAV/VNAV NF019 NF021 2500 2020' MAPT LNAV RWY26 5.4% (3.1°) **∡**256 LNAV €256 2000 RDH 50' MDA THR ELEV 18 0.8 1.1 TO THR 26 (NM 0.0 5.9 9.9 RWY26 1.1 2.0 3.0 4.0 NF021 Ground Speed (KT 090 110 130 150 190 AL 410 725 1054 1383 2020 FPM 500 600 700 800 900 (HGT) 400 708 1037 1366 2003 FAF-MAPT NII CAT В С Е STRAIGHT-IN Α D DA / (OCH) 325' / (309') LNAV/VNAV ALS/NO ALS/ RVR ALS (m) NIL / 1400 / NIL NΑ MDA / (OCH) 410' / (400') **LNAV** ALS/NO ALS/ RVR ALS (m) NIL / 1600 / NIL NIL / 1800 / NIL AIRAC AMDT 2410A1 03 OCT 24