AD ELEV: 18' (CAT A, B, C) APP FLORIANÓPOLIS ATIS TWR NAVEGANTES **GNDC** 127.625 118.20 119.50 119.65 120.325 128.95 129.45 NIL RNP 0.2 RNP 0.3 TEMP LNAV/VNAV FINAL CRS FΔF 076° MIN 0°C / MAX 40°C 1980' DA / (OCH): 338' / (320') DA / (OCH): 520' / (502') APCH Perdida: Subir para 4000, manter rumo 076 até NF001. Após, manter rumo 076 até NF013 para espera. 2) RNP menor que 1.0. Missed APCH: Climb to 4000, maintain course 076 until NF001, After, maintain course 076 until NF013 for holding. 2) RNP below 1.0. NOT TO SCALE NOTES RNP AR APCH. 0767 VAR 20° RF REQ. (IAF) ALT, ELEV, HGT: FT DIST: NM NF102 4000' BRG: MAG (MAHF) 1375 VA/CHG: 07'W NF013 4000 NF001 SCALE No 5 NM 20 10 Km (IF) 155 NF103 4000 ^^ RWY08 2400 156 4000' -<sub>M</sub>- 370' 643 5000' (FAF) 175 NF104 MSA 25 NM WPT NF102 (FROP) NF106 ĪF FAF TA 9000' NF103 **FROP** NF104 2400 NF106 1980 1259' 5.2% (3.0 RWY08 520' 338' 1900' RDH 50' THR ELEV 18' TO THR 08 (NM) 98 6 1 38 1.4 0.8 0.0 NF104 NF106 090 110 150 5.0 2.0 RWY08 Ground Speed (KT) FPM 800 NA 1980 1660 1259 705 520 338 500 600 700 AI T 1642 1241 687 502 320 (HGT) FAF-MAP1 STRAIGHT-IN CAT Α С D Ε DA / (OCH) 338' / (320') **RNP 0.2** ALS/NO ALS/ RVR ALS (m) NIL / 1400 / NIL NA 520' / (502') DA / (OCH) **RNP 0.3** ALS/NO ALS/ RVR ALS (m) NIL / 2400 / NIL AUTORIZAÇÃO ESPECIAL PARA AERONAVE E TRIPULAÇÃO REQUERIDA SPECIAL AUTHORIZATION FOR AIRCRAFT AND CREW REQUIRED