

Haskell - A Search Tree Application Functional Programming

Jens Egholm Pedersen and Anders Kalhauge



Spring 2018

Outline



Search Trees

Binary Search Tree Balanced Search Trees

Haskell IO

Some basic examples Chapter 8 and 9

Assignment



Search Trees

Binary Search Tree Balanced Search Trees


Haskell IO

Some basic examples Chapter 8 and 9


Assignment

Binary Trees










Anatomy of a binary tree






Anatomy of a binary search tree

Binary Search Trees




Analysis



Binary Search Trees



Analysis




 $O(\log n)$

Binary Search Trees




Analysis






Anatomy



Anatomy of a 2-3 search tree




Searching



Search hit (left) and search miss (right) in a 2-3 tree




Inserting



Insert into a 2-node




Inserting



Insert into a single 3-node




Inserting



Insert into a 3-node whose parent is a 2-node




Inserting





Summing up



Splitting a temporary 4-node in a 2-3 tree (summary)



Search Trees

Binary Search Tree Balanced Search Trees

Haskell IO

Some basic examples Chapter 8 and 9

Assignment

Read and Write to console



```
main :: IO ()
main = do
  putStrLn "Hi, what's your name?"
  name <- getLine
  putStrLn ("Hellou"++name)</pre>
```

In GHCi

```
ghci> :t getLine
getLine :: IO String
ghci> :t putStrLn
putStrLn :: String -> IO ()
ghci>
```

Show and Read



```
main :: IO ()
main = do
  putStrLn "Hi, what's your age?"
  line <- getLine
  let age = (read line :: Int)
  putStrLn ((show age)++"years")</pre>
```

Reading lines from file



```
import System.IO

main :: IO ()
main = do

withFile "numbers.txt" ReadMode (\handle -> do
    contents <- hGetContents handle
    let numberLines = lines contents
    putStr (contents++(numberLines!!2)++"\n")
)</pre>
```



```
fact :: Integer -> Integer
fact 0 = 1
fact n = n * fact (n - 1)

main :: IO ()
main = do
   putStrLn ("50!" = ""++(show (fact 50)))
```

```
50! = 30414093201713378043612608166064768844377641568
960512000000000000
```

More information on Haskell IO



Consult chapter 8 and 9 in Learn You a Haskell for Great Good!



Search Trees

Binary Search Trees
Balanced Search Trees

Haskell IO

Some basic examples Chapter 8 and 9

Assignment

Assignment



Create a Haskell application that:

- □ Implements a balanced search tree¹ with functions for finding items, inserting items, and traversing the tree.
- □ Implements a console interface with:
 - Search item
 - □ Insert item
 - □ List all items in order
 - □ Load items from text file

Start with integer numbers as items, expand with any item deferring Ord

Can be done individually or in groups.

¹or at least a binary search tree