

In the Lecture Series Introduction to Database Systems

Logic and Domain Relational Calculus

Presented by Stéphane Bressan

Introduction to Database Systems

Relational Query Languages

- Two mathematical Query Languages form the basis for practical languages like SQL:
 - Relational Calculus: Declarative, describe what you want, rather than how to compute it.
 - Relational Algebra: Procedural (operational), useful for representing execution plans
- Query languages are NOT programming languages:
 - Not designed to be Turing complete

Relational Calculi

There are two calculi:

- Domain relational calculus (DRC).
- Tuple relational calculus (TRC).
- Both are based on logic
- They differ on what variables represent

Learning Objectives

- Understand and write formula in logic
- Understand and write queries in Domain Relational Calculus


Propositional Logic

“Aristotle is Greek”

“Aristotle is Greek and Alexander is Persian”

“Aristotle is not Greek”

“Alexander is Macedonian or Persian”



Christopher Plummer



Colin Farrel


Propositional Logic

“Roxane is Bactrian or not Bactrian”

“Olympias is Greek and is not Greek”

“Olympias is Greek implies Alexander is Greek”

“Roxane is Bactrian implies Roxane is Bactrian”



Rosario Dawson



Angelina Jolie

Semantics of Propositional Logic

The semantic of propositional logic is defined by truth tables

A	B	$(A \vee B)$	$(A \wedge B)$	$(A \Rightarrow B)$	$\neg (A)$
T	T	T	T	T	F
F	T	T	F	T	T
T	F	T	F	F	F
F	F	F	F	T	T

$(\neg A \vee B)$

First Order Logic: Predicates

`greek(aristotle)`

`greek(X)`

`mother(olympias, alexander)`

`mother(X, Y)`

First Order Logic: Quantification

$\exists X \text{ greek}(X)$

$\exists X \text{ mother}(\text{olympias}, X)$

$\exists X \exists Y \text{ mother}(Y, X)$

$\exists Y \exists X \text{ mother}(Y, X)$

First Order Logic: Quantification

$\forall X \text{ greek}(X)$

$\forall Y \exists X \text{ mother}(X, Y)$

$\exists X \forall Y \text{ mother}(X, Y)$

First Order Logic

$$\forall X \forall Y ((\text{mother}(X, Y) \wedge \text{greek}(X)) \Rightarrow \text{greek}(Y))$$

Syntax of First Order Logic

First order logic consists of formulae built from


- **predicates**
- **constants** (*lower case*)
- **variables** (*upper case, quantified or free*),
- **quantifiers**: \forall and \exists
- **logical operators**: \wedge , \vee , \neg and \Rightarrow

Remarks

To avoid confusion we agree that:

A variable is quantified once at most.

If a variable is quantified in a formula, it cannot appear outside of the scope of its quantifier.



Remarks

$$\neg \forall X F$$

is equivalent to

$$\exists X \neg F$$

**Proof by counterexample: Prove $\neg \forall X F$
(i.e., $\forall X F$ is false) by showing $\exists X \neg F$**

$$\neg \exists X F$$

is equivalent to

$$\forall X \neg F$$

**$\neg \exists X (\text{greek}(X) \wedge \text{mother}(X, \text{Alexander})) \rightarrow$
 $\forall X \neg (\text{greek}(X) \wedge \text{mother}(X, \text{Alexander})) \rightarrow$
 $\forall X (\neg \text{greek}(X) \vee \neg \text{mother}(X, \text{Alexander}))$**

(*Here F represents a formula)

Calculus

- A Calculus defines formulae and their meaning
- Domain Relational Calculus (DRC): variables range over values
- Tuple Relational Calculus: (TRC) variables range over tuples

Calculus

How to represent the set of integers 2, 3, and 4?

In extension:

$$\{2, 3, 4\}$$

In Intension (set-builder notation, comprehension, abstraction):

$$\{X \mid X \in \mathbb{N} \wedge 1 < X \wedge X < 5\}$$


Calculus: Where is the Truth?

- The truth is in the database
- If a relation Mother in the database has a tuple mother(olympias, alexander) then Olympias is the mother of Alexander
- Otherwise it is not (*closed world assumption*)

Domain Relational Calculus

Example

- lecturer(matric, name)
- module(code, name, credit)
- teach(matric, code)



Example

- $\{ \langle X \rangle \mid \exists Y \text{ lecturer}(X, Y) \}$
- $\{ \langle X \rangle \mid \exists Y \text{ lecturer}(X, Y) \wedge Y = \text{"john"} \}$
- $\{ \langle X \rangle \mid \text{lecturer}(X, \text{"john"}) \}$
- $\{ \langle X, Y \rangle \mid \text{lecturer}(X, Y) \}$
-- SELECT * FROM lecturer

Syntax of Domain Relational Calculus

- {Head | Body} {variableList | formula}
- Head:
 - Variable list: $\langle X1, X2, \dots \rangle$
 - Variables in the head are free
- Body:
 - Formula in first order logic
 - Variables in the body that are not in the head are quantified

Semantics of Domain Relational Calculus

- {variableList | formula}
- Head:
 - Return the set of tuples of values
 - such that if we replace the variables in the variable list by the values in one such tuples,
- Body:
 - Then the formula in the body is true.

Example

- $\{ \langle X, Y \rangle \mid \text{lecturer}(X, Y) \}$
- $\{ \langle X \rangle \mid \exists Y \text{ lecturer}(X, Y) \}$

Matric	Name
123	John
214	Peter
555	Magdalena

Example

Find the names of lecturers teaching a module with less than 2 credits. Print the names of the lecturers and the names of the corresponding modules.

Example

$$\{ \langle \text{LN}, \text{MN} \rangle \mid \exists M \exists C \exists Cr$$
$$\begin{aligned} & \text{lecturer}(M, \text{LN}) \\ & \wedge \text{module}(C, \text{MN}, Cr) \\ & \wedge \text{teach}(M, C) \\ & \wedge Cr < 2 \} \end{aligned}$$

Example

$$\{ \langle \text{LN}, \text{MN} \rangle \mid \exists M1 \exists M2 \exists C1 \exists C2 \exists Cr$$

lecturer(M1, LN)
 \wedge module(C1, MN, Cr)
 \wedge teach(M2, C2)
 \wedge C1 = C2 \wedge M1 = M2 \wedge Cr < 2

Example SQL

- SELECT
 lecturer.lecName,
 module.moduleName
FROM lecturer, module, teach
WHERE lecturer.matric=teach.matric
AND module.code = teach.code
AND module.credit < 2

Example

$$\{ \langle M1, M2, N \rangle \mid$$
$$\quad \text{lecturer}(M1, N)$$
$$\quad \wedge \text{lecturer}(M2, N)$$
$$\quad \wedge M1 \neq M2 \}$$
$$\{ \langle M1, M2, N1 \rangle \mid \exists N2$$
$$\quad \text{lecturer}(M1, N1)$$
$$\quad \wedge \text{lecturer}(M2, N2)$$
$$\quad \wedge M1 \neq M2$$
$$\quad \wedge N1 = N2 \}$$

Example

Find the names of the lecturers teaching all modules

$$\{ \langle N \rangle \mid \exists M \forall C \forall MN \forall Cr$$

lecturer(M, N)
 \wedge module(C, MN, Cr)
 \wedge teach(M, C)) }

Incorrect! (Why?)

Example

Find the names of the lecturers teaching all modules

$$\{ \langle N \rangle \mid \exists M \forall C \forall MN \forall Cr$$
$$\text{lecturer}(M, N) \wedge$$
$$(\text{module}(C, MN, Cr) \Rightarrow \text{teach}(M, C)) \}$$

Credits

The content of this lecture is based
on chapter 3 of the book
“Introduction to database
Systems”

By
S. Bressan and B. Catania,
McGraw Hill publisher

Clipart and media are licensed from
Microsoft Office Online Clipart
and Media

Copyright © 2016 by Stéphane Bressan

