

In the Lecture Series Introduction to Database Systems

Calculus

Presented by Stéphane Bressan

Introduction to Database Systems

Relational Calculi

There are two calculi:

- Domain relational calculus (DRC);
- T-uple relational calculus (TRC).
- DRC and TRC are query languages
- They are both based on logic

Introduction to Database Systems

Learning Objectives

- Write and understand queries in Domain Relational Calculus
- Write and understand queries in T-uple Relational Calculus

Introduction to Database Systems

Propositional Logic

“Aristotle is Greek”

“Aristotle is Greek and Alexander is Persian”

“Aristotle is not Persian”

“Alexander is Macedonian or Persian”

Introduction to Database Systems

Propositional Logic

“Roxane is Bactrian or not Bactrian”

“Olympias is Greek and is not Greek”

“Olympias is Greek implies Alexander is Greek”

“Roxane is Bactrian implies Roxane is Bactrian”

Introduction to Database Systems

Propositional Logic

“Olympias is Greek implies Alexander is Greek”

“Alexander is not Greek implies Olympias is not Greek”

Introduction to Database Systems

Semantics of Propositional Logic

The semantic of propositional logic is defined by truth tables

A	B	$(A \vee B)$	$(A \wedge B)$	$(A \Rightarrow B)$	$\neg(A)$
T	T	T	T	T	F
F	T	T	F	T	T
T	F	T	F	F	F
F	F	F	F	T	T

$(\neg A \vee B)$

Introduction to Database Systems

First Order Logic: Predicates

`greek(aristotle)`

`greek(X)`

`mother(olympias, alexander)`

`mother(X, Y)`

Introduction to Database Systems

First Order Logic

$\exists X \text{ greek}(X)$

$\exists X \text{ mother}(\text{olympias}, X)$

$\exists X \exists Y \text{ mother}(Y, X)$

$\exists Y \exists X \text{ mother}(Y, X)$

Introduction to Database Systems

First Order Logic

$\forall X \text{ greek}(X)$

$\forall Y \exists X \text{ mother}(X, Y)$

$\exists X \forall Y \text{ mother}(X, Y)$

Introduction to Database Systems

First Order Logic

$\forall X \forall Y ((\text{mother}(X, Y) \wedge \text{greek}(X)) \Rightarrow \text{greek}(Y))$

Introduction to Database Systems

Syntax of First Order Logic

First order logic consists of formulae built from predicates, constants (*lower case*) and variables (*upper case*), and connectives:*

- $(F \wedge G)$
- $(F \vee G)$
- $\neg(F)$
- $(F \Rightarrow G)$

And **quantifiers**: \forall and \exists

Variables can be quantified (bound) or free


Introduction to Database Systems

Semantics of Predicate Logic

To avoid confusion we agree that:

A variable is quantified once at most.

If a variable is quantified in a formula, it cannot appear outside of the scope of its quantifier.



Introduction to Database Systems

Semantics of Predicate Logic

$\neg \forall X F$ is equivalent to $\exists X \neg F$

$\neg \exists X F$ is equivalent to $\forall X \neg F$

(*Here F represents a formula)

Introduction to Database Systems

Calculus

- A Calculus defines formulae and their meaning
- T-uple Relational Calculus: variables range over t-uples (TRC)
- Domain Relational Calculus: variables range over values (DRC)

Introduction to Database Systems

Calculus

How to represent the set of integers 2, 3, and 4?

In extension:

$\{2, 3, 4\}$

In Intention (set-builder notation, comprehension, abstraction):

$\{X \mid X \in \mathbb{N} \wedge 1 < X \wedge X < 5\}$

Introduction to Database Systems

Calculus: Where is the Truth?

- The truth is in the database
- If a relation Mother in the database has a t-uple mother(olympias, alexander) then Olympias is the mother of Alexander
- Otherwise it is not (*closed world assumption*)


Introduction to Database Systems

T-uple relational Calculus

Introduction to Database Systems

Example

- lecturer(matric, name)
- module(code, name, credit),
- teach(matric, code)



Introduction to Database Systems

Example

- $\{T \mid T \in \text{lecturer}\}$
- $\{T \mid \exists T1 (T1 \in \text{lecturer} \wedge T = T1)\}$
- $\{T \mid \exists T1 (T1 \in \text{Lecturer} \wedge T.\text{matric} = T1.\text{matric} \wedge T.\text{name} = T1.\text{name})\}$
by CONVENTION!

SELECT *
FROM
LECTURER

SELECT
matric, name
FROM lecturer

Syntax of T-uple Relational Calculus

- Parenthesis can be omitted if non ambiguous

Introduction to Database Systems

Example

- $\{T \mid \exists T1 T1 \in \text{lecturer} \wedge T.\text{name} = T1.\text{name}\}$

select only the name

Introduction to Database Systems

Example

- $\{T \mid \exists T1 T1 \in \text{lecturer} \wedge T1.\text{name} = \text{"Smith"} \wedge T.\text{matric} = T1.\text{matric}\}$

SELECT matric
FROM lecturer
WHERE name='Smith'

Introduction to Database Systems

Example

- $\{T \mid \exists T1 \exists T2 \exists T3$
 $T1 \in \text{lecturer}$
 $\wedge T2 \in \text{module}$
 $\wedge T3 \in \text{teach}$
 $\wedge T1.\text{matric} = T3.\text{matric}$
 $\wedge T2.\text{code} = T3.\text{code}$
 $\wedge T2.\text{credit} < 3$
 $\wedge T.\text{lec_name} = T1.\text{name}$
 $\wedge T.\text{mod_name} = T2.\text{name}\}$

FROM

WHERE

SELECT

Introduction to Database Systems

Example

```
SELECT
  T1.name as lec_name,
  T2.name as mod_name
FROM lecturer T1, module T2, teach t3
WHERE T1.matric = T3.matric
      AND T2.code = T3.code
      AND T2.credit < 3
```

Introduction to Database Systems

Example (incorrect)

$P \Rightarrow Q$
 $P \vee Q$

- $\{T \mid \exists T1$
 $T1 \in \text{lecturer}$
 $\wedge ((\exists T2 T2 \in \text{module}) \Rightarrow (\exists T3$
 $T3 \in \text{teach}$
 $\wedge T1.\text{matric} = T3.\text{matric}$
 $\wedge T2.\text{code} = T3.\text{code}))$
 $\wedge T.\text{name} = T1.\text{name}\}$

WRONG (Scope)

all quantifiers must be
on top

Introduction to Database Systems

Example (correct)

De Morgan's

- $\{T \mid \exists T1 \forall T2 \exists T3$
 $T1 \in \text{lecturer}$
 $\wedge (T2 \in \text{module} \Rightarrow ($
 $T3 \in \text{teach}$
 $\wedge T1.\text{matric} = T3.\text{matric}$
 $\wedge T2.\text{code} = T3.\text{code}))$
 $\wedge T.\text{name} = T1.\text{name}\}$

$\exists P P(x) \Rightarrow \exists Q Q(x)$

$(\exists P P(x))' \vee (\exists Q Q(x))$

$\forall P (P(x))' \vee \exists Q Q(x)$

$\forall P \exists Q (P(x))' \vee Q(x)$

Introduction to Database Systems

Attention!

- $\exists T \in r (F)$
means $\exists T (T \in r \wedge F)$
- $\exists T1 \in r \exists T2 \in s (F)$
means $\exists T1 \exists T2 (T1 \in r \wedge T2 \in s \wedge F)$

(*Here F represents a formula)

Introduction to Database Systems

Attention!

- $\forall T \in r (F)$
means $\forall T (T \in r \Rightarrow F)$
- $\forall T1 \in r \forall T2 \in s F$
means
 $\forall T1 \forall T2 ((T1 \in r \wedge T2 \in s) \Rightarrow F)$

(*Here F represents a formula)

Introduction to Database Systems

Semantics of T-uple Relational Calculus

Example

- $\forall T \in \text{module} (T.\text{credit} > 1)$

means

- $\forall T (T \in \text{module} \Rightarrow T.\text{credit} > 1)$

and does not mean

- $\forall T (T \in \text{module} \wedge T.\text{credit} > 1)$

Introduction to Database Systems

Semantics of T-uple Relational Calculus

$\{T \mid F(T)\}$

- An **interpretation** I is a mapping of a formula to $\{\text{true}, \text{false}\}$
- An interpretation is defined by a mapping I of the free variable (T) of a formula $(F(T))$ to a t-uple t of constants
- $t \in R$ is true if and only if the t-uple t is in the instance of R in the database
- A **model** is an interpretation for which the formula is true

Introduction to Database Systems

Safety of Queries in T-uple Relational Calculus

$\{T \mid T \notin \text{lecturer}\}$

("mycat", 22, "red") is not a lecturer, any t-uple in the world maybe an answer if it is not already in the lecturer relation.



Introduction to Database Systems

Safety of Queries in T-uple Relational Calculus

$\{T \mid \exists T1 \ T1 \in \text{lecturer} \\ \wedge T1.\text{matric} \neq '1234' \\ \wedge T.\text{name} = T1.\text{name}\}$

Introduction to Database Systems

Safety of Queries in T-uple Relational Calculus

A query is **safe** if the set of t-uples in the answer is a subset of the set of t-uples that can be constructed from the constants explicitly referenced directly (they appear in the query) or indirectly (they appear in a relation mentioned in the query) in the query.

When you can map the relation to a set of tables

Introduction to Database Systems

Safety

We consider only safe queries


Introduction to Database Systems

Domain Relational Calculus

Introduction to Database Systems

Example

- lecturer(matric, name)
- module(code, name, credit),
- teach(matric, code)



Introduction to Database Systems

Example

- $\{ \langle X \rangle \mid \exists Y \text{ lecturer}(X, Y) \}$ → Tuple constructor
- $\{ \langle X \rangle \mid \exists Y \text{ lecturer}(X, Y) \wedge Y = \text{"john"} \}$ → Only print matric
- $\{ \langle X \rangle \mid \text{lecturer}(X, \text{"john"}) \}$ → Same

- How do you express
SELECT * FROM Lecturer

SELECT matric
FROM lecturer

SELECT matric
FROM lecturer
WHERE name='john'

Introduction to Database Systems

Example

Find the names of lecturers teaching a module with less than 2 credits. Print the names of the lecturers and the names of the corresponding modules.

Introduction to Database Systems

Example

$\{ \langle LN, MN \rangle \mid \exists M \exists C \exists Cr$
Lecturer(M, LN)
 \wedge Module(C, MN, Cr)
 \wedge Teach(M, C)
 \wedge Cr < 2 }

COMPACT!!

Introduction to Database Systems

Example SQL

- $\{ \langle LN, MN \rangle \mid \exists M1 \exists M2 \exists C1 \exists C2 \exists Cr$
Lecturer(M1, LN)
 \wedge Module(C1, MN, Cr)
 \wedge Teach(M2, C2)
 \wedge C1 = C2 \wedge M1 = M2 \wedge Cr < 2 }

Added on: Get equality

Introduction to Database Systems

Example SQL

- SELECT
Lecturer.lecName,
Module.moduleName
FROM Lecturer, Module, Teach
WHERE Lecturer.matric=Teach.matric
AND Module.code = Teach.code
AND Module.credit < 2

Introduction to Database Systems

Example

$$\{ \langle M1, M2, N \rangle \mid$$
$$\text{lecturer}(M1, N)$$
$$\wedge \text{lecturer}(M2, N)$$
$$\wedge M1 \neq M2 \}$$

Look for diff lecturers with the same name

Introduction to Database Systems

Example

$$\{ \langle M1, M2, N1 \rangle \mid \exists N2$$
$$\text{lecturer}(M1, N1)$$
$$\wedge \text{lecturer}(M2, N2)$$
$$\wedge M1 \neq M2$$
$$\wedge N1 = N2 \}$$

Introduction to Database Systems

Example

Find the names of the lecturers teaching all modules

$$\{ \langle N \rangle \mid \exists M \forall C \forall MN \forall Cr$$
$$(\text{lecturer}(M, N) \wedge$$
$$(\text{Module}(C, MN, Cr) \Rightarrow \text{teach}(M, C))) \}$$

IF there is a module, then the lecturer must teach it

Introduction to Database Systems

Semantics of Domain Relational Calculus

$$\{ \langle X_1, \dots, X_n \rangle \mid F(X_1, \dots, X_n) \}$$

- An **interpretation** I is a mapping of each formula to **{true, false}**
- An interpretation is defined by a mapping I of the free variables (X_1, \dots, X_n) of a formula $(F(X_1, \dots, X_n))$ to constants
- $R(c_1, \dots, c_n)$ is true if and only if the tuple $\langle c_1, \dots, c_n \rangle$ is in the instance of R in the database
- A **model** is an interpretation for which the formula is true

Introduction to Database Systems

Example

Find the names of the lecturers teaching all modules:

$$\{ \langle N \rangle \mid \exists M \forall C \forall MN \forall Cr$$
$$(\text{lecturer}(M, N) \wedge$$
$$(\text{Module}(C, MN, Cr) \Rightarrow \text{teach}(M, C))) \}$$

Introduction to Database Systems

Example

$$\exists M \forall C \forall MN \forall Cr$$

We are looking for values of N such that the formula below is true for **SOME** value of M and, for that value of M , for **ALL** values of C , MN and Cr and :

$$(\text{lecturer}(M, N) \wedge$$
$$(\text{Module}(C, N, Cr) \Rightarrow \text{teach}(M, C))) \}$$

Introduction to Database Systems

Example

If $\langle M, N \rangle$ if a lecturer and
 $\langle C, N, Cr \rangle$ is not a module the formula is
true!!!!

$$(\text{lecturer}(M, N) \wedge \\ (\text{Module}(C, N, Cr) \Rightarrow \text{teach}(M, C))) \}$$

Introduction to Database Systems

Example

If $\langle M, N \rangle$ if a lecturer and
 $\langle C, N, Cr \rangle$ is a module, and M teaches C
the formula is true

$$(\text{lecturer}(M, N) \wedge \\ (\text{Module}(C, N, Cr) \Rightarrow \text{teach}(M, C))) \}$$

Introduction to Database Systems

Example

The formula is false only if
 $\langle M, N \rangle$ is not a lecturer or if
 $\langle C, N, Cr \rangle$ is a module, and M does not
teach C

$$(\text{lecturer}(M, N) \wedge \\ (\text{Module}(C, N, Cr) \Rightarrow \text{teach}(M, C))) \}$$

Introduction to Database Systems

Safety of Queries in the Domain Calculus

$$\{ \langle M, N \rangle \mid \neg \text{lecturer}(M, N) \}$$

* \neg All variables here
Must NOT be quantified

* Variables in body
must be
quantified



Introduction to Database Systems

Safety of Queries in the Domain Calculus

- A query is **safe** if the set of t-uples in the answer is a subset of the set of t-uples that can be constructed from the constants explicitly referenced directly (they appear in the query) or indirectly (they appear in a relation mentioned in the query) in the query.

Introduction to Database Systems

Safety

- We consider only safe queries

Introduction to Database Systems


Credits

The content of this lecture is based
on chapter 3 of the book
"Introduction to database
Systems"

By
S. Bressan and B. Catania,
McGraw Hill publisher

Clipart and media are licensed from
Microsoft Office Online Clipart
and Media

Copyright © 2013 by Stéphane Bressan



Introduction to Database Systems