

CS2102

Tutorial 06

Question 2

- Make a trigger on customers table to check that customers cannot be workers (or symmetrically, make a trigger on workers table to check that workers cannot be customers).
- Check query?
 -
- Code structure?
 -

Question 2

- Make a trigger on customers table to check that customers cannot be workers (or symmetrically, make a trigger on workers table to check that workers cannot be customers).
- Check query?
 - `SELECT COUNT(*) > 0 FROM Workers W
WHERE NEW.username = W.username;`
- Code structure?
 - IF `check` THEN RETURN `NULL`; ELSE RETURN `NEW`; END IF
 - `Prevent` or `allow` insertion based on `check`

Question 3


- Create a stored procedure `add_customers` that takes in `uname` and `pass` and add the customer in a way that satisfy covering constraint on the ISA (or alternatively, create a stored procedure `add_workers` that takes in `uname`, `pass`, and `expr` and add the customer in a way that satisfy covering constraint on the ISA).
- What needs to be modified?
 - Customers table
 - Users table

Question 3

- Create a stored procedure `add_customers` that takes in `uname` and `pass` and add the customer in a way that satisfy covering constraint on the `ISA` (or alternatively, create a stored procedure `add_workers` that takes in `uname`, `pass`, and `expr` and add the customer in a way that satisfy covering constraint on the `ISA`).
- What needs to be modified?
 - Customers table
 - `INSERT INTO Users VALUES (uname, pass);`
 - Users table
 - `INSERT INTO Customers VALUES (uname);`

Question 4


- Create a trigger on any update and insertion on availability to check for overlap.
- How to check if overlap?
 - Case analysis



$\text{NEW.s_time} < \text{X.s_time} < \text{NEW.e_time} < \text{X.e_time} \implies (\text{NEW.s_time}, \text{X.e_time})$

Question 4


- Create a trigger on any update and insertion on availability to check for overlap.
- How to check if overlap?
 - Case analysis



`X.s_time < NEW.s_time < X.e_time < NEW.e_time ==> (X.s_time, NEW.e_time)`

Question 4


- Create a trigger on any update and insertion on availability to check for overlap.
- How to check if overlap?
 - Case analysis



`NEW.s_time < X.s_time < X.e_time < NEW.e_time ==> (NEW.s_time, NEW.e_time)`

Question 4

- Create a trigger on any update and insertion on availability to check for overlap.
- How to check if overlap?
 - Case analysis



$X.s_time < NEW.s_time < NEW.e_time < X.e_time \implies (X.s_time, S.e_time)$

Question 5

- We want to choose the manager with the highest past work experience that has not become a manager.
- Finding the manager?
 - ```
SELECT uname FROM Workers W
WHERE uname NOT IN (SELECT uname FROM Manages)
ORDER BY expr DESC, uname ASC
LIMIT 1
```

# Question 6

- We wish to prevent bidding on any availability that already has a winner. This can be enforced via trigger on any insertion or update to bid. Create this trigger.
  - Checking the condition?
    -
  - 
  - Code structure
    -

# Question 6

- We wish to prevent bidding on any availability that already has a winner. This can be enforced via trigger on any insertion or update to bid. Create this trigger.
  - Checking the condition?
    - ```
SELECT 1 FROM Bid B
WHERE  NEW.ctuname = B.ctuname AND NEW.s_date = B.s_date
      AND NEW.s_time = B.s_time  AND NEW.e_time = B.e_time
      AND B.is_win;
```
 - 1 if exists, null if not exists
 - Code structure
 - ```
IF check THEN RETURN NULL; ELSE RETURN NEW; END IF
```

# Question 7

- We only allow worker to train care takers if they have a combined total past work experience and current working experience at PetER of 5 years.
- Checking the condition?
  - ```
SELECT DISTINCT uname FROM Workers W
WHERE  (SELECT EXTRACT(AGE(NEW.s_date, W.s_date)))
        >
        5-W.expr
```