

Structured Query Language


- Originally developed in the System-R project of IBM (1974)
- Industry standard for relational databases (SQL92 is an ANSI/ISO standard)


Introduction to Database Sustans


Structured Query Language


- Data Definition Language for defining relations, views, integrity constraints, triggers
- Data Manipulation Language for updating, and querying
- Database Control Language for defining access rights, concurrency control, etc....


Introduction to Database Systems

















```
Duplicates

Find the different names of students who lent a book returned after 2010-03-04 to anniechapman1991@yahoo.com

SELECT DISTINCT s.name AS owner

FROM loan 1, student s
WHERE s.email=1.owner


AND l.returned > '2010-03-04'


AND l.borrower = 'anniechapman1991@yahoo.com';


Owner


DENNS BECKHAM


GE DUO
TSO HULLIN
YEO JIA HAO
...
```





































use order by

Aggregate Queries: Grouping What does this query find? SELECT 1.borrower, 1.borrowed, COUNT(1.book) FROM loan 1 GROUP BY 1.borrowed, 1.borrower, 1.book;



Aggregate Queries: Condition grouping Find the students who borrowed more that one book on any given day SELECT 1.borrower FROM loan 1 GROUP BY 1.borrowed, 1.borrower HAVING COUNT(1.book) >1; Can put Conditions arging/1990@hormal.com arging/1990@hormal.com arging/1990@hormal.com arniechapman1991@yahoo.com ...

aggregate



```
Nested Queries

Find the names of the students from whom anniechapman1991@yahoo.com borrowed a book and returned it after 2010-03-04

SELECT s.name
FROM student s
WHERE s.email = (SELECT 1.own)
FROM loan 1
WHERE f.returned > '2010-03-04'
AND 1.borrower = 'anniechapman1991@yahoo.com');

this does not work
```

```
Nested Queries

Find the names of the students from whom anniechapman1991@yahoo.com borrowed a book and returned it after 2010-03-04

SELECT s.name
FROM student s
WHERE s.email = (ANY) (SELECT 1.owner
FROM loan 1
WHERE 1.returned > '2010-03-04'
AND 1.borrower = 'anniechapman1991@yahoo.com');

22 rows

possible to write a single query
but a lot longer
```

try to give a simple query first no choice use aggregates no choice use nested queries

Nested Queries Find the names of the students from whom anniechapman1991@yahoo.com borrowed a book and returned it after 2010-03-04 SELECT s.name FROM student s WHERE email IN (SELECT 1.owner FROM loan 1 WHERE 1.returned > '2010-03-04' AND 1.borrower = 'anniechapman1991@yahoo.com');

```
Nested Queries

Find the names of the students from whom anniechapman1991@yahoo.com borrowed a book and returned it after 2010-03-04

SELECT s.name
FROM loan 1, student s
WHERE s.email=l.owner
AND 1.returned > '2010-03-04'
AND 1.borrower = 'anniechapman1991@yahoo.com';

27 rows

Does not give same
10. of rows

Live of distinct Ditaban Systems
```

```
Find the different names of the students from whom anniechapman1991@yahoo.com borrowed a book and returned it after 2010-03-04

SELECT DISTINCT a name FROM loan 1, student s
WHERE s, email 1-whiter
AND 1.returned > '2010-03-04'
AND 1.borrower = 'anniechapman1991@yahoo.com';
```

usually used if there is some kind of negation

linvolved

```
Nested Queries

Find the different students from whom anniechapman1991@yahoo.com never borrowed

SELECT s.email
FROM student s
WHERE s.email <> ALL (SELECT 1.owner
FROM loan 1
WHERE 1.borrower = 'anniechapman1991@yahoo.com');

72 rows
```

Nested Queries

Find the different students from whom anniechapman1991@yahoo.com never borrowed

```
SELECT s.email
FROM student s
WHERE NOT EXISTS (SELECT l.owner
FROM loan l
WHERE s.email = l.owner
AND l.borrower = 'anniechapman1991@yahoo.com');
```

Nested Queries (Scope) -

An attribute can only be used within the SELECT and WHERE clauses of the query in which its relation is declared (FROM clause) and within sub-queries queries

like double for loops

i can be used within the inner for loop

n Natalana Cantana

Nested Queries

- There can be multiple nested queries and multiple levels of nested queries
- Nested queries can appear in the WHERE but also the HAVING clauses

Introduction to Database System

Union

```
SELECT *
FROM student T
WHERE T.department='CS'
UNION
SELECT *
FROM student T
WHERE T.department='IS'
```

Find all the information about students in the computer science department or in the information systems department

Introduction to Database Systems

Intersection

```
SELECT T1.email
FROM student T<sup>I</sup>
WHERE T1.department='CS'
INTERSECT
SELECT T2.owner AS email
FROM copy T2
WHERE T2.book='978-0262033848'
```

Find the emails of students in the computer science department owning a book with ISBN14 '978-0262033848'

Introduction to Database Systems

(Non-Symmetric) Difference

```
SELECT T1.email

FROM student T1

WHERE T1.department='CS'

MINUS

SELECT T2.owner AS email

FROM copy T2

WHERE T2.book='978-0262033848'
```

Find all the mails of students in the computer science department but those owning a book with ISBN14 '978-0262033848'

in other systems EXCEPT

Introduction to Database Systems

suggested not to do this

Join

SELECT T1.email FROM student T1, copy T2 WHERE T1.department='CS' AND T2.owner=T1.email AND T2.book='978-0262033848'

Find all the mails of students in the computer science department owning a book with ISBN14 '978-0262033848'

not a set operation just a query

Introduction to Database System

Inner Join

SELECT T1.email
FROM student T1 INNER JOIN copy T2
ON T2.owner=T1.email
WHERE T1.department='CS'
AND T2.book='978-0262033848'

Find all the mails of students in the computer science department owning a book with ISBN14 '978-0262033848'

e May

Introduction to Database Systems

Left Outer Join

Select T1.name,T2.book
FROM student T1, copy T2
WHERE T1.email=T2.owner
UNION
SELECT T3.name, CAST(NULL AS CHAR(14)AS book
FROM student T3
WHERE NOT EXISTS (SELECT *
FROM copy T4
WHERE T3.email=T4.owner)

Find the names of the students and the titles of the books they own. If a student does not own any book, print a NULL value

Introduction to Database Systems

Left Outer Join

Select DISTINCT T1.name,T2.book
FROM student T1 LEFT OUTER JOIN copy T2
ON T1.email=T2.owner

Find the names of the students and the titles of the books they own. If a student does not own any book, print a NULL value

Right Outer Join

Select DISTINCT T2.title, T1.owner FROM copy T1 RIGHT OUTER JOIN book T2 ON T1.book=T2.ISBN14

Find the title of books and the emails of their owner. If a book does not have an owner , print a NULL value

Introduction to Database Systems

Full Outer Join

Same

Select DISTINCT T2.a, T1.c FROM table1 T1 FULL OUTER JOIN table T2 ON T1.b=T2.b

Introduction to Database Systems

Other Join

- (EQUI) JOIN
- NATURAL JOIN USING
- CROSS JOIN

letroduction to Database Susta

Summary

- 1. FROM
- 2. WHERE
- 3. GROUP BY
- 4. HAVING
- 5. ORDER BY
- 6. SELECT

Introduction to Database Sustan

Credits

The content of this lecture is based on chapter 5 of the book "Introduction to database Systems"

By
S. Bressan and B. Catania,

Animated characters are animated using VocaliseTTS under license from Digital Curiosty

Clipart and media are licensed from Microsoft Office Online Clipart and Media

Copyright © 2013 by Stéphane Bressan



Introduction to Database Syste