
FORD TRUCKS 3243S HR EURO3



Basic Features					
Vehicle Type	Road Truck				
Axle	8x2				
Emission	Euro 3				
Cabin Type	High Roof Sleeper Cabin				
Wheelbase (mm)	5200				
Engine					

Ecotorq 12,7 litre Type Displacement (cc) 12740 Diameter x Stroke 130 mm x 160 mm 430 PS (316,3 kW) / 1800 rpm Power 2150 Nm / 1000-1300 rpm Torque 17 +/- 0,5:1 Compression Ratio Oil Filling Volume 50 L Coolant Volume 57 L (77 L with Retarder)

Transmission Clutch 430 mm Single Disc

Automated Transmission / Ratios (1. gear - 16. gear) Ecotorq 16S 2600 DD AMT (17,03 - 1,00)

Steering

Power Assisted Hema ZF 8098 servocom

Chassis						
Chassis Thickness	7 mm with Reinforcement					
Chassis Strength	355 MPa					
Suspension (Front / Rear)	Parabolic Leaf Spring / Compensating Arm Mechanical Suspension					
Axle	Standard Single Reduction					
Axle Ratio	2,64					
Tyres (Front / Rear)	315/80 R 22,5					
Wheel Rim	22.5 x 9.Steel					

Braking System Brakes (Front / Rear) (Ø.mm x mm. Length) 430 x 45 Disc Brake Braking System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater

Engine Brake Power max. 320 kW (Engine Level) Retarder Power max. 450 kW / continuous 160 kW

Electric System 225 Ah Battery

Alternator / Starter Motor 130 A / 6,5 kW Tanks

Fuel Tank 550 L Aluminium



1820

Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5200		
Overall Length			9840		
Distance Between 1st and 2nd Wheel Centers			3770		
Distance Between 2 nd and 3 th Wheel Centers			1430		
Distance Between 3th and 4th Wheel Centers			1320		
Overall Cab Length			2305		
Overall Vehicle Height			3368		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			866		
Rear Overhang			1820		
Useful Chassis Length			7200		
Chassis Height - Front			225		
Chassis Height - Rear			285		
Ground Clearance - Front			355		
Ground Clearance - Rear			367		
Turning Radius			10700		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	7100	7100	12600	10400	32000
Korh Woight	5307	1642	1990	1275	10108

Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	7100	7100	12600	10400	32000
Kerb Weight	5392	1642	1889	1275	10198
Payload	1708	5458	10711	9125	21802

STANDARD EQUIPMENT

- Air Conditioner
- Radio/CD/MP3 Player
- Cruise Control
- Disc Brake
- Engine Brake
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Differential Lock
- Electrically Operated Windows
- Electrically Operated Headlight Levelling
- Electrically Operated and Heated Side Mirrors
- Hill Launch Assist
- Spare Wheel
- Manually Operated Sunroof
- Heated and Air Suspended Driver Seat
- with Lumbar Support
- Rake and Reach Adjustable Steering Column
- Front Fog Lamps
- Immobilizer
- Home Safe Light
- Approach Light
- Brake Lining Wear Sensor
- Tachograph
- Tag Axle Lifting

OPTIONAL EQUIPMENT

- Transmission Driven PTO & Interior Control Unit
- Engine Driven PTO & Interior Control Unit *
- ADR Pack
- Cold Climate Pack
- Auxiliary Cabin Heater (Wet Type)
- Aluminium Alloy Wheels
- Power Cab Tilting
- Metallic Paint / Special Colors
- RHS Free 5900 Wheelbase option **
- Rain Sensor
- Auto Light Sensor
- Digital Tachograph
- Air Suspended Cabin
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- Retarder
- Led Headlamps

*Available for Firefighter Pack Only ** Available with ADR and 250lt LHS Fuel Tank