## FORD TRUCKS 4143XHD EURO3





Basic Features	
Vehicle Type	Tipper
Axle	8x4
Emission	Euro 3
Cabin Type	Day Cab
Wheelbase (mm)	5100

Engine	
Type	Ecotorq 12,7 Litre
Displacement (cc)	12740
Diameter x Stroke	130 mm x 160 mm
Power	430 PS (316,3 kW ) / 1800 rpm
Torque	2150 Nm / 1000-1300 rpm
Compression Ratio	17 +/- 0,5 : 1
Oil Filling Volume	501

Transmission	
Clutch	Twin Clutc

 Manuel Transmission / Ratios (1. gear - 16. gear)
 ZF 16S 2530 (13,805-0,836)

 Automated Transmission / Ratios (1. gear - 16. gear)
 Ecotorq 16S 2600 OD (14,107 - 0,823)

Steering

Coolant Volume

Power Assisted Single Circuit

57 L (77 L with Retarder)

Chassis		
Chassis Thickness	10 mm with Reinforcement	
Chassis Strength	500 MPa	
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / Parabolic Tandem Suspension	
Axle	Hub Reduction	
Axle Ratio (Manual / Automatic)	4,87/4,08	
Tyres	13R22.5	
Wheel Rim	22,5 x 9 Steel	
Braking System		

Braking System	
Brakes (Front / Rear) (Ø.mm x mm. Length)	410 x 200, Z-Cam Brake System
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater
Engine Brake Power	max. 320 kW (Engine Level)
Hydraulic Retarder Power	max. 450 kW / continuous 160 kW
Electric System	

Battery 225 Ah
Alternator / Starter Motor 130 A / 6,5 kW

Tanks

Fuel Tank 315 L Steel



Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5100		
Overall Length			8890		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 <sup>nd</sup> and 3 <sup>th</sup> Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1820		
Overall Vehicle Height			3245		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6490		
Chassis Height - Front			1205		
Chassis Height - Rear			1171		
Ground Clearance - Front			390		
Ground Clearance - Rear			327		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total

Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	41900
Kerb Weight	3565	3641	2528	2203	11936
Payload	4435	4359	10872	11197	29964

## STANDARD EQUIPMENT

- Air Conditioner
- AM/FM/Aux In/USB/Bluetooth (Radio with Bluetooth)
- Transmission Direct (Double Gear) PTO without Flange and Interior Control Unit
- Engine Brake
- Drum Brake
- Cruise Control
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Front Vehicle Antiroll Bar
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Tachograph
- Short Bumper
- Switchable Air Compressor for Improved Fuel Economy
- Reinforced Wheel Rim
- Electro-Hydraulic Power-Assisted Steering System (EHPAS)
- Automatic Traction Control

## **OPTIONAL EQUIPMENT**

- Automated Transmission (with Normal Mode, Off Road Mode, Rocking Mode)
- Engine Driven PTO & Interior Control Unit
- Hydraulic Retarder
- Low Roof Sleeper Cab with Single Bed
- Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry Type Cab Heater \*
- Power Cab Tilting
- Rear Window \*\*
- Digital Tachograph
- Double Passenger Seat \*\*
- Manually Operated SunroofTransmission Direct (Single Gear) PTO with Flange and
- Oil Pan Guard
- Tinted Glass
- Roof Beacon Light

Interior Control Unit

- DAB Radio
- Multimedia System with 9" Touch Screen & Navigation
- (Radio, Bluetooth, USB (A Type C Type), Apple CarPlay, Android Auto, Remote Control)
- Led Headlamps

<sup>\*</sup> Only Available with Low Roof Sleeper Cab Version

<sup>\*\*</sup> Not Available with Low Roof Sleeper Cab Version