FORD TRUCKS 3543T DC EURO3





| Basic Features | |
|----------------|---------|
| Vehicle Type | Tractor |
| Axle | 6x4 |
| Emission | Euro 3 |
| Cabin Type | Day Cab |
| Wheelbase (mm) | 3800 |

| Engine | |
|-------------------|-------------------------------|
| Type | Ecotorq 12.7 litre |
| Displacement (cc) | 12740 |
| Diameter x Stroke | 130 mm x 160 mm |
| Power | 430 PS (316,3 kW) / 1800 rpm |
| Torque | 2150 Nm / 1000-1300rpm |
| Compression Ratio | 17 +/- 0 5 · 1 |

Oil Filling Volume 50 L
Coolant Volume without Retarder 57 L; with Retarder 77 L

Transmission

Clutch $2 \times 400 \text{ mm}$ Twin Clutch Manuel Transmission / Ratios (1. gear - 16. gear) 2F 16S 2530 (13,80 - 0,84)

Steering

Power Assisted Single Circuit

22,5 x 9 Steel

| Chassis | |
|---------------------------|--|
| Chassis Thickness | 10mm with Local Reinforcement |
| Chassis Strength | 500 MPa |
| Suspension (Front / Rear) | Parabolic Leaf Springs / Parabolic Tandem Suspension |
| Axle | Hub Reduction |
| Axle Ratio | 4,87 |
| 5th Wheel | 1400 mm / 3,5 inch King Pin |
| Tyres | 315/80 R 22,5 |

Braking System

Wheel Rim

Brakes (front/rear) (Ø.mm x mm. length) 410 X 200, Z-Cam Brake System

Braking System Dual Brake Circuit – Air Processing Unit with Integrated Oil Seperator and Heater

Engine Brake Power max. 320 kW (Engine Level)

Hydraulic Retarder Power max. 600kW / continuous 160kW

Electrical System

Battery 225 Ah
Alternator / Starter Motor 130 A / 6,5 kW

Tanks

Fuel Tank 400 L Aluminum



| Dimensions (mm) | | | | |
|--|---------|---------|---------|-------|
| Front Overhang | | 15 | 500 | |
| Wheelbase | | 3 | 800 | |
| Overall Length | | 7- | 460 | |
| Distance Between 2 nd and 3 th Wheel Centers | | 13 | 350 | |
| Overall Cab Length | | 2 | 090 | |
| Overall Vehicle Height | | 3 | 223 | |
| Overall Vehicle Width (Excluding Mirrors) | | 2 | 540 | |
| Chassis Width | | 7 | 770 | |
| Rear Overhang | | 3 | 310 | |
| Chassis Height - Front | | 1 | 1114 | |
| Chassis Height - Rear | | 1 | 152 | |
| Ground Clearance - Front | | 3 | 380 | |
| Ground Clearance - Rear | | 3 | 305 | |
| Turning Radius | | 8 | 790 | |
| Weights (kg) | 1. Axle | 2. Axle | 3. Axle | Total |
| Technically Permissible Weights | 8000 | 13400 | 13400 | 32000 |
| Kerb Weight | 5585 | 2806 | 2458 | 10849 |
| Payload | 2415 | 10594 | 10942 | 21151 |
| GCW | | | | 80000 |
| | | | | |

STANDARD EQUIPMENT

- Air Conditioner
- AM/FM/Aux In/USB/Bluetooth (Radio with Bluetooth)
- Transmission Offset (double gear) PTO without Flange
- 4 Point Independent Cab Suspension for Day Cab
- Cruise Control
- Drum Brake
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Ventilation Roof
- Lumbar Support
- Top mounted spare wheel carrier
- Front and Rear Vehicle Antiroll Bars
- Anti-lock Brake System (ABS)
- Pad Wear Indicator
- Immobilizer
- Home Safe Light
- Differential Lock
- Tachograph
- Short Bumper
- Switchable Air Compressor (For Improved Fuel Economy)
- Trailer coupling
- Jost 5th wheel
- Approach Light
- Automatic Traction Control (ATC)
- Electronic Brake System (EBS)

OPTIONAL EQUIPMENT

- Transmission Driven PTO Options & Interior Control Unit
- Engine PTO Options & Interior Control Unit
- Hydraulic Retarder
- Low Roof Sleeper Cab
- Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
- Electrically Operated Cab Tilting
- 1350, 1450 5. Wheel Options
- Rear Window
- ADR
- Tinted Glass
- Electronic Stability Control (ESP)
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- Led Headlamps