

FORD TRUCKS 4143D EURO3





Basic Features	
Vehicle Type	Tipper
Axle	8x4
Emission	Euro 3
Cabin Type	Day Cab
Wheelbase (mm)	5100

Engine	
Type	Ecotorq 12.7 Litre
Displacement (cc)	12740
Diameter x Stroke	130 mm x 160 mm
Power	430 PS (316,3 kW) / 1800 rpm
Torque	2150 Nm / 1000-1300 rpm
Compression Ratio	17 +/- 0,5 : 1
Oil Filling Volume	50 L

	,
Transmission	
Clutch	430 mm Single Disc
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2530 (13,805-0,836)
Automated Transmission / Ratios (1. gear - 16. gear)	Ecotorq 16S 2600 OD (14,107 - 0,823)

Automated Transmission / Ratios (1. gear - 16. gear)

Steering

Coolant Volume

Alternator / Starter Motor

Power Assisted Single Circuit

130 A / 6,5 kW

57 L (77 L with Retarder)

Cilassis					
Chassis Thickness	10 mm with Reinforcement				
Chassis Strength	500 MPa				
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / Reinforced Parabolic Suspension				
Axle	Hub Reduction				
Axle Ratio (Manual / Automatic)	4,08 / 3,57				
Tyres	315/80 R 22,5				
Wheel Rim	22,5 x 9 Steel				
Braking System					

Braking System	
Brakes (Front / Rear) (Ø.mm x mm. Length)	410 x 200, Z-Cam Brake System
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater
Engine Brake Power	max. 320 kW (Engine Level)
Hydraulic Retarder Power	max. 450 kW / continuous 160 kW
Electric System	
Battery	225 Ah

Tanks
Fuel Tank 315 L Steel



Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5100		
Overall Length			8890		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1820		
Overall Vehicle Height			3245		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6490		
Chassis Height - Front			1185		
Chassis Height - Rear			1186		
Ground Clearance - Front			380		
Ground Clearance - Rear			295		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total

Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	41900
Kerb Weight	3741	3623	2028	2027	11419
Payload	4259	4377	11372	11373	30481

STANDARD EQUIPMENT

- Air Conditioner
- 1DIN Radio (Bluetooh, USB, Hands-free, Remote Control)/CD/MP3 Player
- Transmission Direct (Double Gear) PTO without Flange and Interior Control Unit
- Engine Brake
- Drum Brake
- Cruise Control
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Front Vehicle Antiroll Bar
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Tachograph
- Short Bumper
- Switchable Air Compressor for Improved Fuel Economy
- Electro-Hydraulic Power-Assisted Steering System(EHPAS)
- Automatic Traction Control

OPTIONAL EQUIPMENT

- Automated Transmission (with Normal Mode, Off Road Mode, Rocking Mode)
- Engine Driven PTO & Interior Control Unit
- Hydraulic Retarder
- Low Roof Sleeper Cab with Single Bed Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
 - Cold Pack with Dry Type Cab Heater *
- Power Cab Tilting
- Rear Window **
- 4750 mm Wheelbase Version
- Digital Tachograph
- Double Passenger Seat **
- Manually Operated Sunroof
- Transmission Direct (Single Gear) PTO with Flange and Interior Control Unit
- **Tinted Glass**
- · Reinforced Wheel Rim
- Roof Beacon Light
- Less Front Spare Wheel Option
- Rear Towing Hook Option
- DAB Radio
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type C Type), Apple CarPlay, Android Auto, Remote Control)
- Led Headlamps

^{*} Only Available with Low Roof Sleeper Cab Version

^{**} Not Available with Low Roof Sleeper Cab Version