
FORD TRUCKS 4143M EURO3





Basic Features	
Vehicle Type	Mixer
Axle	8x4
Emission	Euro 3
Cabin Type	Day Cab
Wheelbase (mm)	5100

Engine	
Type	Ecotorq 12,7 Litres
Displacement (cc)	12740
Diameter x Stroke	130 mm x 160 mm
Power	430 PS (316,3 kW) / 1800 rpm
Torque	2150 Nm / 1000-1300 rpm
Compression Ratio	17 +/- 0,5 : 1
Oil Filling Volumo	501

Coolant Volume
Transmission

Clutch 430 mm Single Disc Manuel Transmission / Ratios (1. gear - 16. gear) ZF 16S 2530 (13,805-0,836) Automated Transmission / Ratios (1. gear - 16. gear) Ecotorq 16S 2600 OD AMT (14,107 - 0,823)

Steering

Power Assisted Single Circuit

315 L Steel

57 L (77 L with Retarder)

CHassis					
Chassis Thickness	10 mm				
Chassis Strength	500 MPa				
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension				
Axle	Hub Reduction				
Axle Ratio (Manual / Automatic)	4,08/3,57				
Tyres	315/80 R 22,5				
Wheel Rim	22,5 x 9 Steel				

Braking System

Brakes (Front / Rear) (Ø.mm x mm. Length)	410 X 200, Z-Cam Brake System				
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater				
Engine Brake Power	max. 320 kW (Engine Level)				
Hydraulic Retarder Power	max. 450 kW / continuous 160 kW				
Electrical System					

Fuel Tank

Tanks	
Alternator / Starter Motor	130 A / 6,5 kW
Battery	225 Ah



Dimensions (mm)					
Front Overhang			1490		
Wheelbase			5100		
Overall Length			8860		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1330		
Overall Cab Length			1820		
Overall Vehicle Height			3292		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6490		
Chassis Height - Front			1152		
Chassis Height - Rear			1091		
Ground Clearance - Front			379		
Ground Clearance - Rear			296		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	40000

Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	40000
Kerb Weight	3554	3788	1869	1869	11080
Payload	4446	4212	11531	11531	28920

STANDARD EQUIPMENT

- Air Conditioner
- 1DIN Radio (Bluetooh, USB, Hands-free, Remote Control)/CD/MP3 Player
- Engine Driven PTO & Interior Control Unit
- Cruise Control
- Drum Brake
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Front and Rear Vehicle Antiroll Bar
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Tachograph
- Rear Window **
- Short Bumper
- Electro-Hydraulic Power-Assisted Steering System (EHPAS)
- Automatic Traction Control

OPTIONAL EQUIPMENT

- Automated Transmission (with Normal Mode, Off-Road Mode, Rocking Mode)
- Hydraulic Retarder
- ADR Pack
- Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry Type Cab Heater *
- Power Cab Tilting
- Switchable Air Compressor for Improved Fuel Economy
- Transmission Driven PTO Options
- Interior Control Unit
- Digital Tachograph
- Manually Operated Sunroof
- Tinted Glass
- Less Front Spare Wheel Option
- Rear Towing Hook
- DAB Radio
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- Led Headlamps

^{*} Only Available with Low Roof Sleeper Cab Version.

^{**} Not Available with Low Roof Sleeper Cab Version.