## FORD TRUCKS 4443D EURO3





Basic Features	
Vehicle Type	Tipper
Axle	8x4
Emission	Euro 3
Cabin Type	Day Cab
Wheelbase (mm)	5100

Engine	
Type	Ecotorq 12.7 Litre
Displacement (cc)	12740
Diameter x Stroke	130 mm x 160 mm
Power	430 PS (316,3 kW ) / 1800 rpm
Torque	2150 Nm / 1000-1300 rpm
Compression Ratio	17 +/- 0,5 : 1
Oil Filling Volume	50 L

Transmission	
Clutch	430 mm Single Disc
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2230 (13,805-0,836)

Automated Transmission / Ratios (1. gear - 16. gear)

Ecotorq 16S 2600 OD (14,107 - 0,823)

Steering

Coolant Volume

Power Assisted Single Circuit

57 L (77 L with Retarder)

Chassis					
Chassis Thickness	10 mm with Reinforcement				
Chassis Strength	500 MPa				
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / Reinforced Parabolic Suspension				
Axle	Hub Reduction				
Axle Ratio (Manual / Automatic)	4,87				
Tyres	385/65R 22.5				
Wheel Rim	22,5 x 11,75 Steel				
Braking System					

	Braking System					
Brakes (Front / Rear) (Ø.mm x mm. Length)		410 x 200, Z-Cam Brake System				
	Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater				
	Engine Brake Power	max. 320 kW (Engine Level)				
	Hydraulic Retarder Power	max. 450 kW / continuous 160 kW				
	Electric System					

 Battery
 24 V, 2 x 12 V 150 Ah

 Alternator / Starter Motor
 130 A / 6,5 kW

Tanks

Fuel Tank 315 L Steel



Dimensions (mm)					
Front Overhang			1485		
Wheelbase			5100		
Overall Length			8883		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 <sup>nd</sup> and 3 <sup>th</sup> Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1827		
Overall Vehicle Height			3324		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			948		
Useful Chassis Length			6165		
Chassis Height - Front			1260		
Chassis Height - Rear			1269		
Ground Clearance - Front			449		
Ground Clearance - Rear			379		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	9000	9000	13/100	13//00	44000

Technically Permissible Weights	9000	9000	13400	13400	44000
Kerb Weight	3373	4388	1974	1736	11740
Payload	5627	4612	11426	11664	32260

## STANDARD EQUIPMENT

- Air Conditioner
- 1DIN Radio (Bluetooh, USB, Hands-free, Remote Control)/CD/MP3 Player
- Transmission Direct (Double Gear) PTO without Flange and Interior Control Unit
- Engine Brake
- Drum Brake
- Cruise Control
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Front Vehicle Antiroll Bar
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Tachograph
- Short Bumper
- Switchable Air Compressor for Improved Fuel Economy
- Electro-Hydraulic Power-Assisted Steering System (EHPAS)

## **OPTIONAL EQUIPMENT**

- Automated Transmission (with Normal Mode, Off Road Mode, Rocking Mode)
- Engine Driven PTO & Interior Control Unit
- Hydraulic Retarder
- Low Roof Sleeper Cab with Single Bed
- Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry Type Cab Heater \*
- Power Cab Tilting
- Rear Window \*\*
- 4750 mm Wheelbase Version
- Automatic Traction Control
- Digital Tachograph
- Double Passenger Seat \*\*
- Manually Operated Sunroof
- Transmission Direct (Single Gear) PTO with Flange and Interior Control Unit
- Tinted Glass
- Reinforced Wheel Rim
- Roof Beacon Light
- Less Front Spare Wheel Option
- Rear Towing Hook Option
- DAB Radio
- 325/95R 24
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- Led Headlamps

<sup>\*</sup> Only Available with Low Roof Sleeper Cab Version

<sup>\*\*</sup> Not Available with Low Roof Sleeper Cab Version