



University Institute of Engineering

Department of Computer Science & Engineering

EXPERIMENT: 7

NAME : Johnson Kumar **UID** : 23BCS12654
SECTION : KRG_2A **SEMESTER:** 5TH
SUBJECT CODE: 23CSP-339 **SUBJECT** : ADBMS

Problem Statement:

Design a robust PostgreSQL transaction system for the students table where multiple student records are inserted in a single transaction.

If any insert fails due to invalid data, only that insert should be rolled back while preserving the previous successful inserts using savepoints.

The system should provide clear messages for both successful and failed insertions, ensuring data integrity and controlled error handling.


Solution:

```
DROP TABLE IF EXISTS students;
```

```
CREATE TABLE students (
    id SERIAL PRIMARY KEY,
    name VARCHAR(50),
    age INT,
    class INT
);
```

```
DO $$ 
BEGIN
    -- Start a transaction
    BEGIN
        -- Insert multiple students
        INSERT INTO students(name, age, class) VALUES ('Anisha',16,8);
        INSERT INTO students(name, age, class) VALUES ('Neha',17,8);
        INSERT INTO students(name, age, class) VALUES ('Mayank',19,9);

        -- If all succeed
    END;
END;
```



University Institute of Engineering

Department of Computer Science & Engineering

```
RAISE NOTICE ' Transaction Successfully Done';
```

EXCEPTION

```
WHEN OTHERS THEN
```

```
-- If any insert fails
```

```
RAISE NOTICE 'Transaction Failed..! Rolling back changes.';
```

```
RAISE; -- this will rollback the entire transaction
```

```
END;
```

```
END;
```

```
$$;
```

```
SELECT * FROM students;
```

-----WRONG DATA TYPE -----

```
BEGIN;
```

```
SAVEPOINT sp1;
```

```
INSERT INTO students(name, age, class) VALUES ('Aarav',16,8);
```

```
SAVEPOINT sp2;
```

```
BEGIN
```

```
INSERT INTO students(name, age, class) VALUES ('Rahul','wrong',9); -- fails
```

```
EXCEPTION WHEN OTHERS THEN
```

```
RAISE NOTICE 'Failed to insert Rahul, rolling back to savepoint sp2';
```

```
ROLLBACK TO SAVEPOINT sp2;
```

```
END;
```


-- Next insert

```
INSERT INTO students(name, age, class) VALUES ('Sita',17,10);
```

```
COMMIT;
```

Output:

id	name	age	class
1	Anisha	16	8
2	Neha	17	8
3	Mayank	19	9
4	Aarav	16	8
5	Sita	17	10



University Institute of Engineering

Department of Computer Science & Engineering

Learning outcomes:

- Learned how to create and reset tables using DROP TABLE IF EXISTS and CREATE TABLE.
- Understood the use of DO \$\$ blocks for procedural control in PostgreSQL.
- Practiced inserting multiple rows within a transaction to ensure atomic operations.
- Explored exception handling using BEGIN...EXCEPTION...END to manage errors gracefully.
- Used RAISE NOTICE to generate informative messages during execution.