

Python for scientific computing

Python has extensive packages to help with data analysis:

- numpy: matrices, linear algebra, Fourier transform, pseudorandom number generators
- scipy: advanced linear algebra and maths, signal processing, statistics
- pandas: DataFrames, data wrangling and analysis
- matplotlib: visualizations such as line charts, histograms, scatter plots.

NumPy

NumPy is the fundamental package required for high performance scientific computing in Python. It provides:

- `ndarray`: fast and space-efficient n-dimensional numeric array with vectorized arithmetic operations
- Functions for fast operations on arrays without having to write loops
- Linear algebra, random number generation, Fourier transform
- Integrating code written in C, C++, and Fortran (for faster operations)

`pandas` provides a richer, simpler interface to many operations. We'll focus on using `ndarrays` here because they are heavily used in `scikit-learn`.

ndarrays

There are several ways to create numpy arrays.

```
In [95]: # Convert normal Python array to 1-dimensional  
         numpy array  
np.array((1, 2, 53))
```

```
Out[95]: array([ 1,  
                2, 53])
```

```
In [96]: # Convert sequences of sequences of sequences  
         ... to n-dim array  
np.array([(1.5, 2, 3), (4, 5, 6)])
```

```
Out[96]: array([[1.5,  
                2. , 3. ],  
                [4. ,  
                5. , 6. ]])
```

```
In [97]: # Define element type at creation time  
np.array([[1, 2], [3, 4]], dtype=complex)
```

```
Out[97]: array([[1.+0.j, 2.+  
                0.j],  
                [3.+0.j, 4.+  
                0.j]])
```


Useful properties of ndarrays:

```
In [98]: my_array = np.array([[1, 0, 3], [0, 1, 2]])
my_array.ndim      # number of dimensions (axes), also called the rank
my_array.shape      # a matrix with n rows and m columns has shape (n,m)
my_array.size       # the total number of elements of the array
my_array.dtype      # type of the elements in the array
my_array.itemsize   # the size in bytes of each element of the array
```

Out[98]: 2

Out[98]: (2, 3)

Out[98]: 6

Out[98]: dtype('int64')

Out[98]: 8

Quick array creation.

It is cheaper to create an array with placeholders than extending it later.

```
In [99]: np.ones(3) # Default type is float64
         np.zeros([2, 2])
         np.empty([2, 2]) # Fills the array with whatever sits in memory
         np.random.random((2,3))
         np.random.randint(5, size=(2, 4))
```

```
Out[99]: array([1., 1.,
                1.])
```

```
Out[99]: array([[0.,
                 0.],
                [0.,
                 0.]])
```

```
Out[99]: array([[0.,
                 0.],
                [0.,
                 0.]])
```

```
Out[99]: array([[0.221,
                 0.861, 0.549],
                [0.778,
                 0.125, 0.538]])
```

```
Out[99]: array([[3, 1,
                 1, 1],
                [2, 0,
                 3, 3]])
```


Create sequences of numbers

```
In [100]: np.linspace(0, 1, num=4)    # Linearly distributed numbers between 0 and 1
          np.arange(0, 1, step=0.3)   # Fixed step size
          np.arange(12).reshape(3,4) # Create and reshape
          np.eye(4)                   # Identity matrix
```

```
Out[100]: array([0.    ,
                 0.333, 0.667,
                 1.    ])
```

```
Out[100]: array([0. , 0.
                 3, 0.6, 0.9])
```

```
Out[100]: array([[ 0,  1,
                  2,  3],
                 [ 4,  5,
                  6,  7],
                 [ 8,  9,
                  10, 11]])
```

```
Out[100]: array([[1., 0.,
                  0., 0.],
                 [0., 1.,
                  0., 0.],
                 [0., 0.,
                  1., 0.],
                 [0., 0.,
                  0., 1.]])
```


Basic Operations

Arithmetic operators on arrays apply elementwise. A new array is created and filled with the result. Some operations, such as += and *=, act in place to modify an existing array rather than create a new one.

```
In [101]: a = np.array([20, 30, 40, 50])
          b = np.arange(4)
          a, b      # Just printing
          a-b
          b**2
          a > 32
          a += 1
          a

Out[101]: (array([20, 30, 40, 50]), array([0, 1, 2, 3]))

Out[101]: array([20, 29, 38, 47])

Out[101]: array([0, 1, 4, 9])

Out[101]: array([False, False,  True,  True])

Out[101]: array([21, 31, 41, 51])
```


The product operator `*` operates elementwise.
The matrix product can be performed using `dot()`

```
In [102]: A, B = np.array([[1,1], [0,1]]), np.array([[2,0], [3,4]
           ]) # assign multiple variables in one line
           A
           B
           A * B
           np.dot(A, B)
```

```
Out[102]: array
          ([
           1]
```

```
[0
```

```
1]
```

```
Out[102]: array
          ([
           0]
```

```
[3
```

```
4]
```

```
Out[102]: array
          ([
```


Upcasting: Operations with arrays of different types choose the more general/precise one.

```
In [103]: a = np.ones(3, dtype=np.int) #  
           initialize to integers  
           b = np.linspace(0, np.pi, 3) #  
           default type is float  
           a.dtype, b.dtype, (a + b).dtype
```

```
Out[103]: (dtype('int64'), dtype('float64'), dtype('float64'))
```


ndarrays have most unary operations (max,min,sum,...) built in

```
In [104]: a = np.random.random((2,3))  
a  
a.sum(), a.min(),  
a.max()
```

```
Out[104]: array([[0.057, 0.725, 0.083],  
                [0.395, 0.017, 0.825]])
```

```
Out[104]: (2.1028801738915552, 0.016881707307918936,  
          0.8254116092022105)
```


By specifying the axis parameter you can apply an operation along a specified axis of an array

```
In [105]: b = np.arange(12).reshape(3,4)
          b
          b.sum()
          b.sum(axis=0)
          b.sum(axis=1)
```

```
Out[105]: array([[ 0,  1,  2,  3],
                [ 4,  5,  6,  7],
                [ 8,  9, 10, 11]])

Out[105]: 66

Out[105]: array([12, 15, 18, 21])

Out[105]: array([ 6, 22, 38])
```


Universal Functions

NumPy provides familiar mathematical functions such as sin, cos, exp, sqrt, floor,... In NumPy, these are called "universal functions" (ufunc), and operate elementwise on an array, producing an array as output.

```
In [106]: np.sin(np.arange(0, 10))
```

```
Out[106]: array([ 0.      ,  0.841,  0.909,  0.141, -0.75  
7, -0.959, -0.279,  0.657,  
0.989,  0.412])
```


Shape Manipulation

Transpose, flatten, reshape,...

```
In [107]: a = np.floor(10*np.random.random((3,4)))  
a  
a.transpose()  
b = a.ravel() # flatten array  
b  
b.reshape(3, -1) # reshape in 3 rows (and as many columns as needed)
```

```
Out[107]: array([[6., 6., 8., 4.],  
                [3., 5., 9., 4.],  
                [2., 9., 2.,  
                3.]])
```

```
Out[107]: array([[6., 3., 2.],  
                [6., 5., 9.],  
                [8., 9., 2.],  
                [4., 4., 3.]])
```

```
Out[107]: array([6., 6., 8., 4.,  
                3., 5., 9., 4., 2., 9.,  
                2., 3.])
```

```
Out[107]: array([[6., 6., 8., 4.],  
                [3., 5., 9., 4.],  
                [2., 9., 2.,  
                3.]])
```


Arrays can be split and stacked together

```
In [108]: a = np.floor(10*np.random.random((2,6)))  
a  
b, c = np.hsplit(a, 2) # Idem: vsplit for vertical splits  
b  
c  
np.hstack((b, c)) # Idem: vstack for vertical stacks
```

```
Out[108]: array([[7., 4.,  
                2., 6., 8., 5.],  
                [6., 1.,  
                4., 3., 7., 1.]])
```

```
Out[108]: array([[7., 4.,  
                2.],  
                [6., 1.,  
                4.]])
```

```
Out[108]: array([[6., 8.,  
                5.],  
                [3., 7.,  
                1.]])
```

```
Out[108]: array([[7., 4.,  
                2., 6., 8., 5.],  
                [6., 1.,  
                4., 3., 7., 1.]])
```


Indexing and Slicing

Arrays can be indexed and sliced using [start:stop:stepsize]. Defaults are [0:ndim:1]

```
In [109]: a = np.arange(10)  
          **2  
          a  
Out[109]: array([ 0,  1,  4,  9, 16, 25, 36, 49, 64, 81])
```

```
In [110]: a[2]  
Out[110]:
```

```
In [111]: a[3:10:2]  
Out[111]: array([ 9, 25, 49, 64, 81])
```

```
In [112]: a[::-1] # Defaults are used if  
           indices not stated  
Out[112]: array([81, 64, 49, 36, 25, 16,  9,  4,  1,  0])
```

```
In [113]: a[::2]  
Out[113]: array([ 0,  4, 16, 36, 64])
```


For multi-dimensional arrays, axes are comma-separated: [x,y,z].

```
In [114]: b = np.arange(16).reshape(4,4)
          b
          b[2,3] # row 2, column 3

Out[114]: array([[ 0,  1,  2,  3],
                 [ 4,  5,  6,  7],
                 [ 8,  9, 10, 11],
                 [12, 13, 14, 15]])

Out[114]: 11

In [115]: b[0:3,1] # Values 0 to 3 in column 1
          b[:,1] # The whole column 1

Out[115]: array([1, 5, 9])

Out[115]: array([ 1,  5,  9, 13])

In [116]: b[1:3, :] # Rows 1:3, all columns

Out[116]: array([[ 4,  5,  6,  7],
                 [ 8,  9, 10, 11]])

In [117]: # Return the last row
          b[-1]

Out[117]: array([12, 13, 14, 15])
```


Note: dots (...) represent as many colons (:) as needed

- $x[1,2,\dots] = x[1,2,::,::]$
- $x[\dots,3] = x[:,::,::,3]$
- $x[4,\dots,5,:] = x[4,::,5,:]$

Arrays can also be indexed by arrays of integers and booleans.

```
In [118]: a = np.arange(12)
          **2
          i = np.array([ 1,
                        1,3,8,5 ])
          a
          a[i]

Out[118]: array([ 0,  1,  4,  9, 16, 25, 36,
                  49, 64, 81, 100, 121])

Out[118]: array([ 1,  1,  9, 64, 25])
```

A matrix of indices returns a matrix with the corresponding values.

```
In [119]: j = np.array([[ 3, 4], [9, 7]])
          a[j]

Out[119]: array([[ 9, 16],
                  [81, 49]])
```


With boolean indices we explicitly choose which items in the array we want and which ones we don't.

```
In [120]: a = np.arange(12).reshape(3,
4)
a
a[np.array([False, True, True
]), :]
b = a > 4
b
a[b]
```

```
Out[120]: array([[ 0,  1,  2,  3],
[ 4,  5,  6,  7],
[ 8,  9, 10, 11]])
```

```
Out[120]: array([[ 4,  5,  6,  7],
[ 8,  9, 10, 11]])
```

```
Out[120]: array([[False, False, False,
False],
[False,  True,  True,
True],
[ True,  True,  True,
True]])
```

```
Out[120]: array([ 5,  6,  7,  8,  9, 10, 11])
```


Iterating

Iterating is done with respect to the first axis:

In [121]:

```
for row in b:  
    print(row)
```

```
[False False False Fa  
lse]  
[False  True  True  T  
rue]  
[ True  True  True  T  
rue]
```


Operations on each element can be done by flattening the array (or nested loops)

```
In [122]: for element in b.flat: # flat returns an iterator  
         print(element)
```

F
a
l
s
e
F
a
l
s
e
F
a
l
s
e
F
a
l
s
e
F
a
l
s
e
T
r
u
e
T
r
u
e

Copies and Views (or: how to shoot yourself in a foot)

Assigning an array to another variable does NOT create a copy

```
In [123]: a = np.arange(12)  
          b = a  
          a
```

```
Out[123]: array([ 0,  1,  2,  3,  4,  5,  6,  7,  8,  
                9, 10, 11])
```

```
In [124]: b[0] = -100  
          b
```

```
Out[124]: array([-100,  1,  2,  3,  4,  5,  6,  
                7,  8,  9, 10,  
                11])
```

```
In [125]: a
```

```
Out[125]: array([-100,  1,  2,  3,  4,  5,  6,  7,  
                8,  9, 10,  
                11])
```


The view() method creates a NEW array object that looks at the same data.

```
In [126]: a = np.arange(12)
          a
          c = a.view()
          c.resize((2, 6))
          c
```

```
Out[126]: array([ 0,  1,  2,  3,  4,  5,  6,  7,  8,  9, 10, 11])
```

```
Out[126]: array([[ 0,  1,  2,  3,  4,  5],
                 [ 6,  7,  8,  9, 10, 11]])
```

```
In [127]: a[0] = 123
          c # c is also changed now
```

```
Out[127]: array([[123,  1,  2,  3,  4,  5],
                 [ 6,  7,  8,  9, 10, 11]])
```


Slicing an array returns a view of it.

In [128]:

```
c  
s = c[ : , 1:3]  
s[:] = 10  
s  
c
```

```
Out[128]: array([[123,  1,  2,  3,  4,  
                  5],  
                [ 6,  7,  8,  9, 10,  1  
                  1]])
```

```
Out[128]: array([[10, 10],  
                [10, 10]])
```

```
Out[128]: array([[123, 10, 10,  3,  4,  
                  5],  
                [ 6, 10, 10,  9, 10,  1  
                  1]])
```


The `copy()` method makes a deep copy of the array and its data.

```
In [129]: d = a.copy() Out[129]: array([-42, 10, 10, 3, 4, 5, 6, 10, 10, 9, 10, 11])
```

```
d[0] = -42  
d
```

```
In [130]: a Out[130]: array([123, 10, 10, 3, 4, 5, 6, 10, 10, 9, 10, 11])
```


Numpy: further reading

- Numpy Tutorial: [http://wiki.scipy.org/Tentative NumPy Tutorial](http://wiki.scipy.org/Tentative_NumPy_Tutorial)
([http://wiki.scipy.org/Tentative NumPy Tutorial](http://wiki.scipy.org/Tentative_NumPy_Tutorial)).
- "Python for Data Analysis" by Wes McKinney (O'Reilly)

SciPy

SciPy is a collection of packages for scientific computing, among others:

- `scipy.integrate`: numerical integration and differential equation solvers
- `scipy.linalg`: linear algebra routines and matrix decompositions
- `scipy.optimize`: function optimizers (minimizers) and root finding algorithms
- `scipy.signal`: signal processing tools
- `scipy.sparse`: sparse matrices and sparse linear system solvers
- `scipy.stats`: probability distributions, statistical tests, descriptive statistics

Sparse matrices

Sparse matrices are used in scikit-learn for (large) arrays that contain mostly zeros. You can convert a dense (numpy) matrix to a sparse matrix.

```
In [131]: from scipy import sparse
eye = np.eye(4)
eye
sparse_matrix = sparse.csr_matrix(eye) # Compressed Sparse Row matrix
sparse_matrix
print("{}".format(sparse_matrix))
```

```
Out[131]: array([[1., 0., 0., 0.],
                [0., 1., 0., 0.],
                [0., 0., 1., 0.],
                [0., 0., 0., 1.]])
```

```
Out[131]: <4x4 sparse matrix of type
'<class 'numpy.float64'>'
        with 4 stored elements in Compressed Sparse
Row format>
```

(0, 0)	1.0
(1, 1)	1.0
(2, 2)	1.0
(3, 3)	1.0

When the data is too large, you can create a sparse matrix by passing the values and coordinates (COO format).

```
In [132]: data = np.ones(4) # [1, (0, 0)
          1,1,1]
          row_indices = col_indices = np.arange(4) # [0, 1.0
          1,2,3] (1, 2)
          col_indices = np.arange(4) * 2
          eye_coo = sparse.coo_matrix((data, (row_indices, 1.0
          col_indices))) (2, 4)
          print("{}".format(eye_coo)) 1.0
                                     (3, 6)
                                     1.0
```


Further reading

Check the SciPy reference guide (<https://docs.scipy.org/doc/scipy/reference/>) for tutorials and examples of all SciPy capabilities.

pandas

pandas is a Python library for data wrangling and analysis. It provides:

- `DataFrame`: a table, similar to an R `DataFrame` that holds any structured data
 - Every column can have its own data type (strings, dates, floats,...)
- A great range of methods to apply to this table (sorting, querying, joining,...)
- Imports data from a wide range of data formats (CSV, Excel) and databases (e.g. SQL)

Series

A one-dimensional array of data (of any numpy type), with indexed values. It can be created by passing a Python list or dict, a numpy array, a csv file,...

In [133]:

```
import pandas as pd  
pd.Series([1,3,np.nan]) # Default integers are integers  
pd.Series([1,3,5], index=['a','b','c'])  
pd.Series({'a' : 1, 'b': 2, 'c': 3 }) # when given a dict,  
the keys will be used for the index  
pd.Series({'a' : 1, 'b': 2, 'c': 3 }, index = ['b', 'c',  
'd']) # this will try to match labels with keys
```

Out[133]:

0

0

1

0

2

a
N

d
t
y
p
e

l
o
c
a
t

Functions like a numpy array, however with index labels as indices

```
In [134]: a = pd.Series({'a' : 1, 'b': 2, 'c': 3 })
a
a['b']      # Retrieves a value
a[['a','b']] # and can also be sliced
```

```
Out[134]: a      1
          b      2
          c      3
          dtype: int64
```

```
Out[134]: 2
```

```
Out[134]: a      1
          b      2
          dtype: int64
```


numpy array operations on Series preserve the index value

```
In [135]: a
          a[a > 1]
          a * 2
          np.sqrt(a)

Out[135]: a    1
          b    2
          c    3
          dtype: int64
          4

Out[135]: b    2
          c    3
          dtype: int64
          4

Out[135]: a    2
          b    4
          c    6
          dtype: int64
          4

Out[135]: a    1.00
          b    1.41
          c    1.73
          dtype: float64
```


Operations over multiple Series will align the indices

```
In [136]: a = pd.Series({'John' : 1000, 'Mary': 2000, 'Andre': 3000 })  
          b = pd.Series({'John' : 100, 'Andre': 200, 'Cecilia': 300 })  
          a + b
```

```
Out[136]: Andre      3200.0  
          Cecilia      NaN  
          John      1100.0  
          Mary      NaN  
          dtype: float64
```


DataFrame

A DataFrame is a tabular data structure with both a row and a column index. It can be created by passing a dict of arrays, a csv file,...

```
In [137]: data = {'state': ['Ohio', 'Ohio', 'Nevada', 'Nevada'],  
                 'year': [2000, 2001, 2001, 2002],  
                 'pop': [1.5, 1.7, 2.4, 2.9]}  
pd.DataFrame(data)  
pd.DataFrame(data, columns=['year', 'state', 'pop', 'color']) # Will match indices
```

Out[137]:

	pop	state	year
0	1.5	Ohio	2000
1	1.7	Ohio	2001
2	2.4	Nevada	2001
3	2.9	Nevada	2002

Out[137]:

	year	state	pop	color
0	2000	Ohio	1.5	NaN
1	2001	Ohio	1.7	NaN
2	2001	Nevada	2.4	NaN
3	2002	Nevada	2.9	NaN

It can be composed with a numpy array and row and column indices, and decomposed

```
In [138]: dates = pd.date_range('2013-01-01', periods=4)
df = pd.DataFrame(np.random.randn(4,4), index=dates, columns=list('ABCD'))
df
```

Out[138]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84
2013-01-02	-0.62	-1.15	0.34	0.60
2013-01-03	-0.98	-0.66	-1.93	0.87
2013-01-04	-2.14	-0.31	-1.48	1.40

```

In [139]: df.index
Out[139]: DatetimeIndex(['2013-01-01', '2013-01-02', '2013-01-03', '2013-01-04'], dtype='datetime64[ns]', freq='D')

df.columns
Out[139]: Index(['A', 'B', 'C', 'D'], dtype='object')

df.values
Out[139]: array([[ 1.528,  0.744, -0.035, -1.843],
                  [-0.623, -1.15 ,  0.345,  0.599],
                  [-0.984, -0.661, -1.932,  0.87 ],
                  [-2.142, -0.306, -1.477,  1.399]])

```

DataFrames can easily read/write data from/to files

- `read_csv(source)`: load CSV data from file or url
- `read_table(source, sep=', ')`: load delimited data with separator
- `df.to_csv(target)`: writes the DataFrame to a file

```
In [140]: df.to_csv('data.csv', index=False) # Don't export the row index
dfs = pd.read_csv('data.csv')
dfs
dfs.set_value(0, 'A', 10) # Set value in row 0, column 'A' to '10'
dfs.to_csv('data.csv', index=False)
```

Out[140]:

	A	B	C	D
0	1.53	0.74	-0.03	-1.84
1	-0.62	-1.15	0.34	0.60
2	-0.98	-0.66	-1.93	0.87
3	-2.14	-0.31	-1.48	1.40

Out[140]:

	A	B	C	D
0	10.00	0.74	-0.03	-1.84
1	-0.62	-1.15	0.34	0.60
2	-0.98	-0.66	-1.93	0.87
3	-2.14	-0.31	-1.48	1.40

Simple operations

```
In [141]: df.head() # First 5 rows  
          df.tail() # Last 5 rows
```

Out[141]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84
2013-01-02	-0.62	-1.15	0.34	0.60
2013-01-03	-0.98	-0.66	-1.93	0.87
2013-01-04	-2.14	-0.31	-1.48	1.40

Out[141]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84
2013-01-02	-0.62	-1.15	0.34	0.60
2013-01-03	-0.98	-0.66	-1.93	0.87
2013-01-04	-2.14	-0.31	-1.48	1.40

In [142]: `# Quick stats`
`df.describe()` Out[142]:

	A	B	C	D
count	4.00	4.00	4.00	4.00
mean	-0.56	-0.34	-0.77	0.26
std	1.53	0.80	1.10	1.44
min	-2.14	-1.15	-1.93	-1.84
25%	-1.27	-0.78	-1.59	-0.01
50%	-0.80	-0.48	-0.76	0.73
75%	-0.08	-0.04	0.06	1.00
max	1.53	0.74	0.34	1.40

In [143]:

```
# Transposed  
df.T
```

Out[143]:

	2013-01-01 00:00:00	2013-01-02 00:00:00	2013-01-03 00:00:00	2013-01-04 00:00:00
A	1.53	-0.62	-0.98	-2.14
B	0.74	-1.15	-0.66	-0.31
C	-0.03	0.34	-1.93	-1.48
D	-1.84	0.60	0.87	1.40


```
In [144]: df.sort_index(axis=1, ascending=False) # Sort by index labels
df.sort(columns='B') # Sort by values
```

Out[144]:

	D	C	B	A
2013-01-01	-1.84	-0.03	0.74	1.53
2013-01-02	0.60	0.34	-1.15	-0.62
2013-01-03	0.87	-1.93	-0.66	-0.98
2013-01-04	1.40	-1.48	-0.31	-2.14

Out[144]:

	A	B	C	D
2013-01-02	-0.62	-1.15	0.34	0.60
2013-01-03	-0.98	-0.66	-1.93	0.87
2013-01-04	-2.14	-0.31	-1.48	1.40
2013-01-01	1.53	0.74	-0.03	-1.84

Selecting and slicing

```
In [145]: df['A'] # Get single column by label  
df.A      # Shorthand
```

```
Out[145]: 2013-01-01    1.53  
          2013-01-02   -0.62  
          2013-01-03   -0.98  
          2013-01-04   -2.14  
          Freq: D, Name: A, dtype: float64
```

```
Out[145]: 2013-01-01    1.53  
          2013-01-02   -0.62  
          2013-01-03   -0.98  
          2013-01-04   -2.14  
          Freq: D, Name: A, dtype: float64
```



```
In [146]: df[0:2]           # Get rows
           by index number
df.iloc[0:2,0:2] # Get rows
           and columns by index number
df['20130102':'20130103']
           # or row labels
df.loc['20130102':'20130103', ['A','B']] # or row and
           column labels
df.ix[0:2, ['A','B']] # allows mixing integers and labels
```

Out[146]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84
2013-01-02	-0.62	-1.15	0.34	0.60

Out[146]:

	A	B
2013-01-01	1.53	0.74
2013-01-02	-0.62	-1.15

Out[146]:

	A	B	C	D
2013-01-02	-0.62	-1.15	0.34	0.60
2013-01-03	-0.98	-0.66	-1.93	0.87

Out[146]:

	A	B
2013-01-02	-0.62	-1.15
2013-01-03	-0.98	-0.66

Out[146]:

	A	B
2013-01-01	1.53	0.74
2013-01-02	-0.62	-1.15

query() retrieves data matching a boolean expression

```
In [147]: df
df.query('A > -0.4') # Identical to df[df.A > 0.4]
df.query('A > B')    # Identical to df[df.A > df.B]
```

Out[147]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84
2013-01-02	-0.62	-1.15	0.34	0.60
2013-01-03	-0.98	-0.66	-1.93	0.87
2013-01-04	-2.14	-0.31	-1.48	1.40

Out[147]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84

Out[147]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84
2013-01-02	-0.62	-1.15	0.34	0.60

Note: similar to NumPy, indexing and slicing returns a *view* on the data. Use `copy()` to make a deep copy.

Operations

DataFrames offer a wide range of operations (<http://pandas.pydata.org/pandas-docs/stable/generated/pandas.DataFrame.html>): max, mean, min, sum, std,...

```
In [148]: df.mean()           # Mean of all values per
          column
          df.mean(axis=1) # Other axis: means per row
```

```
Out[148]: A    -0.56
          B    -0.34
          C    -0.77
          D     0.26
          dtype: float64
```

```
Out[148]: 2013-01-01    0.10
          2013-01-02   -0.21
          2013-01-03   -0.68
          2013-01-04   -0.63
          Freq: D, dtype: float64
```


All of numpy's universal functions also work with dataframes

In [149]: `np.abs(df)` Out[149]:

	A	B	C	D
2013-01-01	1.53	0.74	0.03	1.84
2013-01-02	0.62	1.15	0.34	0.60
2013-01-03	0.98	0.66	1.93	0.87
2013-01-04	2.14	0.31	1.48	1.40

Other (custom) functions can be applied with apply(func)

```
In [150]: df
df.apply(np.max)
df.apply(lambda x: x.max()
- x.min())
```

Out[150]:

	A	B	C	D
2013-01-01	1.53	0.74	-0.03	-1.84
2013-01-02	-0.62	-1.15	0.34	0.60
2013-01-03	-0.98	-0.66	-1.93	0.87
2013-01-04	-2.14	-0.31	-1.48	1.40

Out[150]: A 1.53
B 0.74
C 0.34
D 1.40
dtype: float64

Out[150]: A 3.67
B 1.89
C 2.28
D 3.24
dtype: float64

Data can be aggregated with `groupby()`

```
In [151]: df = pd.DataFrame({'A' : ['foo',
    'bar', 'foo', 'bar'], 'B' : ['o
ne', 'one', 'two', 'three'],
    'C' : np.rand
om.randn(4), 'D' : np.random.ran
dn(4)})
df
df.groupby('A').sum()
df.groupby(['A', 'B']).sum()
```

Out[151]:

	A	B	C	D
0	foo	one	0.74	-0.29
1	bar	one	0.73	-0.17
2	foo	two	-1.12	1.04
3	bar	three	-1.66	-0.19

Out[151]:

	C	D
A		
bar	-0.93	-0.36
foo	-0.38	0.74

Out[151]:

		C	D
A	B		
bar	one	0.73	-0.17
	three	-1.66	-0.19
foo	one	0.74	-0.29
	two	-1.12	1.04

Data wrangling (some examples)

Merge: combine two dataframes based on common keys

```
In [152]: df1 = pd.DataFrame({'key': ['b', 'b', 'a'], 'data1': range(3)})  
          df2 = pd.DataFrame({'key': ['a', 'b'], 'data2': range(2)})  
          df1  
          df2  
          pd.merge(df1, df2)
```

Out[152]:

	data1	key
0	0	b
1	1	b
2	2	a

Out[152]:

	data2	key
0	0	a
1	1	b

Out[152]:

	data1	key	data2
0	0	b	1
1	1	b	1
2	2	a	0

Append: append one dataframe to another

```
In [153]: df = pd.DataFrame(np.random.randn(2, 4))  
df  
s = pd.DataFrame(np.random.randn(1,4))  
s  
df.append(s, ignore_index=True)
```

Out[153]:

	0	1	2	3
0	-0.01	1.95	0.17	1.27
1	-0.38	-0.12	-0.45	-1.21

Out[153]:

	0	1	2	3
0	0.05	-0.34	-0.73	0.38

Out[153]:

	0	1	2	3
0	-0.01	1.95	0.17	1.27
1	-0.38	-0.12	-0.45	-1.21
2	0.05	-0.34	-0.73	0.38

Remove duplicates

```
In [154]: df = pd.DataFrame({'k1': ['one'] * 3, 'k2': [1, 1, 2]})
df
df.drop_duplicates()
```

Out[154]:

	k1	k2
0	one	1
1	one	1
2	one	2

Out[154]:

	k1	k2
0	one	1
2	one	2

Replace values

```
In [155]: df = pd.DataFrame({'k1': [1, -1], 'k2': [-1, 2]}) # Say that -1 is a sentinel for missing data
df
df.replace(-1, np.nan)
```

Out[155]:

	k1	k2
0	1	-1
1	-1	2

Out[155]:

	k1	k2
0	1.0	NaN
1	NaN	2.0

Discretization and binning

```
In [156]: ages = [20, 22, 25, 27, 21, 23
, 37, 31, 61, 45, 41, 32]
bins = [18, 25, 35, 60, 100]
cats = pd.cut(ages, bins)
cats.labels
pd.value_counts(cats)
```

```
Out[156]: array([0, 0, 0, 1, 0, 0, 2,
1, 3, 2, 2, 1], dtype=int8)

Out[156]: (18, 25]      5
(35, 60]      3
(25, 35]      3
(60, 100]     1
dtype: int64
```


Further reading

- Pandas docs: <http://pandas.pydata.org/pandas-docs/stable/>
(<http://pandas.pydata.org/pandas-docs/stable/>).
- <https://bitbucket.org/hrojas/learn-pandas>
(<https://bitbucket.org/hrojas/learn-pandas>).
- Python for Data Analysis (O'Reilly) by Wes McKinney (the author of pandas)

matplotlib

matplotlib (<http://matplotlib.sourceforge.net>) is the primary scientific plotting library in Python. It provides:

- Publication-quality visualizations (<http://matplotlib.org/gallery.html>), such as line charts, histograms, and scatter plots.
- Integration in pandas to make plotting much easier.
- Interactive plotting in Jupyter notebooks for quick visualizations.
 - Requires some setup. See preamble and %matplotlib (<http://ipython.readthedocs.io/en/stable/interactive/plotting.html?highlight=matplotlib>).
- Many GUI backends, export to PDF, SVG, JPG, PNG, BMP, GIF, etc.
- Ecosystem of libraries for more advanced plotting, e.g. Seaborn (<http://seaborn.pydata.org/>).

Low-level usage


`plot()` is the main function

(http://matplotlib.org/api/pyplot_api.html#matplotlib.pyplot.plot) to generate a plot (but many more exist):

<code>plot(x, y)</code>	Plot x vs y, default settings
<code>plot(x, y, 'bo')</code>	Plot x vs y, blue circle markers
<code>plot(y, 'r+')</code>	Plot y (x = array 0..N-1), red plusses

Every plotting function is completely customizable through a large set of options.


```
In [157]: x = np.linspace(-10, 10, 100) # Sequence for X-axis  
  
y = np.sin(x) # sine values  
p = plt.plot(x, y, marker="x") # Line plot with marker x
```




pandas + matplotlib

pandas DataFrames offer an easier, higher-level interface for matplotlib functions

```
In [158]: df = pd.DataFrame(np.random.randn  
    (500, 4),  
                               columns=['a',  
    'b', 'c', 'd']) # random 4D data  
p = df.cumsum() # Plot cumulative  
    sum of all series  
p.plot()
```


```
Out[158]: <matplotlib.axes._subplo  
ts.AxesSubplot at 0x11dc  
d7b00>
```




```
In [159]: p = df[:10].plot(kind='bar') # First 10 arrays as bar p  
         lots
```





```
In [160]: p = df.boxplot() # Boxplot for each of the 4 series
```













```
In [161]: # Scatter plot using the 4 series for x, y, color, scale
df[:300].plot(kind='scatter', x='a', y='b', c='c',
                           s=df['d']*50, linewidth='0', cmap='plasma')
```

```
Out[161]: <matplotlib.axes._subplots.AxesSubplot at 0x105f86a20>
```







Advanced plotting libraries

Several libraries, such as Seaborn (<http://seaborn.pydata.org/examples/index.html>), offer more advanced plots and easier interfaces.



126	150	180	196	188	233	277	301	318	34
141	178	193	236	235	267	317	366	362	40
135	163	181	235	227	269	313	348	345	38
125	172	183	229	234	270	316	365	363	42
149	178	218	243	264	315	374	422	435	47
170	199	230	264	302	364	413	465	491	54
170	199	242	272	293	347	405	467	505	56
158	184	209	237	259	312	355	404	404	46
133	162	191	211	229	274	306	347	359	40
114	146	172	180	203	237	271	305	319	36
140	166	194	201	229	278	306	336	337	40



Further reading links

- Matplotlib examples (<http://matplotlib.org/gallery.html>).
- Plotting with pandas (<http://pandas.pydata.org/pandas-docs/version/0.18.1/visualization.html>).
- Seaborn examples (<http://seaborn.pydata.org/examples/index.html>).

