UNSA

facturacion@localhost Data Dictionary

12/08/2020





Table of contents

acturad	cion@localhost	6
1. Tab	cion@localhost	6
	Table: cities	
1.2.	Table: clients	6
1.3.	Table: persons	6
1.4.	Table: product_types	7
1.5.	Table: products	8
1.6.	Table: products_providers	8
1.7.	Table: products_warehouses	9
1.8.	Table: providers	9
	Table: roles	
1.10.	Table: sellers	10
1.11.	Table: users	11
1.12.	Table: voucher_details	11
1.13.	Table: voucher_headers	12
1.14.	Table: voucher_types	13
1.15.	Table: warehouses	13

Legend

- **?** Primary key
- Primary key disabled
- 1 User-defined primary key
- **?** Unique key
- ¶ Unique key disabled
- 1 User-defined unique key
- Active trigger
- Disabled trigger
- → Many to one relation
- $\succ_{\mathbf{i}}$ User-defined many to one relation
- ✓ User-defined one to many relation
- \succ User-defined many to many relation
- One to one relation
- user-defined one to one relation
- •**@** Input
- @ Output
- Input/Output
- Uses dependency
- User-defined uses dependency
- Used by dependency
- 🛅 User-defined used by dependency

facturacion@localhost

1. Tables

1.1. Table: cities

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		name	varchar(55)	Nullable Default: NULL

Linked from

	Table	Join	Title / Name / Description
\rightarrow	persons	citiesid = personscity_id	fk_person_city1

Unique keys

		Name / Description
Ŷ	id	PRIMARY

1.2. Table: clients

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		person_id	int(10, 0)	References: persons

Links to

	Table	Join	Title / Name / Description
\rightarrow	persons c	lientsperson_id = personsid	fk_client_person1

Linked from

	Table	Join	Title / Name / Description
\rightarrow	voucher_headers	clientsid = voucher_headersclient_id	fk_voucher_header_client1

Unique keys

		Name / Description
9	id	PRIMARY

1.3. Table: persons

Columns

		Name	Data type	Description / Attributes
▤	1	id	int(10, 0)	Identity / Auto increment
■		name	varchar(95)	Nullable Default: NULL

	Name	Data type	Description / Attributes
■	surname	varchar(95)	Nullable Default: NULL
■	civil_status	int(10, 0)	Nullable Default: NULL
■	phone	varchar(45)	Nullable Default: NULL
	contact	varchar(245)	Nullable Default: NULL
■	code	varchar(11)	Nullable Default: NULL
	city_id	int(10, 0)	Nullable Default: NULL References: cities
■	user_id	int(10, 0)	References: users
	status	tinyint(3, 0)	Nullable Default: NULL
■	created	datetime	Nullable Default: NULL
■	modified	datetime	Nullable Default: NULL
■	dni	int(10, 0)	

Links to

	Table	Join	Title / Name / Description
\rightarrow	cities	personscity_id = citiesid	fk_person_city1
—	users	personsuser_id = usersid	fk_person_user1

Linked from

	Table	Join	Title / Name / Description
\rightarrow	clients	personsid = clientsperson_id	fk_client_person1
\rightarrow	providers	<pre>personsid = providersperson_id</pre>	fk_provider_person1
\rightarrow	sellers	personsid = sellersperson_id	fk_seller_person

Unique keys

		Name / Description
?	id	PRIMARY

1.4. Table: product_types

Columns

		Name	Data type	Description / Attributes	
	1	id	int(10, 0)	Identity / Auto increment	
		name	varchar(45)	Nullable Default: NULL	

Linked from

	Table	Join	Title / Name / Description
\rightarrow	products	<pre>product_typesid = productsproduct_type_id</pre>	fk_product_product_type1

Unique keys

		Name / Description
9	id	PRIMARY

1.5. Table: products

Columns

	Name	Data type	Description / Attributes			
1	id	int(10, 0)	Identity / Auto increment			
	description	varchar(245)	Nullable Default: NULL			
	quantity	int(10, 0)	Nullable Default: NULL			
	product_type_id	int(10, 0)	Nullable Default: NULL References: product_types			
	status	tinyint(3, 0)	Nullable Default: NULL			
	created	datetime	Nullable Default: NULL			
	modified	datetime	Nullable Default: NULL			
	1	id description quantity product_type_id status created	id int(10, 0) description varchar(245) quantity int(10, 0) product_type_id int(10, 0) status tinyint(3, 0) created datetime			

Links to

	Table	Join	Title / Name / Description
>	product_types	<pre>productsproduct_type_id = product_typesid</pre>	fk_product_product_type1

Linked from

	Table	Join	Title / Name / Description
\rightarrow	products_providers	<pre>productsid = products_providersproduct_id</pre>	fk_product_provider_product1
\rightarrow	products_warehouses	<pre>productsid = products_warehousesproduct_id</pre>	fk_product_warehouse_product1
\rightarrow	voucher_details	<pre>productsid = voucher_detailsproduct_id</pre>	fk_voucher_detail_product1

Unique keys

		Name / Description
Ŷ	id	PRIMARY

1.6. Table: products_providers

Columns

		Name	Data type	Description / Attributes
▤	1	id	int(10, 0)	Identity / Auto increment
■		product_id	int(10, 0)	References: products
目		provider_id	int(10, 0)	References: providers
■		stock	int(10, 0)	Nullable Default: NULL
■		price	float(12)	Nullable Default: NULL
■		date	datetime	Nullable Default: NULL

Links to

	Table	Join	Title / Name / Description
-	products	<pre>products_providersproduct_id = productsid</pre>	fk_product_provider_product1
>	providers	<pre>products_providersprovider_id = providersid</pre>	fk_product_provider_provider1

Unique keys

			Name / Description	
9	id	PRIMARY		

1.7. Table: products_warehouses

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		warehouse_id	int(10, 0)	References: warehouses
■		product_id	int(10, 0)	References: products
■		stock	int(10, 0)	Nullable Default: NULL
■		date	datetime	Nullable Default: NULL

Links to

	Table	Join	Title / Name / Description
>	products	<pre>products_warehousesproduct_id = productsid</pre>	fk_product_warehouse_product1
>	warehouses	products_warehouseswarehouse_id = warehousesid	fk_products_warehouses_warehouses1

Unique keys

		Name / Description
Ŷ	id	PRIMARY

1.8. Table: providers

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		person_id	int(10, 0)	References: persons

Links to

	Table	Join	Title / Name / Description
—	persons	providersperson_id = personsid	fk_provider_person1

Linked from

	Table	Join	Title / Name / Description
\rightarrow	products_providers	<pre>providersid = products_providersprovider_id</pre>	fk_product_provider_provider1

Unique keys

		Name / Description
P	id	PRIMARY

1.9. Table: roles

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		name	varchar(45)	Nullable Default: NULL
■		status	tinyint(3, 0)	Nullable Default: NULL
■		created	datetime	Nullable Default: NULL
■		modified	datetime	Nullable Default: NULL

Linked from

	Table	Join	Title / Name / Description
_	users	rolesid = usersrole_id	fk_user_role1

Unique keys

		Name / Description
Ŷ	id	PRIMARY

1.10. Table: sellers

Columns

		Name	Data type	Description / Attributes
目	1	id	int(10, 0)	Identity / Auto increment
■		person_id	int(10, 0)	References: persons

Links to

	Table	Join	Title / Name / Description
—	persons	sellersperson_id = personsid	fk_seller_person

Linked from

	Table	Join	Title / Name / Description
\rightarrow	voucher_headers	sellersid = voucher_headersseller_id	fk_voucher_header_seller1

Unique keys

		Name / Description
P	id	PRIMARY

1.11. Table: users

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■	1	email	varchar(255)	
目		password	varchar(255)	
目		verification	tinyint(3, 0)	Default: 0
		token	varchar(255)	Nullable Default: NULL
目		role_id	int(10, 0)	References: roles
		status	tinyint(3, 0)	Nullable Default: NULL
■		created	datetime	Nullable Default: NULL
■		modified	datetime	Nullable Default: NULL

Links to

	Table	Join	Title / Name / Description
—	roles	usersrole_id = rolesid	fk_user_role1

Linked from

	Table	Join	Title / Name / Description
\rightarrow	persons	users id = personsuser_id	fk_person_user1

Unique keys

		Name / Description
?	id	PRIMARY
P	email	email_UNIQUE

1.12. Table: voucher_details

11

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		quantity	int(10, 0)	Nullable Default: NULL
■		price	float(12)	Nullable Default: NULL
■		product_id	int(10, 0)	References: products
■		voucher_header_id	int(10, 0)	References: voucher_headers

Links to

	Table	Join	Title / Name / Description
-	products	voucher_detailsproduct_id = productsid	fk_voucher_detail_product1
>	voucher_headers	<pre>voucher_detailsvoucher_header_id = voucher_headersid</pre>	fk_voucher_detail_voucher_header1

Unique keys

			Name / Description
P	id	PRIMARY	

1.13. Table: voucher_headers

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		issue_date	datetime	Nullable Default: NULL
■		voucher_type_id	int(10, 0)	References: voucher_types
■		seller_id	int(10, 0)	References: sellers
■		client_id	int(10, 0)	References: clients
■		status	tinyint(3, 0)	Nullable Default: NULL
■		created	datetime	Nullable Default: NULL
B		modified	datetime	Nullable Default: NULL

Links to

	Table	Join	Title / Name / Description
\rightarrow	clients	voucher_headersclient_id = clientsid	fk_voucher_header_client1
\rightarrow	sellers	voucher_headersseller_id = sellersid	fk_voucher_header_seller1
\rightarrow	voucher_types	<pre>voucher_headersvoucher_type_id = voucher_typesid</pre>	fk_voucher_header_voucher_type1

Linked from

		Table	Join	Title / Name / Description
-	→	voucher_details	voucher_headersid = voucher_detailsvoucher_header_id	fk_voucher_detail_voucher_header1

Unique keys

		Name / Description
?	id	PRIMARY

1.14. Table: voucher_types

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
■		name	varchar(45)	Nullable Default: NULL

Linked from

	Table	Join	Title / Name / Description
-	voucher_headers	<pre>voucher_typesid = voucher_headersvoucher_type_id</pre>	fk_voucher_header_voucher_type1

Unique keys

			Name / Description
Ŷ	id	PRIMARY	

1.15. Table: warehouses

Columns

		Name	Data type	Description / Attributes
■	1	id	int(10, 0)	Identity / Auto increment
B		name	varchar(45)	Nullable Default: NULL
B		status	tinyint(3, 0)	Nullable Default: NULL
B		created	datetime	Nullable Default: NULL
B		modified	datetime	Nullable Default: NULL

Linked from

	Table	Join	Title / Name / Description
→	products_warehouses	warehousesid = products_warehouseswarehouse_id	fk_products_warehouses_warehouses1

Unique keys

		Name / Description
9	id	PRIMARY

