

Pregunta del cuestionario

Select all of the statements below written with correct syntax. There may be more than one correct answer. Try them in REPL.

☐

```
val address : String = null
```

☒

```
val amount : Double? = 10.0
```

☒

```
var list: List<String?>? = listOf(null, null)
```

☒

```
list?.size
```



Enviar

Read the code below, try to follow what it does, and then choose the correct answer:

```
var welcomeMessage = "Hello and welcome to Kotlin"
when (welcomeMessage.length) {
    0 -> println("Nothing to say!")
    in 1..50 -> println("Perfect")
    else -> println("Too long!")
}
```

Pregunta del cuestionario

What will the code above print?

- ☐ "Nothing to say!"
- ☒ "Perfect"
- ☐ "Too long!"
- ☐ It won't display anything because there's a syntax error

Enviar

← Anterior

Siguiente →

[Enviar comentarios sobre la página](#)

```
1 byte = 1 bytes
1 kilobyte = 1000 bytes
1 megabyte = 1000000 bytes
1 gigabyte = 1000000000 bytes
1 terabyte = 1000000000000 bytes
1 petabyte = 1000000000000000 bytes
1 exabyte = 1000000000000000000 bytes
```

Pregunta del cuestionario

Which of the statements below is the correct way to initialize the array above to give the correct output.

- ☐ `val array = Array(7)`
- ☐ `val array = {1000}`
- ☒ `val array = Array(7) { 1000.0.pow(it) }`
- ☐ `val array = Array(7) { 1000.0.pow(10) }`



Enviar

[< Anterior](#)

[Siguiente >](#)

[Enviar comentarios sobre la página](#)

```

14 // Resultado: [cayenne]
15
16 // 2. Especies que empiezan con 'c' y terminan con 'e' (Forma 2: indexación)
17 val cAndE2 = spices.filter { it.first() == 'c' && it.last() == 'e' }
18 println("Forma 2 (first/last): $cAndE2")
19 // Resultado: [cayenne]
20
21
22 // 3. Tomar los primeros 3 elementos y filtrar los que empiezan con 'c'
23 val firstThreeStartWithC = spices
24     .take(n = 3)
25     .filter { it.startsWith(char = 'c') }
26 println("Primeros 3 que empiezan con 'c': $firstThreeStartWithC")
27 // Resultado: [curry, cayenne]
28 println("Curries ordenados por longitud: $curriesSorted")

```

Expecting a top level declaration

Pregunta del cuestionario

What is the difference between

```
val random1 = random()  
val random2 = {random()}
```

Try it out in REPL or a file:

- ☐ They both are exactly the same.
- ☐ The first will generate a random number every time random1 is accessed.
- ☒ The second will generate a random number every time random2 is accessed. 
- ☐ They will both generate a random number every time but the return type will be different.

Enviar

UDACITY

For AI Researchers

Panel de Control

Catálogo

Maestrías en IA

RB

← Resumen

Kotlin Bootcamp for Programmers

95%

1

Introduction

2

Kotlin Basics

Introduction

Object Oriented Terminology



Preguntar a Marvin

- dentro del `for`, agrega a la lista la ver número

Para el reto, necesitas:

- una lista mutable para guardar resulta
- un recorrido de 0 a 100
- una condición que revise si el número

Perfil

Suscripción

Establecer horario

Cuentas vinculadas

Notificaciones