

UNIVERSITÀ DEGLI STUDI DI MILANO FACOLTÀ DI SCIENZE E TECNOLOGIE

Master degree in Physics

Title

Supervisor:

Prof. Dr. Stefano Carrazza

Co-supervisor:

Dr. Alessandro Candido

Co-supervisor:

Dr. Andrea Pasquale

Co-supervisor:

Dott. Edoardo Pedicillo

Elisa Stabilini Matricola n° 28326A A.A. 2024/2025

Contents

Quantum computing
Qibo
Results
RB fidelity optimization
3.1.1 Randomized Benchmarking
3.1.2 Optimization methods
3.2 RX90 calibration
3.3 Flux pulse correction
3.3.1 Cryoscope
Conclusions
3.

Contents

Summary

Contents

Quantum computing

Qibo

Results

3.1 RB fidelity optimization

3.1.1 Randomized Benchmarking

Randomized benchmarking (RB) is technique used to characterize the performance of quantum gates measuring their avarage error rates. RB was firstly introduced in 2005 [1], the key idea

disclaimer: this first study was performed using qibocal v0.1 the code currently uploaded on thi GitHub repository is instead compatible with qibocal v0.2 Main idea: improve fidelity (which one?) fine tuning the calibration

Randomized Benchmarking

For the results we present in the following the technique used slightly differ from the

Randomized Benchmarking on qua

3.1.2 Optimization methods

Optuna [Optuna]

Scipy methods [Scipy]

- SQLP ?
- Nelder-Mead \rightarrow approfondimento

CMA - genetics algorithm [CMA]

3.2 RX90 calibration

3.3 Flux pulse correction

3.3.1 Cryoscope

[2]

Conclusions

Bibliography

¹J. Emerson, R. Alicki, and K. Życzkowski, "Scalable noise estimation with random unitary operators", Journal of Optics B: Quantum and Semiclassical Optics 7, S347 (2005).

²M. A. Rol, L. Ciorciaro, F. K. Malinowski, B. M. Tarasinski, R. E. Sagastizabal, C. C. Bultink, Y. Salathe, N. Haandbaek, J. Sedivy, and L. DiCarlo, "Time-domain characterization and correction of on-chip distortion of control pulses in a quantum processor", en, Applied Physics Letters 116, arXiv:1907.04818 [quant-ph], 054001 (2020).

Bibliography

Acknowledgement