## Chapter 1 Quiz 2

maximum capacity is 30kbps.  4. The capacity of a channel is only constrained by its physical bandwidth.  5. Before sending a packet into a datagram network, the source must determine all of the that packet will traverse between source and destination.  6. In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.  7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B.  9. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.			Computer Networking	2017.3.16				
1. Multiplexing technologies allow multiple message signals to share a same medium same time. without interference  2. Data encoding technologies determine the amount of information carried by a single sign of the signal signa		Name:		Student No:				
same time. <b>without interference</b> 2. Data encoding technologies determine the amount of information carried by a single sign Given a 3kHz telephone line with signal-to-noise ratio of 30 dB and a binary sign maximum capacity is 30kbps.  4. The capacity of a channel is only constrained by its physical bandwidth.  5. Before sending a packet into a datagram network, the source must determine all of the that packet will traverse between source and destination.  6. In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.  7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B. 79  9. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	<u>Not</u>	<u>te:</u> Write T or F before eac	ch question number					
<ol> <li>Data encoding technologies determine the amount of information carried by a single sign Given a 3kHz telephone line with signal-to-noise ratio of 30 dB and a binary sign maximum capacity is 30kbps.</li> <li>The capacity of a channel is only constrained by its physical bandwidth.</li> <li>Before sending a packet into a datagram network, the source must determine all of the that packet will traverse between source and destination.</li> <li>In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.</li> <li>ADSL bandwidth is shared, and ADSL provides guaranteed data rate.</li> <li>If network A's throughput is larger than network B's, then network A is better than B.</li> <li>Internet core is a mesh of interconnected routers, and the routers are organized in tiers.</li> <li>Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL &lt; R.</li> <li>TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with pseheduling in router input/output port queuing).</li> <li>The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> </ol> Chapter 1 Quiz 2 Computer Networking 2017.3.16	1.			e signals to share a same medium at the				
Given a 3kHz telephone line with signal-to-noise ratio of 30 dB and a binary signs maximum capacity is 30kbps.  4. The capacity of a channel is only constrained by its physical bandwidth.  5. Before sending a packet into a datagram network, the source must determine all of the that packet will traverse between source and destination.  6. In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.  7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B.  9. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	•	same time. without	interference					
maximum capacity is 30kbps.  4. The capacity of a channel is only constrained by its physical bandwidth.  5. Before sending a packet into a datagram network, the source must determine all of the that packet will traverse between source and destination.  6. In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.  7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B.   9. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	2.	Data encoding technolog	ies determine the amount o	f information carried by a single signal.				
<ol> <li>The capacity of a channel is only constrained by its physical bandwidth.</li> <li>Before sending a packet into a datagram network, the source must determine all of the that packet will traverse between source and destination.</li> <li>In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.</li> <li>ADSL bandwidth is shared, and ADSL provides guaranteed data rate.</li> <li>If network A's throughput is larger than network B's, then network A is better than B.</li> <li>Internet core is a mesh of interconnected routers, and the routers are organized in tiers.</li> <li>Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL &lt; R.</li> <li>TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with packeduling in router input/output port queuing).</li> <li>The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> </ol> Chapter 1 Quiz 2 Computer Networking 2017.3.16	<b>3</b> .	Given a 3kHz telephone line with signal-to-noise ratio of 30 dB and a binary signal, the						
<ol> <li>Before sending a packet into a datagram network, the source must determine all of the that packet will traverse between source and destination.</li> <li>In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.</li> <li>ADSL bandwidth is shared, and ADSL provides guaranteed data rate.</li> <li>If network A's throughput is larger than network B's, then network A is better than B.</li> <li>Internet core is a mesh of interconnected routers, and the routers are organized in tiers.</li> <li>Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL &lt; R.</li> <li>TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with packed uling in router input/output port queuing).</li> <li>The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> </ol> Chapter 1 Quiz 2 Computer Networking 2017.3.16			-					
that packet will traverse between source and destination.  6. In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.  7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B. 7.  9. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with packet) in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	4.	The capacity of a channel is <u>only</u> constrained by its physical bandwidth.						
6. In Cable TV access network, when frequency resource is limited, TDM can be incorpora accommodate more users.  7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B. 7.  9. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with a scheduling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	5.	Before sending a packet into a datagram network, the source must determine all of the links						
accommodate more users.  7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B. 79  9. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with a scheduling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	_	that packet will traverse between source and destination.						
7. ADSL bandwidth is shared, and ADSL provides guaranteed data rate.  8. If network A's throughput is larger than network B's, then network A is better than B. 79. Internet core is a mesh of interconnected routers, and the routers are organized in tiers.  10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with packed uling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	6.	In Cable TV access network, when frequency resource is limited, TDM can be incorporated to						
<ol> <li>If network A's throughput is larger than network B's, then network A is better than B.</li> <li>Internet core is a mesh of interconnected routers, and the routers are organized in tiers.</li> <li>Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL &lt; R.</li> <li>TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).</li> <li>The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> </ol> Chapter 1 Quiz 2 Computer Networking 2017.3.16	•							
<ul> <li>10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL &lt; R.</li> <li>11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).</li> <li>12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> <li>Chapter 1 Quiz 2</li> <li>Computer Networking 2017.3.16</li> </ul>	7.	ADSL bandwidth is shared, and ADSL provides guaranteed data rate.						
<ul> <li>10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL &lt; R.</li> <li>11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).</li> <li>12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> <li>Chapter 1 Quiz 2</li> <li>Computer Networking 2017.3.16</li> </ul>	8.	If network A's throughput is larger than network B's, then network A is better than B. 标准单-						
<ul> <li>10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives queue periodically every 1/a seconds. Also suppose all packets are of length L. The queuing delay is small and bounded as long as aL &lt; R.</li> <li>11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).</li> <li>12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> <li>Chapter 1 Quiz 2</li> <li>Computer Networking 2017.3.16</li> </ul>	9.	Internet core is a mesh of interconnected routers, and the routers are organized in tiers.						
queuing delay is small and bounded as long as aL < R.  11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	10. Consider a queue preceding a transmission link of rate R. Suppose a packet arrives to the queue periodically every 1/a seconds. Also suppose all packets are of length L. Then the							
<ul> <li>11. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with scheduling in router input/output port queuing).</li> <li>12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.</li> <li>Chapter 1 Quiz 2</li> <li>Computer Networking 2017.3.16</li> </ul>								
scheduling in router input/output port queuing).  12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	-							
12. The end-to-end delay of 10 packets equals sum of the end-to-end delay of each packet.  Chapter 1 Quiz 2  Computer Networking 2017.3.16	11.	. TDM is suitable for Circuit switching, whereas ATDM is for packet switching (with packet						
Chapter 1 Quiz 2  Computer Networking 2017.3.16								
Computer Networking 2017.3.16	12.	The end-to-end delay of	10 packets equals sum of the	ne end-to-end delay of each packet.				
Computer Networking 2017.3.16								
Computer Networking 2017.3.16								
Computer Networking 2017.3.16								
Computer Networking 2017.3.16								
	•							
Name: Student No:								
		Name:	St	udent No:				
<u>Note:</u> Write T or F before each question number	Not	t <u>e:</u> Write T or F before eac	ch question number					

1.	2.	3.	4.	5.
6.	7.	8.	9.	10.