Drift to Default: How Autoregressive Video Rollouts Forget Their Opening

Anonymous authors

Abstract

Autoregressive video diffusion models generate long videos chunk by chunk and drift over tens of seconds. We measure drift by intervention: we shift the brightness, colour or scene class of the same opening frame and measure how much of the shift survives. In fifteen preregistered studies on seven open models (six built on the Wan2.1-1.3B architecture, one on the 13B HunyuanVideo), rollouts *relax*: global tone and scene content move from the opening toward a default set by the conditioning, keeping a share α that depends on the model, the prompt and the horizon. Under a generic city prompt, openings of six scene classes lose 39–93% of their class evidence within 30 s. What decides the long-run share is how the opening is held. Attention to a key–value cache alone forgets it completely; an attention sink holds a share that grows with its depth and hinges on its absolute rotary position: re-aligning the sink's positions cuts persistence at 60 s from 0.61 to 0.16 and removes periodic bursts in which the opening, including its scene content, returns. Re-denoising overlapping frames holds nearly all of it over 20 s until the overlap is shrunk. A linear chunk recursion predicted the prompt's per-chunk pull (0.08); bit-exact cache replay measured 0.088 $[0.045, 0.149]$, but the recursion holds only for about 20 s and does not account for the positional effects. In an exploratory analysis, drift separates into forgetting the opening and an offset of the default from where the same prompt starts, near zero for models trained on long rollouts. A content-aware correction and a deeper sink both reduce drift without training; the correction keeps more legitimate brightness changes in some prompts. We report all 42 preregistered primary tests, 15 of which failed.

1 Introduction

Autoregressive video diffusion models generate a video chunk by chunk, each chunk conditioned on the model's own earlier output [3, 1, 2]. This makes streaming and open-ended generation possible and is the basis of interactive world models [37, 38, 39]. It also makes them drift: over tens of seconds the picture darkens or saturates, loses texture, and its content wanders. A growing family of methods targets this failure with rolling windows, attention sinks, re-aligned positions, longer self-rollouts and test-time correction [7, 8, 9, 22, 12, 13, 21]. Most report a few samples per prompt and an aggregate quality score. What drift *is*, in quantitative terms, is rarely measured.

We measure it by intervention. We hold an opening frame, shift its brightness, colour or scene content *within* a scene, let the model continue, and ask how much of the shift survives. The answer has the same form in every model we tested: the rollout *relaxes*. It moves from its opening toward a default state set by the conditioning, and keeps a model-specific share α of where it started,

$$x_\infty \approx \alpha\, x_{\text{open}} + (1-\alpha)\,\mu. \tag{1}$$

Written this way the law is just a linear response, and much of the paper is about which parts of it carry content. Three findings do.

What survives in the long run depends on how the opening is held, not on autoregression as such. Models that read the opening only through a key–value cache forget it completely. An attention sink holds a share that grows with its depth and hinges on its absolute rotary position, which also produces periodic bursts in which the opening returns. Re-denoising overlapping frames holds nearly all of it over 20 s until the overlap is shrunk.




Figure 1: Relaxation. Left: a generated mountain-road opening, darkened or brightened by 16 L* before encoding, continued for 60 s under a generic city prompt by Self Forcing DMD with and without an attention sink. The scene turns into a city street in all three runs; without a sink the colours also blow out. Right: mean brightness over the 24 scenes of study 7 for the three versions of each opening (3-s moving average). Without a sink the versions converge to one default; with a sink they stay apart by a share that fluctuates around half.

The default is set by the conditioning. Lighting words move the default brightness by up to 27 L*, and scene words decide whether a snowy, desert or forest opening stays or becomes a city street within 30 s. Which parts of the conditioning carry tone differs between models.

Drift has two separable parts (exploratory): forgetting the opening, $(1-\alpha)(x_{\text{open}}-\mu)$, and an offset of the default itself from where the same prompt starts, which is small in the two models trained for long rollouts and 4–11 L* in models trained on short clips.

A linear chunk recursion, $\alpha_\infty = w_s/(w_s+w_p)$ with per-chunk pulls of the sink and the prompt, predicted $w_p \approx 0.08$; bit-exact replay of the key–value cache measured 0.088. It describes the first 20 s, not the positional effects that follow. Training-free levers act on either term: an early-step tone correction, a deeper sink, and lighting words calibrated to a model's measured defaults, each with its own cost.

Contributions.

1. A measurement protocol for long-horizon drift: held and perturbed openings, persistence α and default μ for tone and scene content, paired seeds pinned to one GPU architecture, and preregistered analyses.
2. An empirical account of relaxation across seven open models (five Wan-based cache models, SkyReels-V2 and the Matrix-Game-2.0 world model, all of the Wan2.1-1.3B architecture, plus the 13B HunyuanVideo-based FramePack), for tone and scene content, at horizons up to 120 s: what sets μ, what sets the long-run share (how, and at which position, the opening is held), and an exploratory decomposition of drift into forgetting and attractor offset.
3. A phenomenological recursion whose predicted prompt pull we preregistered and then measured by bit-exact replay, with its limits.
4. Training-free levers matched to the two terms, compared on the same prompts and seeds, with their costs and failures.

We preregistered fifteen studies with hashed analysis code and report all 42 primary tests, including the 15 that failed (Table 3). No model is trained; all code and per-video statistics are public.

2 Related work

Autoregressive and long video diffusion. Diffusion Forcing [3] and History-Guided Video Diffusion [32] enable causal rollout with per-frame noise and guidance on the history. CausVid [1] distils a bidirectional teacher [4] into a few-step causal student with DMD [5]; Self Forcing [2] and Self-Forcing++ [22] train on the

student's own (minute-long) rollouts. LongLive [7], Rolling Forcing [8] and Deep Forcing [9] add attention sinks, rolling joint denoising and deeper, re-aligned sinks; LoL [21] traces "sink collapse" to positional periodicity. Segment-wise models condition on overlapping frames (SkyReels-V2 [10], StreamingT2V [26], MAGI-1 [31]), a temporal pyramid (Pyramid Flow [30]) or packed history with anti-drifting sampling (FramePack [23]); training-free schemes lengthen bidirectional models [25, 27, 28, 29]. These works propose mechanisms against drift; we measure what drift does and which mechanism changes which part of it.

Error accumulation, exposure bias and world models. Sampling from one's own output causes exposure bias in sequence models [33, 34] and diffusion models [35, 36]; error analyses of autoregressive video diffusion [14] bound how errors compound, and game and driving world models [37, 38, 39, 49] add noise to context frames for robustness. For global statistics our results suggest a complementary view: the rollout forgets its context and relaxes to the conditioning's default, whose offset from the short-horizon distribution is a training-horizon effect. Global brightness biases of diffusion models arise at the earliest denoising steps [40, 41], consistent with corrections acting only there.

Attention sinks, forgetting and correction. Streaming language models keep the first tokens as an attention sink [11, 42], related to registers in vision transformers [43]; in autoregressive video the sink is usually the first chunk kept in the key–value cache. The closest analogue to our finding is instruction drift in dialogs [44], where attention to the system prompt decays and behaviour reverts to a default. Pathwise test-time correction [12] and FreqForcing [13] anchor rollouts to early frames or their low frequencies; our correction is a minimal member of this family. VBench [15] scores imaging quality with MUSIQ [16]; we measure drift against each prompt's fresh-start distribution [17] and by intervention.

3 Measuring drift by intervention

Models. Appendix Table 2 lists the configurations. Self Forcing (five checkpoints), CausVid, LongLive and Rolling Forcing are causal few-step students of Wan2.1-T2V-1.3B [4] that read their past through a key–value cache of 21 latent frames (LongLive: 12), optionally with an attention sink (the first chunk kept in the cache). SkyReels-V2-DF uses the Wan2.1 VAE and a transformer of the same architecture and size, but extends videos in 97-frame segments that re-denoise the last 17 frames of the previous segment. Matrix-Game-2.0 [49] is a Wan-architecture world model without a text branch, driven by keyboard and mouse actions. FramePack [23] is a 13B model fine-tuned from HunyuanVideo [24]; each 33-frame section sees the opening as a clean prefix frame and as a SigLIP [48] image embedding, plus compressed history. MAGI-1 [31] (4.5B, distilled) has its own VAE and transformer; it generates 1-s chunks that attend to earlier chunks through a key–value cache, in its released configuration to at most the four previous chunks with no sink, and its code also allows attention to the full history. All Wan-based configurations run in one harness that reproduces the official Self Forcing loop bit for bit when no intervention is applied.

Held and perturbed openings. An opening image is held still for the first chunk (9 frames, 0.56 s at 16 fps; SkyReels: 17 frames as a prefix video; FramePack: the input image; MAGI-1: a clean image prefix) and continued under a prompt. Openings are NAVSIM [19] front-camera frames or frames generated by the models themselves. To separate what the model keeps from what the scene is, we shift the *same* opening in CIELAB before encoding: L^* by ± 8 and ± 16, b^* by ± 12. For scene content, we instead generate openings of six scene classes and vary the prompt (Section 4.1).

Persistence and default. For a statistic x (a per-frame CIELAB mean), the persistence at time T is the within-scene least-squares slope of the end value $\bar{x}(T)$, averaged over the window $[T-w, T)$ after the opening, on the opening value x_{open} (mean of the held frames),

$$\alpha(T) = \frac{\partial\, \bar{x}(T)}{\partial\, x_{\text{open}}}\Big|_{\text{scene}}, \qquad \mu(T) = \frac{b_0}{1-\alpha(T)}, \tag{2}$$

where b_0 is the fitted intercept, so μ is the level at which the end equals the opening (the zero-drift level). The window is the last 2 s at 31 s (study 6), 5 s at 20–30 s (studies 8, 9, 11), 10 s at 60 s and at 30 s in studies 12

and 15, and 1 s for curves; Appendix Table 4 compares all models over the same window, 15–20 s. Averaging slopes over 24 scenes gives a scene-bootstrap interval. The fresh default is where prompt-only rollouts end.

Content persistence. For scene content we score each frame with CLIP ViT-L/14 [47] as the log-odds of the opening's class against "a city street", $z = s\,(\cos(f, t_{\text{class}}) - \cos(f, t_{\text{city}}))$, and define $\kappa(T) = (z(T) - \mu_z)/(z_{\text{open}} - \mu_z)$ with μ_z the class score of fresh rollouts of the generic prompt. κ is the content analogue of α: 1 if the class evidence is kept, 0 if the rollout looks like a fresh generic rollout.

Drift metrics for prompt-only rollouts. Where no opening is held, drift is measured against fresh 5-s generations of the same prompt, in colour statistics (D) and DINOv2 [17] features (K; Appendix B).

Pairing and preregistration. With bf16 kernels, the same seed and code give bit-identical videos within a GPU architecture but different videos across A40, A100/A800 and L40S/RTX 6000 Ada. Arms that are compared therefore run in one job, which deletes and regenerates its outputs if a preempted job resumes on another architecture. (In our first study this was not yet enforced; 62% of its nominal pairs crossed architectures, which widens but does not bias its intervals.) Each study's hypotheses, decision rules and analysis code were frozen by SHA-256 hash before its videos were generated (study 1: before analysis, after generation had started); studies 3–15 were also committed publicly first. Tests within a study are Holm-corrected. Table 3 lists every primary test.

4 Rollouts relax toward a conditioning-set default

Tone. Observationally, the 31-s change of every global statistic is anti-correlated with its opening value (r from -0.79 to -0.95; Appendix Table 5), but openings differ in content too, so we intervened: we shifted the brightness and colour temperature of the same opening within each of 24 scenes (12 NAVSIM, 12 generated) and continued every version with the generic prompt (study 6, 31 s; study 10, 60 s). Figure 1 shows the result for Self Forcing: the versions converge, and an attention sink keeps them apart by a fixed share. Figure 2a gives α at 60 s for every configuration. At 60 s every cache configuration has relaxed: α ranges from -0.01 (LongLive without a sink) to 0.79 (Self Forcing GAN), and the ranking agrees with the one at 31 s (Spearman $\rho = 0.78$, $p = 0.008$). Part of the loss is immediate: most configurations lose a fifth to a third of the shift within 4.5 s, and SiD loses almost all of its total there (0.66 of 0.65), which looks like the model rejecting an off-manifold shift rather than forgetting it. Colour temperature behaves like brightness. Persistence varies by checkpoint even with architecture, context and sampler fixed (Self Forcing: 0.35 to 0.79 at 60 s; two SiD checkpoints differ by 0.36), so we attribute it to the checkpoint rather than to the training objective.

4.1 Scene content

Global tone is the easiest statistic to shift and measure, but it is not what a user sees as "the scene". We therefore generated openings of six scene classes (snow, desert, forest, coast, mountain, farmland; four openings each, selected by CLIP before any continuation) and continued each under the generic city prompt and under its own class prompt, with eight configurations (study 9). Content relaxes like tone (Fig. 3). Under the city prompt, κ at 30 s ranges from 0.07 (SiD) to 0.61 (Rolling Forcing); six of eight configurations lose most of the class evidence, and the opening's class is CLIP's top label in only 34% of Self Forcing frames at 30 s. Under the opening's own class prompt the class persists (κ 0.71–1.05), as a fresh rollout of that prompt would also show it: the class prompt keeps 9.3 $[8.1, 10.5]$ more log-odds than the city prompt at 30 s (preregistered; 9.0 after each frame's tone is matched to the opening's). The informative result is the loss under the city prompt. Content persistence is correlated with tone persistence across configurations ($\rho = 0.67$, $p = 0.07$, $n = 8$).

Sinks act differently on content. Self Forcing's sink keeps more of it at 60 s (κ 0.61 vs 0.14, +0.48 $[0.39, 0.57]$, preregistered), but not steadily: κ falls to 0.32 at 30 s and rises again, and in the frames the dunes, the sea and the mountains of the opening reappear after a minute of city (Fig. 3, left). The returns coincide with the positional bursts in tone persistence (Section 5), and they are positional too (study 16, 24 openings): with the sink's keys re-rotated to sit just before the window, the second return vanishes (burst contrast




Figure 2: Persistence at 60 s (study 10; CausVid from study 7). (a) α of an L* shift with scene-bootstrap 95% CIs; hollow markers: 31 s (study 6). (b) Self Forcing with sinks of 0, 1, 3 and 6 latent frames, at their original positions or re-rotated to sit just before the window (dashed). (c) Other models. Curves: 1-s windows, 3-s moving average; shaded: 31–35 s and 50–54 s, where sinks of three or more frames at their original positions produce bursts. The 60-s endpoint window, [50, 60) s, overlaps the second burst; Appendix C reports a burst-free window.

$+0.31 \to +0.01$, -0.29 [-0.37, -0.22]), the first as well ($+0.20 \to -0.03$), and the content kept at 60 s falls from 0.56 to 0.25 (-0.31 [-0.37, -0.25]); both tests were preregistered and hold on tone-normalised embeddings. A re-rotated sink keeps no detectably more content than no sink (0.25 vs 0.15, +0.10 [-0.00, 0.21], preregistered test not supported); its content curve lies on the no-sink curve. What a Self Forcing sink keeps of the scene, it keeps by periodically re-injecting the opening. LongLive's sink, which keeps tone, does not keep content (0.22 vs 0.24, preregistered test not supported).

Content relaxes outside the Wan family too. FramePack, continuing the same 24 openings under the city prompt, keeps 0.55 of the class evidence at 20 s (Self Forcing: 0.40 with a sink, 0.31 without), and the class score falls by 6.7 [5.2, 8.3] log-odds (study 17, preregistered). We separated its two routes by giving the context prefix and the SigLIP embedding different images, the opening or a generated city frame. The context prefix alone keeps 0.24 [0.12, 0.37], levelling off after 14 s; the embedding alone, with a city frame in the context, starts at 0 and *pulls* the video toward the opening's class, to 0.23 [0.16, 0.30] at 20 s and still rising (Fig. 4b); together they keep +0.31 [0.20, 0.41] more than the context alone, about the sum of the two. All four preregistered tests hold, also on tone-normalised embeddings. The same embedding has no effect on tone (study 11), so in FramePack the image embedding sets the default of the scene but not of its brightness.

4.2 The default

The conditioning sets it. Continuing the same 40 openings under four lighting prompts gives four defaults: on Self Forcing, sunny 43, overcast 34, dusk 19 and night 16 L*; on LongLive the same words give 45, 40, 32 and 21 (Appendix, Fig. 6). The prompt sets the target, and the mapping from words to brightness is model-specific. The default also differs between checkpoints of one architecture under the same prompt (zero-drift levels from 17 to 54 L* across configurations), and it tracks where prompt-only rollouts end ($r = 0.93$, slope 1.58; Appendix C).

Persistence is not independent of the prompt. Equation 1 separates a model term (α) from a prompt term (μ), but α itself varies with the prompt: in the lighting experiment, Self Forcing keeps 0.34 of the opening under a sunny prompt and 0.05 under a night prompt (interaction $p = 0.001$, exploratory; LongLive $p = 0.053$). We preregistered this test in four new scene types (a park walk, a drone flight over a coast,




Figure 3: Scene content relaxes to the prompt's default (study 9). Left: a snow and a desert opening continued by Self Forcing DMD under the city prompt or their own class prompt. Under the city prompt both become city streets; with a sink the desert returns at 60 s; without a sink the video collapses. (a) Content persistence $\kappa(t)$ (CLIP log-odds of the opening's class against "city street", 0 = fresh generic rollout, 1 = opening) under the city prompt (solid) and the class prompt (dotted). (b) κ at 30 s, 24 openings, 95% CIs. (c) Content against brightness persistence across configurations.

a kitchen, a market; six self-generated openings each, study 12): Self Forcing's persistence at 60 s differs between them (0.44 to 0.67, $p = 0.049$), as does LongLive's at 30 s (0.10 to 0.43, $p = 0.009$, secondary). Because each scene type has its own prompt and its own openings, this shows that persistence varies with the scene, not with the prompt alone. The sink effects replicate almost exactly outside driving scenes: Self Forcing keeps 0.55 with a sink and 0.02 without at 60 s (+0.53 [0.45, 0.61]), LongLive 0.24 vs 0.05 at 30 s.

Two components of drift. For a prompt-only rollout, Eq. 1 says nothing about why the default should differ from where the same prompt starts. It does, and by how much depends on training (Fig. 5a). For Self Forcing (5-s clips) and CausVid, fresh rollouts end 4–11 L* from where they start (Self Forcing darkens, CausVid brightens); for LongLive and Rolling Forcing, trained or tuned for long rollouts, the offset is 0.7–2.3 L*. Yet LongLive still forgets its opening ($\alpha = 0.19$ with a sink, 0.02 without, at 31 s). In this exploratory analysis drift has two separable parts: *forgetting* the opening, $(1-\alpha)(x_{\text{open}} - \mu)$, which every attention-based model does, and an *attractor offset* $\mu - x_{\text{start}}$, which is near zero in the two models trained for long rollouts (with only two such models, other differences between them and the short-clip models cannot be excluded). Prompt-only drift metrics such as D mix the two, and both keep rising over 31 s even with a sink (Appendix F); relaxation describes the memory of the opening, not the absence of degradation.

5 What decides how much of the opening is kept

Attention sinks keep a share. In study 6, removing LongLive's sink lowered α at 31 s from 0.19 to 0.02 (−0.17 [-0.28, -0.06]) and removing Self Forcing's lowered colour persistence from 0.25 to −0.01. For Self Forcing brightness the preregistered test failed at 31 s (−0.06 [-0.17, 0.05]): without a sink Self Forcing forgets slowly, so at 31 s it had not yet forgotten (Fig. 2b). At 60 s (study 7) the sink keeps 0.58 of the opening and no sink 0.03 (+0.55 [0.45, 0.65]); for CausVid 0.23 vs 0.04. Persistence grows with sink depth (study 10, 60 s): no sink 0.05, one latent frame 0.29, three 0.61, six 0.76 (+0.15 [0.11, 0.20] for six vs three; +0.24 [0.14, 0.34] for one vs none, which reverses an exploratory 31-s anomaly), and LongLive's sink keeps 0.45 against −0.01.

The sink's *position* matters even more. Self Forcing keeps the sink keys at their absolute rotary positions, ever further from the current chunk; re-rotating them to sit just before the window, as Rolling Forcing and Deep Forcing do, lowers persistence at 60 s from 0.61 to 0.16 (-0.44 [-0.54, -0.35], preregistered two-sided). In the window 40–50 s, between the bursts described below, the effect is smaller but clear (-0.27 [-0.38, -0.16]), and persistence still grows with sink depth (0.08, 0.23, 0.48, 0.63). Depth, however, helps only at the original positions (study 16, 24 scenes): re-rotation cuts a six-frame sink from 0.76 to 0.22 (-0.54 [-0.63, -0.46]), and re-rotated sinks of six and three frames keep the same share (0.22 vs 0.23, -0.00 [-0.11, 0.10]; preregistered test of a depth effect not supported; 40–50 s: $+0.03$ [-0.09, 0.14]). Their curves coincide from 10 s on. (The three-frame value is 0.16 in study 10 because 9 of the 24 scenes ran on another GPU architecture this time, which amounts to resampling them; all 72 videos repeated on the same architecture were bit-identical.) A sink at in-distribution positions thus holds a small, steady share of tone (about 0.2) whatever its depth, and almost none of the scene.

Re-conditioning on the opening keeps most of it. SkyReels-V2-DF, which re-denoises the last 17 frames of each segment jointly with the new ones, does not relax ($\alpha = 0.96$ [0.86, 1.07] at 20 s), whatever its guidance, history noise or number of steps (exploratory). Cutting the overlap to 5 frames, with the same number of extensions, makes it relax: α at 15–20 s falls from 1.01 to 0.77 (-0.24 [-0.40, -0.09], preregistered, 12 new scenes). With 17 frames, 5 of 12 scenes have $\alpha > 1$: the overlap passes the opening forward and can amplify it. FramePack [23], a 13B model fine-tuned from HunyuanVideo [24], places the opening as a clean prefix frame in the context of *every* 33-frame section and also feeds its SigLIP embedding as a global condition (study 11, 12 scenes, 20 s). It relaxes: 0.91 of a brightness shift at 5 s and 0.68 [0.57, 0.79] at 20 s with forward sampling (preregistered: more than half, supported). Over the same window that is as much as the best cache configurations keep (six-frame sink 0.72, Rolling Forcing 0.64; Appendix Table 4), not more. A shift sent only through the context prefix levels off at about half (0.53) between 10 and 20 s; FramePack's anti-drifting sampling, which generates sections from the end back toward the opening, keeps 0.86. A shift sent only through the image embedding does nothing (0.01 [-0.14, 0.17]; preregistered test not supported): in FramePack the image embedding does not carry tone. (We did not vary FramePack's text prompt.)

A model of its own architecture. MAGI-1 [31] shares neither architecture nor training with the other models, and its code lets us choose how long the opening stays in the context (study 18, 12 scenes, 30 s). In the released configuration, which attends to the four previous 1-s chunks, the opening leaves the context after about 4 s; persistence is 0.87 at 5 s and falls to 0.34 at 30 s (-0.52 [-0.70, -0.35]) without levelling off (Fig. 4c). With full history the curves coincide for the first 5 s and then separate: persistence levels off near 0.65 from 10 s on (0.64 [0.45, 0.83] at 30 s, $+0.30$ [0.17, 0.43] over the window). All three preregistered tests hold, and none of the 48 videos froze. Keeping the opening in context does not stop the shared drift: fresh rollouts brighten by 15–20 L^* under either setting, and the mean $|\text{end} - \text{open}|$ is no smaller with full history (13.2 vs 11.2 L^*). Full history preserves the difference between openings, not their level.

An action-conditioned world model. Matrix-Game-2.0 [49] generates a world from an image and keyboard and mouse actions, with no text. The opening's latent enters only the first chunk and leaves the 6-frame key–value window after about a second (no sink); its CLIP [47] embedding conditions every chunk. We continued the 24 scenes with a constant forward action and sent the opening's brightness shift through both routes, the context latent only, or the embedding only (study 15). The model often collapses to black: 40 of 144 videos turn black within 30 s, mostly after 19 s, so the preregistered 30-s analysis kept only 7 scenes. There, a shift held only in the context faded (-0.24 [-0.35, -0.14], supported), and the embedding-only shift persisted (0.43 [0.13, 0.71]) but did not pass the Holm-corrected threshold ($p = 0.075$). At 15 s, where 20 scenes remain (exploratory), the picture is clear (Fig. 4): the context-only shift fades from 0.76 at 2 s to 0.10, while the embedding-only shift is small at first (0.08) and then *grows* to 0.25 [0.17, 0.36], the rollout relaxing toward a default that moves with the conditioning; the two routes add up.

A phenomenological recursion. Model a chunk's mean statistic as

$$x_{k+1} = w_w\, \bar{x}_{\text{window}} + w_s\, x_{\text{sink}} + w_p\, \mu, \qquad w_w + w_s + w_p = 1, \tag{3}$$




Figure 4: Models outside the Wan cache family. (a) FramePack (study 11, 12 scenes): the opening's brightness shift sent through both routes, only the clean context prefix, or only the SigLIP image embedding; the anti-drifting sampler; SkyReels-V2 with 17 and 5 overlapping frames for reference. (b) FramePack, scene content (study 17, 24 openings, city prompt): with a city frame in the context, the opening's embedding alone pulls the video toward the opening's class. (c) MAGI-1 (study 18, 12 scenes): the released window of four 1-s chunks against full history (1-s windows, 3-s moving average). (d) Matrix-Game-2.0, an action-conditioned world model without text (study 15, exploratory 15-s analysis, 20 scenes): the context latent leaves the window and is forgotten, while the rollout drifts toward the CLIP-embedded opening. Bands: scene-bootstrap 95% CIs.

where the opening counts as a window chunk until it rolls out and μ is the prompt's default. Without a sink the opening is eventually forgotten; with one, $\alpha_\infty = w_s/(w_s + w_p)$, so a small sink weight can keep a large share if the prompt's pull is also small. Bit-exact replay of the key–value cache measures the weights directly, by regenerating one chunk from identical noise after changing only the sink, the window or the text conditioning: $w_s = 0.053$ $[0.040, 0.066]$ for synthetic tone shifts (0.036 in a dose–response design), and $w_w = 0.76$ (synthetic) to 0.90–0.99 (natural differences), in 10 development prompts $\times$ 2 seeds. Fitted to 120-s curves (6 scenes $\times$ 2 versions), the recursion gives $w_s = 0.060$ $[0.021, 0.097]$ and $w_w = 0.86$, implying $w_p \approx 0.08$. We preregistered this prediction and measured the prompt's pull by swapping only the text conditioning of one chunk to a lighting prompt with a different default (study 14): $w_p = 0.088$ $[0.045, 0.149]$ at 15 s (Fig. 5b, c), proportional to the default difference, with no effect from a prompt of equal default. The three weights sum to 1.00 with the fitted w_w, but to 0.90 or 1.13 with the replay-measured ones, and α_∞ is 0.29–0.41 depending on which w_s is used. Without a sink the measured pull is smaller (0.035 at 15 s), so w_p is not a property of the prompt alone.

The recursion is a first-order description that holds for about 20 s. With a sink, the prompt's pull rises to 0.26 $[0.17, 0.36]$ at 30 s (preregistered test of time invariance, +0.16 $[0.10, 0.24]$); fitted weights depend on the horizon; and persistence jumps abruptly between 31.5 and 34.5 s (+0.45 $[0.36, 0.53]$ with a three-frame sink, +0.46 with six) and again near 52 s, in LongLive and the other Self Forcing checkpoints too (Fig. 2b, c). With re-rotated sinks it is replaced by a small decline (-0.08 [-0.13, -0.02]). Its timing matches the "sink collapse" that LoL [21] attributes to rotary-position periodicity, and the role of intrinsic rotary frequencies in




Figure 5: (a) Two components of drift: persistence of the opening (study 6) against the attractor offset of fresh rollouts (end minus start brightness, 4 seeds); models trained for long rollouts have almost no offset but still forget. (b) The prompt's per-chunk pull measured by bit-exact replay (study 14; 16 seeds; 95% CIs): one chunk regenerated from identical cache, noise and random state with only the text conditioning swapped; grey: the value implied by the recursion fitted to 120-s curves, preregistered for 15 s. (c) The swapped chunk's change against the difference of the prompts' defaults; a prompt with the same default has no effect.

video length extrapolation [50, 51]: the sink keeps its absolute position, and at certain distances the current chunk attends to it strongly. It coincides with the return of the opening's dunes and sea in study 9. Much of what a Self Forcing sink keeps at 60 s is therefore positional: with in-distribution positions it keeps 0.16–0.23 whatever its depth, below what the recursion implies, and no more scene content than no sink; the aliased sink keeps 0.61, above it. The recursion does not explain either value.

6 Two levers

Equation 1 suggests two ways to keep a long rollout near its opening without retraining: raise α, or move μ toward the opening.

Raising α: a content-aware correction. At denoising step 1 of 4, the noisy chunk is denoised once more with a temporary cache that holds only the anchor (the opening chunk). The difference between the per-channel spatial means of the two predictions (the DC tone) is added to the real prediction, scaled by β; the main cache and the random stream are untouched. In a preregistered confirmation on 40 held-out prompts × 4 seeds (study 2), colour drift D fell by 1.48 $[1.19, 1.76]$ at $\beta = 1$ and by 1.78 $[1.45, 2.11]$ at $\beta = 1.5$, with structure drift K non-inferior. Table 1 compares it with post-hoc colour matching to the anchor, which reaches a similar D but, by construction, removes legitimate global changes too: on 7 held-out prompts with real brightness transitions (tunnels, garages, clouds), matching keeps 7–12% of the transition and the correction a median of 83% $[67, 147]$ ($\beta = 1$) and 93% $[83, 148]$ ($\beta = 1.5$; prompt-bootstrap intervals over only seven prompts). The per-prompt values range from 0.58 to 1.71, so on some prompts the correction amplifies the change. The costs are one extra forward pass per chunk (about 25% more compute), more frame-to-frame jitter (×1.13 / ×1.67) and larger jumps at chunk boundaries (×1.32 / ×2.40).

A deeper attention sink, as in Deep Forcing [9], is a strong training-free alternative (study 13, same prompts and seeds, bit-identical pairing). Keeping 6 or 9 latent frames as the sink cuts colour drift by 1.30 and 1.93, the latter more than the correction at $\beta = 1$ (-0.45 [-0.75, -0.15]), with frame-to-frame jitter similar to the correction's (×1.04, ×1.16) and smaller boundary jumps (×0.98, ×1.09). A sink pulls everything toward the opening through attention, and in two of the seven transition prompts the nine-frame sink erased most of a legitimate change (7% and 19% kept, against 151% and 147% for the correction); its median is 0.59 $[0.19, 1.09]$ against 0.83 for the correction, but with seven prompts the intervals overlap. The correction, which moves only the DC tone, is the more conservative choice when real changes matter.

The denoising step is a knob. On the development set, correcting at step 0 removes as much drift as step 1 but erases tunnels (56% of transitions kept vs 94%); steps 2–3 do nothing, consistent with global tone being fixed at the earliest steps [40, 41]. In the relaxation study the correction raised Self Forcing's persistence

Table 1: Correction versus post-hoc colour matching and deeper sinks (study 2 confirmation set: 40 held-out prompts $\times$ 4 seeds; transitions: 7 held-out prompts with legitimate brightness changes). Transitions kept: median over prompts of the corrected over the uncorrected first-to-last brightness change, prompt-bootstrap 95% CI.

Method	ΔD [95% CI]	transitions kept	jitter	boundary jumps
Content-aware correction, $\beta = 1$	-1.48 [-1.76, -1.19]	0.83 [0.67, 1.47]	$\times 1.13$	$\times 1.32$
Content-aware correction, $\beta = 1.5$	-1.78 [-2.11, -1.45]	0.93 [0.83, 1.48]	$\times 1.67$	$\times 2.40$
Post-hoc mean matching	-0.89 [-1.29, -0.50]	0.07	$\times 0.15$	$\times 0.12$
Post-hoc Reinhard [20]	-1.58 [-1.96, -1.19]	0.12	$\times 0.13$	$\times 0.10$
Deeper sink, 6 frames (study 13)	-1.30 [-1.68, -0.93]	0.70 [0.58, 1.12]	$\times 1.04$	$\times 0.98$
Deeper sink, 9 frames (study 13)	-1.93 [-2.31, -1.55]	0.59 [0.19, 1.09]	$\times 1.16$	$\times 1.09$

from 0.28 to 0.40 ($+0.12$ [0.05, 0.20], preregistered) and also the zero-drift level by 5 L^*.

Moving μ: prompts. Since the prompt sets the default, lighting words can be chosen so that the default matches the opening. A free-form Qwen2.5-VL [18] caption of the opening does not reduce brightness drift on either model (Self Forcing -1.21 [-3.09, 0.36], study 3): it calls half of the normally lit frames "dim", though it improves content retention. Choosing the lighting sentence whose *measured* default is nearest the opening's brightness reduces $|\Delta L|$ at 31 s by 26% on Self Forcing (-2.45 [-4.08, -1.04], Holm $p = 0.013$, study 4); the other five preregistered prompt tests failed, including LongLive with its own calibration (study 5). The mapping from words to brightness is model-specific and must be measured per model. Appendix D shows how well Eq. 1 forecasts these outcomes ($r = 0.82$ for the change, 0.46 for the gain).

7 Discussion

Any autoregressive sampler with finite memory that is ergodic under a fixed conditioning will eventually forget its initial state and settle into a conditioning-dependent stationary distribution, so that video rollouts relax is expected. What we measure is *how much* is kept and *what* decides it, and three answers hold across the models we tested. The long-run share depends on how the opening enters the computation: once the opening leaves a key–value window it is forgotten (in the Wan-based cache models and in MAGI-1), while an opening that stays in the context (a sink, MAGI-1's full history, FramePack's per-segment prefix, overlapping frames) holds a share. A sink at in-distribution positions holds a small share of tone, about 0.2 whatever its depth, and no detectable scene content; the larger shares and the returning scenes of sinks at their original positions are positional bursts. The stationary state is set by the conditioning, for tone and for scene content, and models differ in which part of the conditioning carries which attribute: FramePack's image embedding sets the scene but not its brightness. And the stationary state of models trained on short clips is offset from where the same prompt starts; long-rollout training removes the offset but not the forgetting.

For world models, this means that a model conditioned on a real frame and a description drifts toward the description's default unless it re-conditions on the frame. Persistence at a stated horizon and the default with its offset are cheap to measure with our protocol and would make long-video models comparable where a single quality score does not. Anchors that keep the opening also pass its errors forward, and positional bursts can bring a forgotten opening back. In Self Forcing the mechanism that keeps the opening's scene is exactly the unstable one: keeping the opening's content while forgetting its errors is the open problem.

Limitations. Six of the eight models share the Wan2.1-1.3B architecture; FramePack and MAGI-1, the other bases, ran for 20 and 30 s. Content relaxation was replicated on FramePack, but the prompt dependence, the recursion and the decomposition rest on Wan-based models, and the world model collapses after 20–30 s. Interventions shift global tone or select a scene class (CLIP scores are a coarse proxy for content); openings are held images; each configuration of a scene uses one seed; Holm correction is applied within studies only; the correction was not compared with Pathwise test-time correction or FreqForcing.

References

[1] T. Yin, Q. Zhang, R. Zhang, W. T. Freeman, F. Durand, E. Shechtman, X. Huang. From slow bidirectional to fast autoregressive video diffusion models. CVPR 2025 (arXiv:2412.07772).

[2] X. Huang, Z. Li, G. He, M. Zhou, E. Shechtman. Self Forcing: Bridging the train-test gap in autoregressive video diffusion. arXiv:2506.08009, 2025.

[3] B. Chen, D. Martí Monsó, Y. Du, M. Simchowitz, R. Tedrake, V. Sitzmann. Diffusion Forcing: Next-token prediction meets full-sequence diffusion. NeurIPS 2024 (arXiv:2407.01392).

[4] Wan Team. Wan: Open and advanced large-scale video generative models. arXiv:2503.20314, 2025.

[5] T. Yin, M. Gharbi, R. Zhang, E. Shechtman, F. Durand, W. T. Freeman, T. Park. One-step diffusion with distribution matching distillation. CVPR 2024 (arXiv:2311.18828).

[6] M. Zhou, H. Zheng, Z. Wang, M. Yin, H. Huang. Score identity distillation: Exponentially fast distillation of pretrained diffusion models for one-step generation. ICML 2024 (arXiv:2404.04057).

[7] S. Yang, W. Huang, R. Chu, Y. Xiao, Y. Zhao, X. Wang, M. Li, E. Xie, Y. Chen, Y. Lu, S. Han, Y. Chen. LongLive: Real-time interactive long video generation. arXiv:2509.22622, 2025.

[8] K. Liu, W. Hu, J. Xu, Y. Shan, S. Lu. Rolling Forcing: Autoregressive long video diffusion in real time. arXiv:2509.25161, 2025.

[9] J. Yi, W. Jang, P. H. Cho, J. Nam, H. Yoon, S. Kim. Deep Forcing: Training-free long video generation with deep sink and participative compression. arXiv:2512.05081, 2025.

[10] SkyReels Team. SkyReels-V2: Infinite-length film generative model. arXiv:2504.13074, 2025.

[11] G. Xiao, Y. Tian, B. Chen, S. Han, M. Lewis. Efficient streaming language models with attention sinks. ICLR 2024 (arXiv:2309.17453).

[12] X. Xiang, Z. Duan, G. Zhang, H. Zhang, Z. Gao, J. Wu, S. Zhang, T. Wang, Q. Fan, C. Guo. Pathwise test-time correction for autoregressive long video generation. arXiv:2602.05871, 2026.

[13] J. Li, L. Liang, L. Kong, Y. Zhang. FreqForcing: Autoregressive long video generation via spectral self-anchoring. arXiv:2607.27110, 2026.

[14] J. Wang, F. Zhang, X. Li, V. Y. F. Tan, T. Pang, C. Du, A. Sun, Z. Yang. Error analyses of auto-regressive video diffusion models: A unified framework. arXiv:2503.10704, 2025.

[15] Z. Huang et al. VBench: Comprehensive benchmark suite for video generative models. CVPR 2024 (arXiv:2311.17982).

[16] J. Ke, Q. Wang, Y. Wang, P. Milanfar, F. Yang. MUSIQ: Multi-scale image quality transformer. ICCV 2021.

[17] M. Oquab et al. DINOv2: Learning robust visual features without supervision. TMLR 2024 (arXiv:2304.07193).

[18] Qwen Team. Qwen2.5-VL technical report. arXiv:2502.13923, 2025.

[19] D. Dauner et al. NAVSIM: Data-driven non-reactive autonomous vehicle simulation and benchmarking. NeurIPS 2024.

[20] E. Reinhard, M. Ashikhmin, B. Gooch, P. Shirley. Color transfer between images. IEEE CG&A, 2001.

[21] J. Cui, J. Wu, M. Li, T. Yang, X. Li, R. Wang, A. Bai, Y. Ban, C.-J. Hsieh. LoL: Longer than longer, scaling video generation to hour. arXiv:2601.16914, 2026.

[22] J. Cui, J. Wu, M. Li, T. Yang, X. Li, R. Wang, A. Bai, Y. Ban, C.-J. Hsieh. Self-Forcing++: Towards minute-scale high-quality video generation. arXiv:2510.02283, 2025.

[23] L. Zhang, S. Cai, M. Li, G. Wetzstein, M. Agrawala. Frame context packing and drift prevention in next-frame-prediction video diffusion models. arXiv:2504.12626, 2025.

[24] W. Kong et al. HunyuanVideo: A systematic framework for large video generative models. arXiv:2412.03603, 2024.

[25] J. Kim, J. Kang, J. Choi, B. Han. FIFO-Diffusion: Generating infinite videos from text without training. NeurIPS 2024.

[26] R. Henschel et al. StreamingT2V: Consistent, dynamic, and extendable long video generation from text. CVPR 2025 (arXiv:2403.14773).

[27] H. Qiu, M. Xia, Y. Zhang, Y. He, X. Wang, Y. Shan, Z. Liu. FreeNoise: Tuning-free longer video diffusion via noise rescheduling. ICLR 2024.

[28] Y. Lu, Y. Liang, L. Zhu, Y. Yang. FreeLong: Training-free long video generation with SpectralBlend temporal attention. NeurIPS 2024.

[29] D. Ruhe, J. Heek, T. Salimans, E. Hoogeboom. Rolling diffusion models. ICML 2024.

[30] Y. Jin et al. Pyramidal flow matching for efficient video generative modeling. ICLR 2025.

[31] Sand AI. MAGI-1: Autoregressive video generation at scale. arXiv:2505.13211, 2025.

[32] K. Song, B. Chen, M. Simchowitz, Y. Du, R. Tedrake, V. Sitzmann. History-guided video diffusion. ICML 2025 (arXiv:2502.06764).

[33] S. Bengio, O. Vinyals, N. Jaitly, N. Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. NeurIPS 2015.

[34] S. Ross, G. Gordon, D. Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. AISTATS 2011.

[35] M. Ning, E. Sangineto, A. Porrello, S. Calderara, R. Cucchiara. Input perturbation reduces exposure bias in diffusion models. ICML 2023.

[36] M. Ning, M. Li, J. Su, A. A. Salah, I. O. Ertugrul. Elucidating the exposure bias in diffusion models. ICLR 2024.

[37] D. Valevski, Y. Leviathan, M. Arar, S. Fruchter. Diffusion models are real-time game engines. ICLR 2025.

[38] E. Alonso, A. Jelley, V. Micheli, A. Kanervisto, A. Storkey, T. Pearce, F. Fleuret. Diffusion for world modeling: Visual details matter in Atari. NeurIPS 2024.

[39] S. Gao, J. Yang, L. Chen, K. Chitta, Y. Qiu, A. Geiger, J. Zhang, H. Li. Vista: A generalizable driving world model with high fidelity and versatile controllability. NeurIPS 2024.

[40] S. Lin, B. Liu, J. Li, X. Yang. Common diffusion noise schedules and sample steps are flawed. WACV 2024.

[41] N. Guttenberg. Diffusion with offset noise. CrossLabs blog, 2023.

[42] X. Gu, T. Pang, C. Du, Q. Liu, F. Zhang, C. Du, Y. Wang, M. Lin. When attention sink emerges in language models: An empirical view. ICLR 2025.

[43] T. Darcet, M. Oquab, J. Mairal, P. Bojanowski. Vision transformers need registers. ICLR 2024.

[44] K. Li, T. Liu, N. Bashkansky, D. Bau, F. Viégas, H. Pfister, M. Wattenberg. Measuring and controlling instruction (in)stability in language model dialogs. COLM 2024.

[45] P. D. Oldham. A note on the analysis of repeated measurements of the same subjects. Journal of Chronic Diseases 15:969–977, 1962.

[46] A. G. Barnett, J. C. van der Pols, A. J. Dobson. Regression to the mean: what it is and how to deal with it. International Journal of Epidemiology 34(1):215–220, 2005.

[47] A. Radford et al. Learning transferable visual models from natural language supervision. ICML 2021.

[48] X. Zhai, B. Mustafa, A. Kolesnikov, L. Beyer. Sigmoid loss for language image pre-training. ICCV 2023.

[49] X. He, C. Peng, Z. Liu, B. Wang et al. Matrix-Game 2.0: An open-source, real-time, and streaming interactive world model. arXiv:2508.13009, 2025.

[50] M. Zhao, G. He, Y. Chen, H. Zhu, C. Li, J. Zhu. RIFLEx: A free lunch for length extrapolation in video diffusion transformers. ICML 2025 (arXiv:2502.15894).

[51] F. Barbero, A. Vitvitskyi, C. Perivolaropoulos, R. Pascanu, P. Veličković. Round and round we go! What makes rotary positional encodings useful? arXiv:2410.06205, 2024.

A Models, preregistered tests, deviations and withdrawn claims

Table 2: Configurations. Wan-based cache models generate 832×480 at 16 fps in chunks of 3 latent frames (0.75 s); window and sink sizes are in latent frames.

Configuration	Base; training	Steps	Context of the opening
Self Forcing DMD, SiD, SiD v2, GAN [2, 5, 6]	Wan2.1-1.3B; self-rollout on 5-s clips	4	window 21; sink 0/1/3/6, original or re-rotated positions
Self Forcing 10 s	Wan2.1-1.3B; self-rollout on 10-s clips	4	window 21, sink 3
CausVid [1]	Wan2.1-1.3B; teacher-forced DMD	3	window 21, sink 0/3
LongLive [7]	Wan2.1-1.3B; long-rollout tuning	4	window 12, sink 0/3
Rolling Forcing [8]	Wan2.1-1.3B; rolling joint denoising	5	anchor block + 21
SkyReels-V2-DF [10]	Wan2.1-1.3B architecture; diffusion forcing; 544p, 24 fps	30 + CFG	17 (or 5) re-denoised overlapping frames
Matrix-Game-2.0 [49]	Wan2.1-1.3B architecture, no text; actions; 352×640, 25 fps	3	first latent frame only, window 6, no sink; CLIP image embedding
FramePack-F1 / I2V [23]	HunyuanVideo 13B; 480p, 30 fps	25	clean prefix in every section; SigLIP image embedding
MAGI-1 4.5B-distill [31]	own architecture (chunk-wise autoregressive diffusion transformer); 432×768, 24 fps, chunks of 1 s	64, pipelined	released: window of 4 earlier chunks, no sink; or full history

Deviations from the preregistrations.

- *Study 1* was frozen before analysis but after generation of its main videos had started, and its arms were not pinned to one GPU architecture: 62% of its nominal seed pairs ran on different architectures. Its preregistered Wald intervals are reported; the prompt-cluster bootstrap interval for the main contrast is wider ([-10.45, -5.39] for D) but leads to the same conclusion.
- *Study 3:* a preempted job resumed on another GPU type and split four LongLive openings across architectures. We regenerated the affected arms on the original architecture; conclusions are unchanged.
- *Study 6:* the ODE-initialised Self Forcing student was replaced by SiD v2 before generation (it collapses to blur after the opening). GPU pinning was replaced by an architecture guard that regenerates a task's outputs when a resumed job lands on another architecture; paired arms of each preregistered contrast always share a task. Exploratory configurations (sink 1; correction on LongLive and CausVid) were added after freezing but before any data, from separate task lists, so their contrasts with the preregistered arms are not guaranteed to share an architecture. Prompt-only reference rollouts were renamed after generation; no analysis code changed.
- *Study 7* reuses the 24 scenes of study 6, including the 6 whose 120-s curves motivated it. Restricted to the 18 other scenes, the sink effect is +0.53 $[0.42, 0.63]$ (Self Forcing) and +0.18 $[0.13, 0.24]$ (CausVid).
- *Studies 10 and 11* were run on two non-preemptible 4-GPU jobs and A40-only array tasks instead of the preregistered all-queue arrays, because no large GPU was free on the shared queue; all their videos ran on A40 GPUs, so pairing is unaffected. The other studies ran as preregistered.

Withdrawn or revised claims. During the project we withdrew four claims after checks: that MUSIQ rewards collapsed videos (it is merely insensitive); that the sink stabilises the default (trend difference +0.5 [-2.4, 3.5]); that the model follows its context by 76% (true only for artificial shifts); and that early dynamics forecast the final brightness. The recursion's predicted Self Forcing plateau of 0.25–0.54 was missed (0.58 at 60 s).

B Drift metrics for prompt-only rollouts

For rollouts without a held opening, drift is measured against 10 (Self Forcing) or 5 (LongLive) fresh 5-s generations of the same prompt. D is the per-frame Mahalanobis distance of (Lab means, saturation, log sharpness) from the fresh frames' distribution, and K the mean cosine distance of a frame's DINOv2 feature to its 5 nearest fresh-frame features, normalised by the fresh clips' own value; both are averaged over seconds 29–31. Transitions kept is the median over held-out transition prompts of the corrected over the uncorrected first-to-last brightness change; values above 1 mean the correction amplified the change.

C Robustness

Linearity. For 12 of 14 configurations the persistence estimated from ±8 and from ±16 shifts differs by at most 0.09, with intervals including 0. SiD and the sink-1 configuration give near-zero slopes for small shifts (-0.10, -0.15) and positive ones for large shifts (0.18, 0.10); LongLive with a sink keeps a darkening better than a brightening (0.36 vs 0.04). The linear law is a first-order description.

The 60-s endpoint and the positional bursts. The preregistered 60-s window, 50–60 s, overlaps the second burst. Over 40–50 s, Self Forcing keeps 0.48 with a three-frame sink and 0.20 with a re-rotated one (difference -0.27 [-0.38, -0.16]); over the full period 35–60 s, 0.53 and 0.19. Sink depth is monotone in every window (40–50 s: no sink 0.08, one frame 0.23, three 0.48, six 0.63). Some curves are not monotone decays (GAN and SiD v2 lose part of the shift early and regain it), and Rolling Forcing is still declining at 60 s. In the 120-s subset of study 6 (6 scenes), Self Forcing with a sink keeps 0.54, 0.48 and 0.44 at 60, 90 and 118 s. No value we report is shown to be an asymptote; x_∞ in Eq. 1 denotes the long-run tendency, and α is always reported with its horizon.

The default and fresh rollouts. Across 10 configurations, the zero-drift level correlates $r = 0.93$ with where prompt-only rollouts end, but the slope is 1.58 and the mean absolute difference 4.9 L^* (largest for the GAN and SiD v2 checkpoints, whose zero-drift levels are extrapolated from slopes far from 0). Fresh rollouts give the direction and rough size of the default, not its exact value.

Persistence depends on the prompt. In the lighting experiment, the slope of the 31-s change on the opening differs between lighting prompts on Self Forcing (prompt × opening interaction, opening-clustered Wald test $p = 0.001$): persistence is 0.34 under sunny, 0.24 overcast, 0.17 dusk and 0.05 night prompts. On LongLive the interaction is weaker ($p = 0.053$). Dark defaults compress the range of brightness the model produces, which may explain part of this. Study 12 confirms the prompt dependence in four new scene types (Section 4.2).

Real and generated openings. On Self Forcing, real and generated openings fall on the same line ($p = 0.80$); on LongLive, generated openings end 4.3 L^* brighter than real ones of equal brightness ($p = 0.03$).

D The default and the forecast

How well does the law forecast? Taking α and the generic default from the relaxation study and the lighting defaults from the lighting experiment (different scenes and openings), $\Delta L \approx (1 - \alpha)(\mu - L_{\text{open}})$ predicts the 31-s brightness change of each opening in the calibrated-lighting study with $r = 0.82$ (Self Forcing) and 0.77 (LongLive), mean absolute error 3.8 L^*. Most of this correlation reflects the opening's brightness. The forecast of the *benefit* of calibration per opening is weaker ($r = 0.46$ and 0.58), and its mean is overpredicted (-4.5 predicted vs -3.2 and -2.8 observed L^*). The law is a first-order guide to a prompt choice, not a precise forecast.




Figure 6: Brightness change after 31 s against the opening's brightness (one dot per opening, generic or lighting prompt): (a) real and generated openings follow one line; (b) four lighting prompts set four defaults (Self Forcing); (c) two models: similar slopes, different defaults.

E Pitfalls for evaluating long-video models

1. **The GPU architecture changes the video.** With bf16, outputs are bit-identical within an architecture and differ across A40, A100/A800 and L40S/RTX 6000 Ada. Paired designs must pin or guard the architecture.
2. **Resumed jobs can silently break pairing.** Generators that skip existing outputs resume a preempted job wherever it lands.
3. **Image-quality scores miss drift.** MUSIQ, used by VBench for imaging quality, varies only between 66 and 69 across context strategies whose colour drift differs threefold.
4. **Natural variation is too small to estimate persistence.** Within a prompt, seeds start only about 2 L^* apart, so within-prompt slopes of end on start brightness have intervals of about ± 0.4; controlled shifts are needed.
5. **Change-on-baseline regressions mislead.** Regressing change on a baseline measured with error produces spurious regression to the mean [45, 46]. Held openings are measured almost without error, and the interventional design removes the issue.

F Context strategies (study 1)

A preregistered factorial study of 10 window and sink strategies on Self Forcing (40 prompts $\times$ 4 seeds, 31 s) found that a 3-frame sink cuts colour drift D by 7.56 $[6.81, 8.32]$ and DINOv2 drift K by 0.90; that window size matters only without a sink; and that re-rotating the sink's positions, which Self Forcing was not trained for, does not reduce D (-0.03 [-0.79, 0.72]) and increases K ($+0.36$). Darkening persists with a sink (last-2-s $z_L = -1.99$). D and K rise roughly linearly over 31 s under every strategy, without a visible plateau.

Table 3: All preregistered primary tests and their outcomes. Intervals are Wald intervals from the preregistered mixed models in studies 1, 2 and 13 and bootstrap intervals otherwise; p is Holm-adjusted within each study (no correction across studies). Study 3 LongLive rows are as executed; after regenerating four cross-architecture openings the conclusions are unchanged. Units: D, K drift metrics; $|\Delta L|$ in L*; α persistence. Arms: G generic prompt, M VLM caption of the opening, C calibrated lighting plus caption, ttc content-aware correction.

Study	Test	Model	Estimate [95% CI]	p_{Holm}	Outcome
1 Context	sink 3 vs none, D	SF	-7.56 [-8.32, -6.81]	< 0.001	supported
	sink 3 vs none, K	SF	-0.90 [-1.04, -0.76]	< 0.001	supported
	window $\times$ sink, D	SF	$+5.71$ [4.21, 7.22]	< 0.001	supported
	window $\times$ sink, K	SF	$+0.67$ [0.38, 0.95]	< 0.001	supported
2 Correction	ttc β=1, D	SF	-1.48 [-1.76, -1.19]	$< 10^{-23}$	supported
	ttc β=1.5, D	SF	-1.78 [-2.11, -1.45]	$< 10^{-24}$	supported
3 Caption	M $-$ G, $\|\Delta L\|$	SF	-1.21 [-3.09, 0.36]	0.58	not supported
	M+ttc $-$ M, $\|\Delta L\|$	SF	-1.00 [-1.89, -0.12]	0.14	not supported
	M $-$ G, $\|\Delta L\|$	LL	-0.19 [-2.00, 1.63]	1.0	not supported
	M+ttc $-$ M, $\|\Delta L\|$	LL	-0.36 [-1.48, 0.75]	1.0	not supported
4 Calibrated	C $-$ M, $\|\Delta L\|$	SF	-1.24 [-2.54, 0.12]	0.25	not supported
	C $-$ G, $\|\Delta L\|$	SF	-2.45 [-4.08, -1.04]	0.013	supported
	C $-$ M, $\|\Delta L\|$	LL	-1.15 [-2.59, 0.29]	0.26	not supported
	C $-$ G, $\|\Delta L\|$	LL	-1.34 [-3.19, 0.55]	0.26	not supported
5 Calibrated (LL scale)	C $-$ M, $\|\Delta L\|$	LL	-1.36 [-3.06, 0.32]	0.26	not supported
	C $-$ G, $\|\Delta L\|$	LL	-1.55 [-3.50, 0.39]	0.26	not supported
6 Relaxation	no sink $-$ sink, α_L (31 s)	SF	-0.06 [-0.17, 0.05]	0.34	not supported
	no sink $-$ sink, α_L (31 s)	LL	-0.17 [-0.28, -0.06]	0.013	supported
	ttc $-$ none, α_L (31 s)	SF	$+0.12$ [0.05, 0.20]	0.013	supported
	no sink $-$ sink, α_b (31 s)	SF	-0.26 [-0.34, -0.18]	< 0.001	supported
7 Sink at 60 s	sink $-$ no sink, α_L	SF	$+0.55$ [0.45, 0.65]	$< 10^{-9}$	supported
	sink $-$ no sink, α_L	CausVid	$+0.19$ [0.14, 0.24]	$< 10^{-6}$	supported
8 Overlap	5 $-$ 17 frames, α_L (20 s)	SkyReels	-0.24 [-0.40, -0.09]	0.014	supported
9 Content	class $-$ city prompt, class score (30 s)	SF	$+9.33$ [8.11, 10.51]	$< 10^{-9}$	supported
	sink $-$ no sink, κ (30 s)	LL	-0.02 [-0.10, 0.07]	0.72	not supported
	sink $-$ no sink, κ (60 s)	SF	$+0.48$ [0.39, 0.57]	$< 10^{-7}$	supported
10 Atlas	sink 6 $-$ sink 3, α_L (60 s)	SF	$+0.15$ [0.11, 0.20]	$< 10^{-6}$	supported
	sink 1 $-$ no sink, α_L (60 s)	SF	$+0.24$ [0.14, 0.34]	< 0.001	supported
	sink $-$ no sink, α_L (60 s)	LL	$+0.46$ [0.39, 0.53]	$< 10^{-10}$	supported
	re-rotated $-$ original sink, α_L (60 s)	SF	-0.44 [-0.54, -0.35]	$< 10^{-7}$	supported
11 FramePack	α (both routes, 20 s) > 0.5	FramePack-F1	0.68 [0.57, 0.79]	0.033	supported
	α (embedding only, 20 s) > 0	FramePack-F1	0.01 [-0.14, 0.17]	0.87	not supported
	both $-$ context only, α (20 s)	FramePack-F1	$+0.14$ [-0.05, 0.33]	0.38	not supported
12 Prompts	sink $-$ no sink, α_L (60 s), 4 domains	SF	$+0.53$ [0.45, 0.61]	$< 10^{-10}$	supported
	sink $-$ no sink, α_L (30 s), 4 domains	LL	$+0.19$ [0.11, 0.28]	0.005	supported
	α_L differs between domains (ANOVA)	SF	$F = 3.12$	0.049	supported
13 Deep sink	sink 6, D	SF	-1.30 [-1.68, -0.93]	$< 10^{-6}$	supported
	sink 9, D	SF	-1.93 [-2.31, -1.55]	$< 10^{-6}$	supported
14 Prompt pull	$w_p > 0$ at 15 s (replay)	SF	$+0.088$ [0.045, 0.149]	0.006	supported
15 World model	ctx-only shift fades (30 vs 5 s)	Matrix-Game	-0.24 [-0.35, -0.14]	0.024	supported
	emb-only shift persists, α (30 s)	Matrix-Game	$+0.43$ [0.13, 0.71]	0.075	not supported
	both $-$ ctx-only, α (30 s)	Matrix-Game	$+0.33$ [-0.07, 0.71]	0.18	not supported
17 FP content	content falls, class score (20 s)	FramePack-F1	-6.72 [-8.29, -5.20]	$< 10^{-5}$	supported
	κ (context only, 20 s) > 0	FramePack-F1	0.24 [0.12, 0.37]	0.001	supported
	κ (embedding only, 20 s) > 0	FramePack-F1	0.23 [0.16, 0.30]	$< 10^{-6}$	supported
	both $-$ context only, κ (20 s)	FramePack-F1	$+0.31$ [0.20, 0.41]	< 0.001	supported
18 MAGI-1	window: α (30 s) $-$ α (5 s)	MAGI-1	-0.52 [-0.70, -0.35]	< 0.001	supported
	full history $-$ window, α (30 s)	MAGI-1	$+0.30$ [0.17, 0.43]	0.002	supported
	α (full history, 30 s) > 0	MAGI-1	0.64 [0.45, 0.83]	< 0.001	supported

Table 4: Persistence over the same window, 15–20 s after the opening, for every model (exploratory; scene-bootstrap 95% CIs; Matrix-Game: scenes without a black second before 20 s).

Configuration	α	95% CI	scenes
SkyReels-V2-DF, 17 overlap frames	1.01	[0.89, 1.15]	12
FramePack-I2V, anti-drifting sampler	0.86	[0.79, 0.92]	12
SkyReels-V2-DF, 5 overlap frames	0.77	[0.64, 0.90]	12
Self Forcing DMD, sink 6	0.72	[0.65, 0.78]	24
FramePack-F1, both routes	0.68	[0.56, 0.78]	12
Rolling Forcing	0.64	[0.60, 0.67]	24
Self Forcing GAN	0.61	[0.54, 0.67]	24
Self Forcing 10-s	0.54	[0.46, 0.63]	24
FramePack-F1, context prefix only	0.53	[0.31, 0.76]	12
Self Forcing DMD, sink 3	0.49	[0.44, 0.53]	24
Self Forcing DMD, no sink	0.44	[0.38, 0.51]	24
Self Forcing DMD, sink 3 re-rotated	0.38	[0.28, 0.46]	24
Matrix-Game-2.0, both routes	0.37	[0.22, 0.52]	17
Self Forcing SiD	0.34	[0.24, 0.46]	24
LongLive, sink 3	0.33	[0.25, 0.40]	24
Self Forcing DMD, sink 1 re-rotated	0.33	[0.25, 0.41]	24
Self Forcing DMD, sink 1	0.29	[0.17, 0.41]	24
Self Forcing SiD v2	0.24	[0.11, 0.36]	24
Matrix-Game-2.0, embedding only	0.22	[0.06, 0.36]	17
CausVid, sink 3	0.21	[0.16, 0.26]	24
Matrix-Game-2.0, context only	0.10	[-0.02, 0.22]	17
LongLive, no sink	0.08	[0.04, 0.12]	24
CausVid, no sink	0.08	[0.04, 0.12]	24
FramePack-F1, embedding only	0.01	[-0.14, 0.17]	12

Table 5: Every global statistic relaxes toward a default (observational; 40 held openings, generic prompt, 31 s). Persistence = 1 + slope of the change on the opening value; r = correlation of the change with the opening value.

	Self Forcing		LongLive	
Statistic	persistence	r	persistence	r
L^*	0.31	−0.91	0.26	−0.81
a^*	0.38	−0.92	0.39	−0.90
b^*	0.22	−0.88	0.42	−0.80
saturation	0.54	−0.92	0.23	−0.95
log sharpness	0.37	−0.91	0.23	−0.94
L^* contrast	0.34	−0.82	0.37	−0.79