

GE23131-Programming Using C-2024

Quiz navigation



Show one page at a time

Finish review

Status Finished

Started Monday, 13 January 2025, 10:15 AM

Completed Monday, 13 January 2025, 10:31 AM

Duration 16 mins 24 secs

Question 1

Correct

Marked out of 1.00

Flag question

You are a bank account hacker. Initially you have 1 rupee in your account, and you want exactly N rupees in your account. You wrote two hacks, first hack can multiply the amount of money you own by 10, while the second can multiply it by 20. These hacks can be used any number of time. Can you achieve the desired amount N using these hacks.

Constraints:

$$1 \leq T \leq 100$$

$$1 \leq N \leq 10^{12}$$

Input

Input

The test case contains a single integer N.

Output

For each test case, print a single line containing the string "1" if you can make exactly N rupees or "0" otherwise.

SAMPLE INPUT

1

SAMPLE OUTPUT

1

SAMPLE INPUT

2

SAMPLE OUTPUT

0

Answer: (penalty regime: 0 %)

Reset answer

```
1 /*
2  * Complete the 'myFunc' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER n as parameter.
6  */
7 int myFunc(int n)
8 {
9     if(n==1)
10     {
11         return 1;
12     }
13     if(n%10==0)
14     {
15         if(myFunc(n/10))
16         {
17             return 1;
18         }
19     }
20     if(n%20==0)
21     {
22         if(myFunc(n/20))
23         {
24             return 1;
25         }
26     }
27 }
```



```
4 * The function is expected to return an INTEGER.  
5 * The function accepts INTEGER n as parameter.  
6 */  
7 int myFunc(int n)  
8 {  
9     if(n==1)  
10 {  
11     return 1;  
12 }  
13 if(n%10==0)  
14 {  
15     if(myFunc(n/10))  
16 {  
17         return 1;  
18     }  
19 }  
20 if(n%20==0)  
21 {  
22     if(myFunc(n/20))  
23 {  
24         return 1;  
25     }  
26 }  
27 return 0;  
28 }  
29
```

Test

Expected

Got

```

24 {
25     return 1;
26 }
27 }
28 return 0;
29 }
    
```

Test	Expected	Got	
✓ printf("%d", myfunc(1))	1	1	✓
✓ printf("%d", myfunc(2))	0	0	✓
✓ printf("%d", myfunc(10))	1	1	✓
✓ printf("%d", myfunc(25))	0	0	✓
✓ printf("%d", myfunc(200))	1	1	✓

Passed all tests! ✓

Question 2

Correct

Marked out of 1.00

Find the number of ways that a given integer, X , can be expressed as the sum of the N^{th} powers of unique, natural numbers.

Question 2

Correct

Marked out of
1.00

Flag question

Find the number of ways that a given integer, N , can be expressed as the sum of the N^{th} powers of unique, natural numbers.

For example, if $N = 13$ and $N = 2$, we have to find all combinations of unique squares adding up to 13. The only solution is $2^2 + 3^2$.

Function Description

Complete the powerSum function in the editor below. It should return an integer that represents the number of possible combinations.

powerSum has the following parameter(s):

X : the integer to sum to

N : the integer power to raise numbers to

Input Format

The first line contains an integer X .

The second line contains an integer N .

Constraints

Sample Input 0

10

2

Sample Output 0

1

Explanation 0

If $X = 10$ and $N = 2$, we need to find the number of ways that **10** can be represented as the sum of squares of unique numbers.

$$10 = 1^2 + 3^2$$

This is the only way in which **10** can be expressed as the sum of unique squares.

Sample Input 2

100

3

Sample Output 2

1

Explanation 2

100 can be expressed as the sum of the cubes of **1, 2, 3, 4**.

(1 + 8 + 27 + 64 = 100). There is no other way to express **100** as the sum of cubes.

Answer: (penalty regime: 0 %)

Reset answer

1. /
2. Complete the 'powersum' function below:
3. *
4. The function is expected to return an INTEGER.
5. The function accepts following parameters:
6. 1. INTEGER x

(1 + 8 + 27 + 64 = 100). There is no other way to express 100 as the sum of cubes.

Answer: (penalty regime: 0 %)

Reset answer

```
1. /*
2  * Complete the 'powerSum' function below.
3  *
4  * The function, is expected to return an INTEGER.
5  * The function accepts following parameters:
6  * 1. INTEGER x
7  * 2. INTEGER n
8  */
9
10 #include<stdio.h>
11 #include<math.h>
12
13 * int powerSum(int x,int m,int n){
14     if(x==0)
15         return 1;
16     if(x<0||pow(m,n)>x)
17         return 0;
18
19     return powerSum(x -pow(m,n),m+1,n)+powerSum(x, m+1 ,n);
20 }
```

```
7 * 2. INTEGER n
8 */
9
10 #include<stdio.h>
11 #include<math.h>
12
13 * int powerSum(int x,int m,int n){
14     if(x==0)
15         return 1;
16     if(x<0||pow(m,n)>x)
17         return 0;
18
19     return powerSum(x -pow(m,n),m+1,n)+powerSum(x, m+1 ,n);
20 }
```

Test	Expected	Got
✓ printf("%d", powerSum(10, 1, 2))	1	1 ✓

Passed all tests! ✓