

DATA STRUCTURE AND ALGORITHMS LAB

(Course Code: 22UPCSC1C10)

A programming laboratory record submitted to Periyar University, Salem

In partial fulfillment of the requirements for the degree of

MASTER OF COMPUTER APPLICATIONS

By

ELANCHEZHAIN M.

[Reg. No.: U22PG507CAP006]



DEPARTMENT OF COMPUTER SCIENCE

PERIYAR UNIVERSITY

(NAAC `A++` Grade with CGPA 3.61) – NIRF RANK 59 – ARIIA RANK 10

PERIYAR PALKALAI NAGAR,

SALEM – 636 011.

(APRIL - 2023)

CERTIFICATE

This is to certify that the Programming Laboratory entitled
“**DATA STRUCTURE AND ALGORITHMS LAB (22UPCSC1C10)**” is a
bonafide record work done by Mr. /Ms. _____

Register No: _____ as partial fulfillment of the
requirements for the degree of Master of Computer Applications, in the
Department of Computer Science, Periyar University, Salem, during the Academic
Year 2023-2024.

Staff In-charge

Head of the Department

Submitted for the practical examination held on.....

Internal Examiner

External Examiner

CONTENTS

S.NO	DATE	TITLE OF THE PROGRAM	PAGE NO	SIGNATURE
1.		Recursion concepts i) Linear recursion ii) Binary recursion		
2.		Stack ADT		
3.		Queue ADT		
4.		Doubly Linked List ADT		
5.		Heaps using Priority Queues		
6.		Merge sort		
7.		Quick sort		
8.		Binary Search Tree		
9.		Minimum Spanning Tree		
10.		Depth First Search Tree Traversal		

SOURCE CODE:

i) Linear recursion:

```
prime_numbers = []
First_number=int(input("Enter the starting number : "))
Last_number=int(input("Enter the last number : "))
for i in (range(First_number, Last_number)):
    for j in range(2,i-1):
        if i%j==0:
            break
    else:
        prime_numbers.append(i)
print(prime_numbers)

def my_prime_search_index(prime_numbers, current_prime):
    myprime = current_prime
    for i in list(range(len(prime_numbers))):
        if prime_numbers[i] == myprime:
            print("Found at : ", i)
            break
    else :
        print("It is not a prime number")

x=int(input("Enter the prime number to find index : "))
my_prime_search_index( prime_numbers, x )
```

OUTPUT (Linear recursion):

```
Enter the starting number : 5
Enter the last number : 29
[5, 7, 11, 13, 17, 19, 23]
Enter the prime number to find index : 11
Found at : 2
```

SOURCE CODE:

ii) Binary recursion:

```
def binary_search(arr, low, high, key):
    if low > high:
        return -1
    mid = (low + high) // 2
    if arr[mid] == key:
        return mid
    elif arr[mid] < key:
        return binary_search(arr, mid+1, high, key)
    else:
        return binary_search(arr, low, mid-1, key)

arr = list(map(int, input("Enter a sorted list of numbers: ").split()))
key = int(input("Enter the number to be searched: "))
result = binary_search(arr, 0, len(arr)-1, key)
if result == -1:
    print(key, "not found in the list.")
else:
    print(key, "found at index", result)
```

OUTPUT (Binary recursion):

```
Enter a sorted list of numbers: 8 1 3 4 7 6  
Enter the number to be searched: 3  
3 found at index 2
```

SOURCE CODE:

```
queue=[]
while True:
    print("Enter your choice:\n","1.Enqueue\n","2.Dequeue\n",
        "3.queue is empty or not \n","4.Display queue\n",
        "5.Exit\n")
    choice=int(input())
    if choice==1:
        item=input("enter the item to be enqueued:")
        queue.append(item)
    elif choice==2:
        if not queue:
            print("queue is empty")
        else:
            item=queue.pop(0)
            print("dequeue item:",item)
    elif choice==3:
        if not queue:
            print("queue is empty")
        else:
            print("queue is not empty")
    elif choice==4:
        if not queue:
            print("queue is not empty")
        else:
            print("queue=",queue)
```



```
elif choice==5:
```

```
    break
```

```
else:
```

```
    print("Invalid choice")
```

OUTPUT:

```
Enter your choice:
1.Enqueue
2.Dequeue
3.queue is empty or not
4.Display queue
5.Exit

1
enter the item to be enqueued:A
Enter your choice:
1.Enqueue
2.Dequeue
3.queue is empty or not
4.Display queue
5.Exit

1
enter the item to be enqueued:B
Enter your choice:
1.Enqueue
2.Dequeue
3.queue is empty or not
4.Display queue
5.Exit

1
enter the item to be enqueued:C
Enter your choice:
1.Enqueue
2.Dequeue
3.queue is empty or not
4.Display queue
5.Exit

3
queue is not empty
Enter your choice:
1.Enqueue
2.Dequeue
3.queue is empty or not
4.Display queue
5.Exit

2
dequeue item: A
Enter your choice:
1.Enqueue
2.Dequeue
3.queue is empty or not
4.Display queue
5.Exit

4
queue= ['B', 'C']
Enter your choice:
1.Enqueue
2.Dequeue
3.queue is empty or not
4.Display queue
5.Exit

5
```

SOURCE CODE:

```
class Node:

    def __init__(self, data):
        self.data = data
        self.next = None
        self.prev = None


class DoublyLinkedList:

    def __init__(self):
        self.head = None

    def append(self, data):
        new_node = Node(data)
        if self.head is None:
            self.head = new_node
        else:
            curr_node = self.head
            while curr_node.next:
                curr_node = curr_node.next
            curr_node.next = new_node
            new_node.prev = curr_node

    def prepend(self, data):
        new_node = Node(data)
        if self.head is None:
            self.head = new_node
```

```

else:
    new_node.next = self.head
    self.head.prev = new_node
    self.head = new_node

def delete(self, key):
    if self.head is None:
        return

    if self.head.data == key:
        self.head = self.head.next
        if self.head:
            self.head.prev = None
    else:
        curr_node = self.head
        while curr_node.next:
            if curr_node.next.data == key:
                curr_node.next = curr_node.next.next
                if curr_node.next:
                    curr_node.next.prev = curr_node
                break
            curr_node = curr_node.next

def print_list(self):
    curr_node = self.head
    while curr_node:
        print(curr_node.data)

```

```
curr_node = curr_node.next
```

```
doubly_linked_list = DoublyLinkedList()
```

```
while True:
```

```
    print("1. Append to list")
```

```
    print("2. Prepend to list")
```

```
    print("3. Delete from list")
```

```
    print("4. Print list")
```

```
    print("5. Exit")
```

```
    user_choice = input("Enter your choice: ")
```

```
    if user_choice == "1":
```

```
        data = input("Enter the element to append: ")
```

```
        doubly_linked_list.append(data)
```

```
    elif user_choice == "2":
```

```
        data = input("Enter the element to prepend: ")
```

```
        doubly_linked_list.prepend(data)
```

```
    elif user_choice == "3":
```

```
        data = input("Enter the element to delete: ")
```

```
        doubly_linked_list.delete(data)
```

```
    elif user_choice == "4":
```

```
        doubly_linked_list.print_list()
```

```
    elif user_choice == "5":
```

```
        break
```

```
    else:
```

```
        print("Invalid choice. Please try again.")
```

OUTPUT:

```
1. Append to list
2. Prepend to list
3. Delete from list
4. Print list
5. Exit
Enter your choice: 1
Enter the element to append: Dhanush
1. Append to list
2. Prepend to list
3. Delete from list
4. Print list
5. Exit
Enter your choice: 1
Enter the element to append: Vijay
1. Append to list
2. Prepend to list
3. Delete from list
4. Print list
5. Exit
Enter your choice: 2
Enter the element to prepend: Ajith
1. Append to list
2. Prepend to list
3. Delete from list
4. Print list
5. Exit
Enter your choice: 4
Ajith
Dhanush
Vijay
1. Append to list
2. Prepend to list
3. Delete from list
4. Print list
5. Exit
Enter your choice: 3
Enter the element to delete: Dhanush
1. Append to list
2. Prepend to list
3. Delete from list
4. Print list
5. Exit
Enter your choice: 4
Ajith
Vijay
1. Append to list
2. Prepend to list
3. Delete from list
4. Print list
5. Exit
Enter your choice: 5
```

SOURCE CODE:

```
class Stack:

    def __init__(self):
        self.stack = []

    def push(self, element):
        self.stack.append(element)

    def pop(self):
        if not self.is_empty():
            last_element = self.stack[-1]
            del self.stack[-1]
            return last_element
        else:
            return "Stack Already Empty"

    def is_empty(self):
        return self.stack == []

    def print_stack(self):
        print(self.stack)

if __name__ == "__main__":
    s = Stack()
    while True:
        var = int(input("1. PUSH\n2. POP\n3. IS EMPTY\n4. PRINT\n5. EXIT\n"))
```

```
if var == 1:
    item = input("Enter element to push in stack: ")
    s.push(item)
elif var == 2:
    print(s.pop())
elif var == 3:
    print(s.is_empty())
elif var == 4:
    s.print_stack()
elif var == 5:
    break
```


OUTPUT:

```
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
1
Enter element to push in stack: Deva
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
1
Enter element to push in stack: Meera
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
1
Enter element to push in stack: Dhas
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
1
Enter element to push in stack: Sree
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
4
['Deva', 'Meera', 'Dhas', 'Sree']
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
3
False
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
2
Sree
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
4
['Deva', 'Meera', 'Dhas']
1. PUSH
2. POP
3. IS EMPTY
4. PRINT STACK
5. EXIT
5
```

SOURCE CODE:

```
import heapq

class MaxHeap:

    def __init__(self):

        self._heap = []

    def insert(self, item):

        heapq.heappush(self._heap, -item)

    def delete(self):

        if len(self._heap) > 0:

            return -heapq.heappop(self._heap)

        else:

            raise Exception("Heap is empty")

    def peek(self):

        if len(self._heap) > 0:

            return -self._heap[0]

        else:

            raise Exception("Heap is empty")

    def size(self):

        return len(self._heap)
```

```
heap = MaxHeap()
```

```
input_list = input("Enter integers to insert into the heap, separated by  
spaces: ").split()
```

```
for item in input_list:
```

```
    heap.insert(int(item))
```

```
print("The highest priority element in the heap is:", heap.peak())
```

```
print("The deleted element from the heap is:", heap.delete())
```

```
print("The new highest priority element in the heap is:", heap.peak())
```

OUTPUT:

```
Enter integers to insert into the heap, separated by spaces: 5 3 4 7 8 2  
The highest priority element in the heap is: 8  
The deleted element from the heap is: 8  
The new highest priority element in the heap is: 7
```

SOURCE CODE:

```
def merge_sort(arr):  
    if len(arr)<=1:  
        return arr  
    mid=len(arr)//2  
    left=arr[:mid]  
    right=arr[mid:]  
  
    left=merge_sort(left)  
    right=merge_sort(right)  
    return merge(left,right)  
  
def merge(left,right):  
    result=[]  
    i,j=0,0  
    while i<len(left) and j<len(right):  
        if left[i]<right[j]:  
            result.append(left[i])  
            i+=1  
        else:  
            result.append(right[j])  
            j+=1  
  
    result+=left[i:]  
    result+=right[j:]  
    return result
```

```
arr=input("Enter the list of numbers separated by space:").split()
arr=[int(num) for num in arr]
print("Input Array:",arr)
sorted_arr=merge_sort(arr)
print("Sorted Array:",sorted_arr)
```

OUTPUT:

```
Enter the list of numbers separated by space:23 45 12 56 34 1
```

```
Input Array: [23, 45, 12, 56, 34, 1]
```

```
Sorted Array: [1, 12, 23, 34, 45, 56]
```

SOURCE CODE:

```
def quick_sort(arr):  
    if len(arr)<=1:  
        return arr  
    pivot=arr[len(arr)//2]  
    left=[x for x in arr if x<pivot]  
    middle=[x for x in arr if x==pivot]  
    right=[x for x in arr if x>pivot]  
    return quick_sort(left)+middle+quick_sort(right)  
  
arr=[]  
n=int(input("Enter number of elements: "))  
for i in range(n):  
    element=int(input("Enter element { }: ".format(i+1)))  
    arr.append(element)  
  
print("Unsorted array: ",arr)  
sorted_arr=quick_sort(arr)  
print("Sorted array: ",sorted_arr)
```


OUTPUT:

```
Enter number of elements: 5
Enter element 1: 23
Enter element 2: 76
Enter element 3: 48
Enter element 4: 56
Enter element 5: 1
Unsorted array:  [23, 76, 48, 56, 1]
Sorted array:    [1, 23, 48, 56, 76]
```

SOURCE CODE:

```
class DisjointSet:
    def __init__(self, size):
        self.parent = list(range(size))
        self.rank = [0] * size

    def find(self, i):
        if self.parent[i] != i:
            self.parent[i] = self.find(self.parent[i])
        return self.parent[i]

    def union(self, i, j):
        root_i = self.find(i)
        root_j = self.find(j)
        if root_i != root_j:
            if self.rank[root_i] < self.rank[root_j]:
                self.parent[root_i] = root_j
            elif self.rank[root_i] > self.rank[root_j]:
                self.parent[root_j] = root_i
            else:
                self.parent[root_j] = root_i
                self.rank[root_i] += 1

class KruskalMST:
    def __init__(self, edges, num_vertices):
        self.edges = edges
```

```
self.num_vertices = num_vertices

def find_mst(self):
    result = []
    disjoint_set = DisjointSet(self.num_vertices)
    for u, v, weight in sorted(self.edges, key=lambda e: e[2]):
        if disjoint_set.find(u) != disjoint_set.find(v):
            result.append((u, v, weight))
            disjoint_set.union(u, v)
    return result

if __name__ == '__main__':
    edges = [(0, 1, 8), (0, 2, 5), (1, 2, 9), (1, 3, 11), (2, 3, 15), (2, 4, 10),
              (3, 4, 7)]
    kruskal = KruskalMST(edges, num_vertices=5)
    mst = kruskal.find_mst()
    for u, v, weight in mst:
        print(f"Edge: {u}-{v} weight: {weight}")
```

OUTPUT:

```
Edge: 0-2 weight: 5  
Edge: 3-4 weight: 7  
Edge: 0-1 weight: 8  
Edge: 2-4 weight: 10
```

SOURCE CODE:

```
class Node:
    def __init__(self,value):
        self.value=value
        self.left=None
        self.right=None

def depth_first_search(root):
    if root is None:
        return
    print(root.value)
    depth_first_search(root.left)
    depth_first_search(root.right)

root=Node(50)
root.left=Node(10)
root.right=Node(25)
root.left.left=Node(18)
root.left.right=Node(36)
root.right.left=Node(22)
root.right.right=Node(46)

depth_first_search(root)
```

OUTPUT:

50

10

18

36

25

22

46

SOURCE CODE:

```
class Node:

    def __init__(self, val=None):

        self.value = val

        self.left_child = None

        self.right_child = None


class BST:

    def __init__(self):

        self.root = None


    def insert(self, val):

        if not self.root:

            self.root = Node(val)

        else:

            self._insert(val, self.root)


    def _insert(self, val, current_node):

        if val < current_node.value:

            if not current_node.left_child:

                current_node.left_child = Node(val)

            else:

                self._insert(val, current_node.left_child)

        elif val > current_node.value:

            if not current_node.right_child:

                current_node.right_child = Node(val)
```

```
        else:
            self._insert(val, current_node.right_child)
    else:
        print("Value already exists in the tree.")

def find(self, val):
    if self.root:
        res = self._find(val, self.root)
        if res:
            return True
        else:
            return False
    else:
        return False

def _find(self, val, current_node):
    if val == current_node.value:
        return True
    elif val < current_node.value and current_node.left_child:
        return self._find(val, current_node.left_child)
    elif val > current_node.value and current_node.right_child:
        return self._find(val, current_node.right_child)
    return False
```



```
def inorder_traversal(self, node):  
    if node is not None:  
        self.inorder_traversal(node.left_child)  
        print(node.value, end=" ")  
        self.inorder_traversal(node.right_child)
```

```
def preorder_traversal(self, node):  
    if node is not None:  
        print(node.value, end=" ")  
        self.preorder_traversal(node.left_child)  
        self.preorder_traversal(node.right_child)
```

```
def postorder_traversal(self, node):  
    if node is not None:  
        self.postorder_traversal(node.left_child)  
        self.postorder_traversal(node.right_child)  
        print(node.value, end=" ")
```

```
if __name__ == "__main__":  
    bst = BST()  
    while True:  
        print("\nBinary Search Tree Operations:")  
        print("1. Insert a node")  
        print("2. Search for a node")  
        print("3. Traverse the tree (inorder)")  
        print("4. Traverse the tree (preorder)")
```

```
print("5. Traverse the tree (postorder)")
print("6. Exit")

choice = int(input("\nEnter your choice: "))
if choice == 1:
    val = int(input("Enter value to be inserted: "))
    bst.insert(val)
elif choice == 2:
    val = int(input("Enter value to be searched: "))
    if bst.find(val):
        print("Value found in the tree.")
    else:
        print("Value not found in the tree.")
elif choice == 3:
    print("\nInorder Traversal: ", end="")
    bst.inorder_traversal(bst.root)
elif choice == 4:
    print("\nPreorder Traversal: ", end="")
    bst.preorder_traversal(bst.root)
elif choice == 5:
    print("\nPostorder Traversal: ", end="")
    bst.postorder_traversal(bst.root)
elif choice == 6:
    break
else:
    print("Invalid choice. Try again.")
```

OUTPUT:

```
Binary Search Tree Operations:
1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit
```

```
Enter your choice: 1
Enter value to be inserted: 50
```

```
Binary Search Tree Operations:
1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit
```

```
Enter your choice: 1
Enter value to be inserted: 30
```

```
Binary Search Tree Operations:
1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit
```

```
Enter your choice: 1
Enter value to be inserted: 70
```

```
Binary Search Tree Operations:
1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit
```

```
Enter your choice: 2
Enter value to be searched: 30
Value found in the tree.
```

Binary Search Tree Operations:

1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit

Enter your choice: 3

Inorder Traversal: 30 50 70

Binary Search Tree Operations:

1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit

Enter your choice: 4

Preorder Traversal: 50 30 70

Binary Search Tree Operations:

1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit

Enter your choice: 5

Postorder Traversal: 30 70 50

Binary Search Tree Operations:

1. Insert a node
2. Search for a node
3. Traverse the tree (inorder)
4. Traverse the tree (preorder)
5. Traverse the tree (postorder)
6. Exit

Enter your choice: 6