

<b>Ex.No:5</b>	Write a C program to simulate UNIX commands like cp, ls, grep
----------------	---

**AIM:**

To write C programs to simulate UNIX commands like cp, ls, grep.

**Program for simulation of cp and ls unix commands ALGORITHM:**

STEP1: Start the program

STEP2: Declare the variables

STEP3: Create two files, Open the file in write mode and store data into the files

STEP4: Enter name of file to copy

STEP5: Enter name of target file and copy the content to target file

STEP6: Enter the directory name and list the contents

STEP7: Close the file

***Program for CP command:***

```
#include<stdio.h>
#include<stdlib.h>
int main()
{
FILE *file1,*file2;
char filename[100],c;
printf("enter the filename for reading");
scanf("%s",filename);
file1=fopen(filename,"r");
if(file1==NULL)
{
printf("cannot open the file %s \n",filename);
exit(0);
}
printf("Enter the filename for writing");
scanf("%s",filename);
file2=fopen(filename,"w");
if(file2==NULL)
{
printf("cannot open the file %s \n",filename);
exit(0);
}
c=fgetc(file1);
while (c != EOF)
{
fputc(c,file2);
c=fgetc(file1);
}
```

```

printf("The contents are copied to file %s",filename);
fclose(file1);
fclose(file2);
return 0;
}

```

### **Program for ls COMMAND:**

```

#include<stdio.h>
#include<dirent.h>
#include<stdlib.h>
int main()
{
char dirname[20];
DIR*p;
struct dirent *d;
printf("enter the directory name");
scanf("%s",dirname);
p=opendir(dirname);
    if(p==NULL)
    {
        printf("cannot find the directory");
        exit(-1);
    }
    while(d=readdir(p))
    {
        printf("%s\n",d->d_name);
    }
}

```

### **PROGRAM FOR SIMULATION OF GREP UNIX COMMANDS ALGORITHM:**

STEP1: Start the program

STEP2: Declare the variables filename, search, temp

STEP3: Enter the file name and pattern to be checked.

STEP4: Open the file in read mode.

STEP5: Assign the file in temp array and iterate to end of the file and compare for pattern . If it is found print the content in temp file.

STEP6: Stop the program

### **PROGRAM:**

```

#include<stdio.h>
#include<string.h>
#include<stdlib.h>
void main()

```

```

{
FILE *file1;
char filename[100],search[10],temp[10];
printf("ENTER THE FILENAME ");
scanf("%s",filename);
printf("Enter the element to be searched");
scanf("%s",search);
file1=fopen(filename,"r");
while (!feof(file1))
    {
        fgets(temp, sizeof(file1), file1);
        if(strstr(temp,search))
            {
                printf("%s",temp);
            }
    }
fclose(file1);
}

```

Result: Thus C program to simulate UNIX commands like cp, ls, grep have been executed successfully.

