

תרחישי שימוש – Use Cases

System + System Administrator use cases:

Use case – 1: System initialization

1. **Actors:** System.
2. **Pre-conditions:** None
3. **Post-Conditions:** The system is up and running, and users can log in and use it.
4. **Input parameters:** System manager user information, different services information (how to connect to Visa, to Suppliers etc.)
5. **Actions:**
 - a) The system asks for user information for the system manager.
 - b) Authentication – The system checks if the user is subscribed, and if so, sets him as the system manager.
 - c) The system connects to each service provider and checks if the service is up and ready to accept messages.
 - d) If Everything is working the system moves to the main screen, and ready to handle different users and stores.
6. **Alternatives/Extensions:**
 - a) If the user information are not correct, or the user given is not subscribed, the system asks again for details and not moving to the next screen.
 - b) If one of the services fail to receive messages, the system will send notification to the system manager and will halt on the “waiting for the services screen”.

7. Acceptance tests – scenarios:

Scenario Description	Parameters	Expected Result	Scenario
The system manager try to login with a wrong user information.	Invalid user information, valid services information	Failed authentication, a matching error message will be returned.	Bad
The system manager try to connect to the wrong services (payment, suppliers).	Valid user information, Invalid services information	Failed services connection, a matching error message will be returned.	Bad
The system manager was able to connect to the system and initialize the different services.	Valid user information, valid services information	Success, the system will initialize properly.	Good

Use case – 2: Change services

1. **Actors:** System.

2. **Pre-conditions:** The new service exists and is ready to receive messages.

3. **Post-Conditions:** The system can use the new service as usual.

4. **Input parameters:** Information about new service (id, type of service etc.)

5. **Actions:**

- a) The system connects to the new service and checks if it is ready.
- b) When the new service is ready the system removes the old service.
- c) The system sets the new service as the default service for the correct type (Pay, supply etc.)

6. **Alternatives/Extensions:**

- a) If the new service fails to start or the information is incorrect, the system will not let the users to remove the old service.

7. **Acceptance tests – scenarios:**

Scenario Description	Parameters	Expected Result	Scenario
The system try to use a invalid service	Invaild information about the new service	Failed authentication, a matching error message will be returned.	Bad
The system try to change the specific service while the service it handles other transcations.	Valid information	Failed services update, a matching error message will be returned.	Bad
The sysem received correct data and will update the system.	Valid information	Success, the service will update properly.	Good

Use case – 3: Using the services (Pay, Supply)

1. **Actors:** System, Users.

2. **Pre-conditions:** The information that should be sent to the service was collected or created correctly.

3. **Post-Conditions:** The service accepted the request and did what it had to do successfully.

4. **Input parameters:** The parameters that should be sent to the service. (User information, card info, user address etc.)

5. **Actions:**

- a) The system validates that all the parameters are correct.
- b) The system calls the service using the correct API and passes all the parameters.
- c) If the received answer is positive, show a message to the user that the action was done successfully.

6. **Alternatives/Extensions:**

- a) If some of the arguments that were received from the user are incorrect, error message will be shown to the user, and he will be asked to fill this parameter again.
- b) If the service return a negative answer, handle it by the reason. (Wrong information – Correct it. Service too busy – Make the request later, etc.)

7. **Acceptance tests – scenarios:**

Scenario Description	Parameters	Expected Result	Scenario
The service try to process an incorrect transaction.	Invailld transaction details	Failed authentication, a matching error message will be returned.	Bad
The service try to charge an invalid card details.	Valid transaction details, Invalid card info	Failed Charge failed, a matching error message will be returned.	Bad
The service was unable to process the payment.	Valid transaction details, valid card info	Failed Charge failed, a matching error message will be returned.	Bad
The payment service was able to charge the card succesfully.	Valid transaction details, Valid card info	Success, the payment was successfully received.	Good

Scenario Description	Parameters	Expected Result	Scenario
The service try to process an incorrect supply transaction.	Invaild transaction details	Failed authentication, a matching error message will be returned.	Bad
The service try to supply the wrong packages.	Valid transaction details, Invalid package information	Failed supply failed, a matching error message will be returned.	Bad
The service was unable to send a delivery confirmation receipt.	Valid transaction details, valid package information	Failed supply failed, a matching error message will be returned.	Bad
The supply service was able to process the pacakges info and to send a confirmation receipt.	Valid transaction details, Valid package information	Success, the supply was successfully received.	Good

Use case – 4: Pop up messages

1. **Actors:** System.

2. **Pre-conditions:** A subscribed user exists.

3. **Post-Conditions:** The user receives a pop-up message in real time or when he enters the system.

4. **Input parameters:** User phone number, the message

5. **Actions:**

- a) Check what is the type of action, and if the system has to send the message to his phone number or save it and show it to the user when he enters the system.
- b) According to the result of the check, send notification if needed, and save it in the correct database.
- c) When the user enters the system, check if there are any new messages that need to be shown to him.

6. **Alternatives/Extensions:**

- a) If the system is unable to send pop-up message, ask from the user for the correct phone number or permissions.

7. **Acceptance tests – scenarios:**

Scenario Description	Parameters	Expected Result	Scenario
The system try to send a message to the wrong user.	Invaild user information	Failed authentication, a matching error message will be returned.	Bad
The system try to send a wrong message	Valid user information, Invalid message	Failed to pop up messages, a matching error message will be returned.	Bad
The system received corrcet data and will send it to the given user.	Valid user information, Valid message	Success, the system will send the message to the user properly.	Good

Use case – 5: Market history

1. **Actors:** User who are system manager.

2. **Pre-conditions:** Market working and there are stores and buyers.

3. **Post-Conditions:** The System manager has all the information about the stores and user's activities.

4. **Input parameters:** Store information, or the buyer information. (id, name, etc.)

5. **Actions:**

a) The system manager writes as the input the ID of the store or buyer that he wants to check the history of.

b) If the ID is correct, the system accesses the database and assembles a new file which contains all the information about the correct object. (Store, User...)

c) The system returns the file with the relevant data to the store manager.

6. **Alternatives/Extensions:**

a) If the information is incorrect, the system asks for the correct information again.

b) If the system fails to assemble the file, it shows proper error message.

7. **Acceptance tests – scenarios:**

Scenario Description	Parameters	Expected Result	Scenario
The manager try to see the purchases history of an invalid user.	Invalid information	Failed authentication, a matching error message will be returned.	Bad
The system manager requests to see the purchases history and at the same time another purchase is made in the same account, so he will not receive an updated history.	Valid information	Failed to receive the updated history, a matching error message will be returned.	Bad
The system received correct information and the manager is able to see the purchases history.	Valid information	Success, the manager will see the history that he wanted.	Good

Store Visitor use cases (subscriber, guest):

Use case – add to cart

1. **Actors:** User
2. **Pre-conditions:**
 1. none
3. **Post-conditions:**
 - The product was added to the user cart
4. **Input Parameters:**
 1. User token
 2. Search string params (key words)
 3. Product filters string params (price range, ratings, category, name)
 4. Store filters string params (ratings, name, id)
 5. quantity
5. **Main Scenario:**
 1. The user initiates add to cart process with his token and search params
 2. The system authenticates the user
 3. The product is being added to the cart
6. **Alternatives:**
 1. If the user is not authenticated, a matching error message will be returned and the product wont be added
 2. If the product search params are incorrect, a matching error message will be returned and the product wont be added

Test 1: Successful addition to cart

- **Parameters:**
 - Valid token
 - Valid Search string params
 - Valid Product filters string params
 - Valid Store filters string params
 - Valid Quantity
- **Expected Result:**
 - The product is successfully added to the user's cart.

Test 2: User authentication failure

- **Parameters:**
 - Invalid token
 - Valid Search string params
 - Valid Product filters string params
 - Valid Store filters string params
 - Valid Quantity
- **Expected Result:**
 - Error message
 - The product is not added to the cart.

Test 3: Incorrect product search parameters

- **Parameters:**
 - Valid token
 - Invalid Search string params:
 - Valid Product filters string params
 - Valid Store filters string params
 - Valid Quantity
- **Expected Result:**
 - Error message
 - The product is not added to the cart.

Use case - 2: purchase process

1) **Actors:** User

2) **Pre-conditions:**

- a. User already added at least 1 product to cart
- b. Order is valid (each product quantity is in stock)

3) **Post-conditions:**

a. **Success:**

- i. All purchased items are deducted from store's inventory.
- ii. Payment from the customer to the shop's owner is successfully processed.

b. **Failure:**

- i. System reverts to pre-purchase state (atomic action).

4) **Input Parameters:**

- a. User payment parameters (card number, card date, card cvv)
- b. Address of the user

5) **Actions:**

- a. User initiates purchase order provides payment information and address to complete the purchase.
- b. The system authenticates the user
- c. The system checks the availability of the products in the cart
- d. The system charges the user with his payment information
- e. The system ordering a delivery for the items in the cart to the given address.

6) **Alternatives:**

- a. If the user is not authenticated, a matching error message will be returned, the purchase will not be completed, The system reverts to the pre-purchase state, the user wont be charged
- b.** if there is an unavailable product in the cart, a matching error message will be returned, the purchase will not be completed, The system reverts to the pre-purchase state, the user wont be charged
- c.** if the payment fails, a matching error message will be returned, the purchase will not be completed, The system reverts to the pre-purchase state, the user wont be charged

- d. if the delivery fails, a matching error message will be returned, the purchase will not be completed, The system reverts to the pre-purchase state, the user wont be charged

Test 1: Successful purchase

- **Parameters:**
 - User token: valid token
 - User payment parameters: valid user payment information
 - Address of the user: valid address
- **Expected Result:**
 - Products are deducted from inventory.
 - Payment is processed successfully.
 - Delivery is ordered to the given address.

User authentication failure

- **Parameters:**
 - User token: invalid token
 - User payment parameters: valid user payment information
 - Address of the user: valid address
- **Expected Result:**
 - Error message
 - The purchase is not completed.
 - The system reverts to the pre-purchase state.

Unavailable product in cart

- **Parameters:**
 - User token: valid token
 - User payment parameters: valid user payment information
 - Address of the user: valid address
 - Cart: includes unavailable product
- **Expected Result:**
 - Error message
 - The purchase is not completed.

- The system reverts to the pre-purchase state.

Payment failure

- **Parameters:**
 - User token: valid token
 - User payment parameters: invalid payment information
 - Address of the user: valid address
- **Expected Result:**
 - Error message
 - The purchase is not completed.
 - The system reverts to the pre-purchase state.

Delivery failure

- **Parameters:**
 - User token: valid token
 - User payment parameters: valid user payment information
 - Address of the user: invalid address
- **Expected Result:**
 - Error message
 - The purchase is not completed.
 - The system reverts to the pre-purchase state.

Use-Case 3: Subscriber shop opening process

1. **Actors:** Subscriber (Founder)

2. **Pre-conditions:**

- Subscriber is logged in to the system.

3. **Post-conditions:**

- New store created.
- Subscriber assigned as founder.

4. **Input Parameters:**

- User token
- Store name
- contact information: email, phoneNumber, address
- store description
- Inventory

5. **Actions:**

- a) Subscriber initiates the process to open their store.
- b) Subscriber provides store name, description, contact information.
- c) Program creates a new store, and turn Subscriber into a Founder
- d) Subscriber completes the shop opening process and now owns a shop

6. **Scenarios:**

Scenario Description	Parameters	Expected Result	Scenario
Outdated Token	User credentials	an error message pops stating "User's credentials unavailable"	Alternative
Shop name is taken	Store name	an error message pops stating "shop name is already taken"	Alternative
User opens a store	Store name, contact information, store description	Success, a shop was created for the given user	Happy

Use Case: Login

Actors:

- User

Preconditions:

- The user is registered in the system and has valid login credentials.

Postconditions:

1. The user is authenticated and logged in as a Visitor-Subscriber.
2. A user session is created, and the user can access subscriber-specific features.

Input Parameters:

- Username
- Password

Main Scenario:

1. User tries to login with username and password
2. The system verifies the provided credentials against the registered user database.
3. The user gets a token and logs in.

Extensions/Alternatives:

1. If the credentials are invalid, the system displays an error message indicating the failure.
2. If the account is suspended, a matching error

Test 1: Successful login

- **Preconditions:** The user is registered in the system and has valid login credentials.
- **Steps:**
 1. User enters the username and password.
 2. The system verifies the credentials against the registered user database.
 3. The system generates a token and logs in the user.
- **Expected Result:**
 - User is authenticated.
 - User is logged in.

Test 2: Unsuccessful login due to invalid credentials

- **Preconditions:** The user is registered in the system but provides invalid login credentials.
- **Steps:**
 1. User enters the username and incorrect password.
 2. The system verifies the credentials against the registered user database.
- **Expected Result:**
 - Error message
 - The user is not logged in

Test 3: Unsuccessful login due to account suspension

- **Preconditions:** The user's account is suspended.
- **Steps:**
 1. User enters the username and password.
 2. The system verifies the credentials against the registered user database.
- **Expected Result:**

- Error message
- The user is not logged in

Store Owner use cases:

Use case: 4.1 – Inventory management (Add product, Remove product, Update product)

1. **Actor:** Store Owner
2. **Pre-condition:** The store owner exists in the system and is logged in to the system.
3. **Post-conditions:** In the case of success, the product is added/removed/updated according to the given parameters.
4. **Input parameters:** StoreID, Product information (name, price, ...)
5. **Actions:**
 - 1) Store Owner attempts to add/remove/update a product in a specific shop.
 - 2) Authentication – the system checks that the action was requested by an actual store owner of the needed store.
 - 3) Inventory availability – the system checks that the product is available to the requested action in the inventory. (exists if the action is remove/update, not exists if the action is add)
 - 4) Validity – the system checks that the given parameters are valid (positive, non-empty) and follow the standard rules of the store.
 - 5) The system updates the item in the inventory.
 - 6) The system returns a matching success response to the user.
6. **Alternatives/Extensions:**
 - 2) If the authentication failed, a matching error message will be returned and the action will fail.
 - 3) If the item is not available in the inventory, a matching error message will be returned and the action will fail.
 - 4) If the given parameters are invalid (for example zero or empty) or do not follow the standard rules of the store, a matching error message will be returned and the action will fail.

7. Acceptance tests – scenarios:

Scenario Description	Parameters	Expected Result	Scenario
The requesting store owner does not have the right permissions (is not a store owner) in the requested store	Invalid StoreID, valid product information	Failed authentication, a matching error message will be returned.	Bad
The store owner is requesting to remove a non-existent product	Valid StoreID, valid product information	Failed inventory availability, a matching error message will be returned.	Bad
The store owner is requesting to add a new product with invalid product information (quantity -1)	Valid StoreID, invalid product information	Failed validity check, a matching error message will be returned.	Bad
The store owner is requesting to update an existing product, with valid product information	Valid StoreID, valid product information	Success, the product will be updated in the inventory.	Good

Use case: 4.2 – Update store policies (Update purchase policy, Update discount policy)

1. **Actor:** Store Owner
2. **Pre-condition:** The store owner exists in the system and is logged in to the system.
3. **Post-conditions:** In the case of success, the store's purchase/discount policy is updated according to the given parameters.
4. **Input parameters:** StoreID, Purchase/Discount policy information.
5. **Actions:**
 - 1) Store Owner attempts to update the purchase/discount policy of a specific shop.
 - 2) Authentication – the system checks that the action was requested by an actual store owner of the needed store.
 - 3) Validity – the system checks that the given parameters are valid (positive, non-empty) and follow the standard rules of the store.
 - 4) The system updates the purchase/discount policy of the store.
 - 5) The system returns a matching success response to the user.
6. **Alternatives/Extensions:**
 - 2) If the authentication failed, a matching error message will be returned and the action will fail.
 - 3) If the given parameters are invalid (for example zero or empty) or do not follow the standard rules of the store, a matching error message will be returned and the action will fail.

7. Acceptance tests – scenarios:

Scenario Description	Parameters	Expected Result	Scenario
The requesting store owner does not have the right permissions (is not a store owner) in the requested store	Invalid StoreID, valid discount policy information	Failed authentication, a matching error message will be returned.	Bad
The store owner is requesting to update with invalid discount policy information (quantity -1, discount -300%)	Valid StoreID, invalid discount policy information	Failed validity check, a matching error message will be returned.	Bad
The store owner is requesting to update the discount policy of a store, with valid discount policy information	Valid StoreID, valid discount policy information	Success, the discount policy of the store will be updated.	Good

Use case: 4.3 – Store Owner Appointment (Composite: Appointment Offer, Appointment Approval/Rejection)

Use case: 4.3.1 – Store Owner Appointment Offer

1. **Actor:** Store Owner, Subscriber
2. **Pre-condition:** The store owner exists in the system and is logged in to the system.
3. **Post-conditions:** In the case of success, the selected subscriber will receive an appointment offer and will need to accept/reject the offer in the next part of the use case.
4. **Input parameters:** StoreID, username of the subscriber to be appointed as store owner.
5. **Actions:**
 - 1) Store Owner attempts to appoint a subscriber to be a store owner of a specific store.
 - 2) Authentication – the system checks that the action was requested by an actual store owner of the needed store.
 - 3) Validity – the system checks that the given parameters are valid – the given username corresponds to an actual subscriber of the market, the subscriber is not already a store owner of the given store, etc.
 - 4) The system sends an store owner appointment offer to the selected subscriber.
 - 5) The system returns a matching success response to the user.
6. **Alternatives/Extensions:**
 - 2) If the authentication failed, a matching error message will be returned and the action will fail.
 - 3) If the given parameters are invalid (for example if the given username doesn't belong to an actual subscriber, or if the subscriber is already a store owner of the store), a matching error message will be returned and the action will fail.

7. Acceptance tests – scenarios:

Scenario Description	Parameters	Expected Result	Scenario
The requesting store owner does not have the right permissions (is not a store owner) in the requested store	Invalid StoreID, valid subscriber username	Failed authentication, a matching error message will be returned.	Bad
The store owner is requesting to appoint a store owner with invalid username (does not belong to a market subscriber)	Valid StoreID, invalid subscriber username	Failed validity check, a matching error message will be returned.	Bad
The store owner is requesting to appoint a store owner of a store, with valid subscriber username of a subscriber that isn't already a store owner of the specified store	Valid StoreID, valid subscriber username	Success, the subscriber will receive a store owner appointment offer, which will be accepted/rejected by him in the second part of the appointment use case.	Good

Use case: 4.3.2 – Store Owner Appointment Approval/Rejection

1. **Actor:** Subscriber, Store Owner
2. **Pre-condition:** The subscriber exists in the system and is logged in to the system.
3. **Post-conditions:** In the case of success, if the subscriber accepted the appointment offer, the selected subscriber will become an owner of the selected store, marking the new owner as appointed by the previous owner.
4. **Input parameters:** The appointment offer id, approval/rejection of the selected subscriber to the given offer.
5. **Actions:**
 - 1) Subscriber is notified about an incoming appointment offer.
 - 2) Subscriber attempts to accept/reject the appointment offer.
 - 3) Authentication – the system checks that the action was requested by a subscriber of the market.
 - 4) Validity – the system checks that the given parameters are valid (appointment offer id actually exists in the system and belongs to the requesting subscriber).
 - 5) If the subscriber accepted the appointment offer, the subscriber will become an owner of the given store, marking the new owner as appointed by the previous owner and the requesting store owner will be notified accordingly. Otherwise, if the offer is rejected, the system dismisses it and notifies the requesting store owner accordingly.
 - 6) The system returns a matching success response to the user.
6. **Alternatives/Extensions:**
 - 3) If the authentication failed, a matching error message will be returned and the action will fail.
 - 4) If the given parameters are invalid (appointment offer id doesn't exist in the system or doesn't belong to the requesting subscriber), a matching error message will be returned and the action will fail.

7. Acceptance tests – scenarios:

Scenario Description	Parameters	Expected Result	Scenario
The user sent an approval request which did not originate from an actual market subscriber	Invalid appointment offer id, offer approval	Failed authentication, a matching error message will be returned.	Bad
The subscriber sent an approval request for an appointment offer that didn't belong to him	Invalid appointment offer id, offer approval	Failed validity check, a matching error message will be returned.	Bad
The subscriber approved an appointment offer that belonged to him	Valid appointment offer id, offer approval	Success, the subscriber will become an owner of the given store, marking the new owner as appointed by the previous owner and the original requesting store owner will be notified accordingly	Good

Use case: 4.6 – Store Manager Appointment (Composite: Appointment Offer, Appointment Approval/Rejection)

Use case: 4.6.1 – Store Manager Appointment Offer

1. **Actor:** Store Owner, Subscriber
2. **Pre-condition:** The store owner exists in the system and is logged in to the system.
3. **Post-conditions:** In the case of success, the selected subscriber will receive an appointment offer and will need to accept/reject the offer in the next part of the use case.
4. **Input parameters:** StoreID, username of the subscriber to be appointed as store manager.
5. **Actions:**
 - 1) Store Owner attempts to appoint a subscriber to be a store manager of a specific store.
 - 2) Authentication – the system checks that the action was requested by an actual store owner of the needed store.
 - 3) Validity – the system checks that the given parameters are valid – the given username corresponds to an actual subscriber of the market, the subscriber is not already a store owner/store manager of the given store, etc.
 - 4) The system sends an store manager appointment offer to the selected subscriber.
 - 5) The system returns a matching success response to the user.
6. **Alternatives/Extensions:**
 - 2) If the authentication failed, a matching error message will be returned and the action will fail.
 - 3) If the given parameters are invalid (for example if the given username doesn't belong to an actual subscriber, or if the subscriber is already a store owner/store manager of the store), a matching error message will be returned and the action will fail.

7. Acceptance tests – scenarios:

Scenario Description	Parameters	Expected Result	Scenario
The requesting store owner does not have the right permissions (is not a store owner) in the requested store	Invalid StoreID, valid subscriber username	Failed authentication, a matching error message will be returned.	Bad
The store owner is requesting to appoint a store manager with invalid username (does not belong to a market subscriber)	Valid StoreID, invalid subscriber username	Failed validity check, a matching error message will be returned.	Bad
The store owner is requesting to appoint a store manager of a store, with valid subscriber username of a subscriber that isn't already a store owner or a store manager of the specified store	Valid StoreID, valid subscriber username	Success, the subscriber will receive a store manager appointment offer, which will be accepted/rejected by him in the second part of the appointment use case.	Good

Use case: 4.6.2 – Store Manager Appointment Approval/Rejection

1. **Actor:** Subscriber, Store Owner
2. **Pre-condition:** The subscriber exists in the system and is logged in to the system.
3. **Post-conditions:** In the case of success, if the subscriber accepted the appointment offer, the selected subscriber will become a manager of the selected store, marking the new manager as appointed by the previous owner.
4. **Input parameters:** The appointment offer id, approval/rejection of the selected subscriber to the given offer.
5. **Actions:**
 - 1) Subscriber is notified about an incoming appointment offer.
 - 2) Subscriber attempts to accept/reject the appointment offer.
 - 3) Authentication – the system checks that the action was requested by a subscriber of the market.
 - 4) Validity – the system checks that the given parameters are valid (appointment offer id actually exists in the system and belongs to the requesting subscriber).
 - 5) If the subscriber accepted the appointment offer, the subscriber will become a manager of the given store, marking the new manager as appointed by the requesting store owner, and the store owner will be notified accordingly. Otherwise, if the offer is rejected, the system dismisses it and notifies the requesting store owner accordingly.
 - 6) The system returns a matching success response to the user.
6. **Alternatives/Extensions:**
 - 5) If the authentication failed, a matching error message will be returned and the action will fail.
 - 6) If the given parameters are invalid (appointment offer id doesn't exist in the system or doesn't belong to the requesting subscriber), a matching error message will be returned and the action will fail.

7. Acceptance tests – scenarios:

Scenario Description	Parameters	Expected Result	Scenario
The user sent an approval request which did not originate from an actual market subscriber	Invalid appointment offer id, offer approval	Failed authentication, a matching error message will be returned.	Bad
The subscriber sent an approval request for an appointment offer that didn't belong to him	Invalid appointment offer id, offer approval	Failed validity check, a matching error message will be returned.	Bad
The subscriber approved an appointment offer that belonged to him	Valid appointment offer id, offer approval	Success, the subscriber will become a manager of the given store, marking the new manager as appointed by the requesting store owner, and the store owner will be notified accordingly	Good

Use case: 4.7 – Store Manager Permission Management

Actors:

Store owner

Preconditions:

The store owner exists and logged in and the store exists.

Postconditions:

1. The selected manager's permissions have been customized according to the settings defined by the store owner.
2. The manager can now access and perform only the tasks and functions permitted by their customized permissions.

Input parameters: StoreID, MangerID, removed permissions, added permissions.

Main Scenario:

1. **Authentication** – the system checks that the action was requested by an actual store owner of the needed store.
2. **Selecting a manager** – the store owner chooses a store manager that he has appointed.
3. The system checks that the chosen manager was appointed by the requesting store owner.
4. the store owner add/remove permissions from the selected store manager.
5. The system checks that the permissions are valid
6. The system updates the manager's permissions with the customized permissions.

Alternatives/Extensions:

1. If the authentication failed, a matching error message will be returned and the action will fail.
2. If the chosen store manager wasn't appointed by the store owner, a matching error message will be returned and the action will fail
3. If the permissions are invalid (unrecognized to the system/ can't be assigned to store manager, a matching error message will be returned and the action will fail

Test 1: Successful Customization of Manager Permissions

Input: StoreID, ManagerID, removed permissions, added permissions.

Preconditions: The store owner is logged in and exists.

Steps:

1. Store owner selects a manager for permission customization.
2. Removed and added permissions are specified.
3. Permissions are valid and can be assigned to the manager.

Expected Outcome:

- The selected manager's permissions are updated according to the provided settings.
- The manager can access and perform only the tasks and functions permitted by their customized permissions.

Test 2: Authentication Failure

Input: StoreID, ManagerID, removed permissions, added permissions.

Preconditions: The store owner is not logged in or not exist.

Steps:

Store owner attempts to customize manager permissions.

Expected Outcome:

- Error message
- The action fails, and no changes are made to the manager's permissions.

Test 3: Invalid Manager Selection

Input: StoreID, ManagerID, removed permissions, added permissions.

Preconditions:

The store owner is logged in and is an owner of the store.

Steps:

Store owner selects a manager that was not appointed by them.

Expected Outcome:

- Error message
- The action fails, and no changes are made to the manager's permissions.

Test 4: Invalid Permissions

Input: StoreID, ManagerID, removed permissions, added permissions.

Preconditions:

The store owner is logged in and is an owner of the store.

Steps:

Store owner attempts to assign invalid or unrecognized permissions to the manager.

Expected Outcome:

- Error message
- The action fails, and no changes are made to the manager's permissions.

Test 5: Permissions Conflict

Input: StoreID, ManagerID, removed permissions, added permissions.

Preconditions:

The store owner is logged in and is an owner of the store.

Steps:

Store owner attempts to assign permissions that conflict with existing permissions of the manager (adding an existing permission for example).

Expected Outcome:

- Error message
- The action fails, and no changes are made to the manager's permissions.

Use case: 4.9 – Store Manager Permission Management

Actors:

Store founder.

Preconditions:

The store founder exists and logged in and the store exists.

Postconditions:

1. The store is closed and becomes inactive.
2. Access to the closed store's information is restricted to store owners and system administrators.
3. Store owners and managers receive a notification about the closure, but their appointment remains unchanged.
4. Store's products will no longer appear while searching for products.

Input parameters: StoreID

Main Scenario:

1. **Authentication** – the system checks that the action was requested by the store founder of the needed store.
2. The system checks that the store is currently open
3. The system change the store status to inactive
4. The system sends a notification informing the store owners and managers of the store closure.

Alternatives/Extensions:

1. If the authentication failed, a matching error message will be returned and the action will fail.
2. If the store is already closed, a matching error message will be returned and the action will fail.

Test 1: Successful Closure of the Store

Input: StoreID

Preconditions: The store founder is logged in and is the founder of the store.

Steps:

Store founder initiates the closure of the store.

Expected Outcome:

- The store status is changed to inactive.
- Access to the closed store's information is restricted to store owners and system administrators.
- Store owners and managers receive a notification about the closure, but their appointment remains unchanged.
- Store's products will no longer appear while searching for products.

Test 2: Authentication Failure

Input: StoreID

Preconditions:

The store founder is not logged in or is not the founder of the store.

Steps:

Unauthorized user attempts to close the store.

Expected Outcome:

- Error message
- The action fails, and the store status remains unchanged.

Test 3: Attempting to Close an Already Closed Store

Input: StoreID

Preconditions:

The store founder is logged in and is an owner of the store.

The store is already closed.

Steps:

1. Store founder closes the store.
2. Store founder attempts to close the store again.

Expected Outcome:

- Error message
- The action fails, and the store status remains unchanged.

Use case: 4.11 – Request for Information on Store Roles

Actors:

Store owner.

Preconditions:

The store owner exists and logged in and the store exists.

Postconditions:

The store owner has access to detailed information about the roles in their store.

Input parameters: StoreID

Main Scenario:

1. **Authentication** – the system checks that the action was requested by a store owner of the needed store.
2. The system retrieve information about all the roles in the store.

Alternatives/Extensions:

If the authentication failed, a matching error message will be returned and the action will fail.

Test 1: Successful Retrieval of Store Roles Information

Input: StoreID

Preconditions:

The store owner is logged in and is an owner of the store.

Steps:

Store owner initiates a request for information on store roles.

Expected Outcome:

The system retrieves detailed information about all the roles in the store.

Test 2: Authentication Failure

Input: StoreID

Preconditions:

The store owner is not logged in or is not an owner of the store.

Steps:

Unauthorized user attempts to request information on store roles.

Expected Outcome:

- Error message
- The action fails, and the requested information is not retrieved.

Use case: 4.11 – Request for Information on manager permissions.

Actors:

Store owner.

Preconditions:

The store owner exists and logged in and the store exists.

Postconditions:

The store owner has access to detailed information about the roles in their store.

Input parameters: StoreID, ManagerID

Main Scenario:

1. **Authentication** – the system checks that the action was requested by a store owner of the needed store.
2. The system checks that the manager exists and is a manager in the store
3. The system retrieve the manager permissions in the store.

Alternatives/Extensions:

1. If the authentication failed, a matching error message will be returned and the action will fail.
2. If the manager doesn't exists or is not a manager of the store, a matching error message will be returned and the action will fail.

Test 1: Successful Retrieval of Manager Permissions

Input: StoreID, ManagerID

Preconditions: The store owner is logged in and is an owner of the store.
The manager exists and is assigned as a manager in the store.

Steps:

Store owner initiates a request for information on manager permissions.

Expected Outcome:

- The system retrieves information about the permissions assigned to the specified manager in the store.

Test 2: Authentication Failure

Input: StoreID, ManagerID

Preconditions:

The store owner is not logged in or not an owner of the store.

Steps:

Unauthorized user attempts to request information on manager permissions.

Expected Outcome:

- Error message
- The action fails, and the requested information is not retrieved.

Test 3: Manager Does Not Exist or Is Not a Manager in the Store

Input: StoreID, ManagerID

Preconditions: The store owner is logged in and is an owner of the store.

Steps:

1. Store owner initiates a request for information on manager permissions.
2. Store owner specifies a ManagerID that does not exist or is not assigned as a manager in the store.

Expected Outcome:

- Error message
- The action fails, and the requested information is not retrieved.

Use case: 4.13 – Purchase History Retrieval.

Actors:

Store owner.

Preconditions:

The store owner exists and logged in and the store exists.

Postconditions:

The store owner has access to detailed purchase history information.

Input parameters: StoreID

Main Scenario:

1. **Authentication** – the system checks that the action was requested by a store owner of the needed store.
2. The system retrieves the purchase history of the store.

Alternatives/Extensions:

1. If the authentication failed, a matching error message will be returned and the action will fail.
2. If there were no purchases from the store, a message telling there was no purchases will be returned.

Test 1: Successful Retrieval of Purchase History

Input: StoreID

Preconditions:

The store owner is logged in and is an owner of the store.

The store exists.

Steps:

Store owner initiates a request to retrieve purchase history.

Expected Outcome:

- The system retrieves purchase history for the specified store.

Test 2: Authentication Failure

Input: StoreID

Preconditions:

The store owner is not logged in or not an owner of the store.

Steps:

Unauthorized user attempts to retrieve purchase history.

Expected Outcome:

- Error message
- The action fails, and the requested information is not retrieved.

Test 3: No Purchase History Available

Input: StoreID

Preconditions:

The store owner is logged in and is an owner of the store.

The store exists

Steps:

Store owner initiates a request to retrieve purchase history.

Expected Outcome:

- Error message
- The action fails, and the requested information is not retrieved.

Use case: 5 –store manager permitted actions.

Actors:

Store manager.

Preconditions:

The store manager exists and logged in and the store exists.

Postconditions:

The requested action is performed.

Input parameters: StoreID, action.

Main Scenario:

1. **Authentication** – the system checks that the action was requested by a store manager of the needed store.
2. The system checks if the action is within his permissions.
3. The system perform that action

Alternatives/Extensions:

3. If the authentication failed, a matching error message will be returned and the action will fail.
4. If the action is not within the store manager permissions, a matching error message will be returned and the action will fail.

Test 1: Successful Execution of Permitted Action

Input: StoreID, action

Preconditions:

The store manager is logged in and is a manager of the store.

The store exists.

Steps:

Store manager initiates the requested action.

Expected Outcome:

The system successfully performs the requested action

Test 2: Authentication Failure

Input: StoreID, action

Preconditions:

The store manager is not logged in or not a manager of the store.

Steps:

Unauthorized user attempts to initiate the requested action.

Expected Outcome:

- Error message
- The action fails, and the requested information is not retrieved.

Test 3: Action Not Within Store Manager Permissions

Input: StoreID, action

Preconditions:

The store manager is logged in and is a manager of the store.

The store exists.

The requested action is not within the store manager's permissions.

Steps:

Store manager attempts to initiate the requested action.

Expected Outcome:

- Error message
- The action fails, and the requested information is not retrieved.