Self join Quiz

SELF JOIN quiz

stops	route
id	num
name	company
	pos
	stop

1. Select the code that would show it is possible to get from Craiglockhart to Haymarket

```
SELECT DISTINCT a.name, b.name
  FROM stops a JOIN route z IN a.id=z.stop
  JOIN route y ON y.num = z.num
  JOIN stops b IN y.stop=b.id
 WHERE a.name='Craiglockhart' AND b.name ='Haymarket'
```

```
SELECT DISTINCT a.name, b.name
  FROM stops a JOIN route z ON a.id=z.stop
  JOIN route y JOIN stops b ON y.stop=b.id
 WHERE a.name='Craiglockhart' AND b.name ='Haymarket'
```

```
SELECT DISTINCT a.name, b.name
  FROM stops a JOIN route z ON a.id=z.stop
```

```
     JOIN route y ON y.num = z.num
     JOIN stops b ON y.stop=b.id
  WHERE a.name='Craiglockhart' AND b.name ='Haymarket'
```

```
SELECT DISTINCT a.name, b.name from stops a
  JOIN route z ON a.id=z.stop
  JOIN route y ON y.num = z.num
  JOIN stops b ON y.stop=b.id
 WHERE a.name='Craiglockhart' AND b.name ='Sighthill'
```

```
SELECT DISTINCT a.name, b.name
  FROM stops a JOIN route z ON a.id=z.stop
  JOIN route y ON y.num = z.num
  JOIN stops b ON y.stop=b.id
 WHERE y.name='Craiglockhart' AND z.name ='Haymarket'
```

2. Select the code that shows the stops that are on route.num '2A' which can be reached with one bus from Haymarket?

```
SELECT S2.id, S2.name, R2.company, R2.num
  FROM stops S1, stops S2, route R1, route R2
 WHERE S1.name='Haymarket' AND S1.id=R1.stop
   AND S1.company=S2.company AND S1.num=S2.num
   AND R2.stop=S2.id AND R1.num='2A'
```

```
SELECT S2.id, S2.name, R2.company, R2.num
  FROM stops S1, stops S2, route R1, route R2
 WHERE S1.name='Haymarket' AND S1.id=R1.num
```

```
    AND R1.company=R2.company AND R1.num=R2.num
    AND R2.stop=S2.id AND R2.num='2A'
```

```
SELECT S2.id, S2.name, R2.company, R2.num
  FROM stops S1, stops S2, route R1, route R2
 WHERE S1.name='Haymarket' AND S1.id=R1.stop
   AND R1.company=R2.company AND R1.num=R2.num
   AND R2.stop=S2.id
```

```
SELECT S2.id, S2.name, R2.company, R2.num
  FROM stops S1, stops S2, route R1, route R2
 WHERE S1.name='Haymarket' AND S1.id=R1.stop
   AND R1.company=R2.company AND R1.num=R2.num
   AND R2.stop=S2.id AND R2.num='2'
```

```
SELECT S2.id, S2.name, R2.company, R2.num
  FROM stops S1, stops S2, route R1, route R2
 WHERE S1.name='Haymarket' AND S1.id=R1.stop
   AND R1.company=R2.company AND R1.num=R2.num
   AND R2.stop=S2.id AND R2.num='2A'
```

3. Select the code that shows the services available from Tollcross?

```
SELECT a.company, a.num, stopa.name, stopb.name
  FROM route a JOIN route b ON (a.company=b.company AND a.num=b.num)
  JOIN stops stopa ON (a.stop=stopa.id)
  JOIN stops stopb ON (b.stop=stopb.id)
```

```
SELECT a.company, a.num, stopa.name, stopb.name
  FROM route a JOIN route b ON (a.company=b.company AND a.num=b.num)
  JOIN stops stopa ON (a.stop=stopa.id)
  JOIN stops stopb ON (b.stop=stopb.id)
 WHERE stopa.name='Sighthill'
```

```
SELECT a.company, a.num, stopa.name, stopb.name
  FROM route a JOIN route b IN (a.company=b.company AND a.num=b.num)
  JOIN stops stopa IN (a.stop=stopa.id)
  JOIN stops stopb ON (b.stop=stopb.id)
 WHERE stopa.name='Tollcross'
```

```
SELECT a.company, a.num, stopa.name, stopb.name
  FROM route a JOIN route b ON (a.company=b.company AND a.num=b.num)
  JOIN stops stopa ON (a.stop=stopa.id)
  JOIN stops stopb ON (b.stop=stopb.id)
 WHERE stopa.name='Tollcross'
```

```
SELECT a.company, a.num, stopa.name, stopb.name
  FROM route a JOIN route b ON (a.company=b.company AND a.num=b.num)
  JOIN stops stopa ON (a.stop=stopa.id)
  JOIN stops stopb ON (b.stop=stopb.id)
 WHERE stopz.name='Tollcross'
```

Score the test

Your score is: 3 out of 3

This page was last edited on 19 February 2020, at 10:14.