


**THREAD DATA**  
SCALE 8:1


DOUBLE LEAD  
LEFT HAND THREAD

"T" = .218 [5.54] DIA	3.1
"E" = .157 [3.99] DIA	4.1


LEAD = .1604 [4.074]  
PITCH = .0803 [2.040]




SECTION C-C



SECTION D-D



SECTION A-A




SCALE 4:1

NOTE:  
DIMENSIONS IN BRACKETS [ 0.000 ]  
ARE MILLIMETERS

**METEOR**

A	5003917	04-05-07	CONVERTED TO DUAL DIMENSIONS	RWB	CV
REV.	ECN	DATE	REVISION RECORD	DRN	APPR

APPROVALS				THE PLASTEK GROUP					
DRAWN		J.D.SOLIWODA		DATE		12/08/06		ERIE, PENNSYLVANIA	
CHECKED		J.D.SOLIWODA		DATE		12/08/06			
APPROVED		C. VARKEY		DATE		12/07/06			
REFERENCE NO.				DESCRIPTION					
				B/H CORE SUB INSERT					
				2x24 CAV GENGHIS REG SCREW (50786)					
FINISH				SCALE: 4:1		ECN NUMBER		CUSTOMER NUMBER	
MATERIAL				SHRINKAGE:		5003689		44000008	
420 S.S. (STAVAX)									
HARDNESS		QUANTITY REQUIRED		SIZE		DRAWING NO.		REV.	
48-50 Rc		48		D		1983A_102			