

SECTION ON C/L

FIRESTARTER

NOTE:

TO MACHINE .125 [3.18mm] DIA.
(2) HOLES: TILT PART AT 30°,
TILT HEAD AT 20°30'

		TOLERANCES UNLESS NOTE	APP	ROVALS			
		DIMENSIONS IN INCHES 2 PLACE DECIMAL + /01	DRN. S. Schaefer	DATE 08/20/15	1 TH	HE PLASTEK GROUP erie, pennsylvania) /THE\ PLASTEK
		3 PLACE DECIMAL +/001 4 PLACE DECIMAL +/0005	CHK'D S. Schaefer	DATE 08/20/15			GROUP
		DIMENSIONS IN MILLIMETERS 0 PLACE DECIMAL +/- 0.3 1 PLACE DECIMAL +/- 0.25	APPROVED	DATE	DESCRIPTION NOZZLE TIP (1/2 DIA)		ΙΔ)
		2 PLACE DECIMAL +/- 0.025 3 PLACE DECIMAL +/- 0.013	APPROVED	DATE	24 (CAV "GENGHIS" PLATFOR	
		ANGULAR: +/- 0° 15'	REFERENCE		SCALE	ECN NUMBER	CUSTOMER
		THE INFORMATION ON THIS DRAWING IS PROPRIETARY TO THE PLASTEK	TITANIUM NIT	RATE ————————————————————————————————————	F	ULL 5009698	44000008
		GROUP. THIS INFORMATION SHALL NOT BE DISCLOSED OR	MATERIAL				
		REPRODUCED WITHOUT PRIOR WRITTEN CONSENT OF THE PLASTEK GROUP.			SIZE	DRAWING NO.	REV.
REV. ECN DATE F	REVISION RECORD DRN	APPR DO NOT SCALE DRAWING	HDN / FINISH RC 40-44	QTY REQ'D 24 REQ'D	B	2403A.02	4