


SOLDER BAFFLE IN PLACE

NOTE:

1.) BRACKETED DIMENSION ARE IN MM

FIRESTARTER

						TOLERANCES UNLESS NOTED DIMENSIONS IN INCHES 2 PLACE DECIMAL +/- .01 3 PLACE DECIMAL +/- .001 4 PLACE DECIMAL +/- .0005 DIMENSIONS IN MILLIMETERS 0 PLACE DECIMAL +/- 0.3 1 PLACE DECIMAL +/- 0.25 2 PLACE DECIMAL +/- 0.025 3 PLACE DECIMAL +/- 0.013 ANGULAR: +/- 0° 15' THE INFORMATION ON THIS DRAWING IS PROPRIETARY TO THE PLASTEK GROUP. THIS INFORMATION SHALL NOT BE DISCLOSED OR REPRODUCED WITHOUT PRIOR WRITTEN CONSENT OF THE PLASTEK GROUP.	APPROVALS		THE PLASTEK GROUP ERIE, PENNSYLVANIA				
							DRN. J.D.SOLIWODA	DATE 01/24/07	DESCRIPTION W/L DIVERTER (SLIDE) 24 CAVITY "GENGHIS" REG SCREW (50785)				
							CHK'D J.D.SOLIWODA	DATE 01/27/07					
							APPROVED C. VARKEY	DATE 01/27/07					
							APPROVED	DATE	SCALE		ECN NUMBER		CUSTOMER
B	5003919	04/15/07	ADDED DUAL DIMENSIONS	TS	CV	DO NOT SCALE DRAWING	REFERENCE		2X		5003744	44000008	
A	5003800	01/19/07	.06 WIDTH WAS .09 WIDTH	JDS	CV		MATERIAL BRASS		SIZE		DRAWING NO.		REV.
REV.	ECN	DATE	REVISION RECORD	DRN	APPR		HDN / FINISH	QTY REQ'D 48 REQ'D	B		1977A.041		B