

DRILL AND C'BORE FOR 1/4 S.H.C.S., 4 PLACES .875 [22.23] 2.440 [61.98] DIA .875 [22.23] STAMP PLASTEK PART #1977B.057 .875 [22.23]

SECTION ON C/L

NOTE:

- 1.) 1.2500 [31.750] DIA SHOULD BE A LIGHT PRESS FIT WITH THE COIL HEATER. CHECK I.D. OF THE HEATER.
- 2.) BRACKETED DIMENSIONS ARE IN MM

FIRESTARTER

										_				
							TOLERANCES UNLESS NOTED	APPROVALS		_			$\overline{}$	<u> </u>
							2 PLACE DECIMAL +/01	DRN. G. Losasso	DATE 10/02/14	THE PLASTEK GRO			PLAST	•
							0 PLACE DECIMAL +/- 0.3 1 PLACE DECIMAL +/- 0.25 2 PLACE DECIMAL +/- 0.025 3 PLACE DECIMAL +/- 0.013 ANGULAR: +/- 0* 15' THE INFORMATION ON THIS DRAWING	CHK'D	DATE	1	ERIE, F	PENNSTLVANIA	GROUP	
-								APPROVED	DATE	DESCRIPTION SPRUE BUSHING (U.S.)			5) (A)	
								APPROVED	DATE	24 CA	V FIREST	ARTER REG SCF	REW (50'	785)
								REFERENCE		SCALE		ECN NUMBER	CUSTOMER	
	А	5009769	10/27/15	.250 DEEP WAS .188 R.500 SPHERICAL WAS R.630 ADDED (U.S.) TO DESCRIPTION	JDS	CV		MATERIAL		FULL		5009188	44000	8000
								AISI H-13 HDN / FINISH	QTY REQ'D	1 _	RAWING NO.	10770.0		REV.
	REV.	ECN	DATE	REVISION RECORD	DRN	APPR	DO NOT SCALE DRAWING	RC 48-50	1 REQ'D	В		1977B.0	3 /	А