

DRILL AND C'BORE FOR 1/4 S.H.C.S., 4 PLACES 875 [22.23] 2.440 [61.98] DIA .875 [22.23] .875 [22.23]

SECTION ON C/L

NOTE:

- 1.) 1.2500 [31.750] DIA SHOULD BE A LIGHT PRESS FIT WITH THE COIL HEATER. CHECK I.D. OF THE HEATER.
- 2.) BRACKETED DIMENSIONS ARE IN MM

METEOR/FIRESTARTER

						2 PLACE DECIMAL +/01 3 PLACE DECIMAL +/001 4 PLACE DECIMAL +/0005 DIMENSIONS IN MILLIMETERS 0 PLACE DECIMAL +/- 0.3 1 PLACE DECIMAL +/- 0.25 2 PLACE DECIMAL +/- 0.025 3 PLACE DECIMAL +/- 0.013	DRN. J. SOLIWODA	OVALS DATE 11/10/15 DATE 11/10/15	EF	ASTEK GROUP RIE, PENNSYLVANIA	PLASTEK GROUP
							APPROVED C. VARKEY APPROVED REFERENCE	DATE 11/10/15 DATE	DESCRIPTION SPRU	E BUSHING (EUROF TY GENGHIS PLUG ECN NUMBER	
						THE INFORMATION ON THIS DRAWING IS PROPRIETARY TO THE PLASTEK GROUP. THIS INFORMATION SHALL NOT BE DISCLOSED OR REPRODUCED WITHOUT PRIOR WRITTEN CONSENT OF THE PLASTEK GROUP.	MATERIAL AISI H-13 HDN / FINISH QTY REQ'D		FULL SIZE DRAWING		44000008
REV.	ECN	DATE	REVISION RECORD	DRN	APPR	DO NOT SCALE DRAWING	RC 48-50	1	В	1973C.0	02