FUJITSU

POWERFUL PERFORMANCE FOR THE LONG RUN

Fujitsu Services introduces TeamPoS 3000 XL

If you require a high-performance POS terminal that will grow with your retail business, Fujitsu's TeamPoS 3000 XL delivers. This powerful system features Intel® processors and a host of features designed to drive down your total cost of ownership. From standalone point of sale to mission-critical applications such as loyalty, merchandising and customer relationship management, the TeamPoS 3000 XL meets the demanding needs of today's pervasive retailing environment.

TeamPoS 3000 XL – Key Features

Long term performance Offers powerful architecture and a stable platform based on Intel's embedded roadmap for long term support additionally providing a suitable migration path for existing TeamPoS 2000 customers.

Easy to upgrade Several Intel Celeron ® M and Pentium® M processor options let you upgrade as your requirements become more demanding and open architecture design lowers the cost of future upgrades.

Advanced power management Provides an efficient balance of power consumption, CPU utilisation and performance. Reduces your power consumption and allows energy conservation when terminal is inactive.

Unmatched serviceability Components are easy to replace and can be accessed through the front of the unit without removing cables or unstacking peripherals. Ease of maintenance reduces on-site service calls.

Industry-standard design Lower development costs for new and existing systems through compliance with industry standard operating systems, OPOS/JPOS, PC tools and utilities.

System flexibility Compact and standard controllers and extensive peripheral options provide flexibility for location and footprint of system supporting both stacked and dispersed configurations. Additionally a wide choice of peripherals can be supported including legacy (RS232) and futures (USB).

Remote management Industry-standard remote diagnostics and remote management capabilities reduce your help desk calls and service call visits, enabling you to perform maintenance before a device fails.

Environmental compliance Meets RoHS and WEEE compliance standards which protect your investment and ensure a long, useful life.

TeamPoS 3000 XL – Dependable *PoS from Fujitsu*

ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com

FUJITSU

TeamPoS® 3000 XL Technical Specifications

Processor

Supports Intel 1.3 GHz
Celeron M to 2.0 GHz
Pentium M processors

Motherboard

Up to 2 MB cache
Enhanced Speed Step
Technology (Pentium M only)

Core chipset:
855GME

Integrated Ethernet LAN:
10/100 Mbps with wake-on-LAN support

Integrated audio:
Sound Blaster compatible

Graphics/Video

Integrated video with up to 128 MB of memory
Analog/Digital display support
Dual independent display support
Analog RGB, 15-pin interface
Digital DVI, DVI-D interface
UXGA support, up to
1600 x 1200 resolution

Standard I/O Ports

2 x PS/2
1 x Audio (in/out)
1 x LAN 10/100
1 x VGA
1 x DVI

2 x standard COM
(support +5V or 12V)
2 x standard USB (in rear)
2 x additional USB ports
(in front)
1 x +24V USB powered (printer)
1 x Cash Drawer
(supports up to 2 cash drawers)

Optional I/O

Option 1:
2 x RS232, +24VDC
3 x RS232, +5 VDC
6 x Powered USB, +12 VDC

Option II:
3 x Powered USB, +12 VDC

Option III:
6 x Powered USB, +12 VDC

Memory

256MB to 2GB Error Correcting
(ECC) memory
2 x 184 pin DIMM slots
Double Data Rate (DDR)

333MHz memory

Award BIOS

Support latest versions of APM, ACPI, WfM
Boot from LAN
Local and Remote Flash
Password protected
P x E

Expansion Slots

1 x ½ height PCI Slot
1 x Mini-PCI

Disk Support

Up to 2 SATA (2.5")

Removable hard drive with zero insertion connectors for accessibility and ease of maintenance (drives can be replaced without removing cables)

Options:
CDRW/DVD

On board RAID supports RAID 0,1, Auto Recovery

Power Supply

100 to 240 VAC, 50/60 Hz
Auto sensing
270 watts DC output
1 x AC outlet (IEC connector)
Fan Alarm

Battery backup

Optional battery maintains
PC environment through
power outage
Integrated UPS option.

Dimensions

Compact:
340 cm x 450 cm x 120 cm
13.4 in. x 18.3 in. x 4.7 in)

Standard:
450 cm x 465 cm x 120 cm
(17.7 in. x 18.3 in. x 4.7 in.)

Operating Systems

Windows 2000
Windows XP Pro
Windows XPe
Window Embedded for Point of Sale (WEPOS)
Windows Pro Server 2003

Power Management

APM 1.2
ACPMI 1.0

Remote Management

WfM 1.1
DMI 2.0

Additional Features

Plug 'N' Play
CPU fan failure alarm
Optional Wireless LAN
802.11 a/b/g

Colour Options

Fujitsu Black or Fujitsu White

Specification subject to change

ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com