



# Electro-Matic 4UPro

Pixel Pitch: **6mm** LED Color: Full Color  
Pixel Configuration: 3 in 1 SMD Service: Front



## Product Specifications

SPECIFICATIONS	
Brightness	>1500 cd/m <sup>2</sup> (Nits)
Contrast Ratio	3000:1
Grey Level	14 Bit
Frame Frequency	>60 Hz
Refresh Frequency	>1000 Hz
Brightness Control	Manual/Auto/Scheduled
Operating Temperature	-10°C ~ 60°C
Operating Humidity	10% ~ 90% Noncondensing
Power Input	100-240VAC Universal Power Input/Optional 24VDC

DISPLAY FEATURES	
Recommended Use	Indoor Only
Connectivity	Ethernet
Cabinet Rating	NEMA 2 (IP11)
Installation Hardware	Yes (Eye Bolts Included)
Low Power Consumption	Yes
Light Weight	Yes

AVAILABLE SIZES	MATRIX (H X W)	SIZE (H X W)	Weight (lbs)	Power (amps)	# of Lines @ 1.7" Text	# of Lines @ 3.5" Text	# of Lines at 4.7" Text
4UPRO-6IS-032X0128	32 x 128	7.56" X 30.24"	12 lbs	0.7 amps	4 Lines of 18 Characters	2 Lines of 10 Characters	1 Line of 12 Characters
4UPRO-6IS-032X0192	32 x 192	7.56" X 45.35"	18 lbs	1 amps	3 Lines of 24 Characters	2 Lines of 16 Characters	1 Line of 18 Characters
4UPRO-6IS-032X0256	32 x 256	7.56" X 60.47"	24 lbs	1.4 amps	4 Lines of 36 Characters	2 Lines of 21 Characters	1 Line of 24 Characters
4UPRO-6IS-032X0320	32 x 320	7.56" X 75.62"	42 lbs	2.3 amps	4 Lines of 48 Characters	2 Lines of 27 Characters	1 Line of 30 Characters
4UPRO-6IS-064X0128	64 x 128	15.12" X 30.24"	24 lbs	1.4 amps	6 Lines of 16 Characters	4 Lines of 10 Characters	3 Lines of 12 Characters
4UPRO-6IS-064X0192	64 x 192	15.12" X 45.35"	36 lbs	2 amps	6 Lines of 24 Characters	4 Lines of 16 Characters	3 Lines of 18 Characters

