

# 4-Line 4U2SEE™ Indoor Tri-Color Displays

 **ELECTRO-MATIC** VISUAL PRODUCTS

4U2SEE



## Message Capabilities

- 16 System Fonts Available with Bold Option
- Capability to Add Custom Fonts
- Up to 48 In/Out Message Transition Modes
- Shuffle Display Modes Randomly
- Scroll Display Mode for Long, Continuous Messages (Ticker)
- 7 Message Speeds
- Pause Periods from 0 Seconds to 60 Minutes
- Time and Date Formats Built In
- Pre-load and Automatically Schedule Thousands of Messages
- Count-Up ("*Days Since Last Time Accident*") and Count-Down ("*Days Until Christmas*")



## Standard Features

- 1.5" - 9" Characters
- 1024k Flash Memory
- 128k Ram Memory
- 32-Bit CPU
- 140° Viewing Angle
- 0.3" Pitch
- Aluminum Enclosure
- RS232, RS485, USB 2.0 or Ethernet Communication
- 120 VAC, 12 VDC or 12-28 VDC Power Supply
- Programmable via: Handheld Remote, VisionsPlay Software or our Advanced Display Protocol
- RSS Feed capability included with VisionsPlay Software and Internet Access
- ETL Certified to UL48 and CAN/CSA-STD C22.2 No.207
- Hanging Mount

## Additional Options

- Handheld Remote, VisionsPlay 3000 Software, 1-ft. RJ22 to RJ11 Cable
- NEMA 4x Enclosure
- Wireless Connection
- Wall Mount Bracket



# 4-Line 4U2SEE™ Indoor Tri-Color Displays

 **ELECTRO-MATIC** VISUAL PRODUCTS

4U2SEE

## Physical

### 4U4211NXXTX

### 4U4321NXXTX

<b>Display Pixels</b>	32 (h) x 128 (w)	32 (h) x 192 (w)
<b>Cabinet Height</b>	11.6"	11.6"
<b>Cabinet Width</b>	41.2"	60.4"
<b>Cabinet Depth</b>	4.25"	4.25"
<b>Display Weight</b>	26.4 lbs.	35.2 lbs.



## Display

Lines	Character Height	# of Characters
5	1.5"	25*
4	2.1"	21
2	4.2"	16
2	2.5"	14
1	4.8"	14
1	6.6"	7
1	7.2"	8
1	9.0"	7

*\*Bonus characters using special compressed font*

Lines	Character Height	# of Characters
5	1.5"	38*
4	2.1"	32
2	4.2"	24
2	2.5"	21
1	4.8"	21
1	6.6"	10
1	7.2"	12
1	9.0"	10

*\*Bonus characters using special compressed font*



## Standard Specifications

<b>Configuration</b>	Enhanced Version with Ethernet
<b>Pixel Pitch</b>	0.3" (1.5" minimum character height)
<b>LED Color</b>	TriColor (Red, Amber, Green)
<b>Voltage</b>	120 VAC
<b>Temperature Rating</b>	0-45°C (32-113°F)
<b>Standard Communication</b>	RS232, RS485, Ethernet
<b>Full Load Watts</b>	100 Watts Maximum

<b>Estimated LED Lifetime</b>	100,000 hours
<b>Brightness</b>	80 NITs
<b>Viewing Angle</b>	140°
<b>Graphic Capability</b>	ASCII characters, graphic files, string file, time zone and date display
<b>Warranty</b>	1 Year Parts Limited
<b>Cabinet Construction</b>	NEMA-1 Aluminum