4U2SEE™ Indoor Tri-Color Displays



Sm ELECTRO-MATIC VISUAL PRODUCTS









						/ \	
	4U1131	4U1201	4U1261	4U210	4U2161	4U2211	4U2321
Display Pixels	7(h) x 80(w)	7(h) x 120(w)	7(h) x 160(w)	16(h) x 64(w)	16(h) x 96(w)	16(h) x 128(w)	16(h) x 128(w)
Cabinet Height (in)	4"	4"	4"	6.22"	6.22"	6.22"	6.22"
Cabinet Width (in)	26"	38"	50"	21.6"	31"	40.75"	60"
Cabinet Depth (in)	2"	2"	2"	2"	2"	2"	2″
Display Weight	4.4 lbs.	6.6 lbs.	8.8 lbs.	8.8 lbs.	11.4 lbs.	17.1 lbs.	22.8 lbs.
Lines	1	1	1	2	2	2	2
Character Height	1.5" / 2.1"	1.5" / 2.1"	1.5" / 2.1"	2.1"	2.1"	2.1"	2.1"
# of Characters	16 / 13	24 / 20	32 / 26	10	16	21	32

Standard Specifications

Configuration	Enhanced Version with Ethernet
Pixel Pitch	0.3" (1.5" minimum character height)
LED Color	TriColor (Red, Amber, Green)
Voltage	120 VAC
Temperature Rating	0-45°C (32-113°F)
Standard Communication	RS232, RS485, Ethernet, USB
Full Load Watts	60 Watts Maximum for 1 line display

Estimated LED Lifetime	100,000 hours			
Brightness	80 NITs			
Viewing Angle	140°			
Graphic Capability	ASCII characters, graphic files, string file, time zone and date display			
Warranty	1 Year Parts Limited			
Cabinet Construction	NEMA-1 Aluminum			

Order Approval Current		elivery 12-14 weeks		Pric	Pricing		
Project:	Ford - Oakville			Quantity	100		
Site Address				4U1201	\$475.28 / unit		
Name	Jennifer Flemings			4U2211	\$665.39 / unit		
Email/Phone	jjenni53@ford.com / 248-846-3450			*Freight will be quoted at the time of delivery to ensure the best possible market rate.			
Approval Signatur	е	PO	Date	Total			

