



Electro-Matic 4UPro Outdoor

Pixel Pitch: 6mm
Pixel Configuration: 3 in 1 SMD
LED Color: Full Color
Service: Front



Product Specifications

SPECIFICATIONS	
Brightness	> 6000 cd/m ² (Nits)
Contrast Ratio	3000:1
Grey Level	16 Bit
Frame Frequency	>60 Hz
Refresh Frequency	>1920 Hz
Brightness Control	Manual/Auto/Scheduled
Operating Temperature	-20°C ~ 50°C
Operating Humidity	20% ~ 95% RH
Power Input	100-240VAC Universal Power Input

DISPLAY FEATURES	
Recommended Use	Outdoor
Connectivity	Ethernet
Cabinet Rating	NEMA 3 (IP54)
Installation Hardware	Yes (Eye Bolts Included)
Low Power Consumption	Yes
Cabinet Construction	Lightweight Aluminum

Display Part #	HxW (inches)
4UPRO-3.90S-60X160-RGB-1V	9 x 25
4UPRO-60S-032X0128-RGB-1V	7.5 x 30
4UPRO-60S-032X0192-RGB-1V	7.5 x 45
4UPRO-60S-032X0256-RGB-1V	7.5 x 60
4UPRO-60S-064X0128-RGB-1V	15 x 30
4UPRO-60S-064X0192-RGB-1V	15 x 45
4UPRO-60S-096X0192-RGB-1V	22.5 x 45

