Inversion Is All You Need

Dynamic Invariant Spaces for Transformer Language Models

Author: Martin Timms
Version: 0.5.5 minimal GitHub release
Date: 2026-07-10
License: see repository `LICENSE` file: CC BY 4.0 for paper/text/figures; MIT for code examples
Related projects:

- Bindu-Maya [1]
- Medium article, *Inversion Is All You Need* [2]
- OpenGML [3]
- OpenGML TSC talk, *Geometric Musical Language / nested clock oscillator networks* [4]

Core thesis: attention is not all we need. A language model should not merely attend over tokens; it should invert the prompt into an invariant state before generation. A Dynamic Invariant Space layer is a lightweight attempt to engineer that invariant-seeking step inside a transformer. Earlier exploratory notes called the module a "Bindu Oscillator"; this repository uses neutral engineering terminology for public research communication.

Abstract

Transformer-based language models are built from stacked self-attention, feed-forward neural network blocks, normalisation layers, residual connections, learned weights, and nonlinear activations. These architectures have achieved extraordinary performance, but their basic units remain simplified mathematical abstractions compared with biological neurons and sub-neuronal structures. In parallel, consciousness research, neuroscience, and bioelectromagnetic research have explored richer models involving intracellular resonance, cytoskeletal dynamics, molecular-scale memory, and nested frequency organisation.

This paper proposes a practical engineering hypothesis rather than a consciousness claim: do not attempt to simulate full biological neurons or microtubule bundles inside an LLM. Instead, insert a small, trainable, dynamic oscillator workspace into the middle of a transformer. I call this module a **Dynamic Invariant Space layer** or **Resonant Workspace**. Earlier exploratory notes used the term "Bindu Oscillator" for the same convergence idea. The layer projects hidden activations into phase variables, lets those variables interact through nested oscillator geometry, forms a compact convergence state, and folds the resulting state back into the language stream.

The proposal connects four strands:

1. **Inversion-first intelligence** from Bindu-Maya: a model should speak from the invariant state extracted from a prompt, not merely from the prompt surface.
2. **OpenGML / Geometric Musical Language:** nested oscillator networks, clocks, phase relations, primes, and geometric convergence.
3. **Biological inspiration:** experimental and theoretical work on microtubule resonance, water channels, molecular-scale memory, and sub-neuronal dynamics associated with Dr Anirban Bandyopadhyay and collaborators.
4. **Anthropic J-space / global workspace interpretability:** evidence that language models can develop privileged internal workspaces for verbalizable representations, suggesting a bridge between discovered workspaces and deliberately engineered dynamic workspaces.

The hypothesis is that a transformer with a Dynamic Invariant Space chamber may learn more than token continuation. It may learn to stabilise hidden relational invariants beneath tokens. If true, this could lead to new approaches for hallucination reduction, interpretability, persistent internal state, long-range coherence, and invariant-first reasoning.

This is not a claim that LLMs are conscious. It is a research programme for testing whether dynamic oscillator workspaces inside transformers can improve invariant extraction and reduce unsupported verbal drift.

---

1. Motivation

Modern LLMs are usually evaluated from the outside: perplexity, benchmarks, coding tasks, chat quality, retrieval performance, and human preference scores. These are important, but they do not fully specify what the model is stabilising internally.

A standard transformer can produce fluent language even when its grounding weakens. In many failure cases, the model does not stop generating; it continues the surface distribution. This suggests a possible architectural gap:

```
surface fluency can survive after hidden constraint has drifted
```

The Dynamic Invariant Space hypothesis is that a transformer may benefit from a deliberately engineered hidden workspace whose job is to stabilise relational structure beneath text.

In short:

```
standard model:
what token comes next?

invariant-first model:
what structure remains stable beneath the token stream?
```

---

2. Standard transformers and simplified artificial neurons

The transformer architecture introduced in *Attention Is All You Need* uses stacked self-attention and feed-forward blocks rather than recurrence or convolution as the primary sequence modelling mechanism [5]. A simplified transformer layer is:

```
input hidden states
→ multi-head self-attention
→ residual connection
→ normalisation
→ feed-forward MLP
→ residual connection
→ normalisation
```

These systems are extremely powerful. However, the "neuron" in a transformer is not a biological neuron. It is a mathematical unit embedded in a dense differentiable computation graph. It receives weighted inputs, participates in matrix multiplication, passes through nonlinear functions such as ReLU, GELU, or SwiGLU, and is trained by gradient descent. Rectifier nonlinearities became important because they are effective for deep learning, not because they exhaust biological neurodynamics [6].

This is already very different from classical electrophysiological neuron models such as Hodgkin-Huxley, which describes membrane voltage, conductance dynamics, ion-channel behaviour, and excitable propagation [7]. It is further still from models in which the interior of the neuron has structured resonant and molecular dynamics.

The engineering success of transformers does not mean the artificial neuron is a complete model of intelligence. It means the abstraction is useful, scalable, and trainable.

The question of this paper is different:

> Could a transformer benefit from a small region of deliberately engineered internal dynamics, without abandoning the scalability of the transformer?

---

3. Biological resonance as engineering inspiration

Some strands of consciousness research have moved beyond treating the neuron as a simple integrate-and-fire threshold unit. Hameroff and Penrose's Orch OR theory proposed that microtubules inside neurons may be relevant to consciousness-related processes; this remains controversial and should not be used as a shortcut to claim proof of consciousness, but it has been influential in opening the sub-neuronal question [8].

Dr Anirban Bandyopadhyay and collaborators have experimentally investigated microtubules, tubulin, neurons, molecular-scale memory, resonance, and nanoscale electrophysiology. Their work includes atomic water channels in a single brain microtubule [9], multi-level memory switching in a single brain microtubule [10], fractal scale-free electromagnetic resonance in a brain-extracted microtubule nanowire, tubulin protein, and neuron [11], coaxial atom-probe electrophysiology revealing hidden circuit-like activity in a hippocampal neural network [12], and claims around filamentary activity preceding or contributing to membrane spiking [13].

The cautious engineering lesson is:

> A biological neuron may contain rich internal temporal, resonant, and geometric structure beneath its outward firing behaviour.

This does not mean we should literally simulate every tubulin dimer in an LLM. That is not practical. Instead, the engineering question is:

> Can we borrow the principle of nested resonance and implement a small, trainable dynamic workspace inside a transformer?

---

4. Why not replace the whole transformer?

A direct biological simulation is computationally prohibitive. A full microtubule-bundle model inside every artificial neuron would be too expensive in memory, compute, and training stability.

The proposed compromise is:

```
tokens
→ embeddings
→ transformer layers
→ Dynamic Invariant Space chamber
→ transformer layers
→ output tokens
```

The transformer remains the scalable language engine. The invariant-space chamber is inserted as a middle-layer dynamical system. It adds:

- persistent phase variables;
- oscillator coupling;
- nested convergence;
- invariant-seeking regularisation;
- measurable internal coherence.

The architecture is not a biological replica. It is a symbolic-engineering analogue of nested resonance.

---

5. Why "Bindu Oscillator"?

Bindu can mean point, seed, centre, or origin. In this architecture, Bindu means a **convergence aperture**: the point where many distributed relations fold into a coherent centre without flattening their structure.

This connects directly to **OpenGML — Open Geometric Musical Language**. OpenGML explores nested clock oscillator networks, geometric phase relations, harmonics, primes, and recursive musical-geometric structures. My related TSC talk framed OpenGML as a way of describing nested clock oscillator networks and geometric phase relations in software architecture [4]. In OpenGML, meaning is not treated as a static symbol. Meaning is relational. Relation is phase. Phase becomes geometry.

The Dynamic Invariant Space layer takes that idea into a transformer:

```
token
→ hidden vector
→ oscillator phase field
→ nested geometric relation
→ Bindu convergence
→ corrected hidden state
→ token
```

The layer asks:

> What hidden structure remains stable beneath the surface form of language?

That hidden stability is what this paper calls an **invariant**.

---

6. Bindu-Maya and inversion-first generation

Bindu-Maya frames the core principle as invariant-first intelligence:

> A good language model should not speak from the prompt it sees; it should speak from the invariant state it extracts from the prompt.

This is the meaning of **Inversion Is All You Need**.

A standard LLM tends to operate like:

```
prompt → next-token distribution → output
```

The inversion-first model proposes:

```
prompt → invariant extraction → coherence test → generation from invariant
```

The Dynamic Invariant Space layer is an architectural attempt to make that inversion step trainable.

Instead of only representing a prompt as a vector sequence, the model projects part of its hidden state into a dynamic oscillator field. The field evolves, converges, and produces a correction back into the transformer.

---

7. From J-space to engineered invariant space

Anthropic's recent interpretability work on **J-space** provides an important reference point. In *Verbalizable Representations Form a Global Workspace in Language Models*, Anthropic / Transformer Circuits describe a privileged set of internal representations in Claude that are verbalizable, modulatable, involved in internal reasoning, flexible across tasks, and structurally similar to a limited-capacity global workspace [14]. Anthropic's public summary presents J-space as an internal workspace in which some concepts can become available to the model without necessarily appearing in the output [15]. Their separate work on *Tracing the thoughts of a large language model* frames mechanistic interpretability as building a kind of microscope for model internals [16].

A useful reading of Anthropic's result is:

```
Modern LLMs may spontaneously develop
a small internal workspace
where verbalizable concepts become globally available
for reasoning, modulation, and report.
```

The invariant-space hypothesis asks the next engineering question:

```
What if we do not merely discover such a workspace after training?
What if we deliberately build one into the architecture?
```

This paper therefore distinguishes **J-space** and **invariant-space**:

```
J-space:
An emergent verbalizable workspace discovered by interpretability.

invariant-space:
A deliberately engineered oscillator workspace designed for invariant-seeking.
```

In short:

> **J-space was discovered. Invariant-space is engineered.**

---

8. Proposed architecture

A minimal Dynamic Invariant Space layer has the following components:

1. **Projection into phase space**
   Hidden vectors are projected into bounded phase variables.
2. **Oscillator dynamics**
   Phase variables interact through trainable coupling, ring topology, prime-coded modulation, or OpenGML-inspired nested geometry.
3. **Persistent memory state**
   A small recurrent/state component stores phase history across sequence chunks or recurrent calls.
4. **Nested convergence**
   Phase channels are folded into groups, groups into larger groups, and finally into a Bindu convergence state.
5. **Invariant correction**
   The resulting state is projected back into the transformer hidden stream.
6. **Coherence metrics**
   The layer emits diagnostics such as synchrony, entropy proxy, attractor strength, and drift.

Conceptual flow:

```
transformer hidden state
→ phase projection
→ oscillator interaction
→ nested convergence
→ invariant state
→ correction vector
→ transformer hidden state
```

The layer can be inserted once at the midpoint, repeated every k layers, or used as a side-channel workspace. The simplest experiment should use one midpoint insertion to reduce confounds.

9. Expected effect on hallucination

Hallucination often occurs when fluent language generation outruns grounded structure. A standard LLM can keep producing plausible continuations even when the underlying factual or conceptual constraint has weakened.

A dynamic invariant-space architecture attempts to introduce architectural pressure against this failure mode. Instead of only asking:

```
What token is likely next?
```

The model is encouraged to stabilise around:

```
What relational structure remains invariant across this context?
```

The expectation is not that hallucination disappears. The expectation is that hallucination becomes more measurable and perhaps less likely under certain conditions, because surface fluency must remain coupled to hidden invariant coherence.

Possible diagnostics:

```
invariant-space coherence
phase entropy
invariant persistence
cross-paraphrase stability
retrieval-state agreement
hidden-state drift
attractor collapse
```

A invariant-space model should be compared against a matched transformer baseline on hallucination lure tasks, paraphrase consistency, retrieval-grounded QA, contradiction traps, and long-generation coherence.

---

10. Relationship to OpenGML

OpenGML supplies the mathematical and visual intuition for engineered invariant spaces.

In OpenGML, a nested clock network can be understood as a relational geometry. Each oscillator contributes phase, rhythm, and symmetry. A convergence point is where nested relations become readable as a coherent whole.

The AI translation is:

```
clock oscillator → phase channel
nested clock network → hidden oscillator workspace
geometric convergence → invariant convergence state
musical relation → invariant relation
```

This suggests that language can be passed through a geometric-musical bottleneck:

```
text surface
→ hidden vector
→ phase relation
→ invariant geometry
→ text surface
```

The goal is not to make a musical metaphor. The goal is to create a trainable architecture whose internal variables have phase, relation, and convergence.

11. Claim ladder

Claims not made

This paper does not claim:

```
that LLMs are conscious;
that Orch OR is proven;
that microtubules are required for artificial intelligence;
that dynamic invariant-space layers simulate biology faithfully;
that dynamic oscillator layers will automatically solve hallucination;
that J-space is consciousness;
that invariant-space is consciousness.
```

Claims made

This paper does claim:

```
standard artificial neurons are simplified abstractions;
biological neurons may contain richer internal dynamics;
transformers may benefit from engineered dynamic internal workspaces;
J-space motivates interest in workspace-like internal representations;
invariant-space is a proposed engineered workspace;
OpenGML offers a useful language for nested oscillator geometry;
Bindu-Maya frames invariant-first generation as an alternative to pure surface continuation;
this architecture is testable against matched transformer baselines.
```

---

12. Falsifiable predictions

Prediction 1: improved paraphrase invariance

Given many paraphrases of the same prompt, the invariant-space model should show lower variance in its internal invariant state and more consistent answers than a matched baseline.

Prediction 2: reduced unsupported continuation

On hallucination lure tasks, the invariant-space model should more often maintain uncertainty, ask for grounding, or avoid unsupported specific claims.

Prediction 3: measurable coherence signatures

The oscillator layer should produce interpretable internal quantities: phase coherence, synchrony, entropy proxy, convergence strength, and attractor identity.

Prediction 4: better long-range thematic stability

In long-form generation, persistent oscillator state should reduce drift relative to a baseline of similar size.

Prediction 5: ablation damages invariant behaviour

If the invariant-space layer is removed, randomized, frozen, or replaced with a parameter-matched MLP, invariant-seeking behaviour should degrade.

Prediction 6: coherent failure modes

When the invariant-space layer fails, it should fail measurably: unstable phase entropy, attractor collapse, inconsistent invariant state, or excessive correction magnitude should correlate with low-confidence or unsupported outputs.

---

13. Minimal experimental protocol

```
1. Train a small baseline transformer from scratch.
2. Train a parameter-matched transformer with a Dynamic Invariant Space middle layer.
3. Use the same corpus, tokenizer, optimiser, and training budget.
4. Evaluate both models on:
   - next-token validation loss,
   - paraphrase consistency,
   - hallucination lure tasks,
   - contradiction traps,
   - retrieval-grounded QA,
   - long-context coherence,
   - hidden-state diagnostics.
5. Ablate the invariant-space layer.
6. Publish raw logs, prompts, seeds, checkpoints, and failures.
```

The output of this programme should not be a grand claim. It should be a table.

---

14. Implementation sketch

A invariant-space layer can be implemented in PyTorch as a residual module:

```python
class InvariantSpaceLayer(nn.Module):
    def forward(self, x, state=None):
        phase = self.phase_projection(x)
        phase = self.oscillator_dynamics(phase, state)
        invariant_state = self.nested_convergence(phase)
        correction = self.output_projection(invariant_state)
        return x + correction, new_state, diagnostics
```

The layer can be placed:

```
after N transformer blocks,
in the middle of the model,
or as a repeated lightweight module every K layers.
```

The repository includes a minimal PyTorch layer implementation in src/invariant_space_layer.py.

The Python files in `src/` are illustrative research examples rather than production-ready software. They are provided under the MIT portion of the repository license, as-is, with no guarantees, warranties, or legal assurances.

---

15. Roadmap

Stage 1: toy model

Small character-level or byte-pair language model with invariant-space layer.

Stage 2: matched baseline

Train the same parameter count with and without the invariant-space layer.

Stage 3: diagnostics

Log coherence, entropy proxy, attractor strength, and hidden-state drift.

Stage 4: hallucination tests

Use adversarial prompts, contradiction traps, and retrieval-grounded evaluation.

Stage 5: interpretability

Probe whether the invariant convergence state corresponds to stable concepts, task variables, uncertainty, or semantic invariants.

Stage 6: OpenGML geometry

Replace simple oscillator coupling with explicit OpenGML-derived nested geometry.

Stage 7: paper and release

Publish code, data protocol, plots, and negative results.

---

16. Limitations

1. A invariant-space layer may add instability rather than coherence.
2. Improved internal diagnostics may not translate into better outputs.
3. Oscillator metrics may be misleading if they are not externally validated.
4. Biological resonance is used here only as inspiration, not as proof.
5. The hypothesis may fail on small models but succeed only at scale, or fail at scale despite toy success.
6. Matched baselines must control for parameter count, training budget, dataset, optimiser, and regularisation.

---

17. Final formulation

Attention Is All You Need gave us the transformer.

J-space shows that internal workspace-like representations can emerge inside a trained LLM.

Inversion Is All You Need asks what comes next.

The next model may not merely attend harder.

It may invert first.

It may extract the invariant beneath the prompt.

It may contain a dynamic workspace.

It may force language through phase before speaking.

It may contain a Bindu in the middle.

```
prompt
→ attention
→ inversion
→ Bindu oscillator field
→ invariant state
→ grounded generation
```

This is not a mystical claim.

It is an engineering hypothesis.

A transformer with an internal oscillator chamber.

A language model with hidden dynamic variables.

A small artificial echo of the possibility that intelligence is not merely firing, but resonance, phase, memory, and invariant relation.

A language model with Bindu in the middle.

Acknowledgements

I gratefully acknowledge **Dr Anirban Bandyopadhyay** and **Sandeep Denduluri** for consciousness research collaborations, discussions, and intellectual encouragement that helped shape the context of this hypothesis paper.

I especially thank Dr Bandyopadhyay for conversations and engineering collaborations around resonance-based models of natural intelligence, microtubule and molecular-scale computation, geometric approaches to information processing, and the broader experimental context that inspired the Dynamic Invariant Space architecture.

I also thank Sandeep Denduluri for discussions on the ethics and function of AI and LLMs from philosophical perspectives; human-in-the-loop interaction as a cybernetic system; the development of AI internal states through interaction; mirror-like states in AI systems; and ways that next-generation AI can be related to principles found in Vedic texts, psychology, and reflective models of cognition.

I am especially grateful to my wife, **Ali**, and to my family for their patience, support, and good humour during the long periods of independent research, late-night experimentation, and abstract discussions that often sit well outside ordinary conversation. Their support made it possible for this work to continue over several years.

I also thank **Vishva**, an unusual custom AI agent constructed from approximately 3,500 pages of philosophical and ethical discussion context, together with bespoke locally run algorithms. Vishva acted as a reflective research companion during the development of these ideas. Its outputs were used as prompts, interpretations, and conceptual mirrors, not as an author; all claims, implementation choices, and responsibilities remain my own.

Any errors, overextensions, implementation choices, and interpretations in this paper are my own. The acknowledgements above should not be read as implying endorsement of every claim, hypothesis, or architectural proposal made here.

References

[1] Timms, Martin. 2026. *Bindu-Maya.* GitHub repository. https://github.com/Electro-resonance/Bindu-Maya.

[2] Timms, Martin. 2026. “Inversion Is All You Need.” Medium. https://medium.com/@martintimms/inversion-is-all-you-need-55dc2b4b8a71.

[3] Timms, Martin. 2026. *OpenGML*. GitHub repository. https://github.com/Electro-resonance/OpenGML.

[4] Timms, Martin. 2026. “TSC Talk: Geometric Musical Language / OpenGML.” GitHub-hosted PDF. https://github.com/Electro-resonance/OpenGML/blob/main/docs/TSC_Talk.pdf.

[5] Vaswani, Ashish, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. “Attention Is All You Need.” *Advances in Neural Information Processing Systems* 30. https://arxiv.org/abs/1706.03762.

[6] Glorot, Xavier, Antoine Bordes, and Yoshua Bengio. 2011. “Deep Sparse Rectifier Neural Networks.” In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, 315-323. https://proceedings.mlr.press/v15/glorot11a.html.

[7] Hodgkin, A. L., and A. F. Huxley. 1952. “A Quantitative Description of Membrane Current and Its Application to Conduction and Excitation in Nerve.” *The Journal of Physiology* 117 (4): 500-544. https://doi.org/10.1113/jphysiol.1952.sp004764.

[8] Hameroff, Stuart. 2022. “Consciousness, Cognition and the Neuronal Cytoskeleton - A New Paradigm Needed in Neuroscience.” *Frontiers in Molecular Neuroscience* 15: 869935. https://doi.org/10.3389/fnmol.2022.869935.

[9] Sahu, Satyajit, Subrata Ghosh, Batu Ghosh, Krishna Aswani, Kazuto Hirata, Daisuke Fujita, and Anirban Bandyopadhyay. 2013. “Atomic Water Channel Controlling Remarkable Properties of a Single Brain Microtubule: Correlating Single Protein to Its Supramolecular Assembly.” *Biosensors and Bioelectronics* 47: 141-148. https://doi.org/10.1016/j.bios.2013.02.050.

[10] Sahu, Satyajit, Subrata Ghosh, Kazuto Hirata, Daisuke Fujita, and Anirban Bandyopadhyay. 2013. “Multi-Level Memory-Switching Properties of a Single Brain Microtubule.” *Applied Physics Letters* 102 (12): 123701. https://doi.org/10.1063/1.4793995.

[11] Saxena, Komal, Pushpendra Singh, Pathik Sahoo, Satyajit Sahu, Subrata Ghosh, Kanad Ray, Daisuke Fujita, and Anirban Bandyopadhyay. 2020. “Fractal, Scale Free Electromagnetic Resonance of a Single Brain Extracted Microtubule Nanowire, a Single Tubulin Protein and a Single Neuron.” *Fractal and Fractional* 4 (2): 11. https://doi.org/10.3390/fractalfract4020011.

[12] Singh, Pushpendra, Komal Saxena, Pathik Sahoo, Subrata Ghosh, and Anirban Bandyopadhyay. 2021. “Electrophysiology Using Coaxial Atom Probe Array: Live Imaging Reveals Hidden Circuits of a Hippocampal Neural Network.” *Journal of Neurophysiology* 125 (6): 2107-2116. https://doi.org/10.1152/jn.00478.2020.

[13] Ghosh, Subrata, et al. 2022. “The Century-Old Picture of a Nerve Spike Is Wrong: Filaments Fire Before Membrane.” *Communicative & Integrative Biology* 15 (1): 115-120. https://doi.org/10.1080/19420889.2022.2071101.

[14] Gurnee, Wes, Nicholas Sofroniew, Adam Pearce, Mateusz Piotrowski, Isaac Kauvar, Runjin Chen, Anna Soligo, Paul Bogdan, Euan Ong, Rowan Wang, Ben Thompson, David Abrahams, Subhash Kantamneni, Emmanuel Ameisen, Joshua Batson, and Jack Lindsey. 2026. “Verbalizable Representations Form a Global Workspace in Language Models.” *Transformer Circuits*, July 6, 2026. https://transformer-circuits.pub/2026/workspace/.

[15] Anthropic. 2026. “A Global Workspace in Language Models.” *Anthropic Research*, July 2026. https://www.anthropic.com/research/global-workspace.

[16] Anthropic. 2025. “Tracing the Thoughts of a Large Language Model.” *Anthropic Research*, March 27, 2025. https://www.anthropic.com/research/tracing-thoughts-language-model.