









Order	Ø	Nominal	Dimensions					Packaging
Code	Connecting	Cross-	(in mm)					Unit
	Bolt	Section (mm2)	φID	L ₁	W	L ₂	φD	
55803015	M3	1,5	1,8	12,0	6,5	6,0	3,2	100
55803025	M3	2,5	2,3	12,0	7,5	6,0	3,2	100
55804025	M4	2,5	2,3	13,0	7,5	6,0	4,3	100
5580404	M4	4,0	3,0	17,0	8,5	8,0	4,3	100
5580406	M4	6,0	3,5	19,0	10,0	9,5	4,3	100
5580506	M5	6,0	3,5	21,0	10,0	9,5	5,3	100
5580510	M5	10	4,5	22,5	12,0	10,5	5,3	100
5580516	M5	16	5,5	26,0	12,0	13,0	5,3	100
5580610	M6	10	4,5	22,5	12,0	10,5	6,4	100
5580616	M6	16	5,5	27,0	12,0	13,0	6,4	100
5580625	M6	25	7,0	30,0	14,0	15,0	6,4	100
5580635	M6	35	8,5	32,5	17,0	17,0	6,4	100
5580825	M8	25	7,0	32,5	16,0	15,0	8,4	100
5580835	M8	35	8,5	35,0	17,0	17,0	8,4	100
5580850	M8	50	10,0	37,0	20,0	19,0	8,4	100
5580870	M8	70	12,0	43,0	24,0	21,0	8,4	100
5581050	M10	50	10,0	39,0	20,0	19,0	10,5	100
5581070	M10	70	12,0	45,0	24,0	21,0	10,5	100
5581095	M10	95	13,5	48,0	26,0	25,0	10,5	50

Surface coating: Tin-plated

Würth Elektronik eiSos GmbH & Co. KG **EMC & Inductive Solutions**

Max-Eyth-Str. 1 74638 Waldenburg Germany com. +49 79 42 945 - 0

www.we-online.de eiSos@we-online.de SIZE

CREATED CHECKED GENERAL TOLERANCE SKI DIN ISO 2768-1m DaF DESCRIPTION

PROJECTION METHOD

SCALE 3:1

PAGE

1 /1

WaCLUG Cable Lug, Tubular

MATERIAL Cu-EPT, EN13600

ORDER CODE 558 xxx xx

WEIGHT STATUS DATE **BUSINESS UNIT** Released 2015-06-09 XXX XXX XXX eiCan

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Wurth Electronics: 5580404