

TelegramBotPHP

Generated by Doxygen 1.9.2

| | |
|--|-----------|
| 1 TelegramBotPHP documentation | 1 |
| 2 LICENSE | 3 |
| 3 TelegramBotPHP | 5 |
| 3.1 Requirements | 5 |
| 3.2 Download | 5 |
| 3.2.0.1 Using Composer | 5 |
| 3.2.0.2 Using release archives | 6 |
| 3.2.0.3 Using Git | 6 |
| 3.3 Installation | 6 |
| 3.3.0.1 Via Composer's autoloader | 6 |
| 3.3.0.2 Via TelegramBotPHP class | 6 |
| 3.4 Configuration (WebHook) | 6 |
| 3.5 Examples | 6 |
| 3.6 Functions | 7 |
| 3.7 Build keyboards | 7 |
| 3.8 List of Bots using the library | 8 |
| 3.9 Emoticons | 8 |
| 3.10 License | 9 |
| 3.11 Contributing | 9 |
| 3.12 Contact me | 9 |
| 3.13 Support me | 9 |
| 4 Deprecated List | 11 |
| 5 Data Structure Index | 13 |
| 5.1 Data Structures | 13 |
| 6 Data Structure Documentation | 15 |
| 6.1 Telegram Class Reference | 15 |
| 6.1.1 Detailed Description | 20 |
| 6.1.2 Constructor & Destructor Documentation | 20 |
| 6.1.2.1 __construct() | 20 |
| 6.1.3 Member Function Documentation | 21 |
| 6.1.3.1 addStickerToSet() | 21 |
| 6.1.3.2 answerCallbackQuery() | 21 |
| 6.1.3.3 answerInlineQuery() | 22 |
| 6.1.3.4 answerPreCheckoutQuery() | 22 |
| 6.1.3.5 answerShippingQuery() | 22 |
| 6.1.3.6 approveChatJoinRequest() | 23 |
| 6.1.3.7 banChatMember() | 23 |
| 6.1.3.8 banChatSenderChat() | 23 |
| 6.1.3.9 buildInlineKeyBoard() | 24 |

| | |
|--------------------------------------|----|
| 6.1.3.10 buildInlineKeyboardButton() | 24 |
| 6.1.3.11 buildKeyBoard() | 25 |
| 6.1.3.12 buildKeyboardButton() | 26 |
| 6.1.3.13 buildKeyBoardHide() | 26 |
| 6.1.3.14 Callback_ChatID() | 26 |
| 6.1.3.15 Callback_Data() | 27 |
| 6.1.3.16 Callback_FromID() | 27 |
| 6.1.3.17 Callback_ID() | 27 |
| 6.1.3.18 Callback_Message() | 28 |
| 6.1.3.19 Callback_Query() | 28 |
| 6.1.3.20 ChatID() | 28 |
| 6.1.3.21 close() | 28 |
| 6.1.3.22 copyMessage() | 28 |
| 6.1.3.23 createChatInviteLink() | 29 |
| 6.1.3.24 createNewStickerSet() | 29 |
| 6.1.3.25 Date() | 30 |
| 6.1.3.26 declineChatJoinRequest() | 30 |
| 6.1.3.27 deleteChatPhoto() | 30 |
| 6.1.3.28 deleteChatStickerSet() | 31 |
| 6.1.3.29 deleteMessage() | 31 |
| 6.1.3.30 deleteMyCommands() | 31 |
| 6.1.3.31 deleteStickerFromSet() | 32 |
| 6.1.3.32 deleteWebhook() | 32 |
| 6.1.3.33 downloadFile() | 32 |
| 6.1.3.34 editChatInviteLink() | 33 |
| 6.1.3.35 editMessageCaption() | 33 |
| 6.1.3.36 editMessageLiveLocation() | 33 |
| 6.1.3.37 editMessageMedia() | 34 |
| 6.1.3.38 editMessageReplyMarkup() | 34 |
| 6.1.3.39 editMessageText() | 34 |
| 6.1.3.40 endpoint() | 36 |
| 6.1.3.41 exportChatInviteLink() | 36 |
| 6.1.3.42 forwardMessage() | 37 |
| 6.1.3.43 getChat() | 37 |
| 6.1.3.44 getChatAdministrators() | 37 |
| 6.1.3.45 getChatMember() | 38 |
| 6.1.3.46 getChatMemberCount() | 38 |
| 6.1.3.47 getChatMembersCount() | 39 |
| 6.1.3.48 getChatMenuButton() | 39 |
| 6.1.3.49 getContactPhoneNumber() | 39 |
| 6.1.3.50 getData() | 40 |
| 6.1.3.51 getFile() | 40 |

| | |
|---|----|
| 6.1.3.52 <code>getGameHighScores()</code> | 40 |
| 6.1.3.53 <code>getMe()</code> | 41 |
| 6.1.3.54 <code>getMyCommands()</code> | 41 |
| 6.1.3.55 <code>getMyDefaultAdministratorRights()</code> | 41 |
| 6.1.3.56 <code>getStickerSet()</code> | 42 |
| 6.1.3.57 <code>getUpdates()</code> | 42 |
| 6.1.3.58 <code>getUpdateType()</code> | 43 |
| 6.1.3.59 <code>getUserProfilePhotos()</code> | 43 |
| 6.1.3.60 <code>Inline_Query()</code> | 43 |
| 6.1.3.61 <code>kickChatMember()</code> | 44 |
| 6.1.3.62 <code>leaveChat()</code> | 44 |
| 6.1.3.63 <code>logOut()</code> | 44 |
| 6.1.3.64 <code>messageFromGroup()</code> | 45 |
| 6.1.3.65 <code>messageFromGroupTitle()</code> | 45 |
| 6.1.3.66 <code>MessageID()</code> | 45 |
| 6.1.3.67 <code>pinChatMessage()</code> | 45 |
| 6.1.3.68 <code>promoteChatMember()</code> | 46 |
| 6.1.3.69 <code>ReplyToMessageFromUserID()</code> | 46 |
| 6.1.3.70 <code>ReplyToMessageID()</code> | 46 |
| 6.1.3.71 <code>respondSuccess()</code> | 47 |
| 6.1.3.72 <code>restrictChatMember()</code> | 47 |
| 6.1.3.73 <code>revokeChatInviteLink()</code> | 47 |
| 6.1.3.74 <code>sendAnimation()</code> | 48 |
| 6.1.3.75 <code>sendAudio()</code> | 48 |
| 6.1.3.76 <code>sendChatAction()</code> | 48 |
| 6.1.3.77 <code>sendContact()</code> | 49 |
| 6.1.3.78 <code>sendDice()</code> | 49 |
| 6.1.3.79 <code>sendDocument()</code> | 49 |
| 6.1.3.80 <code>sendGame()</code> | 50 |
| 6.1.3.81 <code>sendInvoice()</code> | 50 |
| 6.1.3.82 <code>sendLocation()</code> | 51 |
| 6.1.3.83 <code>sendMediaGroup()</code> | 51 |
| 6.1.3.84 <code>sendMessage()</code> | 51 |
| 6.1.3.85 <code>sendPhoto()</code> | 52 |
| 6.1.3.86 <code>sendPoll()</code> | 52 |
| 6.1.3.87 <code>sendSticker()</code> | 53 |
| 6.1.3.88 <code>sendVenue()</code> | 53 |
| 6.1.3.89 <code>sendVideo()</code> | 53 |
| 6.1.3.90 <code>sendVideoNote()</code> | 54 |
| 6.1.3.91 <code>sendVoice()</code> | 54 |
| 6.1.3.92 <code>serveUpdate()</code> | 55 |
| 6.1.3.93 <code>setChatAdministratorCustomTitle()</code> | 55 |

| | |
|---|----|
| 6.1.3.94 setChatDescription() | 55 |
| 6.1.3.95 setChatMenuButton() | 56 |
| 6.1.3.96 setChatPermissions() | 56 |
| 6.1.3.97 setChatPhoto() | 56 |
| 6.1.3.98 setChatStickerSet() | 57 |
| 6.1.3.99 setChatTitle() | 57 |
| 6.1.3.100 setGameScore() | 58 |
| 6.1.3.101 setMyCommands() | 58 |
| 6.1.3.102 setMyDefaultAdministratorRights() | 58 |
| 6.1.3.103 setPassportDataErrors() | 59 |
| 6.1.3.104 setStickerPositionInSet() | 59 |
| 6.1.3.105 setStickerSetThumb() | 60 |
| 6.1.3.106 setWebhook() | 60 |
| 6.1.3.107 stopMessageLiveLocation() | 60 |
| 6.1.3.108 stopPoll() | 62 |
| 6.1.3.109 Text() | 62 |
| 6.1.3.110 unbanChatMember() | 62 |
| 6.1.3.111 unbanChatSenderChat() | 63 |
| 6.1.3.112 unpinAllChatMessages() | 63 |
| 6.1.3.113 unpinChatMessage() | 64 |
| 6.1.3.114 uploadStickerFile() | 64 |
| 6.1.4 Field Documentation | 64 |
| 6.1.4.1 ANIMATION | 64 |
| 6.1.4.2 AUDIO | 65 |
| 6.1.4.3 CALLBACK_QUERY | 65 |
| 6.1.4.4 CHANNEL_POST | 65 |
| 6.1.4.5 CONTACT | 65 |
| 6.1.4.6 DOCUMENT | 65 |
| 6.1.4.7 EDITED_MESSAGE | 65 |
| 6.1.4.8 INLINE_QUERY | 65 |
| 6.1.4.9 LOCATION | 65 |
| 6.1.4.10 MESSAGE | 66 |
| 6.1.4.11 PHOTO | 66 |
| 6.1.4.12 REPLY | 66 |
| 6.1.4.13 STICKER | 66 |
| 6.1.4.14 VIDEO | 66 |
| 6.1.4.15 VOICE | 66 |
| 6.2 TelegramErrorLogger Class Reference | 66 |
| 6.2.1 Detailed Description | 67 |
| 6.2.2 Member Function Documentation | 67 |
| 6.2.2.1 log() | 67 |

Chapter 1

TelegramBotPHP documentation

This is the API documentation of the TelegramBotPHP project.

For see a bot in action, using this API, add [CowBot](#).

Pages:

[Telegram](#) Class API

[TelegramErrorLogger](#) Class

[Readme](#)

[License](#)

Chapter 2

LICENSE

The MIT License

Copyright (c) 2015-2017 Gabriele Grillo - gabry.grillo@alice.it, shakibonline - shakiba_9@yahoo.com (for the TelegramErrorLogger.php file)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Chapter 3

TelegramBotPHP

A very simple PHP [Telegram Bot API](#).
Compliant with the April 16, 2022 [Telegram Bot API](#) update.

3.1 Requirements

- PHP \geq 5.3
- Curl extension for PHP5 must be enabled.
- [Telegram](#) API key, you can get one simply with [@BotFather](#) with simple commands right after creating your bot.

For the WebHook:

- An VALID SSL certificate ([Telegram](#) API requires this). You can use [Cloudflare's Free Flexible SSL](#) which crypts the web traffic from end user to their proxies if you're using CloudFlare DNS. Since the August 29 update you can use a self-signed ssl certificate.

For the getUpdates(Long Polling):

- Some way to execute the script in order to serve messages (for example cronjob)

3.2 Download

3.2.0.1 Using Composer

From your project directory, run:

```
composer require eleirbag89/telegrambotphp
```

or

```
php composer.phar require eleirbag89/telegrambotphp
```

Note: If you don't have Composer you can download it [HERE](#).

3.2.0.2 Using release archives

<https://github.com/Eleirbag89/TelegramBotPHP/releases>

3.2.0.3 Using Git

From a project directory, run:

```
git clone https://github.com/Eleirbag89/TelegramBotPHP.git
```

3.3 Installation

3.3.0.1 Via Composer's autoloader

After downloading by using Composer, you can include Composer's autoloader:

```
include (__DIR__ . '/vendor/autoload.php');
$telegram = new Telegram('YOUR TELEGRAM TOKEN HERE');
```

3.3.0.2 Via TelegramBotPHP class

Copy Telegram.php into your server and include it in your new bot script:

```
include 'Telegram.php';
$telegram = new Telegram('YOUR TELEGRAM TOKEN HERE');
```

Note: To enable error log file, also copy TelegramErrorLogger.php in the same directory of Telegram.php file.

3.4 Configuration (WebHook)

Navigate to [https://api.telegram.org/bot\(BOT_TOKEN\)/setWebhook?url=https://yoursite.com/your_update.php](https://api.telegram.org/bot(BOT_TOKEN)/setWebhook?url=https://yoursite.com/your_update.php) Or use the [Telegram](#) class setWebhook method.

3.5 Examples

```
$telegram = new Telegram('YOUR TELEGRAM TOKEN HERE');
$chat_id = $telegram->ChatID();
$content = array('chat_id' => $chat_id, 'text' => 'Test');
$telegram->sendMessage($content);
```

If you want to get some specific parameter from the [Telegram](#) response:

```
$telegram = new Telegram('YOUR TELEGRAM TOKEN HERE');
$result = $telegram->getData();
$text = $result['message'] ['text'];
$chat_id = $result['message'] ['chat'] ['id'];
$content = array('chat_id' => $chat_id, 'text' => 'Test');
$telegram->sendMessage($content);
```

To upload a Photo or some other files, you need to load it with CurlFile:

```
// Load a local file to upload. If is already on Telegram's Servers just pass the resource id
$img = curl_file_create('test.png', 'image/png');
$content = array('chat_id' => $chat_id, 'photo' => $img );
$telegram->sendPhoto($content);
```

To download a file on the [Telegram](#)'s servers

```
$file = $telegram->getFile($file_id);
$telegram->downloadFile($file['result'] ['file_path'], './my_downloaded_file_on_local_server.png');
```

See `update.php` or `update cowsay.php` for the complete example. If you wanna see the CowSay Bot in action [add it](#).

If you want to use `getUpdates` instead of the WebHook you need to call the `serveUpdate` function inside a for cycle.

```
$telegram = new Telegram('YOUR TELEGRAM TOKEN HERE');
$req = $telegram->getUpdates();
for ($i = 0; $i < $telegram->UpdateCount(); $i++) {
    // You NEED to call serveUpdate before accessing the values of message in Telegram Class
    $telegram->serveUpdate($i);
    $text = $telegram->Text();
    $chat_id = $telegram->ChatID();
    if ($text == '/start') {
        $reply = 'Working';
        $content = array('chat_id' => $chat_id, 'text' => $reply);
        $telegram->sendMessage($content);
    }
    // DO OTHER STUFF
}
```

See `getUpdates.php` for the complete example.

3.6 Functions

For a complete and up-to-date functions documentation check <http://eleirbag89.github.io/TelegramBotPHP/>

3.7 Build keyboards

[Telegram](#)'s bots can have two different kind of keyboards: Inline and Reply.

The `InlineKeyboard` is linked to a particular message, while the `ReplyKeyboard` is linked to the whole chat.

They are both an array of array of buttons, which represent the rows and columns.

For instance you can arrange a `ReplyKeyboard` like this: using this code:

```
$option = array(
    //First row
    array($telegram->buildKeyboardButton("Button 1"), $telegram->buildKeyboardButton("Button 2")),
    //Second row
    array($telegram->buildKeyboardButton("Button 3"), $telegram->buildKeyboardButton("Button 4"),
        $telegram->buildKeyboardButton("Button 5")),
    //Third row
    array($telegram->buildKeyboardButton("Button 6")) );
$keyb = $telegram->buildKeyBoard($option, $onetime=false);
$content = array('chat_id' => $chat_id, 'reply_markup' => $keyb, 'text' => "This is a Keyboard Test");
$telegram->sendMessage($content);
```

When a user click on the button, the button text is send back to the bot.

For an `InlineKeyboard` it's pretty much the same (but you need to provide a valid URL or a Callback data)

```
$option = array(
    //First row
    array($telegram->buildInlineKeyBoardButton("Button 1", $url="http://link1.com"),
        $telegram->buildInlineKeyBoardButton("Button 2", $url="http://link2.com")),
    //Second row
    array($telegram->buildInlineKeyBoardButton("Button 3", $url="http://link3.com"),
        $telegram->buildInlineKeyBoardButton("Button 4", $url="http://link4.com"),
        $telegram->buildInlineKeyBoardButton("Button 5", $url="http://link5.com")),
    //Third row
    array($telegram->buildInlineKeyBoardButton("Button 6", $url="http://link6.com")) );
$keyb = $telegram->buildInlineKeyBoard($option);
$content = array('chat_id' => $chat_id, 'reply_markup' => $keyb, 'text' => "This is a Keyboard Test");
$telegram->sendMessage($content);
```

This is the list of all the helper functions to make keyboards easily:

```
buildKeyBoard(array $options, $onetime=true, $resize=true, $selective=true)
```

Send a custom keyboard. \$option is an array of array KeyboardButton.
Check [ReplyKeyboardMarkup](#) for more info.

```
buildInlineKeyBoard(array $inline_keyboard)
```

Send a custom keyboard. \$inline_keyboard is an array of array InlineKeyboardButton.
Check [InlineKeyboardMarkup](#) for more info.

```
buildInlineKeyBoardButton($text, $url, $callback_data, $switch_inline_query)
```

Create an InlineKeyboardButton.
Check [InlineKeyboardButton](#) for more info.

```
buildKeyBoardButton($text, $url, $request_contact, $request_location)
```

Create a KeyboardButton.
Check [KeyboardButton](#) for more info.

```
buildKeyBoardHide($selective=true)
```

Hide a custom keyboard.
Check [ReplyKeyBoarHide](#) for more info.

```
buildForceReply($selective=true)
```

Show a Reply interface to the user.
Check [ForceReply](#) for more info.

3.8 List of Bots using the library

Let me know using this [Issue](#) if you have made a bot using this API, I will add it to this section.

- [iHarfBot](#) - Lang: Persian/Farsi
- [AsansorBot](#) - Lang: Persian/Farsi
- [IDPbot](#) - Lang: Persian/Farsi (Down as 14/10/2019)
- [Evil Insult Generator](#) - Lang English/German
- [ibelitbot](#) -Lang Persian (Down as 14/10/2019)
- [Advanced Pools Bot](#) - Lang Italian/English([Contribute](#))
- [Btn_Bot](#) - Lang pt-BR - Cria botões transparente para publicações.
- [DiffSGLaPuntabot](#) [DiffGravinaCTbot](#) [DiffAdranobot](#) - Lang: it/Italian - Bots to handle Recycling in San Giovanni La Punta, Gravina and Adriano (OpenSource Template <https://github.com/Gualty/BOTDifferenziata>)
- [GoBot](#)
- [RaidBot](#)

3.9 Emoticons

For a list of emoticons to use in your bot messages, please refer to the column Bytes of this table: [http↵://apps.timwhitlock.info/emoji/tables/unicode](http://apps.timwhitlock.info/emoji/tables/unicode)

3.10 License

This open-source software is distributed under the MIT License. See LICENSE.md

3.11 Contributing

All kinds of contributions are welcome - code, tests, documentation, bug reports, new features, etc...

- Send feedbacks.
- Submit bug reports.
- Write/Edit the documents.
- Fix bugs or add new features.

3.12 Contact me

You can contact me [via Telegram](#) but if you have an issue please [open](#) one.

3.13 Support me

You can support me using via LiberaPay

or buy me a beer or two using [Paypal](#).

Chapter 4

Deprecated List

Global [Telegram::Callback_ChatID](#) ()

Use [ChatId\(\)](#) instead

Global [Telegram::Callback_Data](#) ()

Use [Text\(\)](#) instead

Chapter 5

Data Structure Index

5.1 Data Structures

Here are the data structures with brief descriptions:

| | |
|-------------------------------------|----|
| Telegram | 15 |
| TelegramErrorLogger | 66 |

Chapter 6

Data Structure Documentation

6.1 Telegram Class Reference

Public Member Functions

- `__construct` (\$bot_token, \$log_errors=true, array \$proxy=[])
Class constructor.
- `endpoint` (\$api, array \$content, \$post=true)
Do requests to [Telegram Bot API](#).
- `getMe` ()
A method for testing your bot.
- `logOut` ()
- `close` ()
- `respondSuccess` ()
A method for responding http to [Telegram](#).
- `sendMessage` (array \$content)
Send a message.
- `copyMessage` (array \$content)
Copy a message.
- `forwardMessage` (array \$content)
Forward a message.
- `sendPhoto` (array \$content)
Send a photo.
- `sendAudio` (array \$content)
Send an audio.
- `sendDocument` (array \$content)
Send a document.
- `sendAnimation` (array \$content)
Send an animation.
- `sendSticker` (array \$content)
Send a sticker.
- `sendVideo` (array \$content)
Send a video.
- `sendVoice` (array \$content)
Send a voice message.
- `sendLocation` (array \$content)

- Send a location.*

 - [editMessageLiveLocation](#) (array \$content)

Edit Message Live Location.
- [stopMessageLiveLocation](#) (array \$content)

Stop Message Live Location.
- [setChatStickerSet](#) (array \$content)

Set Chat Sticker Set.
- [deleteChatStickerSet](#) (array \$content)

Delete Chat Sticker Set.
- [sendMediaGroup](#) (array \$content)

Send Media Group.
- [sendVenue](#) (array \$content)

Send Venue.
- [sendContact](#) (array \$content)
- [sendPoll](#) (array \$content)
- [sendDice](#) (array \$content)
- [sendChatAction](#) (array \$content)

Send a chat action.
- [getUserProfilePhotos](#) (array \$content)

Get a list of profile pictures for a user.
- [getFile](#) (\$file_id)

Use this method to get basic info about a file and prepare it for downloading.
- [kickChatMember](#) (array \$content)

Kick Chat Member.
- [leaveChat](#) (array \$content)

Leave Chat.
- [banChatMember](#) (array \$content)

Ban Chat Member.
- [unbanChatMember](#) (array \$content)

Unban Chat Member.
- [getChat](#) (array \$content)

Get Chat Information.
- [getChatAdministrators](#) (array \$content)

Get chat Administrators.
- [getChatMemberCount](#) (array \$content)

Get chat member count.
- [getChatMembersCount](#) (array \$content)
- [getChatMember](#) (array \$content)
- [answerInlineQuery](#) (array \$content)
- [setGameScore](#) (array \$content)

Set Game Score.
- [getGameHighScores](#) (array \$content)

Get Game Hi Scores.
- [answerCallbackQuery](#) (array \$content)

Answer a callback Query.
- [setMyCommands](#) (array \$content)

Set the list of the bot commands.
- [deleteMyCommands](#) (array \$content)

Delete the list of the bot commands.
- [getMyCommands](#) (array \$content)

Get the list of the bot commands.

- [setChatMenuButton](#) (array \$content)
Set the chat menu button.
- [getChatMenuButton](#) (array \$content)
Get the chat menu button.
- [setMyDefaultAdministratorRights](#) (array \$content)
Set the default administrator rights.
- [getMyDefaultAdministratorRights](#) (array \$content)
Get the default administrator rights.
- [editMessageText](#) (array \$content)
- [editMessageCaption](#) (array \$content)
- [editMessageMedia](#) (array \$content)
- [editMessageReplyMarkup](#) (array \$content)
- [stopPoll](#) (array \$content)
- [downloadFile](#) (\$telegram_file_path, \$local_file_path)
Use this method to download a file.
- [setWebhook](#) (\$url, \$certificate=)
Set a WebHook for the bot.
- [deleteWebhook](#) ()
Delete the WebHook for the bot.
- [getData](#) ()
Get the data of the current message.
- **setData** (array \$data)
Set the data currently used.
- [Text](#) ()
Get the text of the current message.
- **Caption** ()
- [ChatID](#) ()
Get the chat_id of the current message.
- [MessageID](#) ()
Get the message_id of the current message.
- [ReplyToMessageID](#) ()
Get the reply_to_message message_id of the current message.
- [ReplyToMessageFromUserID](#) ()
Get the reply_to_message forward_from user_id of the current message.
- [Inline_Query](#) ()
Get the inline_query of the current update.
- [Callback_Query](#) ()
Get the callback_query of the current update.
- [Callback_ID](#) ()
Get the callback_query id of the current update.
- [Callback_Data](#) ()
Get the data of the current callback.
- [Callback_Message](#) ()
Get the message of the current callback.
- [Callback_ChatID](#) ()
Get the chat_id of the current callback.
- [Callback_FromID](#) ()
Get the from_id of the current callback.
- [Date](#) ()
Get the date of the current message.
- **FirstName** ()

- Get the first name of the user.*

 - **LastName** ()

Get the last name of the user.
- **Username** ()

Get the username of the user.
- **Location** ()

Get the location in the message.
- **UpdateID** ()

Get the update_id of the message.
- **UpdateCount** ()

Get the number of updates.
- **UserID** ()

Get user's id of current message.
- **FromID** ()

Get user's id of current forwarded message.
- **FromChatID** ()

Get chat's id where current message forwarded from.
- **messageFromGroup** ()

Tell if a message is from a group or user chat.
- **getContactPhoneNumber** ()

Get the contact phone number.
- **messageFromGroupTitle** ()

Get the title of the group chat.
- **buildKeyboard** (array \$options, \$onetime=false, \$resize=false, \$selective=true)

Set a custom keyboard.
- **buildInlineKeyboard** (array \$options)

Set an InlineKeyboard.
- **buildInlineKeyboardButton** (\$text, \$url="", \$callback_data="", \$switch_inline_query=null, \$switch_inline_query_current_chat=null, \$callback_game="", \$pay=")

Create an InlineKeyboardButton.
- **buildKeyboardButton** (\$text, \$request_contact=false, \$request_location=false)

Create a KeyboardButton.
- **buildKeyboardHide** (\$selective=true)

Hide a custom keyboard.
- **buildForceReply** (\$selective=true)

Display a reply interface to the user.
- **sendInvoice** (array \$content)

Send an invoice.
- **answerShippingQuery** (array \$content)

Answer a shipping query.
- **answerPreCheckoutQuery** (array \$content)

Answer a PreCheckout query.
- **setPassportDataErrors** (array \$content)

Set Passport data errors.
- **sendGame** (array \$content)

Send a Game.
- **sendVideoNote** (array \$content)

Send a video note.
- **restrictChatMember** (array \$content)

Restrict Chat Member.
- **promoteChatMember** (array \$content)

- Promote Chat Member.*

 - [setChatAdministratorCustomTitle](#) (array \$content)

Set chat Administrator custom title.
- [banChatSenderChat](#) (array \$content)

Ban a channel chat in a super group or channel.
- [unbanChatSenderChat](#) (array \$content)

Unban a channel chat in a super group or channel.
- [setChatPermissions](#) (array \$content)

Set default chat permission for all members.
- [exportChatInviteLink](#) (array \$content)
- [createChatInviteLink](#) (array \$content)
- [editChatInviteLink](#) (array \$content)
- [revokeChatInviteLink](#) (array \$content)
- [approveChatJoinRequest](#) (array \$content)
- [declineChatJoinRequest](#) (array \$content)
- [setChatPhoto](#) (array \$content)

Set Chat Photo.
- [deleteChatPhoto](#) (array \$content)

Delete Chat Photo.
- [setChatTitle](#) (array \$content)

Set Chat Title.
- [setChatDescription](#) (array \$content)

Set Chat Description.
- [pinChatMessage](#) (array \$content)

Pin Chat Message.
- [unpinChatMessage](#) (array \$content)

Unpin Chat Message.
- [unpinAllChatMessages](#) (array \$content)

Unpin All Chat Messages.
- [getStickerSet](#) (array \$content)

Get Sticker Set.
- [uploadStickerFile](#) (array \$content)

Upload Sticker File.
- [createNewStickerSet](#) (array \$content)

Create New Sticker Set.
- [addStickerToSet](#) (array \$content)

Add Sticker To Set.
- [setStickerPositionInSet](#) (array \$content)

Set Sticker Position In Set.
- [deleteStickerFromSet](#) (array \$content)

Delete Sticker From Set.
- [setStickerSetThumb](#) (array \$content)

Set Sticker Thumb From Set.
- [deleteMessage](#) (array \$content)

Delete a message.
- [getUpdates](#) (\$offset=0, \$limit=100, \$timeout=0, \$update=true)

Receive incoming messages using polling.
- [serveUpdate](#) (\$update)

Serve an update.
- [getUpdateType](#) ()

Return current update type.

Data Fields

- const `INLINE_QUERY` = 'inline_query'
- const `CALLBACK_QUERY` = 'callback_query'
- const `EDITED_MESSAGE` = 'edited_message'
- const `REPLY` = 'reply'
- const `MESSAGE` = 'message'
- const `PHOTO` = 'photo'
- const `VIDEO` = 'video'
- const `AUDIO` = 'audio'
- const `VOICE` = 'voice'
- const `ANIMATION` = 'animation'
- const `STICKER` = 'sticker'
- const `DOCUMENT` = 'document'
- const `LOCATION` = 'location'
- const `CONTACT` = 'contact'
- const `CHANNEL_POST` = 'channel_post'

6.1.1 Detailed Description

[Telegram](#) Bot Class.

Author

Gabriele Grillo gabry.grillo@alice.it

6.1.2 Constructor & Destructor Documentation

6.1.2.1 `__construct()`

```
__construct (
    $bot_token,
    $log_errors = true,
    array $proxy = [] )
```

Class constructor.

Create a [Telegram](#) instance from the bot token

Parameters

| | |
|---------------------------|--|
| <code>\$bot_token</code> | the bot token |
| <code>\$log_errors</code> | enable or disable the logging |
| <code>\$proxy</code> | array with the proxy configuration (url, port, type, auth) |

Returns

an instance of the class.

6.1.3 Member Function Documentation

6.1.3.1 addStickerToSet()

```
addStickerToSet (
    array $content )
```

Add Sticker To Set.

See [addStickerToSet](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.2 answerCallbackQuery()

```
answerCallbackQuery (
    array $content )
```

Answer a callback Query.

See [answerCallbackQuery](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.3 answerInlineQuery()

```
answerInlineQuery (
    array $content )
```

See [answerInlineQuery](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.4 answerPreCheckoutQuery()

```
answerPreCheckoutQuery (
    array $content )
```

Answer a PreCheckout query.

See [answerPreCheckoutQuery](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.5 answerShippingQuery()

```
answerShippingQuery (
    array $content )
```

Answer a shipping query.

See [answerShippingQuery](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.6 approveChatJoinRequest()

```
approveChatJoinRequest (
    array $content )
```

See [approveChatJoinRequest](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.7 banChatMember()

```
banChatMember (
    array $content )
```

Ban Chat Member.

See [banChatMember](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.8 banChatSenderChat()

```
banChatSenderChat (
    array $content )
```

Ban a channel chat in a super group or channel.

See [banChatSenderChat](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.9 buildInlineKeyBoard()

```
buildInlineKeyBoard (
    array $options )
```

Set an InlineKeyBoard.

This object represents an inline keyboard that appears right next to the message it belongs to.

Parameters

| | |
|------------------|--|
| <i>\$options</i> | Array of Array of InlineKeyboardButton; Array of button rows, each represented by an Array of InlineKeyboardButton |
|------------------|--|

Returns

the requested keyboard as Json.

6.1.3.10 buildInlineKeyboardButton()

```
buildInlineKeyboardButton (
    $text,
    $url = '',
    $callback_data = '',
    $switch_inline_query = null,
    $switch_inline_query_current_chat = null,
    $callback_game = '',
    $pay = '' )
```

Create an InlineKeyboardButton.

This object represents one button of an inline keyboard. You must use exactly one of the optional fields.

Parameters

| | |
|---------------|---|
| <i>\$text</i> | String; Array of button rows, each represented by an Array of Strings |
| <i>\$url</i> | String Optional. HTTP url to be opened when button is pressed |

Parameters

| | |
|---|---|
| <i>\$callback_data</i> | String Optional. Data to be sent in a callback query to the bot when button is pressed |
| <i>\$switch_inline_query</i> | String Optional. If set, pressing the button will prompt the user to select one of their chats, open that chat and insert the bot's username and the specified inline query in the input field. Can be empty, in which case just the bot's username will be inserted. |
| <i>\$switch_inline_query_current_chat</i> | String Optional. Optional. If set, pressing the button will insert the bot's username and the specified inline query in the current chat's input field. Can be empty, in which case only the bot's username will be inserted. |
| <i>\$callback_game</i> | String Optional. Description of the game that will be launched when the user presses the button. |
| <i>\$pay</i> | Boolean Optional. Specify True, to send a Pay button . |

Returns

the requested button as Array.

6.1.3.11 buildKeyBoard()

```
buildKeyBoard (
    array $options,
    $onetime = false,
    $resize = false,
    $selective = true )
```

Set a custom keyboard.

This object represents a custom keyboard with reply options

Parameters

| | |
|--------------------|---|
| <i>\$options</i> | Array of Array of String; Array of button rows, each represented by an Array of Strings |
| <i>\$onetime</i> | Boolean Requests clients to hide the keyboard as soon as it's been used. Defaults to false. |
| <i>\$resize</i> | Boolean Requests clients to resize the keyboard vertically for optimal fit (e.g., make the keyboard smaller if there are just two rows of buttons). Defaults to false, in which case the custom keyboard is always of the same height as the app's standard keyboard. |
| <i>\$selective</i> | Boolean Use this parameter if you want to show the keyboard to specific users only. Targets: 1) users that are @mentioned in the text of the Message object; 2) if the bot's message is a reply (has reply_to_message_id), sender of the original message. |

Returns

the requested keyboard as Json.

6.1.3.12 buildKeyboardButton()

```
buildKeyboardButton (
    $text,
    $request_contact = false,
    $request_location = false )
```

Create a KeyboardButton.

This object represents one button of an inline keyboard. You must use exactly one of the optional fields.

Parameters

| | |
|---------------------------|--|
| <i>\$text</i> | String; Array of button rows, each represented by an Array of Strings |
| <i>\$request_contact</i> | Boolean Optional. If True, the user's phone number will be sent as a contact when the button is pressed. Available in private chats only |
| <i>\$request_location</i> | Boolean Optional. If True, the user's current location will be sent when the button is pressed. Available in private chats only |

Returns

the requested button as Array.

6.1.3.13 buildKeyBoardHide()

```
buildKeyBoardHide (
    $selective = true )
```

Hide a custom keyboard.

Upon receiving a message with this object, [Telegram](#) clients will hide the current custom keyboard and display the default letter-keyboard. By default, custom keyboards are displayed until a new keyboard is sent by a bot. An exception is made for one-time keyboards that are hidden immediately after the user presses a button.

Parameters

| | |
|--------------------|--|
| <i>\$selective</i> | Boolean Use this parameter if you want to show the keyboard to specific users only. Targets: 1) users that are @mentioned in the text of the Message object; 2) if the bot's message is a reply (has reply_to_message_id), sender of the original message. |
|--------------------|--|

Returns

the requested keyboard hide as Array.

6.1.3.14 Callback_ChatID()

```
Callback_ChatID ( )
```

Get the chat_id of the current callback.

Deprecated Use ChatId() instead

Returns

the String callback_query.

6.1.3.15 Callback_Data()

Callback_Data ()

Get the data of the current callback.

Deprecated Use Text() instead

Returns

the String callback_data.

6.1.3.16 Callback_FromID()

Callback_FromID ()

Get the from_id of the current callback.

Returns

the String callback_query from_id.

6.1.3.17 Callback_ID()

Callback_ID ()

Get the callback_query id of the current update.

Returns

the String callback_query id.

6.1.3.18 Callback_Message()

`Callback_Message ()`

Get the message of the current callback.

Returns

the Message.

6.1.3.19 Callback_Query()

`Callback_Query ()`

Get the callback_query of the current update.

Returns

the String callback_query.

6.1.3.20 ChatID()

`ChatID ()`

Get the chat_id of the current message.

Returns

the String users's chat_id.

6.1.3.21 close()

`close ()`

See [close](#)

Returns

the JSON [Telegram](#)'s reply.

6.1.3.22 copyMessage()

`copyMessage (`
 `array $content)`

Copy a message.

See [copyMessage](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.23 createChatInviteLink()

```
createChatInviteLink (  
    array $content )
```

See [createChatInviteLink](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.24 createNewStickerSet()

```
createNewStickerSet (  
    array $content )
```

Create New Sticker Set.

See [createNewStickerSet](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.25 Date()

```
Date ( )
```

Get the date of the current message.

Returns

the String message's date.

6.1.3.26 declineChatJoinRequest()

```
declineChatJoinRequest (
    array $content )
```

See [declineChatJoinRequest](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.27 deleteChatPhoto()

```
deleteChatPhoto (
    array $content )
```

Delete Chat Photo.

See [deleteChatPhoto](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.28 deleteChatStickerSet()

```
deleteChatStickerSet (
    array $content )
```

Delete Chat Sticker Set.

See [deleteChatStickerSet](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.29 deleteMessage()

```
deleteMessage (
    array $content )
```

Delete a message.

See [deleteMessage](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.30 deleteMyCommands()

```
deleteMyCommands (
    array $content )
```

Delete the list of the bot commands.

See [deleteMyCommands](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.31 deleteStickerFromSet()

```
deleteStickerFromSet (
    array $content )
```

Delete Sticker From Set.

See [deleteStickerFromSet](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.32 deleteWebhook()

```
deleteWebhook ( )
```

Delete the WebHook for the bot.

Use this method to remove webhook integration if you decide to switch back to [getUpdates](#). Returns True on success. Requires no parameters.

Returns

the JSON [Telegram](#)'s reply.

6.1.3.33 downloadFile()

```
downloadFile (
    $telegram_file_path,
    $local_file_path )
```

Use this method to download a file.

Use this method to to download a file from the [Telegram](#) servers.

Parameters

| | |
|-----------------------------|--|
| <i>\$telegram_file_path</i> | String File path on Telegram servers |
| <i>\$local_file_path</i> | String File path where save the file. |

6.1.3.34 editChatInviteLink()

```
editChatInviteLink (
    array $content )
```

See [editChatInviteLink](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.35 editMessageCaption()

```
editMessageCaption (
    array $content )
```

See [editMessageCaption](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.36 editMessageLiveLocation()

```
editMessageLiveLocation (
    array $content )
```

Edit Message Live Location.

See [editMessageLiveLocation](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.37 editMessageMedia()

```
editMessageMedia (
    array $content )
```

See [editMessageMedia](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.38 editMessageReplyMarkup()

```
editMessageReplyMarkup (
    array $content )
```

See [editMessageReplyMarkup](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.39 editMessageText()

```
editMessageText (
    array $content )
```

See `editMessageText` for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.40 endpoint()

```
endpoint (
    $api,
    array $content,
    $post = true )
```

Do requests to [Telegram](#) Bot API.

Contacts the various API's endpoints

Parameters

| | |
|------------------|--|
| <i>\$api</i> | the API endpoint |
| <i>\$content</i> | the request parameters as array |
| <i>\$post</i> | boolean tells if \$content needs to be sends |

Returns

the JSON [Telegram](#)'s reply.

6.1.3.41 exportChatInviteLink()

```
exportChatInviteLink (
    array $content )
```

See [exportChatInviteLink](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.42 forwardMessage()

```
forwardMessage (
    array $content )
```

Forward a message.

See [forwardMessage](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.43 getChat()

```
getChat (
    array $content )
```

Get Chat Information.

See [getChat](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.44 getChatAdministrators()

```
getChatAdministrators (
    array $content )
```

Get chat Administrators.

See [getChatAdministrators](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.45 getChatMember()

```
getChatMember (
    array $content )
```

See [getChatMember](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.46 getChatMemberCount()

```
getChatMemberCount (
    array $content )
```

Get chat member count.

See [getChatMemberCount](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.47 getChatMembersCount()

```
getChatMembersCount (
    array $content )
```

For retrocompatibility

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.48 getChatMenuButton()

```
getChatMenuButton (
    array $content )
```

Get the chat menu button.

See [getChatMenuButton](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.49 getContactPhoneNumber()

```
getContactPhoneNumber ( )
```

Get the contact phone number.

Returns

a String of the contact phone number.

6.1.3.50 `getData()`

```
getData ( )
```

Get the data of the current message.

Get the POST request of a user in a Webhook or the message actually processed in a [getUpdates\(\)](#) enviroment.

Returns

the JSON users's message.

6.1.3.51 `getFile()`

```
getFile (
    $file_id )
```

Use this method to get basic info about a file and prepare it for downloading.

Use this method to get basic info about a file and prepare it for downloading. For the moment, bots can download files of up to 20MB in size. On success, a File object is returned. The file can then be downloaded via the link https://api.telegram.org/file/bot<token>/<file_path>, where <file_path> is taken from the response. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling `getFile` again.

Parameters

| | |
|------------------------|--|
| <code>\$file_id</code> | String File identifier to get info about |
|------------------------|--|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.52 `getGameHighScores()`

```
getGameHighScores (
    array $content )
```

Get Game Hi Scores.

See [getGameHighScores](#) for the input values

Parameters

| | |
|------------------------|---------------------------------|
| <code>\$content</code> | the request parameters as array |
|------------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.53 getMe()

```
getMe ( )
```

A method for testing your bot.

See [getMe](#)

Returns

the JSON [Telegram](#)'s reply.

6.1.3.54 getMyCommands()

```
getMyCommands (
    array $content )
```

Get the list of the bot commands.

See [getMyCommands](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.55 getMyDefaultAdministratorRights()

```
getMyDefaultAdministratorRights (
    array $content )
```

Get the default administrator rights.

See [getMyDefaultAdministratorRights](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.56 getStickerSet()

```
getStickerSet (
    array $content )
```

Get Sticker Set.

See [getStickerSet](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.57 getUpdates()

```
getUpdates (
    $offset = 0,
    $limit = 100,
    $timeout = 0,
    $update = true )
```

Receive incoming messages using polling.

Use this method to receive incoming updates using long polling.

Parameters

| | |
|------------------|---|
| <i>\$offset</i> | Integer Identifier of the first update to be returned. Must be greater by one than the highest among the identifiers of previously received updates. By default, updates starting with the earliest unconfirmed update are returned. An update is considered confirmed as soon as <code>getUpdates</code> is called with an offset higher than its <code>update_id</code> . |
| <i>\$limit</i> | Integer Limits the number of updates to be retrieved. Values between 1—100 are accepted. Defaults to 100 |
| <i>\$timeout</i> | Integer Timeout in seconds for long polling. Defaults to 0, i.e. usual short polling |
| <i>\$update</i> | Boolean If true updates the pending message list to the last update received. Default to true. |

Returns

the updates as Array.

6.1.3.58 getUpdateType()

```
getUpdateType ( )
```

Return current update type.

Return current update type `False` on failure.

Returns

bool|string

6.1.3.59 getUserProfilePhotos()

```
getUserProfilePhotos (
    array $content )
```

Get a list of profile pictures for a user.

See [getUserProfilePhotos](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.60 Inline_Query()

```
Inline_Query ( )
```

Get the inline_query of the current update.

Returns

the Array inline_query.

6.1.3.61 kickChatMember()

```
kickChatMember (
    array $content )
```

Kick Chat Member.

Deprecated

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.62 leaveChat()

```
leaveChat (
    array $content )
```

Leave Chat.

See [leaveChat](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.63 logOut()

```
logOut ( )
```

See [logOut](#)

Returns

the JSON [Telegram](#)'s reply.

6.1.3.64 `messageFromGroup()`

```
messageFromGroup ( )
```

Tell if a message is from a group or user chat.

Returns

BOOLEAN true if the message is from a Group chat, false otherwise.

6.1.3.65 `messageFromGroupTitle()`

```
messageFromGroupTitle ( )
```

Get the title of the group chat.

Returns

a String of the title chat.

6.1.3.66 `MessageID()`

```
MessageID ( )
```

Get the message_id of the current message.

Returns

the String message_id.

6.1.3.67 `pinChatMessage()`

```
pinChatMessage (
    array $content )
```

Pin Chat Message.

See [pinChatMessage](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.68 promoteChatMember()

```
promoteChatMember (
    array $content )
```

Promote Chat Member.

See [promoteChatMember](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.69 ReplyToMessageFromUserID()

```
ReplyToMessageFromUserID ( )
```

Get the reply_to_message forward_from user_id of the current message.

Returns

the String reply_to_message forward_from user_id.

6.1.3.70 ReplyToMessageID()

```
ReplyToMessageID ( )
```

Get the reply_to_message message_id of the current message.

Returns

the String reply_to_message message_id.

6.1.3.71 respondSuccess()

```
respondSuccess ( )
```

A method for responding http to [Telegram](#).

Returns

the HTTP 200 to [Telegram](#).

6.1.3.72 restrictChatMember()

```
restrictChatMember (
    array $content )
```

Restrict Chat Member.

See [restrictChatMember](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.73 revokeChatInviteLink()

```
revokeChatInviteLink (
    array $content )
```

See [revokeChatInviteLink](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.74 `sendAnimation()`

```
sendAnimation (
    array $content )
```

Send an animation.

See `sendAnimation` for the input values

Parameters

| | |
|------------------------|---------------------------------|
| <code>\$content</code> | the request parameters as array |
|------------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.75 `sendAudio()`

```
sendAudio (
    array $content )
```

Send an audio.

See `sendAudio` for the input values

Parameters

| | |
|------------------------|---------------------------------|
| <code>\$content</code> | the request parameters as array |
|------------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.76 `sendChatAction()`

```
sendChatAction (
    array $content )
```

Send a chat action.

See `sendChatAction` for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.77 sendContact()

```
sendContact (
    array $content )
```

See [sendContact](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.78 sendDice()

```
sendDice (
    array $content )
```

See [sendDice](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.79 sendDocument()

```
sendDocument (
    array $content )
```

Send a document.

See [sendDocument](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.80 [sendGame\(\)](#)

```
sendGame (
    array $content )
```

Send a Game.

See [sendGame](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.81 [sendInvoice\(\)](#)

```
sendInvoice (
    array $content )
```

Send an invoice.

See [sendInvoice](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.82 sendLocation()

```
sendLocation (
    array $content )
```

Send a location.

See [sendLocation](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.83 sendMediaGroup()

```
sendMediaGroup (
    array $content )
```

Send Media Group.

See [sendMediaGroup](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.84 sendMessage()

```
sendMessage (
    array $content )
```

Send a message.

See [sendMessage](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.85 sendPhoto()

```
sendPhoto (
    array $content )
```

Send a photo.

See [sendPhoto](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.86 sendPoll()

```
sendPoll (
    array $content )
```

See [sendPoll](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.87 sendSticker()

```
sendSticker (
    array $content )
```

Send a sticker.

See [sendSticker](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.88 sendVenue()

```
sendVenue (
    array $content )
```

Send Venue.

See [sendVenue](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.89 sendVideo()

```
sendVideo (
    array $content )
```

Send a video.

See [sendVideo](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.90 sendVideoNote()

```
sendVideoNote (
    array $content )
```

Send a video note.

See [sendVideoNote](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.91 sendVoice()

```
sendVoice (
    array $content )
```

Send a voice message.

See [sendVoice](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.92 `serveUpdate()`

```
serveUpdate (
    $update )
```

Serve an update.

Use this method to use the builtin function like `Text()` or `Username()` on a specific update.

Parameters

| | |
|-----------------|---|
| <i>\$update</i> | Integer The index of the update in the updates array. |
|-----------------|---|

6.1.3.93 `setChatAdministratorCustomTitle()`

```
setChatAdministratorCustomTitle (
    array $content )
```

Set chat Administrator custom title.

See `setChatAdministratorCustomTitle` for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.94 `setChatDescription()`

```
setChatDescription (
    array $content )
```

Set Chat Description.

See `setChatDescription` for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.95 setChatMenuButton()

```
setChatMenuButton (
    array $content )
```

Set the chat menu button.

See [setChatMenuButton](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.96 setChatPermissions()

```
setChatPermissions (
    array $content )
```

Set default chat permission for all members.

See [setChatPermissions](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.97 setChatPhoto()

```
setChatPhoto (
    array $content )
```

Set Chat Photo.

See [setChatPhoto](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.98 setChatStickerSet()

```
setChatStickerSet (
    array $content )
```

Set Chat Sticker Set.

See [setChatStickerSet](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.99 setChatTitle()

```
setChatTitle (
    array $content )
```

Set Chat Title.

See [setChatTitle](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.100 setGameScore()

```
setGameScore (
    array $content )
```

Set Game Score.

See [setGameScore](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.101 setMyCommands()

```
setMyCommands (
    array $content )
```

Set the list of the bot commands.

See [setMyCommands](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.102 setMyDefaultAdministratorRights()

```
setMyDefaultAdministratorRights (
    array $content )
```

Set the default administrator rights.

See [setMyDefaultAdministratorRights](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.103 setPassportDataErrors()

```
setPassportDataErrors (
    array $content )
```

Set Passport data errors.

See [setPassportDataErrors](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.104 setStickerPositionInSet()

```
setStickerPositionInSet (
    array $content )
```

Set Sticker Position In Set.

See [setStickerPositionInSet](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.105 setStickerSetThumb()

```
setStickerSetThumb (
    array $content )
```

Set Sticker Thumb From Set.

See [setStickerSetThumb](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.106 setWebhook()

```
setWebhook (
    $url,
    $certificate = '' )
```

Set a WebHook for the bot.

Use this method to specify a url and receive incoming updates via an outgoing webhook. Whenever there is an update for the bot, we will send an HTTPS POST request to the specified url, containing a JSON-serialized Update. In case of an unsuccessful request, we will give up after a reasonable amount of attempts.

If you'd like to make sure that the Webhook request comes from [Telegram](#), we recommend using a secret path in the URL, e.g. <https://www.example.com/<token>>. Since nobody else knows your bot's token, you can be pretty sure it's us.

Parameters

| | |
|----------------------|---|
| <i>\$url</i> | String HTTPS url to send updates to. Use an empty string to remove webhook integration |
| <i>\$certificate</i> | InputFile Upload your public key certificate so that the root certificate in use can be checked |

Returns

the JSON [Telegram](#)'s reply.

6.1.3.107 stopMessageLiveLocation()

```
stopMessageLiveLocation (
    array $content )
```

Stop Message Live Location.

See `stopMessageLiveLocation` for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.108 stopPoll()

```
stopPoll (
    array $content )
```

See [stopPoll](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.109 Text()

```
Text ( )
```

Get the text of the current message.

Returns

the String users's text.

6.1.3.110 unbanChatMember()

```
unbanChatMember (
    array $content )
```

Unban Chat Member.

See [unbanChatMember](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.111 unbanChatSenderChat()

```
unbanChatSenderChat (
    array $content )
```

Unban a channel chat in a super group or channel.

See [unbanChatSenderChat](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.112 unpinAllChatMessages()

```
unpinAllChatMessages (
    array $content )
```

Unpin All Chat Messages.

See [unpinAllChatMessages](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.113 unpinChatMessage()

```
unpinChatMessage (
    array $content )
```

Unpin Chat Message.

See [unpinChatMessage](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.3.114 uploadStickerFile()

```
uploadStickerFile (
    array $content )
```

Upload Sticker File.

See [uploadStickerFile](#) for the input values

Parameters

| | |
|------------------|---------------------------------|
| <i>\$content</i> | the request parameters as array |
|------------------|---------------------------------|

Returns

the JSON [Telegram](#)'s reply.

6.1.4 Field Documentation

6.1.4.1 ANIMATION

```
const ANIMATION = 'animation'
```

Constant for type animation.

6.1.4.2 AUDIO

```
const AUDIO = 'audio'
```

Constant for type Audio.

6.1.4.3 CALLBACK_QUERY

```
const CALLBACK_QUERY = 'callback_query'
```

Constant for type Callback Query.

6.1.4.4 CHANNEL_POST

```
const CHANNEL_POST = 'channel_post'
```

Constant for type Channel Post.

6.1.4.5 CONTACT

```
const CONTACT = 'contact'
```

Constant for type Contact.

6.1.4.6 DOCUMENT

```
const DOCUMENT = 'document'
```

Constant for type Document.

6.1.4.7 EDITED_MESSAGE

```
const EDITED_MESSAGE = 'edited_message'
```

Constant for type Edited Message.

6.1.4.8 INLINE_QUERY

```
const INLINE_QUERY = 'inline_query'
```

Constant for type Inline Query.

6.1.4.9 LOCATION

```
const LOCATION = 'location'
```

Constant for type Location.

6.1.4.10 MESSAGE

```
const MESSAGE = 'message'
```

Constant for type Message.

6.1.4.11 PHOTO

```
const PHOTO = 'photo'
```

Constant for type Photo.

6.1.4.12 REPLY

```
const REPLY = 'reply'
```

Constant for type Reply.

6.1.4.13 STICKER

```
const STICKER = 'sticker'
```

Constant for type sticker.

6.1.4.14 VIDEO

```
const VIDEO = 'video'
```

Constant for type Video.

6.1.4.15 VOICE

```
const VOICE = 'voice'
```

Constant for type Voice.

The documentation for this class was generated from the following file:

- Telegram.php

6.2 TelegramErrorLogger Class Reference

Static Public Member Functions

- static [log](#) (\$result, \$content, \$use_rt=true)
Log request and response parameters from/to [Telegram API](#).

6.2.1 Detailed Description

[Telegram](#) Error Logger Class.

Author

shakibonline shakiba_9@yahoo.com

6.2.2 Member Function Documentation

6.2.2.1 log()

```
static log (
    $result,
    $content,
    $use_rt = true ) [static]
```

Log request and response parameters from/to [Telegram](#) API.

Prints the list of parameters from/to [Telegram](#)'s API endpoint

Parameters

| | |
|------------------|---|
| <i>\$result</i> | the Telegram 's response as array |
| <i>\$content</i> | the request parameters as array. |

The documentation for this class was generated from the following file:

- TelegramErrorLogger.php

Index

__construct
Telegram, 20

addStickerToSet
Telegram, 21

ANIMATION
Telegram, 64

answerCallbackQuery
Telegram, 21

answerInlineQuery
Telegram, 21

answerPreCheckoutQuery
Telegram, 22

answerShippingQuery
Telegram, 22

approveChatJoinRequest
Telegram, 23

AUDIO
Telegram, 64

banChatMember
Telegram, 23

banChatSenderChat
Telegram, 23

buildInlineKeyboard
Telegram, 24

buildInlineKeyboardButton
Telegram, 24

buildKeyboard
Telegram, 25

buildKeyboardButton
Telegram, 25

buildKeyboardHide
Telegram, 26

Callback_ChatID
Telegram, 26

Callback_Data
Telegram, 27

Callback_FromID
Telegram, 27

Callback_ID
Telegram, 27

Callback_Message
Telegram, 27

CALLBACK_QUERY
Telegram, 65

Callback_Query
Telegram, 28

CHANNEL_POST

Telegram, 65

ChatID
Telegram, 28

close
Telegram, 28

CONTACT
Telegram, 65

copyMessage
Telegram, 28

createChatInviteLink
Telegram, 29

createNewStickerSet
Telegram, 29

Date
Telegram, 29

declineChatJoinRequest
Telegram, 30

deleteChatPhoto
Telegram, 30

deleteChatStickerSet
Telegram, 30

deleteMessage
Telegram, 31

deleteMyCommands
Telegram, 31

deleteStickerFromSet
Telegram, 32

deleteWebhook
Telegram, 32

DOCUMENT
Telegram, 65

downloadFile
Telegram, 32

editChatInviteLink
Telegram, 33

EDITED_MESSAGE
Telegram, 65

editMessageCaption
Telegram, 33

editMessageLiveLocation
Telegram, 33

editMessageMedia
Telegram, 34

editMessageReplyMarkup
Telegram, 34

editMessageText
Telegram, 34

endpoint

Telegram, 36
exportChatInviteLink
Telegram, 36
forwardMessage
Telegram, 36
getChat
Telegram, 37
getChatAdministrators
Telegram, 37
getChatMember
Telegram, 38
getChatMemberCount
Telegram, 38
getChatMembersCount
Telegram, 38
getChatMenuButton
Telegram, 39
getContactPhoneNumber
Telegram, 39
getData
Telegram, 39
getFile
Telegram, 40
getGameHighScores
Telegram, 40
getMe
Telegram, 41
getMyCommands
Telegram, 41
getMyDefaultAdministratorRights
Telegram, 41
getStickerSet
Telegram, 42
getUpdates
Telegram, 42
getUpdateType
Telegram, 43
getUserProfilePhotos
Telegram, 43
INLINE_QUERY
Telegram, 65
Inline_Query
Telegram, 43
kickChatMember
Telegram, 43
leaveChat
Telegram, 44
LOCATION
Telegram, 65
log
TelegramErrorLogger, 67
logOut
Telegram, 44
MESSAGE

Telegram, 65
messageFromGroup
Telegram, 44
messageFromGroupTitle
Telegram, 45
MessageID
Telegram, 45
PHOTO
Telegram, 66
pinChatMessage
Telegram, 45
promoteChatMember
Telegram, 46
REPLY
Telegram, 66
ReplyToMessageFromUserID
Telegram, 46
ReplyToMessageID
Telegram, 46
respondSuccess
Telegram, 46
restrictChatMember
Telegram, 47
revokeChatInviteLink
Telegram, 47
sendAnimation
Telegram, 47
sendAudio
Telegram, 48
sendChatAction
Telegram, 48
sendContact
Telegram, 49
sendDice
Telegram, 49
sendDocument
Telegram, 49
sendGame
Telegram, 50
sendInvoice
Telegram, 50
sendLocation
Telegram, 51
sendMediaGroup
Telegram, 51
sendMessage
Telegram, 51
sendPhoto
Telegram, 52
sendPoll
Telegram, 52
sendSticker
Telegram, 52
sendVenue
Telegram, 53
sendVideo

- Telegram, [53](#)
- sendVideoNote
 - Telegram, [54](#)
- sendVoice
 - Telegram, [54](#)
- serveUpdate
 - Telegram, [54](#)
- setChatAdministratorCustomTitle
 - Telegram, [55](#)
- setChatDescription
 - Telegram, [55](#)
- setChatMenuButton
 - Telegram, [56](#)
- setChatPermissions
 - Telegram, [56](#)
- setChatPhoto
 - Telegram, [56](#)
- setChatStickerSet
 - Telegram, [57](#)
- setChatTitle
 - Telegram, [57](#)
- setGameScore
 - Telegram, [57](#)
- setMyCommands
 - Telegram, [58](#)
- setMyDefaultAdministratorRights
 - Telegram, [58](#)
- setPassportDataErrors
 - Telegram, [59](#)
- setStickerPositionInSet
 - Telegram, [59](#)
- setStickerSetThumb
 - Telegram, [59](#)
- setWebhook
 - Telegram, [60](#)
- STICKER
 - Telegram, [66](#)
- stopMessageLiveLocation
 - Telegram, [60](#)
- stopPoll
 - Telegram, [62](#)
- Telegram, [15](#)
 - `__construct`, [20](#)
 - `addStickerToSet`, [21](#)
 - `ANIMATION`, [64](#)
 - `answerCallbackQuery`, [21](#)
 - `answerInlineQuery`, [21](#)
 - `answerPreCheckoutQuery`, [22](#)
 - `answerShippingQuery`, [22](#)
 - `approveChatJoinRequest`, [23](#)
 - `AUDIO`, [64](#)
 - `banChatMember`, [23](#)
 - `banChatSenderChat`, [23](#)
 - `buildInlineKeyBoard`, [24](#)
 - `buildInlineKeyboardButton`, [24](#)
 - `buildKeyBoard`, [25](#)
 - `buildKeyboardButton`, [25](#)
 - `buildKeyBoardHide`, [26](#)
 - `Callback_ChatID`, [26](#)
 - `Callback_Data`, [27](#)
 - `Callback_FromID`, [27](#)
 - `Callback_ID`, [27](#)
 - `Callback_Message`, [27](#)
 - `CALLBACK_QUERY`, [65](#)
 - `Callback_Query`, [28](#)
 - `CHANNEL_POST`, [65](#)
 - `ChatID`, [28](#)
 - `close`, [28](#)
 - `CONTACT`, [65](#)
 - `copyMessage`, [28](#)
 - `createChatInviteLink`, [29](#)
 - `createNewStickerSet`, [29](#)
 - `Date`, [29](#)
 - `declineChatJoinRequest`, [30](#)
 - `deleteChatPhoto`, [30](#)
 - `deleteChatStickerSet`, [30](#)
 - `deleteMessage`, [31](#)
 - `deleteMyCommands`, [31](#)
 - `deleteStickerFromSet`, [32](#)
 - `deleteWebhook`, [32](#)
 - `DOCUMENT`, [65](#)
 - `downloadFile`, [32](#)
 - `editChatInviteLink`, [33](#)
 - `EDITED_MESSAGE`, [65](#)
 - `editMessageCaption`, [33](#)
 - `editMessageLiveLocation`, [33](#)
 - `editMessageMedia`, [34](#)
 - `editMessageReplyMarkup`, [34](#)
 - `editMessageText`, [34](#)
 - `endpoint`, [36](#)
 - `exportChatInviteLink`, [36](#)
 - `forwardMessage`, [36](#)
 - `getChat`, [37](#)
 - `getChatAdministrators`, [37](#)
 - `getChatMember`, [38](#)
 - `getChatMemberCount`, [38](#)
 - `getChatMembersCount`, [38](#)
 - `getChatMenuButton`, [39](#)
 - `getContactPhoneNumber`, [39](#)
 - `getData`, [39](#)
 - `getFile`, [40](#)
 - `getGameHighScores`, [40](#)
 - `getMe`, [41](#)
 - `getMyCommands`, [41](#)
 - `getMyDefaultAdministratorRights`, [41](#)
 - `getStickerSet`, [42](#)
 - `getUpdates`, [42](#)
 - `getUpdateType`, [43](#)
 - `getUserProfilePhotos`, [43](#)
 - `INLINE_QUERY`, [65](#)
 - `Inline_Query`, [43](#)
 - `kickChatMember`, [43](#)
 - `leaveChat`, [44](#)
 - `LOCATION`, [65](#)
 - `logOut`, [44](#)
 - `MESSAGE`, [65](#)

- messageFromGroup, [44](#)
- messageFromGroupTitle, [45](#)
- MessageID, [45](#)
- PHOTO, [66](#)
- pinChatMessage, [45](#)
- promoteChatMember, [46](#)
- REPLY, [66](#)
- ReplyToMessageFromUserID, [46](#)
- ReplyToMessageID, [46](#)
- respondSuccess, [46](#)
- restrictChatMember, [47](#)
- revokeChatInviteLink, [47](#)
- sendAnimation, [47](#)
- sendAudio, [48](#)
- sendChatAction, [48](#)
- sendContact, [49](#)
- sendDice, [49](#)
- sendDocument, [49](#)
- sendGame, [50](#)
- sendInvoice, [50](#)
- sendLocation, [51](#)
- sendMediaGroup, [51](#)
- sendMessage, [51](#)
- sendPhoto, [52](#)
- sendPoll, [52](#)
- sendSticker, [52](#)
- sendVenue, [53](#)
- sendVideo, [53](#)
- sendVideoNote, [54](#)
- sendVoice, [54](#)
- serveUpdate, [54](#)
- setChatAdministratorCustomTitle, [55](#)
- setChatDescription, [55](#)
- setChatMenuButton, [56](#)
- setChatPermissions, [56](#)
- setChatPhoto, [56](#)
- setChatStickerSet, [57](#)
- setChatTitle, [57](#)
- setGameScore, [57](#)
- setMyCommands, [58](#)
- setMyDefaultAdministratorRights, [58](#)
- setPassportDataErrors, [59](#)
- setStickerPositionInSet, [59](#)
- setStickerSetThumb, [59](#)
- setWebhook, [60](#)
- STICKER, [66](#)
- stopMessageLiveLocation, [60](#)
- stopPoll, [62](#)
- Text, [62](#)
- unbanChatMember, [62](#)
- unbanChatSenderChat, [63](#)
- unpinAllChatMessages, [63](#)
- unpinChatMessage, [63](#)
- uploadStickerFile, [64](#)
- VIDEO, [66](#)
- VOICE, [66](#)
- TelegramErrorLogger, [66](#)
 - log, [67](#)
- Text
 - Telegram, [62](#)
- unbanChatMember
 - Telegram, [62](#)
- unbanChatSenderChat
 - Telegram, [63](#)
- unpinAllChatMessages
 - Telegram, [63](#)
- unpinChatMessage
 - Telegram, [63](#)
- uploadStickerFile
 - Telegram, [64](#)
- VIDEO
 - Telegram, [66](#)
- VOICE
 - Telegram, [66](#)